


LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:220.23V I:0.6553A P:140.62W PF:0.9743 Freq:50.00Hz Lamp Flux:8720.66x1 lm		
NAME: SB-J01P140WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1500*750mm	

DATA OF LAMP		PHOTOMETRIC DATA Eff: 62.02 lm/W			
MODEL		I _{max} (cd)	1461	S/MH(C0/180)	1.23
NOMINAL POWER(W)		LOR(%)	100.0	S/MH(C90/270)	1.21
RATED VOLTAGE(V)	--	TOTAL FLUX(lm)	8720.7	η UP,DN(C0-180)	24.3,25.7
NOMINAL FLUX(lm)	8720.66	CIE CLASS	DIFFUSE	η UP,DN(C180-360)	23.6,26.3
LAMPS INSIDE	1	η up(%)	48.0	CIBSE SHR NOM	1.25
TEST VOLTAGE(V)	--	η down(%)	52.0	CIBSE SHR MAX	1.35



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-06-24

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum, lamp
10	1428	1404	1385	1395	1437	1429	1411	1409	0- 10	136.6	136.6	1.57,1.57
20	1325	1307	1276	1293	1344	1348	1323	1319	10- 20	386.4	523.0	6,6
30	1169	1168	1133	1152	1195	1214	1167	1176	20- 30	574.0	1097	12.6,12.6
40	985.3	1014	978.2	996.2	1016	1048	996.2	1011	30- 40	681.6	1779	20.4,20.4
50	793.7	856.3	822.3	842.9	823.7	883.2	838.7	849.2	40- 50	712.9	2491	28.6,28.6
60	602.5	699.7	660.2	689.6	631.7	721.3	679.6	690.0	50- 60	678.1	3170	36.3,36.3
70	419.0	547.1	505.4	537.5	447.7	568.1	529.5	542.1	60- 70	590.0	3760	43.1,43.1
80	256.8	401.6	363.0	393.6	281.9	417.6	380.4	393.7	70- 80	465.0	4224	48.4,48.4
90	146.9	243.7	235.1	223.8	145.9	242.5	260.4	256.1	80- 90	312.2	4537	52,52
100	278.5	398.2	380.6	401.3	265.2	349.3	342.6	372.2	90-100	298.3	4835	55.4,55.4
110	431.8	494.5	532.5	506.3	427.1	400.0	490.6	462.1	100-110	438.3	5273	60.5,60.5
120	547.7	687.7	693.9	683.4	563.4	602.8	643.2	657.8	110-120	549.2	5823	66.8,66.8
130	688.8	831.4	851.1	698.0	678.5	682.4	822.8	816.7	120-130	623.9	6446	73.9,73.9
140	839.9	955.9	903.9	775.3	818.9	774.2	851.2	963.2	130-140	630.1	7077	81.1,81.1
150	1118	1074	925.7	1054	1098	1047	998.8	1079	140-150	601.7	7678	88,88
160	1305	1256	1124	1298	1287	1296	1161	1247	150-160	533.8	8212	94.2,94.2
170	1427	1352	1418	1394	1411	1405	1411	1357	160-170	374.3	8586	98.5,98.5
180	1458	1411	1435	1413	1461	1414	1436	1416	170-180	134.4	8721	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

Conical surface Flux(90deg): 2135.4 lm

%lum = 24.5%

%lamp = 24.5%

Conical surface Flux(120deg): 3169.5 lm

%lum = 36.3%


%lamp = 36.3%

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:XIAOMI
Test Date:2023-06-24

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:9.000m [K=1.0000]
Remarks:

LUMINANCE LIMITATION CURVES

Test:U:220.23V I:0.6553A P:140.62W PF:0.9743 Freq:50.00Hz Lamp Flux:8720.66x1 lm		
NAME: SB-J01P140WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1500*750mm	




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:XIAOMI
Test Date:2023-06-24

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:9.000m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:220.23V I:0.6553A P:140.62W PF:0.9743 Freq:50.00Hz Lamp Flux:8720.66x1 lm		
NAME: SB-J01P140WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1500*750mm	

ρ_{cc}	80%			70%			50%			30%			10%			0
ρ_w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρ_{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Coefficients of Utilization(CU)									
0.0	1.08	1.08	1.08	.00	.00	.00	.84	.84	.84	.71	.71	.71	.58	.58	.58	.52
1.0	.92	.87	.83	.85	.81	.77	.72	.69	.66	.60	.58	.56	.49	.47	.46	.41
2.0	.79	.73	.67	.73	.67	.62	.62	.58	.54	.52	.49	.46	.42	.40	.38	.33
3.0	.69	.61	.55	.64	.57	.52	.54	.49	.45	.45	.41	.38	.37	.34	.32	.27
4.0	.61	.53	.46	.57	.49	.43	.48	.42	.38	.40	.36	.32	.33	.30	.27	.23
5.0	.54	.46	.39	.50	.43	.37	.43	.37	.32	.36	.31	.28	.29	.26	.23	.20
6.0	.49	.40	.34	.45	.38	.32	.39	.33	.28	.32	.28	.24	.27	.23	.20	.17
7.0	.44	.36	.30	.41	.33	.28	.35	.29	.25	.29	.25	.21	.24	.21	.18	.15
8.0	.40	.32	.26	.37	.30	.25	.32	.26	.22	.27	.22	.19	.22	.19	.16	.14
9.0	.36	.29	.23	.34	.27	.22	.29	.23	.19	.25	.20	.17	.21	.17	.14	.12
10.0	.33	.26	.21	.31	.24	.20	.27	.21	.18	.23	.18	.15	.19	.16	.13	.11



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-06-24

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

WEC AND CCEC

Test:U:220.23V I:0.6553A P:140.62W PF:0.9743 Freq:50.00Hz Lamp Flux:8720.66x1 lm		
NAME: SB-J01P140WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1500*750mm	

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Wall Exitance Coefficients(WEC)															
0.0																
1.0	.321	.182	.058	.299	.171	.054	.259	.148	.047	.221	.128	.041	.187	.109	.035	
2.0	.287	.157	.048	.267	.147	.045	.230	.128	.040	.196	.110	.034	.165	.093	.029	
3.0	.260	.138	.041	.242	.129	.039	.208	.113	.034	.177	.097	.030	.148	.082	.025	
4.0	.237	.123	.036	.220	.115	.034	.190	.101	.030	.161	.086	.026	.134	.073	.022	
5.0	.218	.111	.032	.202	.104	.030	.174	.091	.027	.148	.078	.023	.123	.066	.020	
6.0	.201	.101	.029	.187	.094	.027	.161	.082	.024	.136	.071	.021	.113	.060	.018	
7.0	.186	.092	.026	.174	.087	.025	.149	.076	.022	.127	.065	.019	.105	.055	.016	
8.0	.174	.085	.024	.162	.080	.023	.139	.070	.020	.118	.060	.017	.098	.050	.015	
9.0	.163	.079	.022	.152	.074	.021	.131	.065	.018	.111	.055	.016	.092	.047	.013	
10.0	.153	.073	.020	.142	.069	.019	.123	.060	.017	.104	.052	.015	.087	.044	.012	

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Ceiling Cavity Exitance Coefficients(CCEC)															
0.0	.556	.556	.556	.475	.475	.475	.324	.324	.324	.186	.186	.186	.060	.060	.060	
1.0	.550	.525	.502	.470	.450	.432	.322	.310	.299	.185	.179	.174	.059	.058	.056	
2.0	.543	.503	.470	.465	.433	.406	.318	.300	.283	.184	.174	.166	.059	.056	.054	
3.0	.535	.487	.449	.459	.420	.389	.315	.292	.273	.182	.171	.161	.058	.055	.053	
4.0	.528	.475	.435	.453	.411	.378	.312	.286	.266	.180	.168	.157	.058	.055	.052	
5.0	.522	.466	.425	.448	.403	.370	.309	.282	.261	.179	.165	.155	.058	.054	.051	
6.0	.515	.459	.418	.443	.397	.364	.305	.278	.258	.177	.164	.153	.057	.053	.051	
7.0	.509	.452	.413	.438	.392	.360	.302	.275	.255	.176	.162	.152	.057	.053	.050	
8.0	.503	.447	.409	.433	.388	.357	.300	.272	.253	.174	.161	.151	.056	.053	.050	
9.0	.497	.443	.406	.428	.384	.354	.297	.270	.251	.173	.160	.150	.056	.052	.050	
10.0	.492	.439	.404	.424	.381	.352	.294	.268	.250	.172	.159	.149	.056	.052	.050	

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-06-24

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

UGR(Unified Glare Rating) Table

Test:U:220.23V I:0.6553A P:140.62W PF:0.9743 Freq:50.00Hz Lamp Flux:8720.66x1 lm											
NAME: SB-J01P140WSZ					TYPE:			WEIGHT:			
SPEC.:4000K					DIM.:			SERIAL No.:			
MFR.: SNOWBALL					SUR.:1500*750mm						
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	Viewed crosswise					Viewed endwise					
x = 2H y = 2H	10.0	11.0	10.8	11.8	12.9	10.3	11.3	11.1	12.1	13.2	
	3H	11.7	12.6	12.6	13.5	14.6	12.3	13.2	13.1	14.0	15.2
	4H	12.5	13.4	13.4	14.3	15.4	13.3	14.2	14.2	15.0	16.2
	6H	13.3	14.1	14.2	15.0	16.2	14.4	15.2	15.3	16.1	17.3
	8H	13.7	14.5	14.6	15.4	16.6	15.0	15.7	15.9	16.6	17.8
	12H	14.1	14.9	15.0	15.8	17.0	15.5	16.3	16.4	17.2	18.4
4H	2H	10.7	11.5	11.6	12.4	13.6	10.9	11.7	11.8	12.6	13.8
	3H	12.7	13.4	13.6	14.3	15.5	13.2	13.9	14.1	14.8	16.0
	4H	13.7	14.4	14.7	15.3	16.5	14.4	15.0	15.3	16.0	17.2
	6H	14.7	15.3	15.7	16.2	17.5	15.7	16.2	16.6	17.2	18.4
	8H	15.2	15.7	16.2	16.7	17.9	16.3	16.9	17.3	17.8	19.1
	12H	15.7	16.2	16.7	17.2	18.4	17.0	17.5	18.0	18.4	19.7
8H	4H	14.3	14.8	15.2	15.8	17.0	14.8	15.4	15.8	16.3	17.6
	6H	15.6	16.0	16.6	17.0	18.3	16.4	16.8	17.4	17.8	19.1
	8H	16.3	16.7	17.3	17.7	19.0	17.3	17.6	18.3	18.6	19.9
	12H	17.0	17.3	18.0	18.3	19.6	18.1	18.5	19.1	19.5	20.8
12H	4H	14.4	14.9	15.4	15.9	17.1	14.9	15.4	15.9	16.3	17.6
	6H	15.9	16.2	16.8	17.2	18.5	16.6	17.0	17.6	18.0	19.3
	8H	16.7	17.0	17.7	18.0	19.3	17.5	17.9	18.6	18.9	20.2
Variations with the observer position at spacings:											
S = 1.0H	+ 0.1 / - 0.1					+ 0.1 / - 0.1					
1.5H	+ 0.2 / - 0.3					+ 0.2 / - 0.3					
2.0H	+ 0.2 / - 0.4					+ 0.2 / - 0.4					

CIE Pub.117, 8721 lm Total Lamp Luminous Flux Corrected ($8\log(F/F_0) = 7.5$)
Area: 1.125 m²

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:XIAOMI
Test Date:2023-06-24

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:9.000m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:220.23V I:0.6553A P:140.62W PF:0.9743 Freq:50.00Hz Lamp Flux:8720.66x1 lm		
NAME: SB-J01P140WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1500*750mm	


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	43	31	25	40	30	24	36	28	22	15
0.80	52	40	32	49	38	31	43	34	29	19
1.00	59	47	39	56	45	38	49	42	34	23
1.25	66	54	46	62	51	44	54	46	40	26
1.50	71	60	52	66	56	49	58	50	44	29
2.00	79	68	61	73	64	57	63	56	51	33
2.50	83	74	66	77	69	63	66	60	55	35
3.00	87	78	71	80	73	67	69	63	59	37
4.00	91	84	78	85	78	73	72	68	64	40
5.00	94	88	83	87	82	77	74	70	67	42
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-06-24

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

ISOCANDELA DIAGRAM

Test:U:220.23V I:0.6553A P:140.62W PF:0.9743 Freq:50.00Hz Lamp Flux:8720.66x1 lm		
NAME: SB-J01P140WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1500*750mm	




C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-06-24

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

AAI Figure

Test:U:220.23V I:0.6553A P:140.62W PF:0.9743 Freq:50.00Hz Lamp Flux:8720.66x1 lm		
NAME: SB-J01P140WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1500*750mm	

Flux out:2839 lm




Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: XIAOMI
 Test Date: 2023-06-24

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity: 65.0%
 Test Distance: 9.000m [K=1.0000]
 Remarks:

ISOLUX DIAGRAM


Test:U:220.23V I:0.6553A P:140.62W PF:0.9743 Freq:50.00Hz Lamp Flux:8720.66x1 lm		
NAME: SB-J01P140WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1500*750mm	



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-06-24

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: XIAOMI
Test Date: 2023-06-24

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity: 65.0%
Test Distance: 9.000m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:220.23V I:0.6553A P:140.62W PF:0.9743 Freq:50.00Hz Lamp Flux:8720.66x1 lm																	
NAME: SB-J01P140WSZ									TYPE:						WEIGHT:		
SPEC.:4000K									DIM.:						SERIAL No.:		
MFR.: SNOWBALL									SUR.:1500*750mm								

Table--1

UNIT: cd

C(DEG) γ (DEG)	0	22.5	45	67.5	90	112.5	135	157.5	180	202.5	225	247.5	270	292.5	315	337.5			
0	1457	1455	1453	1450	1447	1445	1443	1441	1457	1455	1453	1450	1447	1445	1443	1441			
5	1452	1448	1441	1433	1425	1426	1429	1433	1454	1454	1450	1446	1441	1441	1441	1438			
10	1428	1421	1404	1394	1385	1386	1395	1411	1437	1437	1429	1417	1411	1410	1409	1413			
15	1385	1373	1361	1352	1338	1344	1350	1363	1398	1398	1393	1391	1379	1378	1373	1363			
20	1325	1311	1307	1294	1276	1285	1293	1302	1344	1338	1348	1341	1323	1324	1319	1297			
25	1252	1242	1241	1228	1207	1216	1225	1234	1275	1271	1287	1274	1250	1254	1251	1229			
30	1169	1166	1168	1157	1133	1143	1152	1158	1195	1199	1214	1194	1167	1170	1176	1155			
35	1079	1085	1092	1083	1057	1067	1075	1078	1108	1118	1133	1111	1081	1086	1094	1072			
40	985	1000	1014	1007	978	991	996	995	1016	1033	1048	1028	996	1004	1011	987			
45	890	916	934	930	900	916	919	910	921	945	964	948	917	924	929	901			
50	794	830	856	852	822	839	843	825	824	856	883	870	839	845	849	816			
55	699	746	779	772	742	761	767	741	726	766	801	789	760	771	768	730			
60	602	661	700	695	660	683	690	658	632	679	721	712	680	693	690	646			
65	510	582	622	618	581	608	613	582	539	593	642	633	607	617	616	563			
70	419	498	547	545	505	533	537	502	448	508	568	560	529	539	542	481			
75	335	418	473	473	433	460	464	425	362	429	492	483	456	460	464	403			
80	257	343	402	403	363	389	394	350	282	352	418	407	380	392	394	328			
85	185	270	327	314	271	286	304	272	210	278	335	322	294	309	315	256			
90	147	154	244	264	235	245	224	138	146	173	242	265	260	268	256	168			
95	204	266	308	274	267	296	325	262	192	245	284	272	264	287	313	251			
100	279	333	398	380	381	393	401	342	265	300	349	359	343	369	372	305			
105	356	416	456	459	454	459	451	423	345	368	399	425	419	441	413	388			
110	432	476	494	537	533	522	506	485	427	439	400	497	491	498	462	460			
115	468	534	602	611	611	617	614	528	456	483	530	559	567	578	570	514			
120	548	617	688	697	694	699	683	619	563	574	603	647	643	641	658	599			
125	615	676	761	774	770	773	689	623	607	612	635	700	742	746	742	665			
130	689	745	831	861	851	786	698	673	679	671	682	735	823	829	817	736			
135	765	811	899	942	933	763	742	737	748	731	735	761	895	917	885	815			
140	840	914	956	992	904	812	775	804	819	810	774	832	851	982	963	898			
145	1016	1015	1006	1021	882	881	881	971	984	954	898	900	897	1023	1022	1015			
150	1118	1115	1074	1049	926	987	1054	1123	1098	1123	1047	1018	999	1052	1079	1114			
155	1217	1210	1168	1082	1053	1158	1222	1196	1198	1205	1209	1154	1076	1101	1154	1207			
160	1305	1293	1256	1140	1124	1309	1298	1254	1287	1264	1296	1282	1161	1126	1247	1288			
165	1377	1370	1313	1184	1355	1388	1351	1317	1357	1328	1353	1376	1362	1199	1313	1353			
170	1427	1413	1352	1276	1418	1418	1394	1363	1411	1375	1405	1408	1411	1320	1357	1398			
175	1454	1435	1387	1400	1435	1433	1401	1404	1444	1414	1414	1425	1432	1421	1398	1425			
180	1458	1438	1411	1434	1435	1437	1413	1429	1461	1435	1414	1431	1436	1435	1416	1428			

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:XIAOMI
Test Date:2023-06-24

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:9.000m [K=1.0000]
Remarks: