


LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:220.11V I:0.5620A P:118.76W PF:0.9600 Freq:50.00Hz Lamp Flux:7302.32x1 lm		
NAME: SB-J01P120WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1200*600mm	

DATA OF LAMP		PHOTOMETRIC DATA Eff: 61.49 lm/W			
MODEL		I _{max} (cd)	1207	S/MH(C0/180)	1.22
NOMINAL POWER(W)		LOR(%)	100.0	S/MH(C90/270)	1.24
RATED VOLTAGE(V)	--	TOTAL FLUX(lm)	7302.3	η UP,DN(C0-180)	23.0,26.9
NOMINAL FLUX(lm)	7302.32	CIE CLASS	DIFFUSE	η UP,DN(C180-360)	22.8,27.3
LAMPS INSIDE	1	η up(%)	45.8	CIBSE SHR NOM	1.25
TEST VOLTAGE(V)	--	η down(%)	54.2	CIBSE SHR MAX	1.35



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-06-24

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum, lamp
10	1188	1198	1194	1188	1182	1190	1190	1191	0- 10	114.1	114.1	1.56,1.56
20	1108	1141	1119	1125	1102	1123	1113	1128	10- 20	327.8	441.9	6.05,6.05
30	985.0	1024	994.5	1007	980.7	1008	1002	1015	20- 30	490.8	932.7	12.8,12.8
40	838.0	889.7	860.3	878.0	842.8	885.4	874.1	885.8	30- 40	588.0	1521	20.8,20.8
50	683.8	749.8	720.8	748.6	703.2	763.5	740.4	750.7	40- 50	621.6	2142	29.3,29.3
60	525.2	609.5	576.8	614.8	562.4	639.6	599.4	611.0	50- 60	596.4	2739	37.5,37.5
70	372.9	469.6	439.7	487.2	421.0	511.3	452.9	480.7	60- 70	523.2	3262	44.7,44.7
80	238.9	337.2	318.0	368.7	289.6	387.7	327.7	358.1	70- 80	417.7	3680	50.4,50.4
90	126.5	148.5	119.3	175.6	157.0	205.7	142.5	170.6	80- 90	279.9	3960	54.2,54.2
100	252.8	320.5	301.3	335.3	259.3	317.1	288.2	315.0	90-100	256.9	4217	57.7,57.7
110	379.5	414.0	399.6	444.1	381.5	392.5	395.4	393.2	100-110	370.7	4587	62.8,62.8
120	444.6	553.9	524.9	556.6	442.0	535.3	522.0	527.3	110-120	447.1	5034	68.9,68.9
130	563.5	675.6	652.1	589.5	560.7	597.6	646.6	653.8	120-130	509.0	5543	75.9,75.9
140	669.1	771.5	781.5	616.1	653.9	640.4	765.1	754.1	130-140	506.8	6050	82.9,82.9
150	860.0	855.0	728.1	715.3	828.5	736.9	782.2	857.2	140-150	463.6	6514	89.2,89.2
160	1011	966.2	823.8	950.8	987.8	953.1	882.9	962.9	150-160	400.9	6915	94.7,94.7
170	1117	1045	1046	1069	1085	1042	1091	1058	160-170	284.7	7199	98.6,98.6
180	1128	1061	1100	1087	1131	1063	1100	1088	170-180	103.0	7302	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

Conical surface Flux(90deg): 1831.1 lm

%lum = 25.1%

%lamp = 25.1%

Conical surface Flux(120deg): 2738.8 lm

%lum = 37.5%


%lamp = 37.5%

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-06-24

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:220.11V I:0.5620A P:118.76W PF:0.9600 Freq:50.00Hz Lamp Flux:7302.32x1 lm		
NAME: SB-J01P120WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1200*600mm	




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:XIAOMI
Test Date:2023-06-24

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:9.000m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:220.11V I:0.5620A P:118.76W PF:0.9600 Freq:50.00Hz Lamp Flux:7302.32x1 lm		
NAME: SB-J01P120WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1200*600mm	

ρ_{cc}	80%			70%			50%			30%			10%			0
ρ_w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρ_{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Coefficients of Utilization(CU)															
0.0	1.08	1.08	1.08	1.00	1.00	1.00	.86	.86	.86	.72	.72	.72	.60	.60	.60	.54
1.0	.92	.88	.83	.85	.81	.78	.73	.70	.67	.61	.59	.57	.50	.49	.47	.42
2.0	.80	.73	.67	.74	.68	.63	.63	.58	.54	.53	.49	.46	.44	.41	.39	.34
3.0	.69	.61	.55	.64	.57	.52	.55	.49	.45	.46	.42	.39	.38	.35	.32	.28
4.0	.61	.53	.46	.57	.49	.43	.49	.43	.38	.41	.36	.33	.34	.30	.27	.24
5.0	.54	.46	.39	.50	.43	.37	.43	.37	.32	.37	.32	.28	.30	.27	.24	.20
6.0	.49	.40	.34	.45	.38	.32	.39	.33	.28	.33	.28	.24	.27	.24	.21	.18
7.0	.44	.35	.30	.41	.33	.28	.35	.29	.25	.30	.25	.21	.25	.21	.18	.16
8.0	.40	.32	.26	.37	.30	.25	.32	.26	.22	.27	.23	.19	.23	.19	.16	.14
9.0	.36	.28	.23	.34	.27	.22	.29	.24	.20	.25	.20	.17	.21	.17	.15	.13
10.0	.33	.26	.21	.31	.24	.20	.27	.21	.18	.23	.19	.15	.20	.16	.13	.11



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-06-24

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

WEC AND CCEC

Test:U:220.11V I:0.5620A P:118.76W PF:0.9600 Freq:50.00Hz Lamp Flux:7302.32x1 lm		
NAME: SB-J01P120WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1200*600mm	

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Wall Exitance Coefficients(WEC)															
0.0																
1.0	.326	.185	.059	.305	.174	.055	.266	.152	.049	.230	.132	.042	.196	.114	.037	
2.0	.291	.159	.049	.272	.150	.046	.236	.131	.041	.203	.114	.036	.172	.097	.031	
3.0	.263	.140	.042	.245	.131	.040	.213	.115	.035	.182	.100	.031	.154	.085	.026	
4.0	.239	.124	.037	.224	.117	.035	.194	.103	.031	.166	.089	.027	.140	.076	.023	
5.0	.220	.112	.032	.205	.105	.031	.178	.092	.027	.152	.080	.024	.128	.068	.021	
6.0	.203	.102	.029	.189	.096	.028	.164	.084	.024	.140	.073	.021	.118	.062	.018	
7.0	.188	.093	.026	.176	.088	.025	.152	.077	.022	.130	.067	.019	.109	.057	.017	
8.0	.175	.086	.024	.164	.081	.023	.142	.071	.020	.121	.061	.018	.102	.052	.015	
9.0	.164	.079	.022	.153	.075	.021	.133	.066	.019	.114	.057	.016	.096	.049	.014	
10.0	.154	.074	.020	.144	.070	.019	.125	.061	.017	.107	.053	.015	.090	.045	.013	

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Ceiling Cavity Exitance Coefficients(CCEC)															
0.0	.539	.539	.539	.461	.461	.461	.315	.315	.315	.181	.181	.181	.058	.058	.058	
1.0	.533	.508	.485	.456	.436	.417	.312	.300	.289	.180	.173	.168	.058	.056	.054	
2.0	.526	.486	.452	.451	.418	.391	.309	.289	.273	.178	.168	.160	.057	.054	.052	
3.0	.519	.470	.431	.445	.406	.374	.305	.282	.262	.176	.165	.155	.057	.053	.051	
4.0	.512	.458	.417	.439	.396	.362	.302	.276	.255	.175	.162	.151	.056	.053	.050	
5.0	.505	.449	.408	.434	.388	.355	.299	.271	.250	.173	.159	.148	.056	.052	.049	
6.0	.498	.441	.401	.428	.382	.349	.296	.268	.247	.171	.157	.147	.055	.051	.048	
7.0	.492	.435	.395	.423	.377	.345	.292	.264	.244	.170	.156	.145	.055	.051	.048	
8.0	.486	.430	.391	.418	.373	.341	.290	.262	.242	.168	.154	.144	.054	.051	.048	
9.0	.480	.425	.388	.414	.369	.339	.287	.260	.241	.167	.153	.143	.054	.050	.048	
10.0	.475	.422	.386	.410	.366	.337	.284	.258	.239	.166	.152	.143	.054	.050	.047	

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-06-24

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

UGR(Unified Glare Rating) Table

Test:U:220.11V I:0.5620A P:118.76W PF:0.9600 Freq:50.00Hz Lamp Flux:7302.32x1 lm											
NAME: SB-J01P120WSZ					TYPE:			WEIGHT:			
SPEC.:4000K					DIM.:			SERIAL No.:			
MFR.: SNOWBALL					SUR.:1200*600mm						
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	Viewed crosswise					Viewed endwise					
x = 2H y = 2H	11.2	12.3	12.0	13.1	14.1	11.5	12.5	12.3	13.4	14.4	
	3H	13.0	13.9	13.9	14.8	15.9	13.5	14.4	14.3	15.3	16.3
	4H	13.9	14.7	14.7	15.6	16.7	14.5	15.4	15.4	16.3	17.4
	6H	14.7	15.5	15.6	16.4	17.5	15.6	16.4	16.5	17.3	18.4
	8H	15.2	15.9	16.0	16.8	18.0	16.2	17.0	17.1	17.9	19.0
	12H	15.6	16.4	16.5	17.3	18.4	16.8	17.6	17.7	18.5	19.6
4H	2H	12.0	12.8	12.8	13.7	14.8	12.1	13.0	13.0	13.9	15.0
	3H	14.0	14.7	14.9	15.6	16.8	14.4	15.1	15.3	16.0	17.2
	4H	15.0	15.7	15.9	16.6	17.8	15.6	16.2	16.5	17.2	18.3
	6H	16.1	16.7	17.0	17.6	18.8	16.9	17.4	17.8	18.4	19.6
	8H	16.6	17.1	17.5	18.1	19.3	17.5	18.1	18.5	19.0	20.3
	12H	17.2	17.7	18.1	18.6	19.8	18.2	18.7	19.2	19.7	20.9
8H	4H	15.6	16.1	16.5	17.1	18.3	16.0	16.6	16.9	17.5	18.7
	6H	16.9	17.4	17.9	18.3	19.6	17.6	18.0	18.5	19.0	20.2
	8H	17.6	18.0	18.6	19.0	20.3	18.4	18.9	19.4	19.8	21.1
	12H	18.4	18.7	19.4	19.7	21.0	19.3	19.7	20.3	20.7	21.9
12H	4H	15.7	16.2	16.6	17.1	18.4	16.1	16.6	17.0	17.5	18.8
	6H	17.1	17.5	18.1	18.5	19.8	17.7	18.1	18.7	19.1	20.4
	8H	18.0	18.3	19.0	19.3	20.6	18.7	19.1	19.7	20.1	21.4
Variations with the observer position at spacings:											
S = 1.0H	+ 0.1 / - 0.1					+ 0.1 / - 0.1					
1.5H	+ 0.2 / - 0.3					+ 0.2 / - 0.3					
2.0H	+ 0.2 / - 0.4					+ 0.2 / - 0.4					

CIE Pub.117, 7302 lm Total Lamp Luminous Flux Corrected ($8\log(F/F_0) = 6.9$)
Area: 0.72 m²

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:XIAOMI
Test Date:2023-06-24

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:9.000m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:220.11V I:0.5620A P:118.76W PF:0.9600 Freq:50.00Hz Lamp Flux:7302.32x1 lm		
NAME: SB-J01P120WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1200*600mm	


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	43	31	25	41	30	24	37	28	23	15
0.80	52	40	32	49	38	31	44	35	29	19
1.00	60	47	40	56	45	38	50	42	35	23
1.25	66	55	47	62	52	44	55	46	40	27
1.50	72	60	52	67	57	50	58	51	45	30
2.00	79	69	61	74	64	58	64	57	51	34
2.50	83	74	67	78	69	63	67	61	56	36
3.00	87	78	72	81	73	67	70	64	59	39
4.00	92	84	78	85	79	74	73	68	64	42
5.00	95	88	83	88	82	78	75	71	68	44
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-06-24

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

ISOCANDELA DIAGRAM

Test:U:220.11V I:0.5620A P:118.76W PF:0.9600 Freq:50.00Hz Lamp Flux:7302.32x1 lm		
NAME: SB-J01P120WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1200*600mm	




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:XIAOMI
Test Date:2023-06-24

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:9.000m [K=1.0000]
Remarks:

AAI Figure

Test:U:220.11V I:0.5620A P:118.76W PF:0.9600 Freq:50.00Hz Lamp Flux:7302.32x1 lm		
NAME: SB-J01P120WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1200*600mm	




Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: XIAOMI
 Test Date: 2023-06-24

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity: 65.0%
 Test Distance: 9.000m [K=1.0000]
 Remarks:

ISOLUX DIAGRAM


Test:U:220.11V I:0.5620A P:118.76W PF:0.9600 Freq:50.00Hz Lamp Flux:7302.32x1 lm		
NAME: SB-J01P120WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1200*600mm	



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-06-24

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: XIAOMI
Test Date: 2023-06-24

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity: 65.0%
Test Distance: 9.000m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:220.11V I:0.5620A P:118.76W PF:0.9600 Freq:50.00Hz Lamp Flux:7302.32x1 lm																	
NAME: SB-J01P120WSZ									TYPE:						WEIGHT:		
SPEC.:4000K									DIM.:						SERIAL No.:		
MFR.: SNOWBALL									SUR.:1200*600mm								

Table--1

UNIT: cd

C(DEC) γ (DEC)	0	22.5	45	67.5	90	112.5	135	157.5	180	202.5	225	247.5	270	292.5	315	337.5			
0	1206	1206	1205	1203	1201	1200	1200	1198	1206	1206	1205	1203	1201	1200	1200	1198			
5	1203	1204	1203	1203	1201	1196	1195	1194	1201	1199	1197	1195	1197	1197	1194	1194			
10	1188	1193	1198	1196	1194	1191	1188	1177	1182	1180	1190	1191	1190	1191	1191	1182			
15	1155	1167	1179	1176	1167	1170	1164	1149	1149	1151	1164	1167	1162	1167	1169	1158			
20	1108	1125	1141	1132	1119	1124	1125	1107	1102	1112	1123	1119	1113	1118	1128	1116			
25	1052	1076	1087	1077	1060	1066	1069	1056	1046	1058	1068	1067	1060	1069	1072	1063			
30	985	1017	1024	1016	994	1004	1007	1000	981	996	1008	1007	1002	1008	1015	1003			
35	912	949	958	950	927	939	943	937	912	932	947	947	938	950	948	934			
40	838	875	890	881	860	873	878	870	843	867	885	886	874	888	886	866			
45	762	802	820	810	791	806	814	805	774	801	825	824	810	819	820	796			
50	684	727	750	741	721	740	749	737	703	739	764	760	740	754	751	718			
55	601	654	679	671	649	673	682	669	630	672	702	693	670	684	681	644			
60	525	586	610	604	577	608	615	605	562	604	640	625	599	613	611	574			
65	447	510	539	535	508	542	550	538	489	536	577	555	523	542	544	503			
70	373	439	470	467	440	477	487	474	421	473	511	489	453	475	481	430			
75	303	368	402	403	378	413	427	409	353	409	448	424	389	411	419	366			
80	239	301	337	339	318	351	369	346	290	346	388	364	328	350	358	305			
85	182	233	257	238	238	268	303	284	232	285	322	279	232	275	286	239			
90	127	133	149	137	119	158	176	190	157	190	206	168	143	168	171	163			
95	197	228	264	243	201	232	269	241	208	242	268	244	221	249	268	229			
100	253	293	321	309	301	312	335	305	259	301	317	319	288	309	315	275			
105	314	352	358	361	346	358	375	359	317	357	340	364	337	362	333	337			
110	379	418	414	406	400	404	444	427	382	418	392	409	395	403	393	402			
115	450	464	474	468	461	466	469	468	449	462	427	462	457	466	447	435			
120	445	486	554	539	525	531	557	473	442	452	535	523	522	528	527	451			
125	526	563	612	608	590	599	596	562	520	551	586	590	580	586	589	539			
130	563	608	676	672	652	654	589	567	561	553	598	652	647	651	654	574			
135	612	653	723	739	717	643	590	580	606	569	610	674	706	716	704	631			
140	669	711	771	807	781	623	616	618	654	611	640	679	765	784	754	696			
145	725	770	821	845	716	663	647	660	699	654	679	719	749	830	810	761			
150	860	876	855	853	728	702	715	796	829	753	737	762	782	870	857	859			
155	944	952	900	868	766	765	831	910	915	864	837	814	837	892	901	933			
160	1011	1017	966	872	824	893	951	974	988	937	953	917	883	901	963	1003			
165	1074	1075	1029	924	1031	1018	1041	1020	1040	999	1023	1043	975	946	1028	1063			
170	1117	1110	1045	945	1046	1106	1069	1060	1085	1042	1042	1107	1091	1003	1058	1101			
175	1126	1120	1056	1017	1088	1109	1083	1087	1114	1074	1052	1102	1104	1064	1077	1110			
180	1128	1100	1061	1075	1100	1108	1087	1101	1131	1098	1063	1075	1100	1106	1088	1099			

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:XIAOMI
Test Date:2023-06-24

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:9.000m [K=1.0000]
Remarks: