


LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:220.29V I:0.4843A P:100.11W PF:0.9383 Freq:50.00Hz Lamp Flux:6361.51x1 lm		
NAME: SB-J01C100WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1000*1000mm	

DATA OF LAMP		PHOTOMETRIC DATA Eff: 63.55 lm/W			
MODEL		I _{max} (cd)	1202	S/MH(C0/180)	1.25
NOMINAL POWER(W)		LOR(%)	100.0	S/MH(C90/270)	1.24
RATED VOLTAGE(V)	--	TOTAL FLUX(lm)	6361.5	η UP,DN(C0-180)	21.6,28.3
NOMINAL FLUX(lm)	6361.51	CIE CLASS	DIFFUSE	η UP,DN(C180-360)	19.6,30.5
LAMPS INSIDE	1	η up(%)	41.2	CIBSE SHR NOM	1.25
TEST VOLTAGE(V)	--	η down(%)	58.8	CIBSE SHR MAX	1.35



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-06-25

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum,lamp
10	1163	1164	1155	1173	1200	1194	1187	1175	0- 10	113.2	113.2	1.78,1.78
20	1069	1063	1047	1101	1138	1151	1118	1104	10- 20	322.6	435.8	6.85,6.85
30	946.5	933.9	907.9	975.5	1014	1040	993.3	990.6	20- 30	479.6	915.4	14.4,14.4
40	810.6	800.9	763.7	833.7	863.7	896.5	850.1	856.3	30- 40	568.3	1484	23.3,23.3
50	667.7	673.1	617.6	694.2	708.8	751.9	704.8	721.3	40- 50	592.3	2076	32.6,32.6
60	522.5	545.4	477.0	559.1	559.7	613.5	562.2	596.7	50- 60	562.2	2638	41.5,41.5
70	384.5	418.8	340.9	425.4	410.1	473.8	412.3	464.4	60- 70	485.0	3123	49.1,49.1
80	258.0	297.5	220.5	300.2	272.9	339.0	276.9	333.2	70- 80	374.7	3498	55.5,55
90	124.9	161.6	107.5	136.3	115.5	183.7	146.8	181.6	80- 90	242.1	3740	58.8,58.8
100	239.2	295.5	232.2	268.8	203.4	249.3	211.7	272.6	90-100	212.5	3953	62.1,62.1
110	330.6	389.8	331.0	356.4	287.4	320.6	290.8	342.3	100-110	305.9	4259	66.9,66.9
120	416.1	438.3	436.4	399.4	352.7	344.6	381.2	377.5	110-120	362.8	4621	72.6,72.6
130	442.6	562.4	513.6	478.8	396.3	434.1	469.2	487.6	120-130	385.9	5007	78.7,78.7
140	544.5	646.3	562.9	515.5	411.1	465.8	500.2	585.0	130-140	391.8	5399	84.9,84.9
150	635.1	751.5	616.3	597.7	485.2	542.2	554.5	701.3	140-150	355.7	5755	90.5,90.5
160	793.7	823.9	743.5	705.5	731.1	651.7	675.6	776.5	150-160	311.9	6067	95.4,95.4
170	841.6	832.8	799.6	771.8	815.7	725.4	747.9	772.7	160-170	217.8	6284	98.8,98.8
180	853.4	809.4	805.4	808.2	854.7	810.6	806.4	809.0	170-180	77.16	6362	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

Conical surface Flux(90deg): 1780.5 lm

%lum = 28.0%

%lamp = 28.0%

Conical surface Flux(120deg): 2638.3 lm

%lum = 41.5%


%lamp = 41.5%

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-06-25

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:220.29V I:0.4843A P:100.11W PF:0.9383 Freq:50.00Hz Lamp Flux:6361.51x1 lm		
NAME: SB-J01C100WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1000*1000mm	




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:XIAOMI
Test Date:2023-06-25

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:9.000m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:220.29V I:0.4843A P:100.11W PF:0.9383 Freq:50.00Hz Lamp Flux:6361.51lx1 lm		
NAME: SB-J01C100WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1000*1000mm	

ρ_{cc}	80%			70%			50%			30%			10%			0
ρ_w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρ_{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Coefficients of Utilization(CU)									
0.0	1.09	1.09	1.09	1.02	1.02	1.02	.88	.88	.88	.76	.76	.76	.64	.64	.64	.59
1.0	.93	.89	.85	.87	.83	.79	.75	.72	.69	.64	.62	.60	.54	.53	.51	.46
2.0	.81	.74	.68	.75	.69	.64	.65	.60	.56	.56	.52	.49	.47	.44	.42	.38
3.0	.70	.62	.56	.66	.59	.53	.57	.51	.47	.49	.44	.41	.41	.38	.35	.31
4.0	.62	.53	.47	.58	.50	.44	.50	.44	.39	.43	.38	.35	.37	.33	.30	.26
5.0	.55	.46	.40	.52	.44	.38	.45	.39	.34	.39	.34	.30	.33	.29	.26	.23
6.0	.49	.41	.35	.46	.39	.33	.40	.34	.29	.35	.30	.26	.30	.26	.23	.20
7.0	.45	.36	.30	.42	.34	.29	.37	.30	.26	.32	.27	.23	.27	.23	.20	.17
8.0	.40	.32	.27	.38	.31	.25	.33	.27	.23	.29	.24	.20	.25	.21	.18	.16
9.0	.37	.29	.24	.35	.28	.23	.31	.25	.21	.27	.22	.18	.23	.19	.16	.14
10.0	.34	.26	.21	.32	.25	.20	.28	.22	.18	.25	.20	.17	.21	.17	.15	.13



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:XIAOMI
Test Date:2023-06-25

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:9.000m [K=1.0000]
Remarks:

WEC AND CCEC

Test:U:220.29V I:0.4843A P:100.11W PF:0.9383 Freq:50.00Hz Lamp Flux:6361.51x1 lm		
NAME: SB-J01C100WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1000*1000mm	

pcc	80%			70%			50%			30%			10%			0	
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
pfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)										
0.0																	
1.0	.326	.185	.059	.306	.175	.055	.269	.155	.049	.236	.136	.044	.205	.119	.038		
2.0	.291	.160	.049	.273	.151	.046	.240	.134	.041	.209	.117	.037	.181	.102	.032		
3.0	.264	.140	.042	.247	.133	.040	.217	.118	.036	.189	.103	.032	.163	.090	.028		
4.0	.240	.125	.037	.226	.118	.035	.198	.105	.031	.172	.092	.028	.148	.080	.024		
5.0	.221	.112	.033	.207	.106	.031	.182	.095	.028	.158	.083	.025	.135	.072	.022		
6.0	.204	.102	.029	.191	.097	.028	.168	.086	.025	.146	.076	.022	.125	.066	.020		
7.0	.189	.093	.026	.178	.088	.025	.156	.079	.023	.135	.069	.020	.116	.060	.018		
8.0	.176	.086	.024	.166	.081	.023	.145	.073	.021	.126	.064	.018	.108	.056	.016		
9.0	.165	.080	.022	.155	.076	.021	.136	.067	.019	.118	.059	.017	.102	.052	.015		
10.0	.155	.074	.021	.146	.070	.020	.128	.063	.018	.111	.055	.016	.096	.048	.014		

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)									
0.0	.504	.504	.504	.431	.431	.431	.294	.294	.294	.169	.169	.169	.054	.054	.054	
1.0	.498	.473	.450	.426	.406	.387	.291	.279	.268	.168	.161	.156	.054	.052	.050	
2.0	.491	.451	.417	.420	.388	.360	.288	.268	.251	.166	.156	.147	.053	.050	.048	
3.0	.484	.435	.396	.415	.375	.343	.285	.260	.241	.164	.152	.142	.053	.049	.046	
4.0	.476	.423	.381	.409	.365	.331	.281	.254	.233	.163	.149	.138	.052	.049	.045	
5.0	.470	.413	.372	.403	.357	.323	.278	.250	.228	.161	.147	.135	.052	.048	.045	
6.0	.463	.406	.364	.398	.351	.317	.274	.246	.225	.159	.145	.133	.051	.047	.044	
7.0	.456	.399	.359	.393	.346	.313	.271	.243	.222	.158	.143	.132	.051	.047	.044	
8.0	.450	.394	.355	.388	.342	.310	.268	.240	.220	.156	.142	.131	.050	.046	.043	
9.0	.445	.389	.352	.383	.338	.307	.265	.238	.218	.155	.140	.130	.050	.046	.043	
10.0	.439	.386	.350	.379	.335	.305	.263	.236	.217	.153	.139	.129	.050	.046	.043	

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-06-25

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

UGR(Unified Glare Rating) Table

Test:U:220.29V I:0.4843A P:100.11W PF:0.9383 Freq:50.00Hz Lamp Flux:6361.51x1 lm											
NAME: SB-J01C100WSZ					TYPE:			WEIGHT:			
SPEC.:4000K					DIM.:			SERIAL No.:			
MFR.: SNOWBALL					SUR.:1000*1000mm						
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H y = 2H	10.3	11.3	11.0	12.1	13.1	9.9	11.0	10.7	11.8	12.7	
	3H	12.2	13.1	13.0	13.9	14.9	11.7	12.7	12.5	13.5	14.5
	4H	13.1	14.0	14.0	14.9	15.9	12.6	13.5	13.4	14.3	15.3
	6H	14.1	14.9	14.9	15.8	16.8	13.5	14.3	14.3	15.2	16.2
	8H	14.6	15.4	15.4	16.3	17.3	13.9	14.7	14.8	15.6	16.6
	12H	15.2	15.9	16.0	16.8	17.9	14.4	15.2	15.2	16.0	17.1
4H	2H	10.9	11.8	11.7	12.6	13.6	10.6	11.5	11.5	12.4	13.4
	3H	13.0	13.8	13.9	14.7	15.7	12.7	13.5	13.5	14.3	15.4
	4H	14.2	14.9	15.1	15.8	16.9	13.7	14.4	14.6	15.3	16.4
	6H	15.3	16.0	16.2	16.9	18.0	14.8	15.4	15.7	16.3	17.4
	8H	15.9	16.5	16.8	17.4	18.6	15.3	15.9	16.2	16.8	18.0
	12H	16.6	17.1	17.5	18.1	19.2	15.9	16.4	16.8	17.3	18.5
8H	4H	14.6	15.2	15.5	16.1	17.2	14.3	14.8	15.2	15.7	16.9
	6H	16.1	16.5	17.0	17.5	18.7	15.6	16.1	16.5	17.0	18.2
	8H	16.9	17.3	17.8	18.2	19.4	16.3	16.8	17.3	17.7	18.9
	12H	17.7	18.1	18.7	19.1	20.3	17.1	17.5	18.1	18.4	19.6
12H	4H	14.7	15.2	15.6	16.1	17.3	14.3	14.9	15.3	15.8	17.0
	6H	16.2	16.7	17.2	17.6	18.8	15.8	16.3	16.8	17.2	18.4
	8H	17.1	17.5	18.1	18.5	19.7	16.7	17.0	17.6	18.0	19.2
Variations with the observer position at spacings:											
S = 1.0H	+ 0.1 / - 0.1					+ 0.1 / - 0.2					
1.5H	+ 0.2 / - 0.3					+ 0.2 / - 0.3					
2.0H	+ 0.2 / - 0.4					+ 0.2 / - 0.4					

CIE Pub.117, 6362 lm Total Lamp Luminous Flux Corrected ($8\log(F/F_0) = 6.4$)
Area: 1 m²

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:XIAOMI
Test Date:2023-06-25

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:9.000m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:220.29V I:0.4843A P:100.11W PF:0.9383 Freq:50.00Hz Lamp Flux:6361.51x1 lm		
NAME: SB-J01C100WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1000*1000mm	


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	44	33	26	42	32	26	39	30	24	17
0.80	54	41	34	51	40	33	46	37	31	22
1.00	61	49	41	58	47	40	52	45	37	26
1.25	68	56	48	64	54	46	57	49	43	30
1.50	73	62	54	69	59	52	61	53	47	33
2.00	80	70	63	75	66	60	66	59	54	37
2.50	85	76	68	80	71	65	70	63	58	40
3.00	88	80	73	83	75	69	72	67	62	42
4.00	93	86	80	87	81	76	76	71	67	46
5.00	96	90	85	90	84	80	78	74	70	48
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-06-25

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

ISOCANDELA DIAGRAM

Test:U:220.29V I:0.4843A P:100.11W PF:0.9383 Freq:50.00Hz Lamp Flux:6361.5lx1 lm		
NAME: SB-J01C100WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1000*1000mm	




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:XIAOMI
Test Date:2023-06-25

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:9.000m [K=1.0000]
Remarks:

AAI Figure

Test:U:220.29V I:0.4843A P:100.11W PF:0.9383 Freq:50.00Hz Lamp Flux:6361.51x1 lm		
NAME: SB-J01C100WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1000*1000mm	




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-06-25

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

ISOLUX DIAGRAM


Test:U:220.29V I:0.4843A P:100.11W PF:0.9383 Freq:50.00Hz Lamp Flux:6361.5lx1 lm		
NAME: SB-J01C100WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1000*1000mm	



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:XIAOMI
Test Date:2023-06-25

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:9.000m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: XIAOMI
Test Date: 2023-06-25

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity: 65.0%
Test Distance: 9.000m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:220.29V I:0.4843A P:100.11W PF:0.9383 Freq:50.00Hz Lamp Flux:6361.51x1 lm																	
NAME: SB-J01C100WSZ									TYPE:						WEIGHT:		
SPEC.:4000K									DIM.:						SERIAL No.:		
MFR.: SNOWBALL									SUR.:1000*1000mm								

Table--1

UNIT: cd

C(°) γ (°)	0	22.5	45	67.5	90	112.5	135	157.5	180	202.5	225	247.5	270	292.5	315	337.5			
0	1201	1199	1198	1196	1195	1193	1192	1191	1201	1199	1198	1196	1195	1193	1192	1191			
5	1193	1194	1192	1190	1186	1185	1188	1190	1201	1197	1194	1191	1191	1191	1188	1184			
10	1163	1166	1164	1161	1155	1160	1173	1187	1200	1196	1194	1189	1187	1185	1175	1158			
15	1123	1122	1117	1116	1107	1120	1145	1164	1179	1178	1184	1169	1162	1161	1146	1120			
20	1069	1070	1063	1057	1047	1069	1101	1121	1138	1144	1151	1134	1118	1119	1104	1075			
25	1010	1011	1000	990	979	1009	1042	1064	1081	1092	1102	1084	1060	1062	1051	1020			
30	947	948	934	922	908	943	976	998	1014	1029	1040	1023	993	998	991	959			
35	880	882	866	855	835	874	905	927	940	959	970	954	922	933	925	895			
40	811	815	801	786	764	804	834	853	864	885	897	883	850	864	856	829			
45	740	749	737	719	691	734	763	780	787	811	823	812	778	796	785	763			
50	668	682	673	653	618	664	694	709	709	736	752	742	705	729	721	696			
55	595	618	609	590	547	599	626	639	635	662	681	670	634	660	658	629			
60	522	551	545	524	477	529	559	571	560	588	614	597	562	586	597	560			
65	454	483	481	459	408	460	491	500	484	516	544	524	486	516	531	493			
70	384	416	419	393	341	394	425	431	410	444	474	451	412	447	464	425			
75	320	352	357	330	278	330	361	362	339	375	404	382	341	380	396	359			
80	258	291	298	269	221	267	300	298	273	309	339	313	277	314	333	294			
85	204	230	235	208	164	200	233	235	212	244	267	248	219	252	267	233			
90	125	145	162	133	107	123	136	124	116	148	184	170	147	165	182	133			
95	199	226	235	214	189	203	219	200	169	191	204	181	156	193	222	215			
100	239	268	295	266	232	251	269	241	203	228	249	231	212	245	273	254			
105	285	312	346	306	280	272	315	272	245	270	286	268	253	283	313	296			
110	331	370	390	372	331	348	356	325	287	300	321	325	291	343	342	334			
115	377	427	361	422	387	404	286	377	326	345	285	365	342	373	330	378			
120	416	421	438	452	436	436	399	366	353	329	345	403	381	406	378	381			
125	379	466	519	504	486	466	465	345	264	326	420	435	423	442	444	422			
130	443	527	562	561	514	483	479	472	396	444	434	447	469	496	488	483			
135	497	567	598	600	530	510	494	484	378	448	448	471	472	546	538	520			
140	544	606	646	631	563	533	516	481	411	440	466	489	500	576	585	558			
145	589	654	690	668	590	553	535	494	447	460	482	508	529	600	632	600			
150	635	731	751	696	616	618	598	508	485	470	542	565	554	628	701	684			
155	749	801	804	732	703	691	651	586	661	549	598	636	630	663	754	765			
160	794	832	824	775	744	738	705	689	731	667	652	679	676	695	776	808			
165	825	846	830	816	778	771	737	779	776	771	688	712	714	754	773	827			
170	842	848	833	820	800	796	772	807	816	805	725	745	748	773	773	826			
175	846	840	843	816	809	811	814	824	846	830	791	781	782	792	808	816			
180	853	838	809	803	805	807	808	819	855	836	811	802	806	806	809	818			

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-06-25

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks: