


LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:220.01V I:0.6521A P:139.85W PF:0.9748 Freq:50.00Hz Lamp Flux:8255.37x1 lm		
NAME: SB-J01C140WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1500*1500mm	

DATA OF LAMP		PHOTOMETRIC DATA Eff: 59.03 lm/W			
MODEL		I _{max} (cd)	1151	S/MH(C0/180)	1.46
NOMINAL POWER(W)		LOR(%)	100.0	S/MH(C90/270)	1.44
RATED VOLTAGE(V)	--	TOTAL FLUX(lm)	8255.4	η UP,DN(C0-180)	23.1,25.9
NOMINAL FLUX(lm)	8255.37	CIE CLASS	DIFFUSE	η UP,DN(C180-360)	23.5,27.5
LAMPS INSIDE	1	η up(%)	46.6	CIBSE SHR NOM	1.50
TEST VOLTAGE(V)	--	η down(%)	53.4	CIBSE SHR MAX	1.55



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOXIN
 Test Date:2023-06-25

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum, lamp
10	1151	1117	1113	1105	1145	1128	1102	1080	0- 10	106.1	106.1	1.29,1.29
20	1141	1138	1106	1100	1143	1122	1106	1081	10- 20	316.3	422.4	5.12,5.12
30	1104	1103	1055	1048	1115	1074	1074	1071	20- 30	507.3	929.7	11.3,11.3
40	1022	970.1	969.1	909.7	1026	965.8	992.4	1057	30- 40	649.1	1579	19.1,19.1
50	874.4	827.9	825.7	772.3	882.1	827.2	861.6	920.3	40- 50	711.5	2290	27.7,27.7
60	682.4	684.7	648.9	632.5	724.7	681.8	709.7	766.7	50- 60	692.7	2983	36.1,36.1
70	496.9	541.7	475.8	494.5	547.1	535.0	541.1	608.5	60- 70	610.3	3593	43.5,43.5
80	327.8	404.4	319.0	359.7	383.5	396.2	370.8	456.7	70- 80	485.3	4079	49.4,49.4
90	215.0	241.9	154.3	246.5	190.6	214.6	200.8	299.2	80- 90	329.8	4408	53.4,53.4
100	368.8	358.8	329.3	380.5	275.7	361.9	340.2	363.0	90-100	305.4	4714	57.1,57.1
110	529.3	476.1	478.7	472.9	411.9	436.1	512.2	506.4	100-110	441.3	5155	62.4,62.4
120	638.3	608.0	636.4	576.0	452.4	608.2	689.5	645.2	110-120	535.8	5691	68.9,68.9
130	725.3	695.3	668.5	632.3	603.3	673.4	751.0	775.7	120-130	588.2	6279	76.1,76.1
140	797.1	840.8	788.7	789.4	749.5	775.8	870.8	875.9	130-140	577.0	6856	83.1,83.1
150	940.4	927.0	927.5	958.8	946.9	953.5	971.9	996.2	140-150	563.4	7420	89.9,89.9
160	974.1	948.9	988.2	1005	976.8	1012	1009	1026	150-160	456.7	7876	95.4,95.4
170	997.1	991.1	992.0	1035	993.4	1015	1006	1050	160-170	283.7	8160	98.8,98.8
180	995.7	1008	991.5	1041	997.3	1010	992.8	1042	170-180	95.47	8255	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

Conical surface Flux(90deg): 1932.2 lm

%lum = 23.4%

%lamp = 23.4%

Conical surface Flux(120deg): 2983 lm

%lum = 36.1%


%lamp = 36.1%

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOXIN
 Test Date:2023-06-25

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:220.01V I:0.6521A P:139.85W PF:0.9748 Freq:50.00Hz Lamp Flux:8255.37x1 lm		
NAME: SB-J01C140WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1500*1500mm	




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:XIAOXIN
Test Date:2023-06-25

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:9.000m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:220.01V I:0.6521A P:139.85W PF:0.9748 Freq:50.00Hz Lamp Flux:8255.37x1 lm		
NAME: SB-J01C140WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1500*1500mm	

ρ_{cc}	80%			70%			50%			30%			10%			0
ρ_w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρ_{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Coefficients of Utilization(CU)															
0.0	1.08	1.08	1.08	1.00	1.00	1.00	.85	.85	.85	.72	.72	.72	.59	.59	.59	.53
1.0	.92	.87	.83	.85	.81	.77	.72	.69	.66	.60	.58	.56	.50	.48	.46	.41
2.0	.79	.72	.66	.73	.67	.62	.62	.57	.53	.52	.48	.45	.42	.40	.38	.33
3.0	.69	.61	.54	.64	.56	.51	.54	.49	.44	.45	.41	.37	.37	.34	.31	.27
4.0	.60	.52	.45	.56	.48	.42	.48	.42	.37	.40	.35	.32	.33	.29	.26	.23
5.0	.54	.45	.38	.50	.42	.36	.42	.36	.31	.36	.31	.27	.29	.25	.23	.19
6.0	.48	.39	.33	.44	.37	.31	.38	.32	.27	.32	.27	.23	.26	.23	.20	.17
7.0	.43	.35	.29	.40	.32	.27	.34	.28	.24	.29	.24	.20	.24	.20	.17	.15
8.0	.39	.31	.25	.36	.29	.24	.31	.25	.21	.26	.22	.18	.22	.18	.15	.13
9.0	.35	.28	.22	.33	.26	.21	.28	.23	.19	.24	.19	.16	.20	.16	.14	.11
10.0	.32	.25	.20	.30	.23	.19	.26	.21	.17	.22	.18	.14	.19	.15	.12	.10



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOXIN
 Test Date:2023-06-25

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

WEC AND CCEC

Test:U:220.01V I:0.6521A P:139.85W PF:0.9748 Freq:50.00Hz Lamp Flux:8255.37x1 lm		
NAME: SB-J01C140WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1500*1500mm	

pcc	80%			70%			50%			30%			10%			0	
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
pfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)										
0.0																	
1.0	.330	.188	.060	.309	.176	.056	.270	.155	.049	.233	.134	.043	.199	.116	.037		
2.0	.294	.161	.049	.275	.151	.047	.239	.133	.041	.205	.115	.036	.174	.099	.031		
3.0	.266	.141	.042	.248	.133	.040	.215	.117	.035	.184	.101	.031	.156	.086	.027		
4.0	.242	.126	.037	.226	.118	.035	.196	.104	.031	.167	.090	.027	.141	.077	.023		
5.0	.222	.113	.033	.207	.106	.031	.179	.093	.027	.153	.081	.024	.129	.069	.021		
6.0	.205	.103	.029	.191	.097	.028	.165	.085	.025	.141	.073	.022	.119	.062	.019		
7.0	.190	.094	.027	.177	.088	.025	.153	.078	.022	.131	.067	.020	.110	.057	.017		
8.0	.177	.086	.024	.165	.081	.023	.143	.071	.020	.122	.062	.018	.102	.053	.015		
9.0	.165	.080	.022	.154	.075	.021	.134	.066	.019	.114	.057	.016	.096	.049	.014		
10.0	.155	.074	.021	.145	.070	.020	.126	.062	.017	.107	.053	.015	.090	.045	.013		

pcc	80%			70%			50%			30%			10%			0	
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
pfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)										
0.0	.546	.546	.546	.466	.466	.466	.318	.318	.318	.183	.183	.183	.058	.058	.058		
1.0	.540	.514	.491	.462	.441	.422	.316	.303	.292	.182	.176	.170	.058	.057	.055		
2.0	.533	.492	.458	.456	.424	.396	.313	.293	.276	.180	.171	.162	.058	.055	.053		
3.0	.526	.477	.437	.451	.411	.379	.310	.286	.266	.179	.167	.157	.057	.054	.051		
4.0	.519	.465	.423	.445	.402	.368	.306	.280	.259	.177	.164	.153	.057	.053	.050		
5.0	.512	.455	.414	.440	.394	.360	.303	.275	.254	.176	.162	.151	.057	.053	.050		
6.0	.505	.448	.407	.434	.388	.354	.300	.272	.251	.174	.160	.149	.056	.052	.049		
7.0	.499	.442	.402	.429	.383	.350	.297	.268	.248	.172	.158	.148	.056	.052	.049		
8.0	.493	.437	.398	.425	.379	.347	.294	.266	.246	.171	.157	.147	.055	.051	.049		
9.0	.487	.432	.395	.420	.375	.344	.291	.264	.244	.169	.156	.146	.055	.051	.048		
10.0	.482	.428	.392	.416	.372	.342	.288	.262	.243	.168	.155	.145	.055	.051	.048		

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOXIN
 Test Date:2023-06-25

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

UGR(Unified Glare Rating) Table

Test:U:220.01V I:0.6521A P:139.85W PF:0.9748 Freq:50.00Hz Lamp Flux:8255.37x1 lm											
NAME: SB-J01C140WSZ					TYPE:			WEIGHT:			
SPEC.:4000K					DIM.:			SERIAL No.:			
MFR.: SNOWBALL					SUR.:1500*1500mm						
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	Viewed crosswise					Viewed endwise					
x = 2H y = 2H	8.0	9.1	8.9	9.9	11.0	8.0	9.0	8.8	9.8	10.9	
	3H	10.0	10.9	10.9	11.8	12.9	9.9	10.9	10.8	11.7	12.8
	4H	11.0	11.8	11.8	12.7	13.8	10.9	11.8	11.8	12.6	13.8
	6H	12.0	12.8	12.8	13.7	14.8	11.9	12.7	12.8	13.6	14.7
	8H	12.5	13.2	13.3	14.1	15.3	12.4	13.1	13.3	14.1	15.2
	12H	13.0	13.8	13.9	14.7	15.8	12.9	13.7	13.8	14.6	15.7
4H	2H	8.7	9.6	9.6	10.4	11.6	8.6	9.5	9.5	10.4	11.5
	3H	10.9	11.6	11.8	12.5	13.7	10.8	11.6	11.7	12.5	13.7
	4H	12.0	12.7	12.9	13.6	14.8	12.0	12.7	12.9	13.6	14.8
	6H	13.2	13.8	14.1	14.7	16.0	13.2	13.8	14.1	14.7	15.9
	8H	13.8	14.4	14.7	15.3	16.5	13.8	14.3	14.7	15.3	16.5
	12H	14.5	15.0	15.4	15.9	17.2	14.5	15.0	15.4	15.9	17.2
8H	4H	12.5	13.1	13.5	14.0	15.2	12.5	13.0	13.4	14.0	15.2
	6H	14.0	14.4	14.9	15.4	16.7	14.0	14.4	15.0	15.4	16.7
	8H	14.8	15.2	15.8	16.2	17.4	14.8	15.2	15.8	16.2	17.5
	12H	15.7	16.0	16.7	17.0	18.3	15.7	16.1	16.7	17.1	18.4
12H	4H	12.6	13.1	13.6	14.1	15.3	12.6	13.1	13.5	14.0	15.3
	6H	14.2	14.6	15.2	15.6	16.9	14.2	14.6	15.2	15.6	16.9
	8H	15.1	15.5	16.1	16.5	17.8	15.1	15.5	16.1	16.5	17.8
Variations with the observer position at spacings:											
S = 1.0H	+ 0.1 / - 0.1					+ 0.1 / - 0.1					
1.5H	+ 0.2 / - 0.3					+ 0.2 / - 0.3					
2.0H	+ 0.2 / - 0.4					+ 0.2 / - 0.4					

CIE Pub.117, 8255 lm Total Lamp Luminous Flux Corrected ($8\log(F/F_0) = 7.3$)
Area: 2.25 m²

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:XIAOXIN
Test Date:2023-06-25

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:9.000m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:220.01V I:0.6521A P:139.85W PF:0.9748 Freq:50.00Hz Lamp Flux:8255.37x1 lm		
NAME: SB-J01C140WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1500*1500mm	


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	42	30	24	40	29	23	36	27	21	14
0.80	51	39	31	48	37	30	43	33	28	18
1.00	59	46	38	55	44	37	48	41	33	22
1.25	66	53	45	61	51	43	54	45	39	26
1.50	71	59	51	66	56	48	57	49	43	28
2.00	78	68	60	73	64	57	63	56	50	33
2.50	83	73	66	77	69	62	66	60	55	35
3.00	86	78	71	80	73	67	69	63	58	37
4.00	91	84	78	85	78	73	72	68	64	40
5.00	94	88	82	87	82	77	75	71	67	42
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOXIN
 Test Date:2023-06-25

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

ISOCANDELA DIAGRAM

Test:U:220.01V I:0.6521A P:139.85W PF:0.9748 Freq:50.00Hz Lamp Flux:8255.37x1 lm		
NAME: SB-J01C140WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1500*1500mm	




C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOXIN
 Test Date:2023-06-25

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

AAI Figure

Test:U:220.01V I:0.6521A P:139.85W PF:0.9748 Freq:50.00Hz Lamp Flux:8255.37x1 lm		
NAME: SB-J01C140WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1500*1500mm	




Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: XIAOXIN
 Test Date: 2023-06-25

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity: 65.0%
 Test Distance: 9.000m [K=1.0000]
 Remarks:

ISOLUX DIAGRAM


Test:U:220.01V I:0.6521A P:139.85W PF:0.9748 Freq:50.00Hz Lamp Flux:8255.37x1 lm		
NAME: SB-J01C140WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1500*1500mm	



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:XIAOXIN
Test Date:2023-06-25

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:9.000m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: XIAOXIN
Test Date: 2023-06-25

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity: 65.0%
Test Distance: 9.000m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:220.01V I:0.6521A P:139.85W PF:0.9748 Freq:50.00Hz Lamp Flux:8255.37x1 lm																	
NAME: SB-J01C140WSZ									TYPE:						WEIGHT:		
SPEC.:4000K									DIM.:						SERIAL No.:		
MFR.: SNOWBALL									SUR.:1500*1500mm								

Table--1

UNIT: cd

C(DEG) γ (DEG)	0	22.5	45	67.5	90	112.5	135	157.5	180	202.5	225	247.5	270	292.5	315	337.5			
0	1135	1129	1120	1110	1101	1095	1092	1090	1135	1129	1120	1110	1101	1095	1092	1090			
5	1140	1126	1116	1107	1106	1099	1096	1101	1142	1138	1125	1108	1098	1087	1081	1083			
10	1151	1139	1117	1110	1113	1106	1105	1107	1145	1141	1128	1112	1102	1087	1080	1087			
15	1150	1145	1133	1106	1112	1108	1108	1113	1146	1138	1128	1118	1106	1088	1084	1089			
20	1141	1145	1138	1101	1106	1101	1100	1102	1143	1131	1122	1118	1106	1078	1081	1081			
25	1126	1132	1133	1098	1086	1081	1084	1087	1132	1108	1101	1099	1098	1064	1073	1071			
30	1104	1110	1103	1084	1055	1053	1048	1063	1115	1078	1074	1075	1074	1063	1071	1058			
35	1069	1048	1039	1045	1020	999	979	1007	1084	1043	1032	1035	1036	1049	1064	1043			
40	1022	980	970	981	969	934	910	937	1026	1001	966	971	992	1025	1057	1027			
45	957	910	899	915	904	862	841	867	955	934	898	903	932	1001	994	982			
50	874	836	828	843	826	791	772	796	882	864	827	831	862	939	920	909			
55	777	763	755	770	739	717	701	725	804	792	755	756	788	861	844	831			
60	682	685	685	693	649	644	632	651	725	715	682	682	710	779	767	753			
65	586	607	612	616	561	566	563	578	635	636	606	606	627	693	687	674			
70	497	527	542	538	476	490	494	506	547	559	535	528	541	605	608	591			
75	408	453	472	464	394	418	428	436	461	477	465	455	456	518	533	509			
80	328	378	404	391	319	347	360	365	384	397	396	381	371	429	457	430			
85	260	309	336	321	251	265	255	284	308	319	315	305	294	353	383	357			
90	215	195	242	222	154	219	247	220	191	213	215	225	201	251	299	270			
95	294	291	275	275	254	295	320	287	222	263	299	296	266	281	290	306			
100	369	367	359	345	329	360	381	356	276	334	362	366	340	347	363	364			
105	441	436	424	400	407	424	429	422	337	403	425	437	424	428	434	439			
110	529	500	476	488	479	498	473	463	412	466	436	511	512	515	506	509			
115	567	524	491	557	562	568	554	431	452	422	569	582	602	596	529	592			
120	638	578	608	628	636	570	576	578	452	581	608	612	690	679	645	566			
125	718	658	658	679	640	605	611	611	591	631	641	654	726	752	715	676			
130	725	708	695	720	669	635	632	651	603	657	673	693	751	799	776	740			
135	764	760	745	743	752	705	710	676	676	669	712	735	822	833	819	793			
140	797	852	841	760	789	853	789	739	750	714	776	849	871	862	876	856			
145	895	934	902	855	901	924	884	885	910	886	860	946	948	943	943	969			
150	940	957	927	945	927	960	959	982	947	992	954	988	972	1015	996	1010			
155	959	970	942	982	968	999	994	1008	964	1002	992	987	994	1039	1018	1028			
160	974	978	949	996	988	1004	1005	1004	977	993	1012	990	1009	1039	1026	1033			
165	986	972	971	997	992	1003	1019	1003	986	976	1025	985	1008	1029	1041	1028			
170	997	973	991	985	992	999	1035	998	993	972	1015	981	1006	1013	1050	1019			
175	1000	976	1010	971	987	994	1035	1001	991	969	1007	974	996	999	1052	1016			
180	996	974	1008	977	992	996	1041	1005	997	972	1010	975	993	995	1042	1004			

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:XIAOXIN
Test Date:2023-06-25

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:9.000m [K=1.0000]
Remarks: