


LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:220.15V I:0.3885A P:81.654W PF:0.9548 Freq:50.00Hz Lamp Flux:5191.12x1 lm		
NAME: SB-J01C80WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:800*800mm	

DATA OF LAMP		PHOTOMETRIC DATA Eff: 63.57 lm/W			
MODEL		I _{max} (cd)	895.0	S/MH(C0/180)	1.22
NOMINAL POWER(W)		LOR(%)	100.0	S/MH(C90/270)	1.20
RATED VOLTAGE(V)	--	TOTAL FLUX(lm)	5191.1	η UP,DN(C0-180)	23.1,27.5
NOMINAL FLUX(lm)	5191.12	CIE CLASS	DIFFUSE	η UP,DN(C180-360)	21.7,27.6
LAMPS INSIDE	1	η up(%)	44.9	CIBSE SHR NOM	1.25
TEST VOLTAGE(V)	--	η down(%)	55.1	CIBSE SHR MAX	1.35



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-06-25

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum,lamp
10	876.1	884.3	879.2	888.8	884.9	883.9	870.0	875.3	0- 10	84.67	84.67	1.63,1.63
20	814.2	829.3	810.6	835.2	823.1	831.0	808.8	818.5	10- 20	241.6	326.3	6.28,6.28
30	719.9	733.6	712.1	742.7	728.1	736.9	715.8	733.1	20- 30	358.6	684.9	13.2,13.2
40	619.0	634.1	600.7	640.0	630.2	637.3	613.1	633.8	30- 40	425.7	1111	21.4,21.4
50	515.4	540.4	490.0	540.8	528.3	546.1	505.5	543.8	40- 50	448.3	1559	30,30
60	413.1	443.2	381.8	441.5	423.1	451.2	398.9	452.5	50- 60	430.3	1989	38.3,38.3
70	308.6	346.1	279.0	346.7	318.7	354.1	294.9	355.5	60- 70	376.4	2366	45.6,45.6
80	216.4	253.0	187.4	256.6	225.2	258.3	198.8	258.6	70- 80	297.9	2664	51.3,51.3
90	84.59	118.6	94.54	146.2	107.0	121.6	74.42	107.4	80- 90	199.2	2863	55.1,55.1
100	195.4	239.4	201.7	260.9	209.2	229.1	169.4	205.9	90-100	180.8	3044	58.6,58.6
110	268.5	298.5	295.3	323.5	286.5	296.3	251.1	268.6	100-110	265.9	3310	63.8,63.8
120	347.4	317.0	389.5	372.7	373.7	315.8	328.8	265.2	110-120	328.1	3638	70.1,70.1
130	283.4	462.5	488.2	491.4	345.0	451.4	430.7	423.8	120-130	349.7	3987	76.8,76.8
140	358.2	516.8	542.1	533.2	442.1	490.2	492.6	477.3	130-140	352.8	4340	83.6,83.6
150	426.5	581.5	603.0	574.4	514.4	528.4	552.8	543.2	140-150	321.8	4662	89.8,89.8
160	627.7	687.0	653.7	648.8	654.9	629.7	624.3	664.1	150-160	269.2	4931	95,95
170	722.4	710.4	708.6	698.4	746.9	693.0	693.9	693.0	160-170	191.9	5123	98.7,98.7
180	747.7	706.6	716.2	699.6	748.2	706.8	716.4	699.1	170-180	68.19	5191	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

Conical surface Flux(90deg): 1334.5 lm

%lum = 25.7%

%lamp = 25.7%

Conical surface Flux(120deg): 1989.1 lm

%lum = 38.3%


%lamp = 38.3%

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-06-25

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:220.15V I:0.3885A P:81.654W PF:0.9548 Freq:50.00Hz Lamp Flux:5191.12x1 lm		
NAME: SB-J01C80WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:800*800mm	




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:XIAOMI
Test Date:2023-06-25

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:9.000m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:220.15V I:0.3885A P:81.654W PF:0.9548 Freq:50.00Hz Lamp Flux:5191.12x1 lm		
NAME: SB-J01C80WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:800*800mm	

ρ_{cc}	80%			70%			50%			30%			10%			0
ρ_w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρ_{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Coefficients of Utilization(CU)															
0.0	1.08	1.08	1.08	1.01	1.01	1.01	.86	.86	.86	.73	.73	.73	.61	.61	.61	.55
1.0	.92	.88	.84	.86	.82	.78	.73	.70	.68	.62	.60	.58	.51	.50	.48	.43
2.0	.80	.73	.67	.74	.68	.63	.63	.59	.55	.53	.50	.47	.44	.42	.39	.35
3.0	.70	.62	.55	.65	.58	.52	.55	.50	.45	.47	.43	.39	.39	.36	.33	.29
4.0	.61	.53	.46	.57	.49	.44	.49	.43	.38	.41	.37	.33	.34	.31	.28	.24
5.0	.55	.46	.40	.51	.43	.37	.44	.37	.33	.37	.32	.28	.31	.27	.24	.21
6.0	.49	.40	.34	.45	.38	.32	.39	.33	.28	.33	.28	.25	.28	.24	.21	.18
7.0	.44	.36	.30	.41	.34	.28	.36	.29	.25	.30	.25	.22	.25	.22	.19	.16
8.0	.40	.32	.26	.37	.30	.25	.32	.26	.22	.28	.23	.19	.23	.20	.17	.14
9.0	.36	.29	.23	.34	.27	.22	.30	.24	.20	.25	.21	.17	.22	.18	.15	.13
10.0	.33	.26	.21	.31	.24	.20	.27	.22	.18	.24	.19	.16	.20	.16	.14	.12



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-06-25

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

WEC AND CCEC

Test:U:220.15V I:0.3885A P:81.654W PF:0.9548 Freq:50.00Hz Lamp Flux:5191.12x1 lm		
NAME: SB-J01C80WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:800*800mm	

pcc	80%			70%			50%			30%			10%			0	
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
pfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)										
0.0																	
1.0	.326	.185	.059	.305	.174	.055	.266	.153	.049	.231	.133	.043	.198	.115	.037		
2.0	.291	.159	.049	.272	.150	.046	.237	.132	.041	.204	.114	.036	.174	.098	.031		
3.0	.263	.140	.042	.246	.132	.040	.213	.116	.035	.184	.101	.031	.156	.086	.027		
4.0	.239	.124	.037	.224	.117	.035	.194	.103	.031	.167	.090	.027	.141	.077	.023		
5.0	.220	.112	.032	.205	.105	.031	.178	.093	.027	.153	.081	.024	.129	.069	.021		
6.0	.203	.102	.029	.190	.096	.028	.165	.084	.025	.141	.073	.022	.119	.063	.019		
7.0	.188	.093	.026	.176	.088	.025	.153	.077	.022	.131	.067	.020	.111	.057	.017		
8.0	.175	.086	.024	.164	.081	.023	.142	.071	.020	.122	.062	.018	.103	.053	.015		
9.0	.164	.079	.022	.154	.075	.021	.133	.066	.019	.115	.057	.016	.097	.049	.014		
10.0	.154	.074	.020	.144	.070	.019	.125	.061	.017	.108	.053	.015	.091	.046	.013		

pcc	80%			70%			50%			30%			10%			0	
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
pfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)										
0.0	.532	.532	.532	.455	.455	.455	.310	.310	.310	.178	.178	.178	.057	.057	.057		
1.0	.526	.501	.478	.450	.430	.411	.308	.296	.284	.177	.171	.165	.057	.055	.053		
2.0	.519	.479	.445	.444	.412	.385	.305	.285	.268	.176	.166	.157	.056	.054	.051		
3.0	.512	.463	.424	.439	.399	.368	.301	.277	.258	.174	.162	.152	.056	.053	.050		
4.0	.505	.451	.410	.433	.390	.356	.298	.272	.251	.172	.159	.148	.055	.052	.049		
5.0	.498	.442	.400	.428	.382	.348	.294	.267	.246	.171	.157	.146	.055	.051	.048		
6.0	.491	.434	.393	.422	.376	.342	.291	.263	.242	.169	.155	.144	.055	.051	.048		
7.0	.485	.428	.388	.417	.371	.338	.288	.260	.240	.167	.153	.143	.054	.050	.047		
8.0	.479	.423	.384	.412	.367	.335	.285	.257	.238	.166	.152	.142	.054	.050	.047		
9.0	.473	.418	.381	.408	.363	.332	.282	.255	.236	.165	.151	.141	.053	.049	.047		
10.0	.468	.414	.379	.403	.360	.330	.280	.253	.235	.163	.150	.140	.053	.049	.046		

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-06-25

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

UGR(Unified Glare Rating) Table

Test:U:220.15V I:0.3885A P:81.654W PF:0.9548 Freq:50.00Hz Lamp Flux:5191.12x1 lm											
NAME: SB-J01C80WSZ					TYPE:			WEIGHT:			
SPEC.:4000K					DIM.:			SERIAL No.:			
MFR.: SNOWBALL					SUR.:800*800mm						
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H y = 2H	10.9	11.9	11.7	12.7	13.8	10.6	11.6	11.4	12.5	13.5	
	3H	12.9	13.8	13.7	14.6	15.7	12.5	13.4	13.3	14.2	15.3
	4H	13.8	14.7	14.7	15.6	16.7	13.4	14.3	14.2	15.1	16.2
	6H	14.9	15.7	15.7	16.6	17.7	14.3	15.1	15.2	16.0	17.1
	8H	15.4	16.2	16.3	17.1	18.2	14.8	15.6	15.7	16.5	17.6
	12H	16.0	16.8	16.9	17.7	18.8	15.3	16.1	16.2	17.0	18.1
4H	2H	11.6	12.4	12.4	13.3	14.4	11.3	12.2	12.2	13.1	14.2
	3H	13.8	14.5	14.6	15.4	16.5	13.4	14.2	14.3	15.1	16.2
	4H	14.9	15.6	15.8	16.5	17.7	14.6	15.2	15.5	16.1	17.3
	6H	16.2	16.7	17.1	17.7	18.9	15.7	16.3	16.6	17.2	18.4
	8H	16.8	17.3	17.7	18.3	19.5	16.2	16.8	17.2	17.7	18.9
	12H	17.5	18.0	18.5	19.0	20.2	16.9	17.4	17.8	18.3	19.5
8H	4H	15.4	15.9	16.3	16.9	18.1	15.1	15.6	16.0	16.6	17.8
	6H	16.9	17.4	17.9	18.3	19.6	16.5	17.0	17.5	17.9	19.2
	8H	17.8	18.2	18.7	19.1	20.4	17.3	17.7	18.2	18.7	19.9
	12H	18.7	19.1	19.7	20.0	21.3	18.1	18.5	19.1	19.4	20.7
12H	4H	15.5	16.0	16.4	16.9	18.1	15.2	15.7	16.1	16.6	17.9
	6H	17.1	17.5	18.1	18.5	19.7	16.7	17.2	17.7	18.1	19.4
	8H	18.1	18.4	19.0	19.4	20.7	17.6	18.0	18.6	19.0	20.2
Variations with the observer position at spacings:											
S = 1.0H	+ 0.1 / - 0.1					+ 0.1 / - 0.1					
1.5H	+ 0.2 / - 0.3					+ 0.2 / - 0.3					
2.0H	+ 0.2 / - 0.4					+ 0.2 / - 0.4					

CIE Pub.117, 5191 lm Total Lamp Luminous Flux Corrected ($8\log(F/F_0) = 5.7$)
Area: 0.64 m²

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:XIAOMI
Test Date:2023-06-25

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:9.000m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:220.15V I:0.3885A P:81.654W PF:0.9548 Freq:50.00Hz Lamp Flux:5191.12x1 lm		
NAME: SB-J01C80WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:800*800mm	


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	43	32	25	41	31	24	37	28	23	16
0.80	52	40	33	49	38	32	44	35	29	20
1.00	60	48	40	56	45	38	50	43	35	24
1.25	67	55	47	63	52	45	55	47	41	28
1.50	72	60	52	67	57	50	59	51	45	30
2.00	79	69	61	74	65	58	64	57	52	35
2.50	84	74	67	78	70	63	68	61	56	37
3.00	87	79	72	81	74	68	70	65	60	39
4.00	92	85	79	86	79	74	74	69	65	42
5.00	95	89	83	88	83	78	76	72	68	44
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-06-25

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

ISOCANDELA DIAGRAM

Test:U:220.15V I:0.3885A P:81.654W PF:0.9548 Freq:50.00Hz Lamp Flux:5191.12x1 lm		
NAME: SB-J01C80WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:800*800mm	




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:XIAOMI
Test Date:2023-06-25

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:9.000m [K=1.0000]
Remarks:

AAI Figure

Test:U:220.15V I:0.3885A P:81.654W PF:0.9548 Freq:50.00Hz Lamp Flux:5191.12x1 lm		
NAME: SB-J01C80WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:800*800mm	




Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: XIAOMI
 Test Date: 2023-06-25

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity: 65.0%
 Test Distance: 9.000m [K=1.0000]
 Remarks:

ISOLUX DIAGRAM


Test:U:220.15V I:0.3885A P:81.654W PF:0.9548 Freq:50.00Hz Lamp Flux:5191.12x1 lm		
NAME: SB-J01C80WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:800*800mm	



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: XIAOMI
 Test Date: 2023-06-25

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity: 65.0%
 Test Distance: 9.000m [K=1.0000]
 Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: XIAOMI
Test Date: 2023-06-25

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity: 65.0%
Test Distance: 9.000m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:220.15V I:0.3885A P:81.654W PF:0.9548 Freq:50.00Hz Lamp Flux:5191.12x1 lm		
NAME: SB-J01C80WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:800*800mm	

Table--1

UNIT: cd

C(°) γ (°)	0	22.5	45	67.5	90	112.5	135	157.5	180	202.5	225	247.5	270	292.5	315	337.5			
0	891	891	891	890	889	889	889	888	891	891	891	890	889	889	889	888			
5	889	892	894	894	893	894	894	891	893	892	889	887	885	885	885	885			
10	876	885	884	882	879	885	889	887	885	884	884	876	870	872	875	873			
15	850	862	863	858	852	862	868	867	862	864	861	854	845	848	851	851			
20	814	828	829	823	811	827	835	832	823	829	831	821	809	814	818	817			
25	769	786	785	778	763	781	792	786	777	782	787	781	766	773	778	774			
30	720	736	734	729	712	732	743	738	728	735	737	734	716	725	733	724			
35	673	689	683	678	657	681	692	690	679	687	686	685	663	675	681	677			
40	619	638	634	629	601	630	640	642	630	636	637	634	613	626	634	629			
45	569	591	586	578	546	580	590	596	581	587	592	584	559	576	589	582			
50	515	543	540	526	490	529	541	546	528	538	546	532	505	527	544	537			
55	465	493	493	478	435	476	491	496	475	488	499	483	453	479	499	489			
60	413	444	443	425	382	426	442	447	423	439	451	431	399	431	453	440			
65	361	394	392	374	329	376	393	395	370	390	403	379	345	380	405	389			
70	309	342	346	326	279	327	347	345	319	341	354	328	295	330	355	339			
75	262	292	299	277	231	278	300	297	271	294	305	278	245	282	307	289			
80	216	246	253	230	187	231	257	249	225	251	258	230	199	235	259	244			
85	174	202	206	181	147	184	211	205	182	204	212	177	155	181	209	198			
90	84.6	119	119	120	94.5	123	146	131	107	127	122	99.7	74.4	87.7	107	96.2			
95	161	181	191	167	152	180	216	201	174	192	188	148	123	142	166	163			
100	195	213	239	223	202	230	261	236	209	231	229	191	169	186	206	201			
105	231	260	281	264	248	272	296	289	247	273	264	228	208	220	234	238			
110	269	311	299	295	295	287	324	332	286	324	296	238	251	217	269	295			
115	308	352	364	339	344	342	389	372	330	363	337	317	293	301	299	324			
120	347	395	317	387	390	401	373	418	374	405	316	353	329	349	265	349			
125	380	358	396	435	442	457	426	426	394	411	381	405	374	390	360	322			
130	283	307	462	482	488	501	491	383	345	369	451	450	431	449	424	289			
135	347	395	488	522	536	516	517	476	417	460	473	462	484	495	451	371			
140	358	429	517	568	542	544	533	509	442	486	490	482	493	537	477	404			
145	391	450	550	593	575	571	557	507	473	496	502	522	526	561	511	431			
150	427	483	582	608	603	591	574	522	514	515	528	542	553	571	543	467			
155	464	570	652	625	622	627	622	551	555	550	585	587	566	587	618	550			
160	628	679	687	649	654	677	649	600	655	608	630	638	624	616	664	662			
165	686	725	697	659	692	699	675	654	718	658	667	676	662	635	681	714			
170	722	740	710	705	709	707	698	701	747	703	693	697	694	686	693	729			
175	744	735	705	714	717	712	701	709	757	718	708	711	711	705	692	728			
180	748	728	707	715	716	711	700	721	748	728	707	715	716	711	699	720			

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:XIAOMI
Test Date:2023-06-25

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:9.000m [K=1.0000]
Remarks: