


## LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:220.31V I:0.5741A P:121.81W PF:0.9631 Freq:50.00Hz Lamp Flux:7830.02x1 lm		
NAME: SB-J01C120WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1200*1200mm	

DATA OF LAMP		PHOTOMETRIC DATA Eff: 64.28 lm/W			
MODEL		I <sub>max</sub> (cd)	1273	S/MH(C0/180)	1.27
NOMINAL POWER(W)		LOR(%)	100.0	S/MH(C90/270)	1.27
RATED VOLTAGE(V)	--	TOTAL FLUX(lm)	7830.0	η UP,DN(C0-180)	25.6,25.1
NOMINAL FLUX(lm)	7830.02	CIE CLASS	DIFFUSE	η UP,DN(C180-360)	21.4,27.9
LAMPS INSIDE	1	η up(%)	47.0	CIBSE SHR NOM	1.25
TEST VOLTAGE(V)	--	η down(%)	53.0	CIBSE SHR MAX	1.35



C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:XIAOMI  
 Test Date:2023-06-25

γ Range: 0 - 180DEG  
 γ Interval: 1.0DEG  
 Test System:EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
 Humidity:65.0%  
 Test Distance:9.000m [K=1.0000]  
 Remarks:

## ZONAL FLUX DIAGRAM

## ZONAL FLUX DIAGRAM:

$\gamma$	C0	C45	C90	C135	C180	C225	C270	C315	$\gamma$	$\Phi$ zone	$\Phi$ total	%lum,lamp
10	1250	1234	1220	1235	1262	1265	1260	1259	0- 10	120.1	120.1	1.53,1.53
20	1167	1153	1115	1152	1199	1213	1199	1206	10- 20	343.6	463.7	5.92,5.92
30	1035	1030	976.2	1032	1084	1110	1082	1098	20- 30	516.4	980.1	12.5,12.5
40	884.6	890.7	824.2	896.6	944.8	978.5	936.7	962.5	30- 40	619.1	1599	20.4,20.4
50	729.4	748.0	669.6	759.9	793.3	838.6	785.2	813.6	40- 50	652.2	2251	28.8,28.8
60	572.1	607.8	516.1	619.5	634.5	696.2	635.9	667.3	50- 60	624.4	2876	36.7,36.7
70	420.0	469.6	371.2	479.5	479.2	557.6	487.5	532.5	60- 70	547.1	3423	43.7,43.7
80	283.5	339.3	245.0	342.6	331.5	418.5	343.0	405.4	70- 80	433.6	3857	49.3,49.3
90	162.7	235.6	200.3	214.2	156.7	251.3	206.2	251.2	80- 90	294.3	4151	53,53
100	315.7	402.0	329.5	375.7	255.4	277.2	235.0	309.1	90-100	274.3	4425	56.5,56.5
110	461.1	531.8	473.6	484.4	387.2	381.9	356.2	410.4	100-110	400.3	4825	61.6,61.6
120	532.8	691.1	628.3	637.8	448.2	485.1	484.4	529.2	110-120	489.7	5315	67.9,67.9
130	683.0	809.9	762.9	678.8	548.7	578.2	549.5	638.2	120-130	547.3	5862	74.9,74.9
140	810.6	926.4	855.1	746.9	651.8	651.1	661.7	768.5	130-140	548.7	6411	81.9,81.9
150	1021	1078	964.2	916.6	763.7	809.5	899.3	932.5	140-150	518.8	6930	88.5,88.5
160	1149	1179	1164	1056	1051	955.3	1035	1063	150-160	466.1	7396	94.5,94.5
170	1231	1220	1215	1170	1185	1129	1137	1164	160-170	320.3	7716	98.5,98.5
180	1245	1222	1196	1184	1246	1224	1198	1188	170-180	113.7	7830	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

Conical surface Flux(90deg): 1925.2 lm

%lum = 24.6%

%lamp = 24.6%

Conical surface Flux(120deg): 2875.8 lm

%lum = 36.7%


%lamp = 36.7%

C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:XIAOMI  
 Test Date:2023-06-25

$\gamma$  Range: 0 - 180DEG  
 $\gamma$  Interval: 1.0DEG  
 Test System:EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
 Humidity:65.0%  
 Test Distance:9.000m [K=1.0000]  
 Remarks:

## LUMINANCE LIMITATION CURVES

Test:U:220.31V I:0.5741A P:121.81W PF:0.9631 Freq:50.00Hz Lamp Flux:7830.02x1 lm		
NAME: SB-J01C120WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1200*1200mm	




C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:XIAOMI  
Test Date:2023-06-25

γ Range: 0 - 180DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
Humidity:65.0%  
Test Distance:9.000m [K=1.0000]  
Remarks:

## CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:220.31V I:0.5741A P:121.81W PF:0.9631 Freq:50.00Hz Lamp Flux:7830.02x1 lm		
NAME: SB-J01C120WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1200*1200mm	

$\rho_{cc}$	80%			70%			50%			30%			10%			0	
$\rho_w$	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
$\rho_{fc}$	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Coefficients of Utilization(CU)										
0.0	1.08	1.08	1.08	.00	.00	.00	.85	.85	.85	.71	.71	.71	.59	.59	.59	.53	
1.0	.92	.87	.83	.85	.81	.78	.72	.69	.67	.60	.58	.56	.50	.48	.47	.41	
2.0	.79	.73	.67	.73	.67	.62	.62	.58	.54	.52	.49	.46	.43	.40	.38	.33	
3.0	.69	.61	.55	.64	.57	.51	.55	.49	.45	.46	.42	.38	.37	.34	.32	.28	
4.0	.61	.53	.46	.57	.49	.43	.48	.42	.38	.40	.36	.32	.33	.30	.27	.23	
5.0	.54	.46	.39	.50	.43	.37	.43	.37	.32	.36	.31	.28	.30	.26	.23	.20	
6.0	.49	.40	.34	.45	.37	.32	.39	.33	.28	.33	.28	.24	.27	.23	.20	.17	
7.0	.44	.35	.30	.41	.33	.28	.35	.29	.25	.30	.25	.21	.25	.21	.18	.15	
8.0	.40	.32	.26	.37	.30	.25	.32	.26	.22	.27	.22	.19	.22	.19	.16	.14	
9.0	.36	.28	.23	.34	.27	.22	.29	.23	.19	.25	.20	.17	.21	.17	.14	.12	
10.0	.33	.26	.21	.31	.24	.20	.27	.21	.17	.23	.18	.15	.19	.16	.13	.11	



C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:XIAOMI  
 Test Date:2023-06-25

$\gamma$  Range: 0 - 180DEG  
 $\gamma$  Interval: 1.0DEG  
 Test System:EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
 Humidity:65.0%  
 Test Distance:9.000m [K=1.0000]  
 Remarks:

## WEC AND CCEC

Test:U:220.31V I:0.5741A P:121.81W PF:0.9631 Freq:50.00Hz Lamp Flux:7830.02x1 lm		
NAME: SB-J01C120WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1200*1200mm	

pcc	80%			70%			50%			30%			10%			0	
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
pfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)										
0.0																	
1.0	.324	.184	.058	.303	.173	.055	.263	.151	.048	.226	.130	.042	.192	.112	.036		
2.0	.289	.158	.049	.270	.149	.046	.233	.130	.040	.200	.112	.035	.169	.095	.030		
3.0	.261	.139	.042	.244	.131	.039	.211	.114	.035	.180	.099	.030	.151	.084	.026		
4.0	.238	.124	.036	.222	.116	.034	.192	.102	.030	.163	.088	.026	.137	.075	.023		
5.0	.219	.112	.032	.204	.105	.031	.176	.092	.027	.150	.079	.024	.125	.067	.020		
6.0	.202	.101	.029	.188	.095	.027	.162	.083	.024	.138	.072	.021	.116	.061	.018		
7.0	.187	.093	.026	.175	.087	.025	.151	.076	.022	.128	.066	.019	.107	.056	.016		
8.0	.175	.085	.024	.163	.080	.023	.141	.070	.020	.120	.061	.018	.100	.051	.015		
9.0	.163	.079	.022	.153	.074	.021	.132	.065	.018	.112	.056	.016	.094	.048	.014		
10.0	.153	.074	.020	.143	.069	.019	.124	.061	.017	.106	.052	.015	.088	.044	.013		

pcc	80%			70%			50%			30%			10%			0	
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
pfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)										
0.0	.548	.548	.548	.469	.469	.469	.320	.320	.320	.184	.184	.184	.059	.059	.059		
1.0	.542	.517	.494	.464	.444	.425	.317	.305	.294	.183	.177	.171	.059	.057	.055		
2.0	.535	.495	.462	.458	.426	.399	.314	.295	.278	.181	.172	.163	.058	.056	.053		
3.0	.528	.480	.441	.453	.414	.382	.311	.287	.268	.180	.168	.158	.058	.054	.052		
4.0	.521	.468	.427	.447	.404	.371	.308	.282	.261	.178	.165	.154	.057	.054	.051		
5.0	.514	.458	.417	.442	.397	.363	.304	.277	.256	.176	.163	.152	.057	.053	.050		
6.0	.508	.451	.410	.436	.390	.357	.301	.273	.253	.175	.161	.150	.056	.053	.050		
7.0	.501	.445	.405	.431	.385	.353	.298	.270	.250	.173	.159	.149	.056	.052	.049		
8.0	.495	.439	.401	.426	.381	.350	.295	.268	.248	.172	.158	.148	.056	.052	.049		
9.0	.490	.435	.398	.422	.378	.347	.292	.265	.247	.170	.157	.147	.055	.051	.049		
10.0	.485	.431	.396	.418	.374	.345	.290	.263	.245	.169	.156	.146	.055	.051	.049		

C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:XIAOMI  
 Test Date:2023-06-25

γ Range: 0 - 180DEG  
 γ Interval: 1.0DEG  
 Test System:EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
 Humidity:65.0%  
 Test Distance:9.000m [K=1.0000]  
 Remarks:

UGR(Unified Glare Rating) Table

Test:U:220.31V I:0.5741A P:121.81W PF:0.9631 Freq:50.00Hz Lamp Flux:7830.02x1 lm											
NAME: SB-J01C120WSZ					TYPE:			WEIGHT:			
SPEC.:4000K					DIM.:			SERIAL No.:			
MFR.: SNOWBALL					SUR.:1200*1200mm						
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H y = 2H	8.9	9.9	9.7	10.7	11.8	8.5	9.5	9.3	10.3	11.4	
	3H	10.8	11.7	11.6	12.5	13.6	10.3	11.2	11.1	12.0	13.1
	4H	11.7	12.6	12.6	13.4	14.6	11.1	12.0	12.0	12.9	14.0
	6H	12.7	13.5	13.6	14.4	15.5	12.0	12.8	12.9	13.7	14.9
	8H	13.2	13.9	14.1	14.8	16.0	12.5	13.3	13.4	14.2	15.3
	12H	13.8	14.5	14.7	15.4	16.6	12.9	13.7	13.8	14.6	15.7
4H	2H	9.5	10.3	10.4	11.2	12.3	9.2	10.1	10.1	10.9	12.1
	3H	11.6	12.4	12.5	13.3	14.4	11.2	12.0	12.1	12.9	14.0
	4H	12.8	13.4	13.7	14.4	15.5	12.3	13.0	13.2	13.9	15.1
	6H	13.9	14.5	14.9	15.5	16.7	13.4	14.0	14.3	14.9	16.1
	8H	14.5	15.1	15.5	16.0	17.3	13.9	14.5	14.9	15.4	16.7
	12H	15.2	15.7	16.2	16.7	17.9	14.5	15.0	15.4	15.9	17.2
8H	4H	13.2	13.7	14.2	14.7	15.9	12.8	13.4	13.8	14.3	15.6
	6H	14.7	15.1	15.6	16.1	17.4	14.2	14.7	15.2	15.6	16.9
	8H	15.5	15.9	16.5	16.9	18.1	15.0	15.3	15.9	16.3	17.6
	12H	16.3	16.7	17.3	17.7	19.0	15.7	16.0	16.7	17.0	18.3
12H	4H	13.3	13.8	14.2	14.7	16.0	12.9	13.4	13.9	14.4	15.6
	6H	14.8	15.2	15.8	16.2	17.5	14.4	14.8	15.4	15.8	17.1
	8H	15.8	16.1	16.8	17.1	18.4	15.3	15.6	16.3	16.6	17.9
Variations with the observer position at spacings:											
S = 1.0H	+ 0.1 / - 0.1					+ 0.1 / - 0.1					
1.5H	+ 0.2 / - 0.3					+ 0.2 / - 0.3					
2.0H	+ 0.2 / - 0.4					+ 0.2 / - 0.4					

CIE Pub.117, 7830 lm Total Lamp Luminous Flux Corrected ( $8\log(F/F_0) = 7.2$ )  
Area: 1.44 m<sup>2</sup>

C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:XIAOMI  
Test Date:2023-06-25

$\gamma$  Range: 0 - 180DEG  
 $\gamma$  Interval: 1.0DEG  
Test System:EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
Humidity:65.0%  
Test Distance:9.000m [K=1.0000]  
Remarks:

## UTILIZATION FACTORS TABLE

Test:U:220.31V I:0.5741A P:121.81W PF:0.9631 Freq:50.00Hz Lamp Flux:7830.02x1 lm		
NAME: SB-J01C120WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1200*1200mm	


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	43	31	25	40	30	24	36	28	22	15
0.80	52	40	32	49	38	31	43	34	29	19
1.00	59	47	39	56	45	38	49	42	34	23
1.25	66	54	46	62	51	44	54	46	40	27
1.50	71	60	52	67	56	49	58	50	44	29
2.00	79	68	61	73	64	57	63	56	51	33
2.50	83	74	66	77	69	63	67	60	55	36
3.00	87	78	71	81	73	67	69	64	59	38
4.00	91	84	78	85	79	73	73	68	64	41
5.00	94	88	83	87	82	77	75	71	67	43
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:XIAOMI  
 Test Date:2023-06-25

γ Range: 0 - 180DEG  
 γ Interval: 1.0DEG  
 Test System:EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
 Humidity:65.0%  
 Test Distance:9.000m [K=1.0000]  
 Remarks:

## ISOCANDELA DIAGRAM

Test:U:220.31V I:0.5741A P:121.81W PF:0.9631 Freq:50.00Hz Lamp Flux:7830.02x1 lm		
NAME: SB-J01C120WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1200*1200mm	




C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:XIAOMI  
Test Date:2023-06-25

γ Range: 0 - 180DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
Humidity:65.0%  
Test Distance:9.000m [K=1.0000]  
Remarks:

## AAI Figure

Test:U:220.31V I:0.5741A P:121.81W PF:0.9631 Freq:50.00Hz Lamp Flux:7830.02x1 lm		
NAME: SB-J01C120WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1200*1200mm	




Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature: 25.3DEG  
 Operators: XIAOMI  
 Test Date: 2023-06-25

γ Range: 0 - 180DEG  
 γ Interval: 1.0DEG  
 Test System: EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
 Humidity: 65.0%  
 Test Distance: 9.000m [K=1.0000]  
 Remarks:

## ISOLUX DIAGRAM


Test:U:220.31V I:0.5741A P:121.81W PF:0.9631 Freq:50.00Hz Lamp Flux:7830.02x1 lm		
NAME: SB-J01C120WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1200*1200mm	



C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature: 25.3DEG  
 Operators: XIAOMI  
 Test Date: 2023-06-25

$\gamma$  Range: 0 - 180DEG  
 $\gamma$  Interval: 1.0DEG  
 Test System: EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
 Humidity: 65.0%  
 Test Distance: 9.000m [K=1.0000]  
 Remarks:

### Planar Illuminance Curve



C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature: 25.3DEG  
Operators: XIAOMI  
Test Date: 2023-06-25

$\gamma$  Range: 0 - 180DEG  
 $\gamma$  Interval: 1.0DEG  
Test System: EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
Humidity: 65.0%  
Test Distance: 9.000m [K=1.0000]  
Remarks:

## LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:220.31V I:0.5741A P:121.81W PF:0.9631 Freq:50.00Hz Lamp Flux:7830.02x1 lm		
NAME: SB-J01C120WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1200*1200mm	

Table--1

UNIT: cd

C(DEG) γ (DEG)	0	22.5	45	67.5	90	112.5	135	157.5	180	202.5	225	247.5	270	292.5	315	337.5			
0	1270	1269	1268	1267	1266	1266	1265	1264	1270	1269	1268	1267	1266	1266	1265	1264			
5	1264	1259	1256	1253	1251	1253	1256	1258	1271	1273	1273	1272	1270	1269	1268	1264			
10	1250	1243	1234	1225	1220	1226	1235	1245	1262	1266	1265	1263	1260	1261	1259	1254			
15	1216	1213	1201	1181	1172	1183	1201	1216	1239	1243	1246	1242	1237	1239	1240	1228			
20	1167	1166	1153	1129	1115	1132	1152	1174	1199	1205	1213	1207	1199	1205	1206	1183			
25	1105	1107	1095	1070	1048	1071	1095	1120	1146	1155	1166	1161	1146	1159	1157	1128			
30	1035	1039	1030	1006	976	1004	1032	1058	1084	1097	1110	1102	1082	1102	1098	1063			
35	961	967	962	937	900	934	965	991	1017	1032	1046	1034	1011	1036	1032	993			
40	885	894	891	864	824	863	897	922	945	965	978	962	937	964	963	922			
45	808	821	819	791	747	791	829	852	869	895	909	890	861	891	889	849			
50	729	749	748	718	670	718	760	781	793	823	839	819	785	820	814	775			
55	651	677	678	644	591	647	690	708	715	750	768	747	711	748	740	701			
60	572	605	608	575	516	580	620	634	635	674	696	675	636	676	667	626			
65	496	534	538	503	442	508	549	562	559	598	628	602	563	604	600	550			
70	420	461	470	433	371	438	480	486	479	524	558	529	488	530	533	477			
75	349	391	404	366	305	371	410	413	403	451	487	457	413	452	469	407			
80	284	324	339	302	245	304	343	344	331	382	418	387	343	384	405	346			
85	225	258	264	222	172	215	257	274	262	313	347	317	274	321	341	284			
90	163	214	236	214	200	223	214	174	157	203	251	227	206	243	251	199			
95	244	284	324	296	265	292	303	251	208	221	222	195	163	208	242	254			
100	316	368	402	366	329	359	376	315	255	273	277	262	235	282	309	304			
105	387	443	473	436	399	407	436	382	322	334	335	300	296	332	371	373			
110	461	517	532	511	474	497	484	446	387	391	382	389	356	415	410	435			
115	536	574	577	592	552	575	472	512	454	451	346	441	419	456	424	494			
120	533	563	691	671	628	652	638	439	448	407	485	493	484	517	529	511			
125	611	682	759	753	710	709	678	591	463	553	546	520	526	569	589	604			
130	683	756	810	831	763	733	679	641	549	604	578	562	549	609	638	662			
135	747	814	858	887	810	769	711	657	595	614	617	595	601	667	695	718			
140	811	877	926	918	855	794	747	695	652	654	651	631	662	698	769	771			
145	874	971	998	974	900	830	813	708	702	676	724	758	730	776	867	870			
150	1021	1072	1078	1015	964	946	917	781	764	763	809	848	899	894	932	998			
155	1088	1134	1147	1086	1114	1047	986	940	975	924	882	926	969	985	999	1068			
160	1149	1182	1179	1158	1164	1107	1056	1074	1051	1054	955	991	1035	1044	1063	1111			
165	1197	1216	1198	1196	1200	1151	1144	1108	1122	1115	1051	1050	1089	1096	1107	1145			
170	1231	1230	1220	1203	1215	1198	1170	1147	1185	1170	1129	1131	1137	1145	1164	1169			
175	1246	1230	1229	1196	1208	1195	1177	1168	1224	1206	1194	1167	1179	1179	1190	1180			
180	1245	1225	1222	1183	1196	1195	1184	1179	1246	1223	1224	1181	1198	1194	1188	1178			

C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:XIAOMI  
Test Date:2023-06-25

γ Range: 0 - 180DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
Humidity:65.0%  
Test Distance:9.000m [K=1.0000]  
Remarks: