


LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:220.10V I:0.2917A P:61.015W PF:0.9504 Freq:50.00Hz Lamp Flux:4054.55x1 lm		
NAME: SB-J01A60WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1200*1200mm	

DATA OF LAMP		PHOTOMETRIC DATA Eff: 66.45 lm/W			
MODEL		I _{max} (cd)	1251	S/MH(C0/180)	1.20
NOMINAL POWER(W)		LOR(%)	100.0	S/MH(C90/270)	1.23
RATED VOLTAGE(V)	--	TOTAL FLUX(lm)	4054.5	η UP,DN(C0-180)	6.8,40.4
NOMINAL FLUX(lm)	4054.55	CIE CLASS	SEMI-D.	η UP,DN(C180-360)	7.7,45.2
LAMPS INSIDE	1	η up(%)	14.4	CIBSE SHR NOM	1.25
TEST VOLTAGE(V)	--	η down(%)	85.6	CIBSE SHR MAX	1.35



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:XIAOMI
Test Date:2023-06-25

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:9.000m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum,lamp
10	1209	1192	1185	1173	1221	1225	1229	1218	0- 10	117.0	117.0	2.89,2.89
20	1107	1085	1072	1074	1135	1142	1154	1134	10- 20	328.4	445.5	11,11
30	956.6	942.2	922.7	938.3	998.1	1017	1027	1008	20- 30	482.6	928.0	22.9,22.9
40	787.7	780.8	756.0	782.3	839.8	863.4	867.3	850.0	30- 40	560.7	1489	36.7,36.7
50	619.4	620.1	589.6	626.4	673.9	704.2	704.9	686.7	40- 50	566.4	2055	50.7,50.7
60	455.5	467.9	431.8	475.4	511.1	553.2	542.5	535.0	50- 60	514.6	2570	63.4,63.4
70	305.7	329.9	288.1	336.1	350.1	405.6	390.7	391.8	60- 70	419.3	2989	73.7,73.7
80	174.8	210.7	165.2	214.6	208.9	270.7	252.6	265.6	70- 80	301.4	3290	81.2,81.2
90	44.66	65.40	75.68	86.37	97.27	163.9	140.0	166.0	80- 90	179.3	3470	85.6,85.6
100	82.11	114.9	90.87	123.5	85.35	121.4	102.9	116.6	90-100	106.7	3576	88.2,88.2
110	88.54	124.2	91.06	130.7	96.30	134.0	107.8	130.9	100-110	117.7	3694	91.1,91.1
120	89.46	119.4	89.00	121.7	100.1	115.2	109.3	111.4	110-120	111.2	3805	93.9,93.9
130	66.79	104.1	80.91	103.0	89.19	115.7	92.08	107.8	120-130	90.48	3896	96.1,96.1
140	57.30	83.08	52.98	82.35	74.56	101.4	80.89	95.29	130-140	69.41	3965	97.8,97.8
150	54.73	67.37	40.64	68.99	60.72	86.79	79.31	85.15	140-150	47.01	4012	99,99
160	41.99	47.51	36.51	49.31	50.15	68.26	58.38	66.36	150-160	28.13	4040	99.7,99.7
170	26.24	26.88	21.89	14.28	23.58	31.48	41.70	42.52	160-170	11.94	4052	99.9,99.9
180	11.67	12.95	13.93	14.17	11.72	12.85	13.87	14.03	170-180	2.226	4055	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

Conical surface Flux(90deg): 1775.2 lm

%lum = 43.8%

%lamp = 43.8%

Conical surface Flux(120deg): 2569.7 lm

%lum = 63.4%


%lamp = 63.4%

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-06-25

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:220.10V I:0.2917A P:61.015W PF:0.9504 Freq:50.00Hz Lamp Flux:4054.55x1 lm		
NAME: SB-J01A60WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1200*1200mm	




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:XIAOMI
Test Date:2023-06-25

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:9.000m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:220.10V I:0.2917A P:61.015W PF:0.9504 Freq:50.00Hz Lamp Flux:4054.55x1 lm		
NAME: SB-J01A60WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1200*1200mm	

ρ_{cc}	80%			70%			50%			30%			10%			0	
ρ_w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
ρ_{fc}	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Coefficients of Utilization(CU)										
0.0	1.16	1.16	1.16	1.11	1.11	1.11	1.03	1.03	1.03	.96	.96	.96	.89	.89	.89	.86	
1.0	.99	.94	.90	.95	.91	.87	.88	.85	.82	.82	.79	.77	.76	.74	.72	.69	
2.0	.86	.79	.73	.83	.76	.71	.77	.71	.67	.71	.67	.63	.66	.63	.60	.57	
3.0	.75	.67	.60	.73	.65	.59	.67	.61	.56	.63	.58	.53	.58	.54	.50	.48	
4.0	.67	.58	.51	.64	.56	.50	.60	.53	.48	.56	.50	.45	.52	.47	.43	.41	
5.0	.59	.50	.44	.57	.49	.43	.54	.47	.41	.50	.44	.39	.47	.42	.38	.35	
6.0	.53	.45	.38	.52	.43	.37	.49	.41	.36	.45	.39	.35	.43	.37	.33	.31	
7.0	.48	.40	.34	.47	.39	.33	.44	.37	.32	.41	.35	.31	.39	.34	.29	.27	
8.0	.44	.36	.30	.43	.35	.29	.40	.33	.28	.38	.32	.27	.36	.30	.26	.24	
9.0	.41	.32	.27	.39	.32	.27	.37	.30	.26	.35	.29	.25	.33	.28	.24	.22	
10.0	.37	.30	.24	.36	.29	.24	.34	.28	.23	.33	.27	.22	.31	.26	.22	.20	



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-06-25

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

WEC AND CCEC

Test:U:220.10V I:0.2917A P:61.015W PF:0.9504 Freq:50.00Hz Lamp Flux:4054.55x1 lm		
NAME: SB-J01A60WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1200*1200mm	

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)									
0.0																
1.0	.337	.191	.061	.325	.185	.059	.303	.174	.056	.284	.164	.053	.265	.154	.050	
2.0	.302	.166	.051	.292	.161	.050	.273	.152	.047	.255	.143	.045	.238	.135	.043	
3.0	.274	.146	.044	.265	.142	.043	.247	.134	.041	.231	.127	.039	.216	.120	.037	
4.0	.250	.130	.038	.242	.126	.037	.226	.120	.036	.211	.113	.034	.198	.107	.033	
5.0	.230	.117	.034	.222	.114	.033	.208	.108	.032	.194	.103	.031	.182	.097	.029	
6.0	.212	.106	.030	.205	.104	.030	.192	.098	.029	.180	.093	.027	.168	.089	.026	
7.0	.196	.097	.028	.190	.095	.027	.178	.090	.026	.167	.086	.025	.157	.081	.024	
8.0	.183	.089	.025	.177	.087	.025	.167	.083	.024	.156	.079	.023	.147	.075	.022	
9.0	.171	.083	.023	.166	.081	.023	.156	.077	.022	.147	.074	.021	.138	.070	.020	
10.0	.161	.077	.021	.156	.075	.021	.147	.072	.020	.138	.069	.019	.130	.065	.019	

pcc	80%			70%			50%			30%			10%			0	
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
pfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)										
0.0	.300	.300	.300	.257	.257	.257	.175	.175	.175	.101	.101	.101	.032	.032	.032		
1.0	.293	.267	.243	.251	.229	.209	.171	.157	.145	.099	.091	.084	.032	.029	.027		
2.0	.285	.243	.208	.244	.210	.180	.167	.145	.126	.097	.084	.074	.031	.027	.024		
3.0	.277	.226	.186	.238	.195	.161	.163	.136	.113	.094	.079	.067	.030	.026	.022		
4.0	.270	.214	.171	.231	.185	.148	.159	.129	.104	.092	.075	.062	.030	.025	.020		
5.0	.262	.204	.160	.225	.176	.139	.155	.123	.098	.090	.072	.058	.029	.024	.019		
6.0	.255	.195	.153	.219	.169	.133	.151	.119	.094	.088	.070	.056	.028	.023	.018		
7.0	.248	.189	.147	.213	.164	.128	.147	.115	.091	.086	.068	.054	.028	.022	.018		
8.0	.242	.183	.143	.208	.159	.125	.144	.112	.088	.084	.066	.053	.027	.022	.017		
9.0	.236	.178	.140	.203	.155	.122	.141	.109	.086	.082	.064	.052	.027	.021	.017		
10.0	.230	.174	.137	.198	.151	.120	.138	.106	.085	.080	.063	.051	.026	.021	.017		

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-06-25

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

UGR(Unified Glare Rating) Table

Test:U:220.10V I:0.2917A P:61.015W PF:0.9504 Freq:50.00Hz Lamp Flux:4054.55x1 lm											
NAME: SB-J01A60WSZ					TYPE:			WEIGHT:			
SPEC.:4000K					DIM.:			SERIAL No.:			
MFR.: SNOWBALL					SUR.:1200*1200mm						
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	Viewed crosswise					Viewed endwise					
x = 2H y = 2H	10.2	11.5	10.6	12.0	12.4	10.0	11.3	10.4	11.8	12.2	
	3H	11.8	13.1	12.3	13.5	14.1	11.6	12.8	12.1	13.3	13.8
	4H	12.6	13.8	13.1	14.3	14.8	12.3	13.5	12.9	14.0	14.6
	6H	13.3	14.4	13.9	14.9	15.5	13.1	14.2	13.6	14.7	15.2
	8H	13.7	14.7	14.2	15.3	15.8	13.4	14.5	13.9	15.0	15.6
	12H	14.0	15.0	14.6	15.6	16.2	13.8	14.8	14.3	15.4	16.0
4H	2H	10.8	11.9	11.3	12.4	13.0	10.6	11.8	11.1	12.3	12.8
	3H	12.7	13.7	13.2	14.2	14.8	12.5	13.5	13.0	14.0	14.6
	4H	13.6	14.6	14.2	15.1	15.7	13.4	14.3	14.0	14.9	15.5
	6H	14.5	15.4	15.1	16.0	16.6	14.3	15.1	14.9	15.7	16.4
	8H	15.0	15.8	15.6	16.4	17.0	14.7	15.5	15.4	16.1	16.8
	12H	15.4	16.1	16.1	16.8	17.5	15.3	16.0	15.9	16.6	17.3
8H	4H	14.0	14.8	14.6	15.4	16.1	13.9	14.6	14.5	15.2	15.9
	6H	15.2	15.9	15.9	16.5	17.2	15.0	15.7	15.7	16.3	17.0
	8H	15.8	16.4	16.5	17.1	17.8	15.6	16.2	16.3	16.9	17.6
	12H	16.5	17.0	17.2	17.6	18.4	16.4	16.9	17.0	17.5	18.3
12H	4H	14.1	14.8	14.7	15.4	16.1	13.9	14.6	14.6	15.3	16.0
	6H	15.4	16.0	16.0	16.6	17.4	15.2	15.8	15.9	16.4	17.2
	8H	16.1	16.6	16.8	17.3	18.1	15.9	16.4	16.6	17.1	17.9
Variations with the observer position at spacings:											
S = 1.0H	+ 0.1 / - 0.2					+ 0.1 / - 0.2					
1.5H	+ 0.2 / - 0.3					+ 0.2 / - 0.3					
2.0H	+ 0.1 / - 0.3					+ 0.2 / - 0.4					

CIE Pub.117, 4055 lm Total Lamp Luminous Flux Corrected ($8\log(F/F_0) = 4.9$)
Area: 1.44 m²

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:XIAOMI
Test Date:2023-06-25

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:9.000m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:220.10V I:0.2917A P:61.015W PF:0.9504 Freq:50.00Hz Lamp Flux:4054.55x1 lm		
NAME: SB-J01A60WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1200*1200mm	


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	53	41	34	52	40	34	50	40	33	27
0.80	62	50	43	61	49	42	58	48	41	34
1.00	70	58	50	68	57	50	65	57	49	40
1.25	77	65	58	75	64	57	71	62	55	46
1.50	82	71	63	79	69	62	75	66	60	50
2.00	89	79	72	86	77	70	80	73	68	57
2.50	93	84	77	90	82	75	84	77	72	60
3.00	96	88	82	93	86	80	87	81	76	64
4.00	101	94	88	97	91	86	90	86	81	68
5.00	103	97	93	99	94	90	92	88	85	71
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-06-25

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

ISOCANDELA DIAGRAM

Test:U:220.10V I:0.2917A P:61.015W PF:0.9504 Freq:50.00Hz Lamp Flux:4054.55x1 lm		
NAME: SB-J01A60WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1200*1200mm	




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:XIAOMI
Test Date:2023-06-25

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:9.000m [K=1.0000]
Remarks:

AAI Figure

Test:U:220.10V I:0.2917A P:61.015W PF:0.9504 Freq:50.00Hz Lamp Flux:4054.55x1 lm		
NAME: SB-J01A60WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1200*1200mm	




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-06-25

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

ISOLUX DIAGRAM


Test:U:220.10V I:0.2917A P:61.015W PF:0.9504 Freq:50.00Hz Lamp Flux:4054.55x1 lm		
NAME: SB-J01A60WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1200*1200mm	



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-06-25

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: XIAOMI
Test Date: 2023-06-25

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity: 65.0%
Test Distance: 9.000m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:220.10V I:0.2917A P:61.015W PF:0.9504 Freq:50.00Hz Lamp Flux:4054.55x1 lm																	
NAME: SB-J01A60WSZ									TYPE:						WEIGHT:		
SPEC.:4000K									DIM.:						SERIAL No.:		
MFR.: SNOWBALL									SUR.:1200*1200mm								

Table--1

UNIT: cd

C(DEC) γ (DEC)	0	22.5	45	67.5	90	112.5	135	157.5	180	202.5	225	247.5	270	292.5	315	337.5			
0	1251	1249	1248	1248	1247	1248	1239	1241	1251	1249	1248	1248	1247	1248	1239	1241			
5	1238	1233	1229	1227	1224	1225	1215	1227	1244	1246	1247	1248	1249	1249	1240	1235			
10	1209	1200	1192	1189	1185	1185	1173	1198	1221	1225	1225	1226	1229	1230	1218	1211			
15	1166	1154	1144	1139	1134	1133	1126	1157	1186	1190	1188	1192	1198	1197	1180	1172			
20	1107	1095	1085	1078	1072	1073	1074	1102	1135	1139	1142	1146	1154	1152	1134	1117			
25	1036	1024	1018	1008	1001	1004	1010	1035	1071	1075	1084	1089	1097	1095	1076	1049			
30	957	946	942	932	923	928	938	961	998	1003	1017	1021	1027	1025	1008	973			
35	873	864	863	852	840	848	861	884	921	927	942	945	949	942	931	892			
40	788	782	781	770	756	767	782	805	840	849	863	864	867	862	850	811			
45	703	700	700	688	672	686	704	726	756	769	783	784	785	780	768	729			
50	619	625	620	612	590	611	626	645	674	689	704	705	705	701	687	648			
55	537	547	542	534	509	533	550	570	595	608	628	627	624	625	612	569			
60	455	471	468	458	432	458	475	493	511	528	553	550	542	550	535	491			
65	379	396	397	385	358	386	404	418	429	450	478	472	465	476	462	415			
70	306	325	330	316	288	317	336	344	350	376	406	397	391	403	392	344			
75	237	259	268	253	224	254	273	274	276	306	336	329	319	333	326	280			
80	175	199	211	195	165	196	215	211	209	243	271	264	253	269	266	219			
85	118	146	162	149	120	150	164	156	148	184	212	205	192	211	212	168			
90	44.7	59.0	65.4	62.0	75.7	90.2	86.4	73.4	97.3	133	164	157	140	164	166	122			
95	73.9	78.2	95.8	96.0	89.7	98.4	112	90.7	88.0	104	108	103	84.3	93.5	101	95.8			
100	82.1	103	115	107	90.9	111	124	107	85.3	108	121	107	103	113	117	100.0			
105	85.1	109	123	110	91.7	115	129	112	91.4	115	130	119	107	120	125	107			
110	88.5	111	124	112	91.1	115	131	115	96.3	117	134	128	108	132	131	108			
115	88.7	112	105	113	90.7	117	123	116	97.6	118	126	125	113	133	113	107			
120	89.5	92.9	119	112	89.0	116	122	108	100	118	115	123	109	127	111	99.8			
125	49.0	74.6	114	105	85.6	112	115	85.9	81.9	94.8	123	113	101	103	116	92.5			
130	66.8	88.8	104	101	80.9	93.4	103	102	89.2	113	116	110	92.1	101	108	93.8			
135	62.3	81.8	92.7	92.6	58.8	83.3	90.3	90.3	80.2	101	108	103	87.8	100	99.7	87.8			
140	57.3	73.8	83.1	83.1	53.0	75.3	82.3	78.9	74.6	92.1	101	97.2	80.9	92.3	95.3	82.4			
145	52.1	67.6	74.4	66.3	46.6	65.4	73.5	69.2	67.9	83.8	94.1	91.7	77.4	85.6	93.2	78.6			
150	54.7	64.8	67.4	54.7	40.6	58.1	69.0	57.7	60.7	75.4	86.8	79.4	79.3	81.2	85.1	79.9			
155	50.1	54.5	57.8	46.4	36.1	45.8	59.5	52.8	59.5	71.1	77.4	63.9	68.2	74.9	76.5	71.3			
160	42.0	44.7	47.5	39.8	36.5	31.7	49.3	47.5	50.1	63.7	68.3	53.2	58.4	64.4	66.4	60.8			
165	34.0	33.2	36.5	34.8	29.3	24.7	31.3	35.9	41.4	53.4	48.5	44.9	49.7	54.4	56.1	51.0			
170	26.2	24.4	26.9	25.8	21.9	18.3	14.3	16.7	23.6	31.0	31.5	37.4	41.7	45.5	42.5	41.9			
175	19.3	17.9	17.4	15.6	12.9	10.4	10.1	9.91	11.1	20.5	24.8	27.9	31.7	34.7	34.5	31.4			
180	11.7	11.8	12.9	13.4	13.9	14.0	14.2	13.3	11.7	11.8	12.9	13.4	13.9	14.1	14.0	13.2			

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:XIAOMI
Test Date:2023-06-25

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:9.000m [K=1.0000]
Remarks: