


## LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:220.28V I:0.2735A P:57.798W PF:0.9594 Freq:50.00Hz Lamp Flux:4779.75x1 lm		
NAME: SB-U01A60WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1200mm	

DATA OF LAMP		PHOTOMETRIC DATA Eff: 82.70 lm/W			
MODEL		I <sub>max</sub> (cd)	659.8	S/MH(C0/180)	1.27
NOMINAL POWER(W)		LOR(%)	100.0	S/MH(C90/270)	1.31
RATED VOLTAGE(V)	--	TOTAL FLUX(lm)	4779.7	η UP,DN(C0-180)	23.2,26.2
NOMINAL FLUX(lm)	4779.75	CIE CLASS	DIFFUSE	η UP,DN(C180-360)	21.9,28.7
LAMPS INSIDE	1	η up(%)	45.1	CIBSE SHR NOM	1.50
TEST VOLTAGE(V)	--	η down(%)	54.9	CIBSE SHR MAX	1.50



C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:XIAOMI  
 Test Date:2023-05-31

γ Range: 0 - 180DEG  
 γ Interval: 1.0DEG  
 Test System:EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
 Humidity:65.0%  
 Test Distance:9.000m [K=1.0000]  
 Remarks:

## ZONAL FLUX DIAGRAM

## ZONAL FLUX DIAGRAM:

$\gamma$	C0	C45	C90	C135	C180	C225	C270	C315	$\gamma$	$\Phi$ zone	$\Phi$ total	%lum,lamp
10	649.7	639.3	612.6	593.9	646.2	608.7	637.0	652.7	0- 10	60.67	60.67	1.27,1.27
20	613.9	615.4	565.0	537.3	610.2	557.4	608.6	652.0	10- 20	173.7	234.3	4.9,4.9
30	552.7	567.0	515.2	487.5	558.2	510.6	558.9	617.8	20- 30	263.8	498.2	10.4,10.4
40	502.5	516.8	468.8	444.4	514.3	467.1	512.3	560.5	30- 40	327.5	825.7	17.3,17.3
50	458.2	472.6	424.4	400.9	471.6	424.9	467.1	510.9	40- 50	367.9	1194	25,25
60	416.6	429.6	381.1	356.0	431.1	381.0	422.2	463.8	50- 60	387.1	1581	33.1,33.1
70	372.5	387.8	337.2	311.4	387.7	334.4	376.6	419.7	60- 70	384.9	1966	41.1,41.1
80	326.2	343.1	291.7	190.2	341.2	265.4	328.0	373.8	70- 80	359.4	2325	48.6,48.6
90	215.0	288.0	216.5	246.5	222.3	244.0	213.1	321.1	80- 90	298.9	2624	54.9,54.9
100	252.7	265.1	294.5	307.6	263.6	283.9	265.5	210.0	90-100	278.4	2902	60.7,60.7
110	322.0	274.8	342.8	313.7	318.9	312.9	294.3	255.5	100-110	303.5	3206	67.1,67.1
120	375.5	333.5	386.9	351.8	370.9	362.2	338.0	297.1	110-120	324.3	3530	73.9,73.9
130	334.8	367.5	357.2	341.0	352.9	328.0	380.7	333.2	120-130	314.3	3844	80.4,80.4
140	360.3	361.9	370.3	361.1	362.4	339.0	358.8	378.4	130-140	277.1	4122	86.2,86.2
150	394.2	384.8	474.2	510.9	393.5	472.6	364.7	362.6	140-150	243.6	4365	91.3,91.3
160	501.2	480.7	538.3	561.8	500.9	532.0	497.4	389.0	150-160	212.2	4577	95.8,95.8
170	567.1	543.1	559.1	561.9	569.7	555.2	541.2	519.5	160-170	149.3	4727	98.9,98.9
180	581.6	561.2	559.1	554.0	582.0	560.0	559.3	554.5	170-180	53.06	4780	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

Conical surface Flux(90deg): 1005.9 lm

%lum = 21.0%

%lamp = 21.0%

Conical surface Flux(120deg): 1580.6 lm

%lum = 33.1%


%lamp = 33.1%

C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:XIAOMI  
 Test Date:2023-05-31

$\gamma$  Range: 0 - 180DEG  
 $\gamma$  Interval: 1.0DEG  
 Test System:EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
 Humidity:65.0%  
 Test Distance:9.000m [K=1.0000]  
 Remarks:

## LUMINANCE LIMITATION CURVES

Test:U:220.28V I:0.2735A P:57.798W PF:0.9594 Freq:50.00Hz Lamp Flux:4779.75x1 lm		
NAME: SB-U01A60WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1200mm	



LUMINANCE cd/(m2)		
G(DEG)	C0/180	C90/270
85	2877	2199
80	1662	1486
75	1196	1080
70	964	872
65	827	752
60	737	674
55	675	622
50	631	584
45	600	558


C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:XIAOMI  
Test Date:2023-05-31

$\gamma$  Range: 0 - 180DEG  
 $\gamma$  Interval: 1.0DEG  
Test System:EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
Humidity:65.0%  
Test Distance:9.000m [K=1.0000]  
Remarks:

## CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:220.28V I:0.2735A P:57.798W PF:0.9594 Freq:50.00Hz Lamp Flux:4779.75x1 lm		
NAME: SB-U01A60WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1200mm	

$\rho_{cc}$	80%			70%			50%			30%			10%			0
$\rho_w$	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
$\rho_{fc}$	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio                      Coefficients of Utilization(CU)															
0.0	1.08	1.08	1.08	1.01	1.01	1.01	.86	.86	.86	.73	.73	.73	.61	.61	.61	.55
1.0	.90	.85	.81	.84	.79	.75	.71	.68	.65	.60	.57	.55	.49	.47	.45	.40
2.0	.77	.70	.64	.71	.65	.59	.61	.56	.51	.51	.47	.43	.41	.39	.36	.31
3.0	.67	.58	.52	.62	.54	.48	.53	.47	.42	.44	.39	.35	.36	.32	.29	.25
4.0	.59	.50	.43	.54	.46	.40	.46	.40	.35	.39	.34	.30	.31	.28	.25	.21
5.0	.52	.43	.36	.48	.40	.34	.41	.35	.30	.34	.29	.25	.28	.24	.21	.18
6.0	.46	.38	.31	.43	.35	.29	.37	.30	.26	.31	.26	.22	.25	.21	.18	.15
7.0	.42	.33	.27	.39	.31	.26	.33	.27	.22	.28	.23	.19	.23	.19	.16	.13
8.0	.38	.30	.24	.35	.28	.22	.30	.24	.20	.26	.21	.17	.21	.17	.14	.12
9.0	.34	.26	.21	.32	.25	.20	.28	.22	.17	.23	.19	.15	.19	.16	.13	.11
10.0	.32	.24	.19	.29	.22	.18	.25	.20	.16	.22	.17	.14	.18	.14	.11	.09



C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:XIAOMI  
Test Date:2023-05-31

$\gamma$  Range: 0 - 180DEG  
 $\gamma$  Interval: 1.0DEG  
Test System:EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
Humidity:65.0%  
Test Distance:9.000m [K=1.0000]  
Remarks:

## WEC AND CCEC

Test:U:220.28V I:0.2735A P:57.798W PF:0.9594 Freq:50.00Hz Lamp Flux:4779.75x1 lm		
NAME: SB-U01A60WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1200mm	

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio                      Wall Exitance Coefficients(WEC)															
0.0																
1.0	.363	.206	.065	.342	.195	.062	.303	.174	.056	.267	.154	.049	.234	.136	.044	
2.0	.314	.172	.053	.295	.162	.050	.259	.144	.045	.227	.127	.040	.196	.111	.035	
3.0	.279	.149	.044	.262	.140	.042	.229	.124	.038	.199	.109	.033	.171	.095	.029	
4.0	.252	.131	.038	.236	.123	.036	.206	.109	.033	.178	.096	.029	.153	.083	.025	
5.0	.229	.117	.034	.215	.110	.032	.187	.097	.029	.162	.085	.025	.138	.074	.022	
6.0	.210	.105	.030	.197	.099	.029	.172	.088	.026	.148	.077	.023	.126	.066	.020	
7.0	.194	.096	.027	.182	.091	.026	.158	.080	.023	.137	.070	.020	.116	.060	.018	
8.0	.180	.088	.025	.169	.083	.023	.147	.073	.021	.127	.064	.019	.108	.055	.016	
9.0	.168	.081	.023	.157	.077	.022	.137	.068	.019	.118	.059	.017	.100	.051	.015	
10.0	.157	.075	.021	.148	.071	.020	.129	.063	.018	.111	.055	.016	.094	.047	.014	

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Ceiling Cavity Exitance Coefficients(CCEC)															
0.0	.534	.534	.534	.456	.456	.456	.312	.312	.312	.179	.179	.179	.057	.057	.057	
1.0	.530	.502	.477	.454	.431	.410	.310	.297	.284	.179	.172	.165	.057	.055	.053	
2.0	.524	.481	.444	.449	.414	.384	.308	.286	.268	.177	.167	.157	.057	.054	.051	
3.0	.517	.465	.424	.443	.401	.367	.304	.279	.258	.176	.163	.152	.056	.053	.050	
4.0	.510	.453	.410	.437	.392	.356	.301	.273	.251	.174	.160	.148	.056	.052	.049	
5.0	.503	.444	.401	.432	.384	.349	.297	.268	.246	.172	.158	.146	.055	.051	.048	
6.0	.496	.437	.394	.426	.378	.343	.294	.265	.243	.171	.156	.144	.055	.051	.048	
7.0	.489	.430	.389	.421	.373	.339	.291	.262	.240	.169	.154	.143	.055	.050	.047	
8.0	.483	.425	.386	.416	.369	.336	.288	.259	.238	.167	.153	.142	.054	.050	.047	
9.0	.477	.421	.383	.411	.365	.334	.285	.257	.237	.166	.152	.141	.054	.050	.047	
10.0	.471	.417	.380	.406	.362	.332	.282	.255	.236	.164	.151	.141	.053	.049	.047	

C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:XIAOMI  
 Test Date:2023-05-31

γ Range: 0 - 180DEG  
 γ Interval: 1.0DEG  
 Test System:EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
 Humidity:65.0%  
 Test Distance:9.000m [K=1.0000]  
 Remarks:

UGR(Unified Glare Rating) Table

Test:U:220.28V I:0.2735A P:57.798W PF:0.9594 Freq:50.00Hz Lamp Flux:4779.75x1 lm											
NAME: SB-U01A60WSZ					TYPE:			WEIGHT:			
SPEC.:4000K					DIM.:			SERIAL No.:			
MFR.: SNOWBALL					SUR.:1200mm						
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	Viewed crosswise					Viewed endwise					
x = 2H y = 2H	8.7	9.7	9.5	10.6	11.6	8.4	9.5	9.2	10.3	11.4	
	3H	11.3	12.3	12.1	13.1	14.2	11.0	11.9	11.8	12.8	13.9
	4H	12.8	13.7	13.6	14.5	15.6	12.4	13.3	13.2	14.2	15.3
	6H	14.4	15.2	15.3	16.1	17.3	13.9	14.8	14.8	15.7	16.8
	8H	15.3	16.1	16.2	17.0	18.2	14.8	15.6	15.7	16.5	17.6
	12H	16.3	17.1	17.2	18.0	19.1	15.6	16.3	16.4	17.2	18.4
4H	2H	9.5	10.4	10.4	11.3	12.4	9.3	10.3	10.2	11.1	12.2
	3H	12.3	13.1	13.2	14.0	15.2	12.1	12.9	13.0	13.8	14.9
	4H	13.9	14.6	14.8	15.6	16.7	13.7	14.4	14.6	15.3	16.5
	6H	15.7	16.3	16.6	17.3	18.5	15.4	16.0	16.3	16.9	18.1
	8H	16.7	17.3	17.6	18.2	19.5	16.3	16.9	17.3	17.9	19.1
	12H	17.8	18.4	18.8	19.3	20.5	17.2	17.7	18.1	18.7	19.9
8H	4H	14.5	15.1	15.5	16.1	17.3	14.3	14.9	15.3	15.9	17.1
	6H	16.6	17.1	17.6	18.1	19.3	16.4	16.9	17.3	17.8	19.1
	8H	17.8	18.2	18.7	19.2	20.5	17.5	17.9	18.5	18.9	20.2
	12H	19.1	19.5	20.1	20.5	21.7	18.6	19.0	19.6	20.0	21.3
12H	4H	14.7	15.2	15.6	16.2	17.4	14.5	15.0	15.4	16.0	17.2
	6H	16.9	17.3	17.8	18.3	19.6	16.7	17.1	17.6	18.1	19.3
	8H	18.2	18.6	19.1	19.5	20.8	17.9	18.3	18.9	19.3	20.6
Variations with the observer position at spacings:											
S = 1.0H	+ 0.1 / - 0.1					+ 0.1 / - 0.1					
1.5H	+ 0.2 / - 0.3					+ 0.2 / - 0.3					
2.0H	+ 0.3 / - 0.4					+ 0.3 / - 0.4					

CIE Pub.117, 4780 lm Total Lamp Luminous Flux Corrected ( $8\log(F/F_0) = 5.4$ )  
Area: 1.13 m<sup>2</sup>

C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:XIAOMI  
Test Date:2023-05-31

$\gamma$  Range: 0 - 180DEG  
 $\gamma$  Interval: 1.0DEG  
Test System:EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
Humidity:65.0%  
Test Distance:9.000m [K=1.0000]  
Remarks:

## UTILIZATION FACTORS TABLE

Test:U:220.28V I:0.2735A P:57.798W PF:0.9594 Freq:50.00Hz Lamp Flux:4779.75x1 lm		
NAME: SB-U01A60WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1200mm	


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	41	29	22	39	28	21	35	26	20	13
0.80	50	37	29	47	35	28	42	32	26	16
1.00	57	44	36	54	42	34	47	39	31	20
1.25	64	51	42	60	48	40	52	43	37	24
1.50	69	57	48	65	53	46	56	47	41	26
2.00	76	65	57	71	61	54	62	54	48	30
2.50	81	71	63	76	66	59	65	58	52	33
3.00	85	75	68	79	71	64	68	62	56	36
4.00	90	82	75	83	76	70	72	66	62	39
5.00	93	86	80	86	80	75	74	69	65	41
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:XIAOMI  
 Test Date:2023-05-31

γ Range: 0 - 180DEG  
 γ Interval: 1.0DEG  
 Test System:EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
 Humidity:65.0%  
 Test Distance:9.000m [K=1.0000]  
 Remarks:

## ISOCANDELA DIAGRAM

Test:U:220.28V I:0.2735A P:57.798W PF:0.9594 Freq:50.00Hz Lamp Flux:4779.75x1 lm		
NAME: SB-U01A60WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1200mm	




C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:XIAOMI  
Test Date:2023-05-31

$\gamma$  Range: 0 - 180DEG  
 $\gamma$  Interval: 1.0DEG  
Test System:EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
Humidity:65.0%  
Test Distance:9.000m [K=1.0000]  
Remarks:

## AAI Figure

Test:U:220.28V I:0.2735A P:57.798W PF:0.9594 Freq:50.00Hz Lamp Flux:4779.75x1 lm		
NAME: SB-U01A60WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1200mm	




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:XIAOMI  
 Test Date:2023-05-31

γ Range: 0 - 180DEG  
 γ Interval: 1.0DEG  
 Test System:EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
 Humidity:65.0%  
 Test Distance:9.000m [K=1.0000]  
 Remarks:

### ISOLUX DIAGRAM


Test:U:220.28V I:0.2735A P:57.798W PF:0.9594 Freq:50.00Hz Lamp Flux:4779.75x1 lm		
NAME: SB-U01A60WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1200mm	



C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature: 25.3DEG  
 Operators: XIAOMI  
 Test Date: 2023-05-31

γ Range: 0 - 180DEG  
 γ Interval: 1.0DEG  
 Test System: EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
 Humidity: 65.0%  
 Test Distance: 9.000m [K=1.0000]  
 Remarks:

### Planar Illuminance Curve



C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature: 25.3DEG  
Operators: XIAOMI  
Test Date: 2023-05-31

$\gamma$  Range: 0 - 180DEG  
 $\gamma$  Interval: 1.0DEG  
Test System: EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
Humidity: 65.0%  
Test Distance: 9.000m [K=1.0000]  
Remarks:

## LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:220.28V I:0.2735A P:57.798W PF:0.9594 Freq:50.00Hz Lamp Flux:4779.75x1 lm		
NAME: SB-U01A60WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1200mm	

Table--1

UNIT: cd

C(DEG) γ (DEG)	0	22.5	45	67.5	90	112.5	135	157.5	180	202.5	225	247.5	270	292.5	315	337.5			
0	658	657	638	638	637	637	637	637	658	657	638	638	637	637	637	637			
5	653	652	642	635	629	623	620	619	651	651	628	634	640	644	646	647			
10	650	647	639	627	613	601	594	594	646	646	609	622	637	648	653	658			
15	638	633	631	611	590	575	565	565	633	632	584	604	628	646	655	657			
20	614	609	615	589	565	550	537	540	610	608	557	579	609	636	652	657			
25	582	579	593	564	540	525	512	514	584	580	535	554	584	616	640	647			
30	553	551	567	543	515	501	488	490	558	553	511	529	559	590	618	626			
35	526	525	541	518	492	478	465	468	537	528	488	506	537	563	590	595			
40	502	501	517	494	469	455	444	446	514	505	467	484	512	537	561	564			
45	480	479	494	471	446	434	424	425	492	484	446	462	489	512	536	538			
50	458	458	473	450	424	412	401	404	472	463	425	440	467	488	511	514			
55	437	437	452	428	403	390	378	383	451	444	403	419	444	464	487	491			
60	417	415	430	408	381	367	356	360	431	424	381	397	422	442	464	468			
65	395	394	409	386	359	345	334	337	410	403	358	374	400	420	442	448			
70	372	371	388	365	337	322	311	313	388	381	334	351	377	397	420	427			
75	350	347	366	343	316	299	282	287	365	357	309	327	352	374	397	405			
80	326	323	343	321	292	252	190	164	341	329	265	300	328	350	374	382			
85	283	291	319	295	217	203	233	238	309	296	206	234	300	324	348	356			
90	215	159	288	220	217	253	247	241	222	202	244	215	213	294	321	329			
95	258	249	156	248	283	279	288	281	276	260	270	277	229	179	271	289			
100	253	245	265	267	294	296	308	313	264	253	284	275	265	254	210	217			
105	280	280	265	280	317	324	314	340	280	281	300	296	274	262	262	268			
110	322	315	275	300	343	348	314	331	319	312	313	326	294	265	256	229			
115	352	346	303	312	367	370	357	332	344	346	341	354	313	272	276	267			
120	376	367	333	313	387	384	352	339	371	373	362	372	338	281	297	306			
125	373	348	365	356	385	346	332	340	374	337	331	387	363	313	320	343			
130	335	345	368	380	357	342	341	345	353	363	328	346	381	350	333	367			
135	350	366	364	365	363	345	351	358	358	367	332	346	356	381	336	392			
140	360	373	362	373	370	360	361	370	362	366	339	347	359	364	378	368			
145	374	389	383	378	395	422	455	441	376	376	361	355	356	371	373	386			
150	394	409	385	394	474	505	511	488	394	389	473	416	365	373	363	391			
155	457	485	397	462	517	533	543	536	456	452	509	493	427	375	378	399			
160	501	524	481	512	538	551	562	556	501	496	532	517	497	441	389	403			
165	545	545	519	535	553	559	565	562	544	531	547	539	523	506	471	475			
170	567	557	543	550	559	563	562	565	570	559	555	549	541	532	520	512			
175	575	563	556	559	561	561	559	562	578	565	559	556	553	549	542	535			
180	582	569	561	561	559	558	554	555	582	568	560	561	559	557	554	555			

C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:XIAOMI  
Test Date:2023-05-31

γ Range: 0 - 180DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
Humidity:65.0%  
Test Distance:9.000m [K=1.0000]  
Remarks: