


## LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:220.27V I:0.2426A P:50.667W PF:0.9482 Freq:50.00Hz Lamp Flux:3631.9x1 lm		
NAME: SB-J01B50WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1000*500mm	

DATA OF LAMP		PHOTOMETRIC DATA Eff: 71.68 lm/W			
MODEL		I <sub>max</sub> (cd)	1169	S/MH(C0/180)	1.16
NOMINAL POWER(W)		LOR(%)	100.0	S/MH(C90/270)	1.07
RATED VOLTAGE(V)	--	TOTAL FLUX(lm)	3631.9	η UP,DN(C0-180)	7.7,44.4
NOMINAL FLUX(lm)	3631.9	CIE CLASS	SEMI-D.	η UP,DN(C180-360)	6.4,41.4
LAMPS INSIDE	1	η up(%)	14.1	CIBSE SHR NOM	1.25
TEST VOLTAGE(V)	--	η down(%)	85.9	CIBSE SHR MAX	1.35



C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:XIAOMI  
 Test Date:2023-06-24

γ Range: 0 - 180DEG  
 γ Interval: 1.0DEG  
 Test System:EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
 Humidity:65.0%  
 Test Distance:9.000m [K=1.0000]  
 Remarks:

## ZONAL FLUX DIAGRAM

## ZONAL FLUX DIAGRAM:

$\gamma$	C0	C45	C90	C135	C180	C225	C270	C315	$\gamma$	$\Phi$ zone	$\Phi$ total	%lum,lamp
10	1131	1154	1160	1149	1140	1107	1088	1092	0- 10	109.0	109.0	3,3
20	1034	1073	1071	1070	1043	992.2	958.3	978.1	10- 20	305.0	414.1	11.4,11.4
30	891.6	931.1	914.8	928.3	900.2	842.7	814.7	833.8	20- 30	440.6	854.6	23.5,23.5
40	731.4	766.5	752.7	763.1	737.5	694.3	680.8	690.3	30- 40	503.7	1358	37.4,37.4
50	569.5	609.5	602.5	605.3	572.7	561.0	554.7	562.8	40- 50	504.5	1863	51.3,51.3
60	416.4	466.2	457.8	459.1	415.3	433.2	424.0	439.1	50- 60	457.1	2320	63.9,63.9
70	278.2	336.4	321.6	326.0	273.8	312.8	300.1	320.0	60- 70	371.7	2692	74.1,74.1
80	156.4	222.8	204.3	214.4	152.6	207.0	190.8	212.0	70- 80	267.2	2959	81.5,81.5
90	39.90	74.96	89.12	101.3	54.30	75.10	67.69	78.64	80- 90	160.0	3119	85.9,85.9
100	57.35	116.2	114.2	117.0	61.26	102.3	94.97	101.9	90-100	89.77	3208	88.3,88.3
110	63.66	113.0	114.9	116.2	70.07	99.15	96.49	88.55	100-110	103.5	3312	91.2,91.2
120	67.66	101.1	114.2	101.5	75.14	82.22	91.24	82.20	110-120	95.16	3407	93.8,93.8
130	44.12	108.5	111.4	110.5	48.60	92.74	81.54	86.66	120-130	81.22	3488	96,96
140	44.87	93.91	100.3	80.86	48.09	65.28	74.69	75.19	130-140	64.04	3552	97.8,97.8
150	39.29	76.95	65.12	62.10	42.41	45.44	48.48	57.60	140-150	41.47	3594	99,99
160	40.77	61.15	51.64	55.99	44.93	34.20	34.56	39.50	150-160	23.70	3618	99.6,99.6
170	33.91	45.02	45.62	45.77	37.99	24.02	22.62	22.10	160-170	11.49	3629	99.9,99.9
180	28.00	24.53	24.79	24.55	28.02	24.61	24.36	24.58	170-180	2.864	3632	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

Conical surface Flux(90deg): 1613.8 lm

%lum = 44.4%

%lamp = 44.4%

Conical surface Flux(120deg): 2319.9 lm

%lum = 63.9%


%lamp = 63.9%

C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:XIAOMI  
 Test Date:2023-06-24

$\gamma$  Range: 0 - 180DEG  
 $\gamma$  Interval: 1.0DEG  
 Test System:EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
 Humidity:65.0%  
 Test Distance:9.000m [K=1.0000]  
 Remarks:

## LUMINANCE LIMITATION CURVES

Test:U:220.27V I:0.2426A P:50.667W PF:0.9482 Freq:50.00Hz Lamp Flux:3631.9x1 lm		
NAME: SB-J01B50WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1000*500mm	



LUMINANCE cd/(m2)		
G(DEG)	C0/180	C90/270
85	2373	3573
80	1802	2353
75	1660	1998
70	1627	1881
65	1638	1834
60	1666	1831
55	1713	1845
50	1772	1874
45	1839	1916


C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:XIAOMI  
Test Date:2023-06-24

$\gamma$  Range: 0 - 180DEG  
 $\gamma$  Interval: 1.0DEG  
Test System:EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
Humidity:65.0%  
Test Distance:9.000m [K=1.0000]  
Remarks:

## CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:220.27V I:0.2426A P:50.667W PF:0.9482 Freq:50.00Hz Lamp Flux:3631.9x1 lm		
NAME: SB-J01B50WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1000*500mm	

$\rho_{cc}$	80%			70%			50%			30%			10%			0	
$\rho_w$	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
$\rho_{fc}$	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Coefficients of Utilization(CU)										
0.0	1.16	1.16	1.16	1.11	1.11	1.11	1.03	1.03	1.03	.96	.96	.96	.89	.89	.89	.86	
1.0	.99	.95	.90	.96	.91	.88	.89	.85	.82	.82	.80	.77	.77	.74	.72	.69	
2.0	.86	.79	.73	.83	.77	.71	.77	.72	.67	.72	.67	.64	.67	.63	.60	.57	
3.0	.75	.67	.61	.73	.65	.59	.68	.61	.56	.63	.58	.54	.59	.55	.51	.48	
4.0	.67	.58	.51	.65	.56	.50	.60	.53	.48	.56	.50	.46	.53	.48	.44	.41	
5.0	.60	.51	.44	.58	.49	.43	.54	.47	.41	.51	.45	.40	.47	.42	.38	.36	
6.0	.54	.45	.39	.52	.44	.38	.49	.42	.36	.46	.40	.35	.43	.38	.34	.31	
7.0	.49	.40	.34	.47	.39	.33	.45	.37	.32	.42	.36	.31	.39	.34	.30	.28	
8.0	.45	.36	.30	.43	.35	.30	.41	.34	.29	.38	.32	.28	.36	.31	.27	.25	
9.0	.41	.33	.27	.40	.32	.27	.38	.31	.26	.35	.29	.25	.34	.28	.24	.22	
10.0	.38	.30	.25	.37	.29	.24	.35	.28	.24	.33	.27	.23	.31	.26	.22	.20	



C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:XIAOMI  
 Test Date:2023-06-24

$\gamma$  Range: 0 - 180DEG  
 $\gamma$  Interval: 1.0DEG  
 Test System:EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
 Humidity:65.0%  
 Test Distance:9.000m [K=1.0000]  
 Remarks:

## WEC AND CCEC

Test:U:220.27V I:0.2426A P:50.667W PF:0.9482 Freq:50.00Hz Lamp Flux:3631.9x1 lm		
NAME: SB-J01B50WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1000*500mm	

pcc	80%			70%			50%			30%			10%			0														
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0														
pfc	20%			20%			20%			20%			20%			0														
RCR	RCR:Room Cavity Ratio															Wall Exitance Coefficients(WEC)														
0.0																														
1.0	.335	.191	.060	.324	.185	.059	.302	.173	.055	.283	.163	.052	.264	.153	.049															
2.0	.301	.165	.051	.291	.160	.049	.272	.151	.047	.254	.142	.045	.238	.134	.042															
3.0	.273	.145	.044	.264	.141	.043	.246	.134	.041	.230	.126	.039	.216	.119	.037															
4.0	.249	.129	.038	.241	.126	.037	.225	.119	.036	.211	.113	.034	.197	.107	.033															
5.0	.229	.116	.034	.221	.114	.033	.207	.108	.032	.194	.102	.030	.181	.097	.029															
6.0	.211	.106	.030	.204	.103	.030	.191	.098	.029	.179	.093	.027	.168	.088	.026															
7.0	.196	.097	.027	.190	.094	.027	.178	.090	.026	.167	.086	.025	.157	.081	.024															
8.0	.182	.089	.025	.177	.087	.025	.166	.083	.024	.156	.079	.023	.146	.075	.022															
9.0	.171	.083	.023	.166	.081	.023	.156	.077	.022	.146	.073	.021	.138	.070	.020															
10.0	.160	.077	.021	.156	.075	.021	.146	.072	.020	.138	.068	.019	.130	.065	.019															

pcc	80%			70%			50%			30%			10%			0	
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
pfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)										
0.0	.298	.298	.298	.255	.255	.255	.174	.174	.174	.100	.100	.100	.032	.032	.032		
1.0	.291	.264	.241	.249	.227	.207	.170	.156	.143	.098	.090	.083	.031	.029	.027		
2.0	.283	.241	.206	.242	.208	.178	.166	.144	.124	.096	.084	.073	.031	.027	.024		
3.0	.275	.224	.184	.236	.193	.159	.162	.134	.112	.093	.078	.066	.030	.025	.022		
4.0	.267	.211	.169	.229	.183	.147	.158	.127	.103	.091	.075	.061	.029	.024	.020		
5.0	.260	.201	.158	.223	.174	.138	.154	.122	.097	.089	.071	.058	.029	.023	.019		
6.0	.252	.193	.151	.217	.167	.131	.150	.117	.093	.087	.069	.055	.028	.023	.018		
7.0	.246	.186	.145	.211	.162	.126	.146	.113	.090	.085	.067	.053	.027	.022	.018		
8.0	.239	.181	.141	.206	.157	.123	.142	.110	.087	.083	.065	.052	.027	.021	.017		
9.0	.233	.176	.137	.201	.153	.120	.139	.107	.085	.081	.063	.051	.026	.021	.017		
10.0	.228	.172	.135	.196	.149	.118	.136	.105	.083	.079	.062	.050	.026	.020	.017		

C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:XIAOMI  
 Test Date:2023-06-24

γ Range: 0 - 180DEG  
 γ Interval: 1.0DEG  
 Test System:EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
 Humidity:65.0%  
 Test Distance:9.000m [K=1.0000]  
 Remarks:

UGR(Unified Glare Rating) Table

Test:U:220.27V I:0.2426A P:50.667W PF:0.9482 Freq:50.00Hz Lamp Flux:3631.9x1 lm											
NAME: SB-J01B50WSZ					TYPE:			WEIGHT:			
SPEC.:4000K					DIM.:			SERIAL No.:			
MFR.: SNOWBALL					SUR.:1000*500mm						
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H y = 2H	14.0	15.3	14.4	15.7	16.2	14.2	15.5	14.6	16.0	16.4	
	3H	15.6	16.8	16.1	17.3	17.8	16.0	17.2	16.5	17.7	18.2
	4H	16.3	17.5	16.8	18.0	18.5	16.8	18.0	17.3	18.5	19.0
	6H	17.0	18.1	17.5	18.6	19.2	17.7	18.8	18.3	19.3	19.9
	8H	17.3	18.4	17.9	18.9	19.5	18.2	19.2	18.7	19.8	20.3
	12H	17.6	18.7	18.2	19.2	19.8	18.7	19.7	19.2	20.2	20.8
4H	2H	14.6	15.8	15.2	16.3	16.8	14.8	16.0	15.3	16.5	17.0
	3H	16.5	17.5	17.1	18.1	18.7	16.8	17.9	17.4	18.4	19.0
	4H	17.5	18.4	18.0	19.0	19.6	17.9	18.8	18.5	19.4	20.0
	6H	18.4	19.2	19.0	19.8	20.4	19.0	19.8	19.6	20.4	21.0
	8H	18.8	19.5	19.4	20.1	20.8	19.5	20.3	20.2	20.9	21.6
	12H	19.2	19.9	19.8	20.5	21.2	20.2	20.9	20.8	21.5	22.2
8H	4H	18.0	18.7	18.6	19.3	20.0	18.3	19.1	18.9	19.7	20.4
	6H	19.1	19.8	19.8	20.4	21.1	19.7	20.3	20.3	20.9	21.7
	8H	19.7	20.3	20.4	21.0	21.7	20.4	21.0	21.1	21.6	22.4
	12H	20.3	20.8	21.0	21.5	22.3	21.2	21.7	21.9	22.4	23.2
12H	4H	18.0	18.8	18.7	19.4	20.1	18.4	19.1	19.0	19.7	20.4
	6H	19.3	19.9	20.0	20.6	21.3	19.8	20.4	20.5	21.1	21.8
	8H	20.1	20.6	20.7	21.2	22.0	20.7	21.2	21.4	21.9	22.6
Variations with the observer position at spacings:											
S = 1.0H	+ 0.1 / - 0.2					+ 0.1 / - 0.2					
1.5H	+ 0.2 / - 0.3					+ 0.2 / - 0.3					
2.0H	+ 0.2 / - 0.4					+ 0.2 / - 0.4					

CIE Pub.117, 3632 lm Total Lamp Luminous Flux Corrected ( $8\log(F/F_0) = 4.5$ )  
Area: 0.5 m<sup>2</sup>

C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:XIAOMI  
Test Date:2023-06-24

$\gamma$  Range: 0 - 180DEG  
 $\gamma$  Interval: 1.0DEG  
Test System:EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
Humidity:65.0%  
Test Distance:9.000m [K=1.0000]  
Remarks:

## UTILIZATION FACTORS TABLE

Test:U:220.27V I:0.2426A P:50.667W PF:0.9482 Freq:50.00Hz Lamp Flux:3631.9x1 lm		
NAME: SB-J01B50WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1000*500mm	


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	53	41	35	52	41	34	50	40	34	27
0.80	62	51	43	61	50	43	58	48	42	34
1.00	70	59	51	68	58	50	65	58	49	41
1.25	77	66	58	75	65	57	71	62	56	47
1.50	82	71	64	80	70	63	75	67	61	51
2.00	89	79	72	86	77	71	81	74	68	57
2.50	93	84	77	90	82	76	84	78	72	61
3.00	96	89	82	93	86	80	87	81	77	64
4.00	101	94	89	97	91	86	91	86	82	69
5.00	103	98	93	100	95	90	93	89	85	71
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:XIAOMI  
 Test Date:2023-06-24

γ Range: 0 - 180DEG  
 γ Interval: 1.0DEG  
 Test System:EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
 Humidity:65.0%  
 Test Distance:9.000m [K=1.0000]  
 Remarks:

## ISOCANDELA DIAGRAM

Test:U:220.27V I:0.2426A P:50.667W PF:0.9482 Freq:50.00Hz Lamp Flux:3631.9x1 lm		
NAME: SB-J01B50WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1000*500mm	




C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:XIAOMI  
Test Date:2023-06-24

$\gamma$  Range: 0 - 180DEG  
 $\gamma$  Interval: 1.0DEG  
Test System:EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
Humidity:65.0%  
Test Distance:9.000m [K=1.0000]  
Remarks:

## AAI Figure

Test:U:220.27V I:0.2426A P:50.667W PF:0.9482 Freq:50.00Hz Lamp Flux:3631.9x1 lm		
NAME: SB-J01B50WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1000*500mm	




Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature: 25.3DEG  
 Operators: XIAOMI  
 Test Date: 2023-06-24

γ Range: 0 - 180DEG  
 γ Interval: 1.0DEG  
 Test System: EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
 Humidity: 65.0%  
 Test Distance: 9.000m [K=1.0000]  
 Remarks:

## ISOLUX DIAGRAM


Test:U:220.27V I:0.2426A P:50.667W PF:0.9482 Freq:50.00Hz Lamp Flux:3631.9x1 lm		
NAME: SB-J01B50WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1000*500mm	



C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature: 25.3DEG  
 Operators: XIAOMI  
 Test Date: 2023-06-24

$\gamma$  Range: 0 - 180DEG  
 $\gamma$  Interval: 1.0DEG  
 Test System: EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
 Humidity: 65.0%  
 Test Distance: 9.000m [K=1.0000]  
 Remarks:

### Planar Illuminance Curve



C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature: 25.3DEG  
Operators: XIAOMI  
Test Date: 2023-06-24

$\gamma$  Range: 0 - 180DEG  
 $\gamma$  Interval: 1.0DEG  
Test System: EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
Humidity: 65.0%  
Test Distance: 9.000m [K=1.0000]  
Remarks:

## LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:220.27V I:0.2426A P:50.667W PF:0.9482 Freq:50.00Hz Lamp Flux:3631.9x1 lm		
NAME: SB-J01B50WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1000*500mm	

Table--1

UNIT: cd

C(DEG) γ (DEG)	0	22.5	45	67.5	90	112.5	135	157.5	180	202.5	225	247.5	270	292.5	315	337.5			
0	1169	1165	1162	1158	1156	1153	1151	1149	1169	1165	1162	1158	1156	1153	1151	1149			
5	1158	1163	1166	1169	1168	1164	1157	1149	1162	1150	1141	1134	1130	1128	1129	1131			
10	1131	1144	1154	1160	1160	1156	1149	1135	1140	1121	1107	1094	1088	1087	1092	1100			
15	1090	1110	1123	1127	1127	1126	1119	1103	1099	1076	1057	1037	1029	1029	1041	1055			
20	1034	1060	1073	1073	1071	1073	1070	1054	1043	1017	992	968	958	960	978	997			
25	966	998	1008	1003	998	1003	1005	991	975	947	919	896	886	889	907	930			
30	892	925	931	922	915	922	928	919	900	871	843	823	815	817	834	856			
35	812	847	849	840	832	839	846	841	820	792	767	754	747	751	761	780			
40	731	767	767	759	753	758	763	761	738	714	694	687	681	684	690	705			
45	650	686	686	682	677	680	682	680	654	637	625	621	615	618	624	631			
50	570	606	610	608	602	606	605	600	573	562	561	555	555	556	563	561			
55	491	533	537	540	529	538	531	526	493	489	497	491	489	494	501	493			
60	416	459	466	470	458	467	459	450	415	421	433	428	424	431	439	425			
65	346	388	400	403	388	396	390	378	343	356	372	367	360	369	379	361			
70	278	321	336	337	322	330	326	310	274	294	313	309	300	309	320	302			
75	215	258	277	278	259	270	267	248	211	236	258	254	243	255	265	244			
80	156	201	223	223	204	216	214	192	153	181	207	203	191	204	212	188			
85	103	147	173	173	156	168	167	141	101	131	159	154	143	155	163	136			
90	39.9	62.2	75.0	107	89.1	112	101	89.3	54.3	55.7	75.1	74.8	67.7	75.0	78.6	62.7			
95	55.5	80.5	97.2	98.5	99.6	98.4	95.1	81.6	57.6	76.1	86.9	87.7	92.4	95.2	91.4	77.2			
100	57.3	88.0	116	119	114	119	117	90.1	61.3	84.1	102	97.1	95.0	101	102	81.2			
105	60.4	92.5	116	118	116	116	117	95.7	65.7	86.8	105	100	96.7	98.5	102	83.1			
110	63.7	98.1	113	115	115	116	116	102	70.1	89.2	99.2	103	96.5	100	88.6	84.8			
115	66.2	101	118	107	114	108	119	105	73.3	88.4	94.9	93.0	91.1	81.5	93.3	82.9			
120	67.7	102	101	113	114	113	102	106	75.1	87.0	82.2	95.0	91.2	92.6	82.2	73.2			
125	60.2	80.4	115	115	114	117	117	80.1	63.8	62.9	98.1	91.5	87.4	91.4	92.9	61.5			
130	44.1	88.0	108	114	111	116	111	91.7	48.6	72.1	92.7	90.1	81.5	91.2	86.7	69.0			
135	47.6	83.0	103	109	107	113	95.4	81.2	52.6	61.3	80.3	89.0	77.7	79.6	76.8	64.6			
140	44.9	75.9	93.9	102	100	99.0	80.9	66.6	48.1	46.8	65.3	78.1	74.7	73.1	75.2	57.3			
145	41.7	68.6	85.3	95.1	92.7	77.9	71.3	59.5	45.7	40.2	55.9	63.5	65.7	70.4	66.2	51.6			
150	39.3	62.5	76.9	86.4	65.1	69.4	62.1	53.3	42.4	34.6	45.4	53.5	48.5	61.6	57.6	45.3			
155	37.0	60.1	68.3	76.1	58.2	61.1	57.3	54.2	40.5	33.6	37.4	44.6	41.4	52.5	48.1	41.4			
160	40.8	55.0	61.2	61.2	51.6	55.1	56.0	54.0	44.9	34.2	34.2	36.1	34.6	39.9	39.5	34.4			
165	37.4	49.1	55.7	47.8	44.8	55.9	52.8	48.4	41.4	29.5	29.7	32.5	27.6	29.5	31.1	27.1			
170	33.9	44.3	45.0	38.7	45.6	46.7	45.8	43.4	38.0	25.6	24.0	25.0	22.6	20.3	22.1	21.9			
175	30.1	35.6	35.2	31.8	37.6	38.0	37.6	36.3	34.8	26.8	20.3	16.8	14.6	13.4	16.3	21.7			
180	28.0	27.4	24.5	25.5	24.8	25.5	24.5	25.4	28.0	27.0	24.6	25.5	24.4	25.5	24.6	25.4			

C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:XIAOMI  
Test Date:2023-06-24

γ Range: 0 - 180DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
Humidity:65.0%  
Test Distance:9.000m [K=1.0000]  
Remarks: