


## LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:220.24V I:0.3190A P:67.513W PF:0.9610 Freq:50.00Hz Lamp Flux:5361.17x1 lm		
NAME: SB-U01A70WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1500mm	

DATA OF LAMP		PHOTOMETRIC DATA Eff: 79.41 lm/W			
MODEL		I <sub>max</sub> (cd)	783.6	S/MH(C0/180)	1.24
NOMINAL POWER(W)		LOR(%)	100.0	S/MH(C90/270)	1.15
RATED VOLTAGE(V)	--	TOTAL FLUX(lm)	5361.2	η UP,DN(C0-180)	21.7,27.8
NOMINAL FLUX(lm)	5361.17	CIE CLASS	DIFFUSE	η UP,DN(C180-360)	23.3,27.2
LAMPS INSIDE	1	η up(%)	45.0	CIBSE SHR NOM	1.50
TEST VOLTAGE(V)	--	η down(%)	55.0	CIBSE SHR MAX	1.50



C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:XIAOMI  
 Test Date:2023-06-02

γ Range: 0 - 180DEG  
 γ Interval: 1.0DEG  
 Test System:EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
 Humidity:65.0%  
 Test Distance:9.000m [K=1.0000]  
 Remarks:

## ZONAL FLUX DIAGRAM

## ZONAL FLUX DIAGRAM:

$\gamma$	C0	C45	C90	C135	C180	C225	C270	C315	$\gamma$	$\Phi$ zone	$\Phi$ total	%lum,lamp
10	758.8	774.0	774.5	765.8	762.6	744.8	738.6	746.6	0- 10	73.19	73.19	1.37,1.37
20	704.1	721.1	724.4	718.0	717.4	676.9	669.2	694.2	10- 20	207.1	280.3	5.23,5.23
30	634.3	640.8	642.6	644.6	646.3	601.9	594.6	627.7	20- 30	306.8	587.2	11.11
40	575.4	574.5	568.2	577.7	586.0	537.1	528.6	568.0	30- 40	373.4	960.6	17.9,17.9
50	524.3	514.4	503.8	518.0	532.7	483.6	473.0	514.0	40- 50	414.1	1375	25.6,25.6
60	474.2	459.1	443.8	462.7	482.5	434.0	423.0	463.4	50- 60	431.3	1806	33.7,33.7
70	421.0	402.0	385.0	406.7	431.4	383.5	372.3	412.5	60- 70	425.1	2231	41.6,41.6
80	366.4	344.5	325.5	350.6	377.2	331.8	319.9	360.8	70- 80	396.0	2627	49.49
90	256.9	154.8	147.8	238.8	231.4	206.0	183.4	222.0	80- 90	321.3	2948	55.55
100	311.8	276.5	291.8	289.8	292.9	290.8	309.2	305.9	90-100	290.2	3239	60.4,60.4
110	367.6	322.8	350.8	348.0	347.4	345.6	370.3	358.6	100-110	340.7	3579	66.8,66.8
120	364.4	365.7	386.6	373.4	356.5	380.3	421.3	387.1	110-120	359.9	3939	73.5,73.5
130	373.4	384.2	387.6	351.9	356.1	412.4	458.9	419.6	120-130	350.6	4290	80.80
140	401.8	415.9	399.0	350.0	365.3	434.8	508.5	464.7	130-140	312.4	4602	85.8,85.8
150	487.2	495.5	466.0	440.0	437.0	480.0	572.0	555.5	140-150	277.6	4880	91.91
160	584.8	564.1	562.6	583.3	552.1	583.8	616.0	612.9	150-160	250.3	5130	95.7,95.7
170	630.7	612.2	607.5	633.1	614.7	610.1	623.8	649.5	160-170	171.0	5301	98.9,98.9
180	650.8	629.2	626.0	658.8	650.6	629.1	626.1	658.9	170-180	60.17	5361	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

Conical surface Flux(90deg): 1164 lm

%lum = 21.7%

%lamp = 21.7%

Conical surface Flux(120deg): 1805.9 lm

%lum = 33.7%


%lamp = 33.7%

C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:XIAOMI  
 Test Date:2023-06-02

$\gamma$  Range: 0 - 180DEG  
 $\gamma$  Interval: 1.0DEG  
 Test System:EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
 Humidity:65.0%  
 Test Distance:9.000m [K=1.0000]  
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:220.24V I:0.3190A P:67.513W PF:0.9610 Freq:50.00Hz Lamp Flux:5361.17x1 lm		
NAME: SB-U01A70WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1500mm	




C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:XIAOMI  
Test Date:2023-06-02

γ Range: 0 - 180DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
Humidity:65.0%  
Test Distance:9.000m [K=1.0000]  
Remarks:

## CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:220.24V I:0.3190A P:67.513W PF:0.9610 Freq:50.00Hz Lamp Flux:5361.17x1 lm		
NAME: SB-U01A70WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1500mm	

$\rho_{cc}$	80%			70%			50%			30%			10%			0
$\rho_w$	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
$\rho_{fc}$	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio                      Coefficients of Utilization(CU)															
0.0	1.08	1.08	1.08	1.01	1.01	1.01	.86	.86	.86	.73	.73	.73	.61	.61	.61	.55
1.0	.91	.86	.81	.84	.79	.75	.71	.68	.65	.60	.57	.55	.49	.47	.46	.41
2.0	.78	.70	.64	.72	.65	.60	.61	.56	.52	.51	.47	.44	.42	.39	.36	.32
3.0	.67	.59	.52	.62	.55	.49	.53	.47	.42	.44	.40	.36	.36	.33	.30	.26
4.0	.59	.50	.43	.55	.47	.41	.47	.40	.35	.39	.34	.30	.32	.28	.25	.21
5.0	.52	.43	.37	.49	.41	.35	.41	.35	.30	.35	.30	.26	.29	.25	.21	.18
6.0	.47	.38	.32	.43	.36	.30	.37	.31	.26	.31	.26	.22	.26	.22	.19	.16
7.0	.42	.34	.28	.39	.31	.26	.34	.27	.23	.28	.23	.20	.23	.19	.16	.14
8.0	.38	.30	.24	.36	.28	.23	.31	.24	.20	.26	.21	.17	.21	.18	.15	.12
9.0	.35	.27	.21	.32	.25	.20	.28	.22	.18	.24	.19	.15	.20	.16	.13	.11
10.0	.32	.24	.19	.30	.23	.18	.26	.20	.16	.22	.17	.14	.18	.15	.12	.10



C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:XIAOMI  
 Test Date:2023-06-02

$\gamma$  Range: 0 - 180DEG  
 $\gamma$  Interval: 1.0DEG  
 Test System:EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
 Humidity:65.0%  
 Test Distance:9.000m [K=1.0000]  
 Remarks:

## WEC AND CCEC

Test:U:220.24V I:0.3190A P:67.513W PF:0.9610 Freq:50.00Hz Lamp Flux:5361.17x1 lm		
NAME: SB-U01A70WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1500mm	

pcc	80%			70%			50%			30%			10%			0	
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
pfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)										
0.0																	
1.0	.359	.204	.065	.338	.193	.061	.299	.172	.055	.263	.152	.049	.230	.133	.043		
2.0	.311	.171	.052	.292	.161	.050	.257	.143	.044	.224	.126	.039	.194	.110	.035		
3.0	.277	.148	.044	.260	.139	.042	.227	.123	.037	.197	.108	.033	.170	.094	.029		
4.0	.250	.130	.038	.234	.123	.036	.205	.108	.032	.177	.095	.029	.151	.082	.025		
5.0	.228	.116	.034	.213	.110	.032	.186	.097	.029	.161	.085	.025	.137	.073	.022		
6.0	.209	.105	.030	.196	.099	.028	.171	.087	.025	.147	.076	.022	.125	.066	.020		
7.0	.193	.096	.027	.181	.090	.026	.158	.080	.023	.136	.070	.020	.115	.060	.018		
8.0	.179	.088	.025	.168	.083	.023	.146	.073	.021	.126	.064	.018	.107	.055	.016		
9.0	.167	.081	.023	.157	.076	.021	.137	.068	.019	.118	.059	.017	.100	.051	.015		
10.0	.157	.075	.021	.147	.071	.020	.128	.063	.018	.110	.055	.016	.094	.047	.014		

pcc	80%			70%			50%			30%			10%			0	
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
pfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)										
0.0	.533	.533	.533	.456	.456	.456	.311	.311	.311	.179	.179	.179	.057	.057	.057		
1.0	.529	.501	.476	.453	.430	.410	.310	.296	.283	.178	.171	.165	.057	.055	.053		
2.0	.523	.480	.444	.448	.413	.384	.307	.286	.268	.177	.166	.157	.057	.054	.051		
3.0	.516	.464	.423	.442	.401	.367	.304	.278	.257	.175	.162	.152	.056	.053	.050		
4.0	.509	.452	.410	.436	.391	.356	.300	.272	.251	.174	.160	.148	.056	.052	.049		
5.0	.501	.443	.400	.431	.383	.348	.297	.268	.246	.172	.157	.146	.055	.051	.048		
6.0	.494	.436	.394	.425	.377	.343	.293	.264	.242	.170	.155	.144	.055	.051	.048		
7.0	.488	.430	.389	.420	.372	.339	.290	.261	.240	.168	.154	.143	.054	.050	.047		
8.0	.482	.424	.385	.415	.368	.336	.287	.258	.238	.167	.152	.142	.054	.050	.047		
9.0	.476	.420	.382	.410	.364	.333	.284	.256	.237	.165	.151	.141	.054	.050	.047		
10.0	.470	.416	.380	.406	.361	.331	.281	.254	.235	.164	.150	.140	.053	.049	.047		

C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:XIAOMI  
 Test Date:2023-06-02

γ Range: 0 - 180DEG  
 γ Interval: 1.0DEG  
 Test System:EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
 Humidity:65.0%  
 Test Distance:9.000m [K=1.0000]  
 Remarks:

UGR(Unified Glare Rating) Table

Test:U:220.24V I:0.3190A P:67.513W PF:0.9610 Freq:50.00Hz Lamp Flux:5361.17x1 lm											
NAME: SB-U01A70WSZ					TYPE:			WEIGHT:			
SPEC.:4000K					DIM.:			SERIAL No.:			
MFR.: SNOWBALL					SUR.:1500mm						
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	Viewed crosswise					Viewed endwise					
x = 2H y = 2H	7.6	8.7	8.4	9.5	10.5	7.3	8.3	8.1	9.2	10.2	
	10.2	11.2	11.1	12.0	13.1	9.8	10.7	10.6	11.6	12.7	
	11.7	12.6	12.5	13.5	14.5	11.1	12.1	12.0	12.9	14.0	
	13.3	14.1	14.1	15.0	16.1	12.7	13.5	13.5	14.4	15.5	
	14.2	15.0	15.1	15.9	17.0	13.5	14.3	14.4	15.2	16.4	
	15.2	16.0	16.1	16.9	18.0	14.5	15.3	15.4	16.2	17.3	
4H	2H	8.3	9.2	9.2	10.1	11.2	8.1	9.0	9.0	9.9	11.0
	3H	11.2	11.9	12.0	12.8	14.0	10.8	11.6	11.7	12.5	13.6
	4H	12.8	13.5	13.7	14.4	15.6	12.3	13.0	13.2	13.9	15.1
	6H	14.6	15.2	15.5	16.1	17.3	14.0	14.6	14.9	15.6	16.8
	8H	15.6	16.1	16.5	17.1	18.3	14.9	15.5	15.9	16.5	17.7
	12H	16.7	17.3	17.7	18.2	19.4	16.0	16.5	16.9	17.5	18.7
8H	4H	13.3	13.9	14.2	14.8	16.0	12.9	13.5	13.8	14.4	15.7
	6H	15.4	15.9	16.3	16.8	18.1	14.9	15.4	15.8	16.3	17.6
	8H	16.5	17.0	17.5	18.0	19.2	16.0	16.4	17.0	17.4	18.7
	12H	17.9	18.3	18.9	19.3	20.6	17.3	17.7	18.3	18.6	19.9
12H	4H	13.4	13.9	14.3	14.9	16.1	13.1	13.6	14.0	14.6	15.8
	6H	15.6	16.0	16.6	17.0	18.3	15.1	15.6	16.1	16.6	17.8
	8H	16.9	17.3	17.9	18.3	19.5	16.4	16.8	17.4	17.7	19.0
Variations with the observer position at spacings:											
S = 1.0H	+ 0.1 / - 0.1					+ 0.1 / - 0.1					
1.5H	+ 0.2 / - 0.3					+ 0.2 / - 0.3					
2.0H	+ 0.3 / - 0.4					+ 0.3 / - 0.4					

CIE Pub.117, 5361 lm Total Lamp Luminous Flux Corrected ( $8\log(F/F_0) = 5.8$ )  
Area: 1.766 m<sup>2</sup>

C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:XIAOMI  
Test Date:2023-06-02

$\gamma$  Range: 0 - 180DEG  
 $\gamma$  Interval: 1.0DEG  
Test System:EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
Humidity:65.0%  
Test Distance:9.000m [K=1.0000]  
Remarks:

## UTILIZATION FACTORS TABLE

Test:U:220.24V I:0.3190A P:67.513W PF:0.9610 Freq:50.00Hz Lamp Flux:5361.17x1 lm		
NAME: SB-U01A70WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1500mm	


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	41	29	22	39	28	22	35	26	20	13
0.80	50	37	29	47	36	28	42	33	26	17
1.00	57	44	36	54	42	35	48	40	32	21
1.25	64	52	43	60	49	41	53	44	37	24
1.50	69	57	49	65	54	46	57	48	42	27
2.00	77	66	57	72	62	54	62	54	48	31
2.50	82	71	63	76	67	60	66	58	53	34
3.00	85	76	68	79	71	64	68	62	57	36
4.00	90	82	76	84	77	71	72	67	62	39
5.00	93	86	80	87	81	75	74	70	66	42
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:XIAOMI  
 Test Date:2023-06-02

γ Range: 0 - 180DEG  
 γ Interval: 1.0DEG  
 Test System:EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
 Humidity:65.0%  
 Test Distance:9.000m [K=1.0000]  
 Remarks:

## ISOCANDELA DIAGRAM

Test:U:220.24V I:0.3190A P:67.513W PF:0.9610 Freq:50.00Hz Lamp Flux:5361.17x1 lm		
NAME: SB-U01A70WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1500mm	




C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:XIAOMI  
Test Date:2023-06-02

$\gamma$  Range: 0 - 180DEG  
 $\gamma$  Interval: 1.0DEG  
Test System:EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
Humidity:65.0%  
Test Distance:9.000m [K=1.0000]  
Remarks:



## AAI Figure

Test:U:220.24V I:0.3190A P:67.513W PF:0.9610 Freq:50.00Hz Lamp Flux:5361.17x1 lm		
NAME: SB-U01A70WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1500mm	




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:XIAOMI  
 Test Date:2023-06-02

γ Range: 0 - 180DEG  
 γ Interval: 1.0DEG  
 Test System:EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
 Humidity:65.0%  
 Test Distance:9.000m [K=1.0000]  
 Remarks:

## ISOLUX DIAGRAM


Test:U:220.24V I:0.3190A P:67.513W PF:0.9610 Freq:50.00Hz Lamp Flux:5361.17x1 lm		
NAME: SB-U01A70WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1500mm	



C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature: 25.3DEG  
 Operators: XIAOMI  
 Test Date: 2023-06-02

$\gamma$  Range: 0 - 180DEG  
 $\gamma$  Interval: 1.0DEG  
 Test System: EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
 Humidity: 65.0%  
 Test Distance: 9.000m [K=1.0000]  
 Remarks:

### Planar Illuminance Curve



C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature: 25.3DEG  
Operators: XIAOMI  
Test Date: 2023-06-02

$\gamma$  Range: 0 - 180DEG  
 $\gamma$  Interval: 1.0DEG  
Test System: EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
Humidity: 65.0%  
Test Distance: 9.000m [K=1.0000]  
Remarks:

## LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:220.24V I:0.3190A P:67.513W PF:0.9610 Freq:50.00Hz Lamp Flux:5361.17x1 lm		
NAME: SB-U01A70WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1500mm	

Table--1

UNIT: cd

C(DEG) γ (DEG)	0	22.5	45	67.5	90	112.5	135	157.5	180	202.5	225	247.5	270	292.5	315	337.5			
0	781	781	781	780	779	778	777	776	781	781	781	780	779	778	777	776			
5	770	778	783	783	781	776	772	770	775	768	764	761	761	761	762	763			
10	759	768	774	778	774	770	766	762	763	753	745	739	739	740	747	752			
15	736	747	754	757	756	752	748	744	746	728	715	707	708	714	725	733			
20	704	715	721	723	724	722	718	714	717	694	677	667	669	679	694	703			
25	668	677	680	682	684	684	682	679	682	657	636	626	631	642	660	668			
30	634	642	641	641	643	646	645	643	646	621	602	588	595	606	628	633			
35	603	613	607	607	604	613	609	613	617	588	568	553	560	574	598	603			
40	575	582	574	572	568	578	578	583	586	558	537	522	529	543	568	574			
45	549	555	544	540	535	546	547	555	558	531	509	493	500	515	540	547			
50	524	528	514	509	504	516	518	527	533	505	484	466	473	489	514	522			
55	499	501	487	478	473	485	490	501	507	480	458	441	447	464	488	497			
60	474	475	459	450	444	457	463	475	483	456	434	416	423	440	463	473			
65	448	448	431	420	415	427	435	448	457	430	409	391	398	415	438	447			
70	421	421	402	391	385	398	407	422	431	406	383	366	372	390	413	421			
75	393	393	373	361	355	370	378	394	405	381	357	340	346	364	386	395			
80	366	364	344	331	325	341	351	367	377	355	332	314	320	340	361	369			
85	333	331	310	297	290	299	310	335	348	324	296	279	291	313	334	340			
90	257	170	155	163	148	209	239	226	231	217	206	196	183	188	222	193			
95	311	290	248	247	269	266	263	284	298	290	272	276	281	279	285	287			
100	312	290	277	269	292	283	290	288	293	298	291	294	309	305	306	304			
105	347	329	306	294	322	300	316	331	326	316	316	320	336	327	336	343			
110	368	353	323	310	351	326	348	357	347	359	346	355	370	360	359	376			
115	395	371	303	337	371	353	331	373	379	386	335	385	395	394	322	391			
120	364	333	366	361	387	373	373	336	356	343	380	410	421	423	387	356			
125	376	372	387	389	414	390	387	383	371	396	413	438	448	448	412	388			
130	373	382	384	389	388	355	352	345	356	383	412	448	459	466	420	399			
135	384	390	396	388	385	349	339	354	356	383	415	471	482	487	439	413			
140	402	406	416	403	399	360	350	371	365	394	435	484	508	502	465	431			
145	409	418	419	410	406	364	345	385	367	399	446	498	530	527	500	450			
150	487	496	496	466	466	437	440	484	437	461	480	536	572	568	555	545			
155	542	547	532	523	521	500	527	540	499	517	539	569	603	601	583	579			
160	585	574	564	558	563	551	583	575	552	569	584	598	616	628	613	607			
165	615	594	592	584	592	580	614	608	589	597	600	618	619	646	636	628			
170	631	609	612	601	608	604	633	631	615	614	610	627	624	652	650	644			
175	645	618	623	614	617	633	648	646	634	626	621	630	625	657	655	652			
180	651	631	629	633	626	657	659	659	651	631	629	633	626	657	659	659			

C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:XIAOMI  
Test Date:2023-06-02

γ Range: 0 - 180DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
Humidity:65.0%  
Test Distance:9.000m [K=1.0000]  
Remarks: