


## LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:220.21V I:0.3342A P:71.140W PF:0.9667 Freq:50.00Hz Lamp Flux:4405.44x1 lm		
NAME: SB-J01B70WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1500*750mm	

DATA OF LAMP		PHOTOMETRIC DATA Eff: 61.93 lm/W			
MODEL		I <sub>max</sub> (cd)	1432	S/MH(C0/180)	1.13
NOMINAL POWER(W)		LOR(%)	100.0	S/MH(C90/270)	1.09
RATED VOLTAGE(V)	--	TOTAL FLUX(lm)	4405.4	η UP,DN(C0-180)	7.9,43.8
NOMINAL FLUX(lm)	4405.44	CIE CLASS	SEMI-D.	η UP,DN(C180-360)	6.9,41.4
LAMPS INSIDE	1	η up(%)	14.7	CIBSE SHR NOM	1.25
TEST VOLTAGE(V)	--	η down(%)	85.3	CIBSE SHR MAX	1.30



C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:XIAOMI  
 Test Date:2023-06-24

γ Range: 0 - 180DEG  
 γ Interval: 1.0DEG  
 Test System:EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
 Humidity:65.0%  
 Test Distance:9.000m [K=1.0000]  
 Remarks:

## ZONAL FLUX DIAGRAM

## ZONAL FLUX DIAGRAM:

$\gamma$	C0	C45	C90	C135	C180	C225	C270	C315	$\gamma$	$\Phi$ zone	$\Phi$ total	%lum,lamp
10	1410	1402	1381	1347	1374	1363	1364	1373	0- 10	133.3	133.3	3.03,3.03
20	1313	1303	1250	1217	1247	1225	1211	1257	10- 20	372.5	505.8	11.5,11.5
30	1152	1137	1067	1043	1069	1038	1016	1080	20- 30	537.4	1043	23.7,23.7
40	956.9	945.6	882.5	859.4	867.8	844.5	833.5	890.1	30- 40	613.5	1657	37.6,37.6
50	751.3	759.0	706.9	681.8	666.5	666.2	663.7	711.7	40- 50	612.2	2269	51.5,51.5
60	551.5	584.5	536.6	516.3	478.0	503.1	501.7	548.9	50- 60	550.2	2819	64,64
70	368.2	423.7	380.3	365.9	303.2	347.4	347.9	390.9	60- 70	442.8	3262	74,74
80	209.6	281.6	246.5	237.8	155.9	214.6	216.6	252.5	70- 80	312.8	3575	81.1,81.1
90	77.29	164.6	100.2	99.64	53.93	88.37	108.4	141.7	80- 90	181.6	3756	85.3,85.3
100	65.08	138.5	138.6	147.3	63.98	126.4	128.5	134.2	90-100	116.5	3873	87.9,87.9
110	71.35	145.7	147.4	129.0	70.83	93.70	136.1	126.4	100-110	128.4	4001	90.8,90.8
120	55.16	148.8	153.9	149.1	69.06	114.6	140.5	127.0	110-120	120.6	4122	93.6,93.6
130	61.95	141.5	146.1	109.1	58.99	98.74	127.1	122.2	120-130	105.3	4227	96,96
140	57.07	118.5	110.3	89.73	54.08	77.69	96.02	99.75	130-140	77.77	4305	97.7,97.7
150	59.53	92.24	73.11	89.41	59.83	65.24	72.02	73.36	140-150	51.38	4356	98.9,98.9
160	52.36	72.93	64.10	79.67	52.74	46.15	50.29	48.60	150-160	31.12	4387	99.6,99.6
170	44.88	52.85	59.85	56.22	45.08	26.23	28.51	28.08	160-170	14.41	4402	99.9,99.9
180	37.96	35.34	36.41	35.74	38.03	34.92	36.10	35.21	170-180	3.560	4405	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

Conical surface Flux(90deg): 1967.2 lm

%lum = 44.7%

%lamp = 44.7%

Conical surface Flux(120deg): 2819.2 lm

%lum = 64.0%


%lamp = 64.0%

C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:XIAOMI  
 Test Date:2023-06-24

$\gamma$  Range: 0 - 180DEG  
 $\gamma$  Interval: 1.0DEG  
 Test System:EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
 Humidity:65.0%  
 Test Distance:9.000m [K=1.0000]  
 Remarks:

## LUMINANCE LIMITATION CURVES

Test:U:220.21V I:0.3342A P:71.140W PF:0.9667 Freq:50.00Hz Lamp Flux:4405.44x1 lm		
NAME: SB-J01B70WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1500*750mm	




C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:XIAOMI  
Test Date:2023-06-24

$\gamma$  Range: 0 - 180DEG  
 $\gamma$  Interval: 1.0DEG  
Test System:EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
Humidity:65.0%  
Test Distance:9.000m [K=1.0000]  
Remarks:

## CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:220.21V I:0.3342A P:71.140W PF:0.9667 Freq:50.00Hz Lamp Flux:4405.44x1 lm		
NAME: SB-J01B70WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1500*750mm	

$\rho_{cc}$	80%			70%			50%			30%			10%			0	
$\rho_w$	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
$\rho_{fc}$	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Coefficients of Utilization(CU)										
0.0	1.16	1.16	1.16	1.11	1.11	1.11	1.03	1.03	1.03	.95	.95	.95	.89	.89	.89	.85	
1.0	.99	.95	.91	.96	.91	.88	.89	.85	.82	.82	.80	.77	.76	.74	.72	.69	
2.0	.86	.79	.73	.83	.77	.71	.77	.72	.67	.72	.67	.64	.67	.63	.60	.57	
3.0	.76	.67	.61	.73	.65	.59	.68	.62	.56	.63	.58	.54	.59	.55	.51	.48	
4.0	.67	.58	.52	.65	.57	.50	.60	.54	.48	.56	.51	.46	.53	.48	.44	.41	
5.0	.60	.51	.44	.58	.50	.44	.54	.47	.42	.51	.45	.40	.47	.42	.38	.36	
6.0	.54	.45	.39	.52	.44	.38	.49	.42	.37	.46	.40	.35	.43	.38	.34	.31	
7.0	.49	.40	.34	.47	.39	.34	.45	.38	.32	.42	.36	.31	.39	.34	.30	.28	
8.0	.45	.36	.31	.43	.36	.30	.41	.34	.29	.39	.32	.28	.36	.31	.27	.25	
9.0	.41	.33	.28	.40	.32	.27	.38	.31	.26	.36	.30	.25	.34	.28	.24	.22	
10.0	.38	.30	.25	.37	.30	.25	.35	.28	.24	.33	.27	.23	.31	.26	.22	.20	



C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:XIAOMI  
 Test Date:2023-06-24

$\gamma$  Range: 0 - 180DEG  
 $\gamma$  Interval: 1.0DEG  
 Test System:EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
 Humidity:65.0%  
 Test Distance:9.000m [K=1.0000]  
 Remarks:

## WEC AND CCEC

Test:U:220.21V I:0.3342A P:71.140W PF:0.9667 Freq:50.00Hz Lamp Flux:4405.44x1 lm		
NAME: SB-J01B70WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1500*750mm	

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)									
0.0																
1.0	.330	.188	.060	.319	.182	.058	.297	.170	.054	.277	.160	.051	.259	.150	.048	
2.0	.298	.163	.050	.288	.158	.049	.268	.149	.046	.250	.140	.044	.233	.132	.042	
3.0	.271	.144	.043	.261	.140	.042	.244	.132	.040	.228	.125	.038	.212	.118	.036	
4.0	.247	.129	.038	.239	.125	.037	.223	.118	.035	.208	.112	.034	.195	.106	.032	
5.0	.227	.116	.034	.220	.113	.033	.205	.107	.031	.192	.101	.030	.179	.096	.029	
6.0	.210	.105	.030	.203	.103	.030	.190	.097	.028	.178	.092	.027	.166	.088	.026	
7.0	.195	.096	.027	.189	.094	.027	.177	.089	.026	.165	.085	.025	.155	.080	.024	
8.0	.182	.089	.025	.176	.087	.024	.165	.082	.024	.155	.078	.023	.145	.074	.022	
9.0	.170	.082	.023	.165	.080	.023	.155	.076	.022	.145	.073	.021	.136	.069	.020	
10.0	.160	.077	.021	.155	.075	.021	.146	.071	.020	.137	.068	.019	.129	.065	.019	

pcc	80%			70%			50%			30%			10%			0	
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
pfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)										
0.0	.303	.303	.303	.259	.259	.259	.177	.177	.177	.101	.101	.101	.032	.032	.032		
1.0	.295	.269	.246	.252	.231	.212	.173	.159	.146	.099	.092	.085	.032	.030	.028		
2.0	.287	.246	.211	.246	.212	.183	.168	.146	.127	.097	.085	.075	.031	.028	.024		
3.0	.279	.229	.189	.239	.197	.164	.164	.137	.115	.095	.080	.068	.030	.026	.022		
4.0	.271	.216	.174	.233	.187	.151	.160	.130	.106	.093	.076	.063	.030	.025	.021		
5.0	.264	.206	.163	.227	.178	.142	.156	.124	.100	.090	.073	.059	.029	.024	.020		
6.0	.257	.198	.155	.221	.171	.135	.152	.120	.096	.088	.071	.057	.029	.023	.019		
7.0	.250	.191	.150	.215	.166	.131	.149	.116	.093	.086	.068	.055	.028	.022	.018		
8.0	.244	.185	.146	.210	.161	.127	.145	.113	.090	.084	.067	.054	.027	.022	.018		
9.0	.238	.181	.142	.205	.157	.124	.142	.110	.088	.083	.065	.053	.027	.021	.017		
10.0	.232	.176	.140	.200	.153	.122	.139	.108	.086	.081	.064	.052	.026	.021	.017		

C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:XIAOMI  
 Test Date:2023-06-24

γ Range: 0 - 180DEG  
 γ Interval: 1.0DEG  
 Test System:EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
 Humidity:65.0%  
 Test Distance:9.000m [K=1.0000]  
 Remarks:

UGR(Unified Glare Rating) Table

Test:U:220.21V I:0.3342A P:71.140W PF:0.9667 Freq:50.00Hz Lamp Flux:4405.44x1 lm											
NAME: SB-J01B70WSZ					TYPE:			WEIGHT:			
SPEC.:4000K					DIM.:			SERIAL No.:			
MFR.: SNOWBALL					SUR.:1500*750mm						
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H y = 2H	12.2	13.5	12.7	14.0	14.4	12.0	13.3	12.4	13.7	14.2	
	3H	13.9	15.1	14.4	15.5	16.1	13.8	15.0	14.2	15.4	16.0
	4H	14.6	15.8	15.1	16.3	16.8	14.6	15.8	15.2	16.3	16.8
	6H	15.3	16.4	15.9	16.9	17.5	15.5	16.6	16.1	17.1	17.7
	8H	15.7	16.7	16.2	17.3	17.8	16.0	17.0	16.5	17.6	18.2
	12H	16.0	17.0	16.6	17.6	18.2	16.5	17.5	17.1	18.1	18.7
4H	2H	12.8	14.0	13.4	14.5	15.0	12.7	13.8	13.2	14.3	14.9
	3H	14.8	15.8	15.3	16.3	16.9	14.7	15.7	15.3	16.2	16.8
	4H	15.7	16.6	16.3	17.2	17.8	15.8	16.7	16.3	17.2	17.9
	6H	16.6	17.5	17.3	18.1	18.7	16.8	17.7	17.4	18.2	18.9
	8H	17.1	17.8	17.7	18.4	19.1	17.4	18.2	18.0	18.8	19.5
	12H	17.5	18.2	18.1	18.8	19.5	18.0	18.7	18.7	19.3	20.1
8H	4H	16.2	16.9	16.8	17.6	18.2	16.2	17.0	16.8	17.6	18.3
	6H	17.4	18.0	18.0	18.7	19.4	17.6	18.2	18.2	18.9	19.6
	8H	18.0	18.6	18.7	19.2	20.0	18.3	18.9	19.0	19.6	20.3
	12H	18.7	19.1	19.3	19.8	20.6	19.2	19.7	19.9	20.3	21.1
12H	4H	16.3	17.0	16.9	17.6	18.3	16.3	17.0	16.9	17.6	18.3
	6H	17.6	18.2	18.3	18.8	19.6	17.8	18.3	18.4	19.0	19.7
	8H	18.3	18.8	19.0	19.5	20.3	18.6	19.1	19.3	19.8	20.6
Variations with the observer position at spacings:											
S = 1.0H	+ 0.1 / - 0.2					+ 0.1 / - 0.2					
1.5H	+ 0.2 / - 0.3					+ 0.2 / - 0.3					
2.0H	+ 0.2 / - 0.4					+ 0.2 / - 0.4					

CIE Pub.117, 4405 lm Total Lamp Luminous Flux Corrected ( $8\log(F/F_0) = 5.2$ )  
Area: 1.125 m<sup>2</sup>

C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:XIAOMI  
Test Date:2023-06-24

$\gamma$  Range: 0 - 180DEG  
 $\gamma$  Interval: 1.0DEG  
Test System:EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
Humidity:65.0%  
Test Distance:9.000m [K=1.0000]  
Remarks:

## UTILIZATION FACTORS TABLE

Test:U:220.21V I:0.3342A P:71.140W PF:0.9667 Freq:50.00Hz Lamp Flux:4405.44x1 lm		
NAME: SB-J01B70WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1500*750mm	


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	53	42	35	52	41	34	50	40	34	27
0.80	63	51	43	61	50	43	58	48	42	34
1.00	70	59	51	69	58	51	65	58	49	41
1.25	77	66	58	75	65	58	71	62	56	47
1.50	82	71	64	80	70	63	75	67	61	51
2.00	89	79	72	86	77	71	81	74	68	57
2.50	93	84	78	90	82	76	84	78	73	61
3.00	97	89	82	93	86	80	87	81	77	64
4.00	101	94	89	97	91	86	90	86	82	68
5.00	103	98	93	100	95	90	93	89	85	71
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:XIAOMI  
 Test Date:2023-06-24

γ Range: 0 - 180DEG  
 γ Interval: 1.0DEG  
 Test System:EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
 Humidity:65.0%  
 Test Distance:9.000m [K=1.0000]  
 Remarks:

## ISOCANDELA DIAGRAM

Test:U:220.21V I:0.3342A P:71.140W PF:0.9667 Freq:50.00Hz Lamp Flux:4405.44x1 lm		
NAME: SB-J01B70WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1500*750mm	




C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:XIAOMI  
Test Date:2023-06-24

$\gamma$  Range: 0 - 180DEG  
 $\gamma$  Interval: 1.0DEG  
Test System:EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
Humidity:65.0%  
Test Distance:9.000m [K=1.0000]  
Remarks:



## AAI Figure

Test:U:220.21V I:0.3342A P:71.140W PF:0.9667 Freq:50.00Hz Lamp Flux:4405.44x1 lm		
NAME: SB-J01B70WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1500*750mm	




Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature: 25.3DEG  
 Operators: XIAOMI  
 Test Date: 2023-06-24

γ Range: 0 - 180DEG  
 γ Interval: 1.0DEG  
 Test System: EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
 Humidity: 65.0%  
 Test Distance: 9.000m [K=1.0000]  
 Remarks:

## ISOLUX DIAGRAM


Test:U:220.21V I:0.3342A P:71.140W PF:0.9667 Freq:50.00Hz Lamp Flux:4405.44x1 lm		
NAME: SB-J01B70WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1500*750mm	



C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature: 25.3DEG  
 Operators: XIAOMI  
 Test Date: 2023-06-24

$\gamma$  Range: 0 - 180DEG  
 $\gamma$  Interval: 1.0DEG  
 Test System: EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
 Humidity: 65.0%  
 Test Distance: 9.000m [K=1.0000]  
 Remarks:

### Planar Illuminance Curve



C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature: 25.3DEG  
Operators: XIAOMI  
Test Date: 2023-06-24

$\gamma$  Range: 0 - 180DEG  
 $\gamma$  Interval: 1.0DEG  
Test System: EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
Humidity: 65.0%  
Test Distance: 9.000m [K=1.0000]  
Remarks:

## LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:220.21V I:0.3342A P:71.140W PF:0.9667 Freq:50.00Hz Lamp Flux:4405.44x1 lm																	
NAME: SB-J01B70WSZ									TYPE:						WEIGHT:		
SPEC.:4000K									DIM.:						SERIAL No.:		
MFR.: SNOWBALL									SUR.:1500*750mm								

Table--1

UNIT: cd

C(DEG) γ (DEG)	0	22.5	45	67.5	90	112.5	135	157.5	180	202.5	225	247.5	270	292.5	315	337.5			
0	1430	1426	1423	1420	1417	1416	1402	1405	1430	1426	1423	1420	1417	1416	1402	1405			
5	1429	1427	1423	1418	1411	1405	1385	1387	1411	1404	1401	1401	1403	1405	1397	1401			
10	1410	1410	1402	1392	1381	1371	1347	1351	1374	1366	1363	1360	1364	1372	1373	1382			
15	1371	1372	1363	1345	1326	1316	1291	1296	1319	1310	1304	1295	1298	1312	1326	1343			
20	1313	1317	1303	1276	1250	1239	1217	1225	1247	1238	1225	1210	1211	1230	1257	1284			
25	1238	1245	1226	1192	1161	1150	1132	1142	1162	1153	1135	1114	1114	1138	1173	1209			
30	1152	1160	1137	1100	1067	1054	1043	1051	1069	1059	1038	1017	1016	1041	1080	1123			
35	1057	1067	1042	1007	973	959	951	956	969	962	940	921	923	947	984	1029			
40	957	969	946	915	882	867	859	858	868	863	845	831	834	857	890	931			
45	854	870	851	825	794	779	769	761	766	766	753	744	748	770	799	834			
50	751	772	759	738	707	693	682	667	667	671	666	660	664	686	712	738			
55	650	676	670	652	621	616	597	581	573	579	586	577	585	602	629	644			
60	552	587	585	571	537	534	516	494	478	490	503	496	502	522	549	555			
65	458	498	502	489	456	454	439	411	388	405	423	419	423	443	468	468			
70	368	413	424	413	380	380	366	333	303	326	347	344	348	365	391	385			
75	285	333	350	341	310	312	298	261	226	251	278	277	279	294	319	306			
80	210	260	282	275	247	250	238	198	156	183	215	217	217	230	252	235			
85	139	194	222	215	190	194	180	141	91.3	126	162	164	161	181	194	168			
90	77.3	136	165	136	100	98.0	99.6	82.5	53.9	84.6	88.4	107	108	122	142	115			
95	60.2	87.3	104	100.0	117	137	138	104	59.7	91.7	123	126	116	123	119	89.7			
100	65.1	108	139	140	139	146	147	106	64.0	85.8	126	133	129	138	134	93.7			
105	68.5	111	147	144	143	150	150	118	67.5	87.3	123	141	135	146	137	92.2			
110	71.4	119	146	152	147	156	129	119	70.8	90.2	93.7	145	136	147	126	100			
115	73.4	117	139	156	152	159	153	101	53.4	79.2	117	141	141	144	125	95.8			
120	55.2	111	149	155	154	161	149	113	69.1	89.8	115	136	141	141	127	93.3			
125	63.3	110	147	156	153	159	131	95.9	60.4	74.3	109	132	137	137	130	91.9			
130	62.0	104	141	150	146	138	109	88.7	59.0	64.1	98.7	119	127	131	122	85.1			
135	59.8	97.7	131	144	140	113	102	82.4	56.9	56.1	89.5	106	118	124	111	78.7			
140	57.1	90.3	118	135	110	96.8	89.7	79.1	54.1	50.0	77.7	95.5	96.0	111	99.7	70.8			
145	61.5	86.4	105	114	80.3	90.8	87.9	83.3	63.5	52.4	71.5	83.7	82.2	95.0	86.8	65.4			
150	59.5	80.3	92.2	93.9	73.1	85.7	89.4	83.3	59.8	51.1	65.2	74.4	72.0	78.7	73.4	56.7			
155	56.0	73.7	81.0	77.1	73.4	87.5	87.9	75.6	56.3	44.9	57.1	65.0	63.1	63.9	61.1	48.0			
160	52.4	66.3	72.9	66.0	64.1	82.4	79.7	67.2	52.7	37.2	46.1	54.1	50.3	50.2	48.6	39.8			
165	48.5	58.8	62.9	55.5	68.6	72.4	67.3	58.1	48.8	29.7	35.6	41.0	41.1	39.4	37.6	31.6			
170	44.9	50.9	52.8	48.1	59.9	58.2	56.2	49.8	45.1	28.5	26.2	26.9	28.5	28.0	28.1	26.9			
175	41.3	43.3	42.2	44.3	47.5	46.3	43.6	40.9	40.0	31.2	23.6	19.8	18.7	19.0	23.8	30.2			
180	38.0	36.9	35.3	37.1	36.4	35.9	35.7	35.3	38.0	36.3	34.9	36.5	36.1	35.3	35.2	34.7			

C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:XIAOMI  
Test Date:2023-06-24

γ Range: 0 - 180DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
Humidity:65.0%  
Test Distance:9.000m [K=1.0000]  
Remarks: