


## LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:220.20V I:0.2027A P:41.038W PF:0.9195 Freq:50.00Hz Lamp Flux:2850.65x1 lm		
NAME: SB-J01B40WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:800*400mm	

DATA OF LAMP		PHOTOMETRIC DATA Eff: 69.46 lm/W			
MODEL		I <sub>max</sub> (cd)	904.5	S/MH(C0/180)	1.15
NOMINAL POWER(W)		LOR(%)	100.0	S/MH(C90/270)	1.13
RATED VOLTAGE(V)	--	TOTAL FLUX(lm)	2850.6	η UP,DN(C0-180)	6.4,44.1
NOMINAL FLUX(lm)	2850.65	CIE CLASS	SEMI-D.	η UP,DN(C180-360)	6.4,43.0
LAMPS INSIDE	1	η up(%)	12.9	CIBSE SHR NOM	1.25
TEST VOLTAGE(V)	--	η down(%)	87.1	CIBSE SHR MAX	1.35



C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:XIAOMI  
 Test Date:2023-06-24

γ Range: 0 - 180DEG  
 γ Interval: 1.0DEG  
 Test System:EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
 Humidity:65.0%  
 Test Distance:9.000m [K=1.0000]  
 Remarks:

## ZONAL FLUX DIAGRAM

## ZONAL FLUX DIAGRAM:

$\gamma$	C0	C45	C90	C135	C180	C225	C270	C315	$\gamma$	$\Phi$ zone	$\Phi$ total	%lum,lamp
10	877.6	894.1	899.0	883.8	868.3	858.4	862.2	861.4	0- 10	84.60	84.60	2.97,2.97
20	804.1	835.0	820.0	819.4	791.7	785.0	777.6	791.4	10- 20	238.0	322.6	11.3,11.3
30	698.7	719.0	695.7	704.8	691.3	675.4	668.6	680.7	20- 30	345.2	667.8	23.4,23.4
40	582.2	591.9	574.2	585.5	581.2	567.5	565.0	569.6	30- 40	397.7	1065	37.4,37.4
50	460.3	473.3	465.3	471.0	466.3	460.0	462.3	461.3	40- 50	403.5	1469	51.5,51.5
60	337.2	361.6	352.1	363.1	347.8	358.4	351.7	355.7	50- 60	367.9	1837	64.4,64.4
70	226.9	257.3	247.8	263.3	237.5	259.7	249.0	255.8	60- 70	300.8	2138	75,75
80	126.4	169.7	155.8	174.5	139.5	173.3	155.8	167.1	70- 80	217.3	2355	82.6,82.6
90	32.98	62.58	58.94	65.48	47.48	60.31	49.77	54.16	80- 90	128.2	2483	87.1,87.1
100	48.52	76.93	65.61	81.28	56.77	73.05	62.00	75.13	90-100	66.89	2550	89.5,89.5
110	51.36	75.50	68.61	76.09	54.41	81.18	69.28	73.96	100-110	74.69	2625	92.1,92.1
120	51.93	79.49	69.32	79.23	50.81	82.13	71.68	79.34	110-120	69.50	2694	94.5,94.5
130	48.01	70.74	65.36	65.91	36.49	70.70	68.91	73.46	120-130	58.84	2753	96.6,96.6
140	32.71	60.37	57.07	52.33	27.86	54.61	60.52	64.16	130-140	43.80	2797	98.1,98.1
150	27.40	50.48	44.77	35.40	21.95	36.11	45.04	50.98	140-150	28.95	2826	99.1,99.1
160	26.36	37.12	28.00	23.87	17.68	25.95	27.48	37.76	150-160	15.70	2842	99.7,99.7
170	21.55	25.06	19.97	16.85	14.89	19.53	20.17	26.85	160-170	7.298	2849	99.9,99.9
180	13.33	12.96	13.03	13.35	13.37	12.98	13.03	13.34	170-180	1.782	2851	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

Conical surface Flux(90deg): 1269.2 lm

%lum = 44.5%

%lamp = 44.5%

Conical surface Flux(120deg): 1836.9 lm

%lum = 64.4%


%lamp = 64.4%

C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:XIAOMI  
 Test Date:2023-06-24

$\gamma$  Range: 0 - 180DEG  
 $\gamma$  Interval: 1.0DEG  
 Test System:EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
 Humidity:65.0%  
 Test Distance:9.000m [K=1.0000]  
 Remarks:

## LUMINANCE LIMITATION CURVES

Test:U:220.20V I:0.2027A P:41.038W PF:0.9195 Freq:50.00Hz Lamp Flux:2850.65x1 lm		
NAME: SB-J01B40WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:800*400mm	




C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:XIAOMI  
Test Date:2023-06-24

γ Range: 0 - 180DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
Humidity:65.0%  
Test Distance:9.000m [K=1.0000]  
Remarks:

## CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:220.20V I:0.2027A P:41.038W PF:0.9195 Freq:50.00Hz Lamp Flux:2850.65x1 lm		
NAME: SB-J01B40WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:800*400mm	

$\rho_{cc}$	80%			70%			50%			30%			10%			0	
$\rho_w$	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
$\rho_{fc}$	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Coefficients of Utilization(CU)										
0.0	1.16	1.16	1.16	1.12	1.12	1.12	1.04	1.04	1.04	.97	.97	.97	.90	.90	.90	.87	
1.0	.99	.95	.90	.96	.92	.88	.89	.86	.83	.83	.80	.78	.77	.75	.73	.70	
2.0	.86	.79	.73	.83	.77	.71	.77	.72	.67	.72	.68	.64	.67	.64	.61	.58	
3.0	.75	.67	.60	.73	.65	.59	.68	.62	.56	.64	.58	.54	.59	.55	.51	.48	
4.0	.67	.58	.51	.65	.56	.50	.60	.53	.48	.57	.51	.46	.53	.48	.44	.41	
5.0	.60	.51	.44	.58	.49	.43	.54	.47	.41	.51	.45	.40	.48	.42	.38	.36	
6.0	.54	.45	.38	.52	.44	.38	.49	.42	.36	.46	.40	.35	.43	.38	.34	.31	
7.0	.49	.40	.34	.47	.39	.33	.45	.37	.32	.42	.36	.31	.40	.34	.30	.28	
8.0	.44	.36	.30	.43	.35	.30	.41	.34	.29	.39	.32	.28	.36	.31	.27	.25	
9.0	.41	.33	.27	.40	.32	.27	.38	.31	.26	.36	.29	.25	.34	.28	.24	.22	
10.0	.38	.30	.25	.37	.29	.24	.35	.28	.24	.33	.27	.23	.31	.26	.22	.20	



C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:XIAOMI  
 Test Date:2023-06-24

$\gamma$  Range: 0 - 180DEG  
 $\gamma$  Interval: 1.0DEG  
 Test System:EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
 Humidity:65.0%  
 Test Distance:9.000m [K=1.0000]  
 Remarks:

## WEC AND CCEC

Test:U:220.20V I:0.2027A P:41.038W PF:0.9195 Freq:50.00Hz Lamp Flux:2850.65x1 lm		
NAME: SB-J01B40WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:800*400mm	

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio                      Wall Exitance Coefficients(WEC)															
0.0																
1.0	.338	.192	.061	.327	.187	.059	.306	.176	.056	.287	.166	.053	.270	.156	.050	
2.0	.304	.166	.051	.294	.162	.050	.275	.153	.048	.258	.145	.045	.242	.137	.043	
3.0	.275	.146	.044	.266	.143	.043	.250	.135	.041	.234	.128	.039	.220	.122	.038	
4.0	.251	.130	.038	.243	.127	.038	.228	.121	.036	.214	.115	.035	.201	.109	.033	
5.0	.230	.117	.034	.223	.114	.033	.209	.109	.032	.197	.104	.031	.185	.099	.030	
6.0	.212	.106	.030	.206	.104	.030	.193	.099	.029	.182	.095	.028	.171	.090	.027	
7.0	.197	.097	.028	.191	.095	.027	.180	.091	.026	.169	.087	.025	.159	.083	.024	
8.0	.184	.090	.025	.178	.088	.025	.168	.084	.024	.158	.080	.023	.149	.076	.022	
9.0	.172	.083	.023	.167	.081	.023	.157	.078	.022	.148	.074	.021	.140	.071	.021	
10.0	.161	.077	.021	.157	.076	.021	.148	.072	.020	.140	.069	.020	.132	.066	.019	

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Ceiling Cavity Exitance Coefficients(CCEC)															
0.0	.289	.289	.289	.247	.247	.247	.168	.168	.168	.097	.097	.097	.031	.031	.031	
1.0	.281	.255	.231	.241	.219	.199	.165	.151	.138	.095	.087	.080	.030	.028	.026	
2.0	.274	.232	.196	.234	.199	.170	.161	.138	.118	.093	.080	.069	.030	.026	.023	
3.0	.266	.215	.174	.228	.185	.151	.156	.129	.106	.090	.075	.062	.029	.024	.020	
4.0	.258	.202	.159	.221	.174	.138	.152	.121	.097	.088	.071	.057	.028	.023	.019	
5.0	.250	.192	.148	.215	.166	.129	.148	.116	.091	.086	.068	.054	.028	.022	.018	
6.0	.243	.183	.141	.209	.159	.122	.144	.111	.087	.084	.065	.052	.027	.021	.017	
7.0	.236	.177	.135	.203	.153	.118	.140	.107	.083	.082	.063	.050	.026	.021	.016	
8.0	.230	.171	.131	.198	.148	.114	.137	.104	.081	.080	.061	.048	.026	.020	.016	
9.0	.224	.166	.127	.193	.144	.111	.134	.101	.079	.078	.060	.047	.025	.020	.016	
10.0	.218	.162	.125	.188	.141	.109	.130	.099	.077	.076	.059	.046	.025	.019	.015	

C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:XIAOMI  
 Test Date:2023-06-24

γ Range: 0 - 180DEG  
 γ Interval: 1.0DEG  
 Test System:EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
 Humidity:65.0%  
 Test Distance:9.000m [K=1.0000]  
 Remarks:

UGR(Unified Glare Rating) Table

Test:U:220.20V I:0.2027A P:41.038W PF:0.9195 Freq:50.00Hz Lamp Flux:2850.65x1 lm											
NAME: SB-J01B40WSZ					TYPE:			WEIGHT:			
SPEC.:4000K					DIM.:			SERIAL No.:			
MFR.: SNOWBALL					SUR.:800*400mm						
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H y = 2H	14.8	16.2	15.2	16.6	17.0	14.8	16.2	15.3	16.6	17.0	
	3H	16.4	17.7	16.9	18.1	18.6	16.6	17.9	17.1	18.3	18.8
	4H	17.2	18.4	17.7	18.9	19.4	17.5	18.7	18.0	19.1	19.7
	6H	17.9	19.0	18.4	19.5	20.0	18.4	19.5	18.9	20.0	20.5
	8H	18.2	19.3	18.7	19.8	20.3	18.8	19.9	19.3	20.4	20.9
	12H	18.5	19.5	19.0	20.1	20.6	19.3	20.3	19.8	20.8	21.4
4H	2H	15.4	16.6	15.9	17.1	17.6	15.5	16.6	15.9	17.1	17.6
	3H	17.3	18.4	17.9	18.9	19.5	17.5	18.5	18.0	19.0	19.6
	4H	18.3	19.2	18.8	19.8	20.4	18.5	19.5	19.1	20.0	20.6
	6H	19.2	20.0	19.7	20.6	21.2	19.6	20.4	20.2	21.0	21.6
	8H	19.6	20.4	20.2	20.9	21.6	20.1	20.9	20.7	21.5	22.2
	12H	20.0	20.7	20.6	21.3	22.0	20.7	21.4	21.3	22.0	22.7
8H	4H	18.7	19.5	19.3	20.1	20.8	18.9	19.7	19.5	20.3	21.0
	6H	19.9	20.6	20.5	21.2	21.9	20.3	20.9	20.9	21.6	22.2
	8H	20.5	21.1	21.1	21.7	22.4	21.0	21.6	21.6	22.2	22.9
	12H	21.1	21.6	21.8	22.3	23.0	21.8	22.3	22.5	23.0	23.7
12H	4H	18.8	19.5	19.4	20.1	20.8	19.0	19.7	19.6	20.3	21.0
	6H	20.1	20.7	20.7	21.3	22.0	20.4	21.0	21.1	21.7	22.4
	8H	20.8	21.3	21.5	22.0	22.7	21.3	21.8	21.9	22.4	23.2
Variations with the observer position at spacings:											
S = 1.0H	+ 0.1 / - 0.2					+ 0.1 / - 0.2					
1.5H	+ 0.2 / - 0.3					+ 0.2 / - 0.3					
2.0H	+ 0.2 / - 0.4					+ 0.2 / - 0.4					

CIE Pub.117, 2851 lm Total Lamp Luminous Flux Corrected ( $8\log(F/F_0) = 3.6$ )  
Area: 0.32 m<sup>2</sup>

C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:XIAOMI  
Test Date:2023-06-24

$\gamma$  Range: 0 - 180DEG  
 $\gamma$  Interval: 1.0DEG  
Test System:EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
Humidity:65.0%  
Test Distance:9.000m [K=1.0000]  
Remarks:

## UTILIZATION FACTORS TABLE

Test:U:220.20V I:0.2027A P:41.038W PF:0.9195 Freq:50.00Hz Lamp Flux:2850.65x1 lm		
NAME: SB-J01B40WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:800*400mm	


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	53	41	34	52	41	34	50	40	34	27
0.80	63	51	43	61	50	43	58	48	42	34
1.00	70	59	51	69	58	50	65	58	49	41
1.25	77	66	58	75	65	58	71	62	56	47
1.50	82	71	64	80	70	63	75	67	61	51
2.00	89	80	72	86	78	71	81	74	68	58
2.50	93	84	78	90	82	76	85	78	73	61
3.00	97	89	82	93	86	81	87	82	77	65
4.00	101	94	89	97	92	87	91	86	82	69
5.00	104	98	93	100	95	90	93	89	86	72
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:XIAOMI  
 Test Date:2023-06-24

γ Range: 0 - 180DEG  
 γ Interval: 1.0DEG  
 Test System:EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
 Humidity:65.0%  
 Test Distance:9.000m [K=1.0000]  
 Remarks:

## ISOCANDELA DIAGRAM

Test:U:220.20V I:0.2027A P:41.038W PF:0.9195 Freq:50.00Hz Lamp Flux:2850.65x1 lm		
NAME: SB-J01B40WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:800*400mm	




C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature: 25.3DEG  
 Operators: XIAOMI  
 Test Date: 2023-06-24

γ Range: 0 - 180DEG  
 γ Interval: 1.0DEG  
 Test System: EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
 Humidity: 65.0%  
 Test Distance: 9.000m [K=1.0000]  
 Remarks:



## AAI Figure

Test:U:220.20V I:0.2027A P:41.038W PF:0.9195 Freq:50.00Hz Lamp Flux:2850.65x1 lm		
NAME: SB-J01B40WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:800*400mm	




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:XIAOMI  
 Test Date:2023-06-24

γ Range: 0 - 180DEG  
 γ Interval: 1.0DEG  
 Test System:EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
 Humidity:65.0%  
 Test Distance:9.000m [K=1.0000]  
 Remarks:

## ISOLUX DIAGRAM


Test:U:220.20V I:0.2027A P:41.038W PF:0.9195 Freq:50.00Hz Lamp Flux:2850.65x1 lm		
NAME: SB-J01B40WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:800*400mm	



C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature: 25.3DEG  
 Operators: XIAOMI  
 Test Date: 2023-06-24

γ Range: 0 - 180DEG  
 γ Interval: 1.0DEG  
 Test System: EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
 Humidity: 65.0%  
 Test Distance: 9.000m [K=1.0000]  
 Remarks:

### Planar Illuminance Curve



C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature: 25.3DEG  
Operators: XIAOMI  
Test Date: 2023-06-24

$\gamma$  Range: 0 - 180DEG  
 $\gamma$  Interval: 1.0DEG  
Test System: EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
Humidity: 65.0%  
Test Distance: 9.000m [K=1.0000]  
Remarks:

## LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:220.20V I:0.2027A P:41.038W PF:0.9195 Freq:50.00Hz Lamp Flux:2850.65x1 lm																	
NAME: SB-J01B40WSZ									TYPE:						WEIGHT:		
SPEC.:4000K									DIM.:						SERIAL No.:		
MFR.: SNOWBALL									SUR.:800*400mm								

Table--1

UNIT: cd

C(DEG) γ (DEG)	0	22.5	45	67.5	90	112.5	135	157.5	180	202.5	225	247.5	270	292.5	315	337.5			
0	901	899	897	896	894	893	892	891	901	899	897	896	894	893	892	891			
5	892	898	900	902	904	903	898	891	892	888	888	887	884	881	881	881			
10	878	889	894	896	899	896	884	872	868	863	858	863	862	858	861	866			
15	847	865	873	870	868	868	860	846	836	830	827	826	828	828	834	833			
20	804	827	835	826	820	817	819	807	792	786	785	778	778	783	791	793			
25	753	781	781	766	760	758	763	762	742	737	731	726	723	729	739	745			
30	699	727	719	704	696	694	705	713	691	687	675	671	669	674	681	689			
35	641	668	656	641	632	630	644	659	637	634	620	616	615	617	623	632			
40	582	606	592	582	574	572	585	601	581	575	567	563	565	563	570	573			
45	523	550	531	528	519	522	528	545	524	516	514	510	514	511	515	516			
50	460	486	473	473	465	468	471	484	466	459	460	459	462	458	461	460			
55	398	425	416	420	409	416	416	424	407	406	408	408	407	405	409	404			
60	337	365	362	365	352	364	363	366	348	352	358	356	352	352	356	349			
65	282	309	307	313	299	313	312	312	291	302	308	306	298	302	304	296			
70	227	254	257	262	248	263	263	260	238	254	260	257	249	252	256	245			
75	174	203	213	212	201	215	218	209	187	209	215	212	201	207	211	198			
80	126	156	170	169	156	170	174	164	139	165	173	168	156	163	167	153			
85	83.0	113	128	129	116	129	133	121	94.6	122	134	129	116	124	129	112			
90	33.0	53.1	62.6	69.5	58.9	69.8	65.5	61.2	47.5	50.3	60.3	54.0	49.8	51.4	54.2	45.7			
95	46.7	59.6	66.9	69.6	65.5	71.2	73.6	69.3	58.8	67.1	66.2	64.6	62.7	64.9	65.8	59.1			
100	48.5	64.2	76.9	79.2	65.6	76.4	81.3	72.1	56.8	70.5	73.1	73.5	62.0	75.1	75.1	62.5			
105	50.0	62.8	78.9	75.9	71.1	74.9	81.6	67.3	55.3	71.2	77.1	76.4	67.0	69.3	72.7	65.9			
110	51.4	70.1	75.5	69.5	68.6	69.2	76.1	72.3	54.4	76.0	81.2	69.6	69.3	68.2	74.0	72.5			
115	52.1	70.7	82.4	66.6	69.5	62.0	80.4	69.8	53.1	75.4	83.5	68.3	69.7	68.8	78.4	73.5			
120	51.9	70.0	79.5	73.6	69.3	70.0	79.2	67.9	50.8	71.1	82.1	73.7	71.7	74.2	79.3	67.9			
125	50.9	67.0	63.7	73.3	68.0	68.7	61.5	64.2	47.7	64.7	66.2	73.8	71.6	76.5	65.9	64.2			
130	48.0	47.7	70.7	72.0	65.4	67.0	65.9	43.9	36.5	46.0	70.7	70.7	68.9	72.1	73.5	50.4			
135	29.8	51.9	66.1	69.4	61.6	63.9	60.9	38.4	24.6	40.8	66.0	69.0	64.7	72.0	69.0	52.7			
140	32.7	48.2	60.4	65.2	57.1	59.5	52.3	42.1	27.9	45.3	54.6	59.9	60.5	66.3	64.2	51.3			
145	30.2	44.3	56.1	57.7	50.1	49.2	42.4	31.4	23.9	34.4	44.3	48.3	51.6	60.1	58.0	46.0			
150	27.4	39.9	50.5	50.8	44.8	38.4	35.4	25.9	21.9	29.5	36.1	38.5	45.0	53.2	51.0	42.4			
155	25.1	36.4	43.8	44.9	32.0	30.9	29.1	22.2	19.6	25.2	30.6	32.5	31.0	44.7	44.1	37.9			
160	26.4	34.2	37.1	36.7	28.0	25.3	23.9	19.4	17.7	23.0	25.9	27.7	27.5	37.1	37.8	36.4			
165	25.0	29.5	30.8	29.2	24.3	21.2	20.6	20.5	18.3	22.4	23.0	23.1	24.2	29.3	32.1	32.0			
170	21.5	25.3	25.1	23.3	20.0	18.5	16.8	16.7	14.9	18.9	19.5	21.3	20.2	23.9	26.9	27.0			
175	18.1	18.9	20.8	19.3	17.7	16.5	13.3	11.6	11.7	14.3	15.3	17.9	19.7	19.9	22.0	21.7			
180	13.3	13.2	13.0	12.8	13.0	13.1	13.4	13.8	13.4	13.1	13.0	12.8	13.0	13.1	13.3	13.8			

C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:XIAOMI  
Test Date:2023-06-24

γ Range: 0 - 180DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
Humidity:65.0%  
Test Distance:9.000m [K=1.0000]  
Remarks: