


## LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:220.43V I:0.2712A P:51.621W PF:0.8635 Freq:50.00Hz Lamp Flux:3435.24x1 lm		
NAME: SB-J01A50WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1000*1000mm	

DATA OF LAMP		PHOTOMETRIC DATA Eff: 66.55 lm/W			
MODEL		I <sub>max</sub> (cd)	1080	S/MH(C0/180)	1.20
NOMINAL POWER(W)		LOR(%)	100.0	S/MH(C90/270)	1.19
RATED VOLTAGE(V)	--	TOTAL FLUX(lm)	3435.2	η UP,DN(C0-180)	7.0,40.9
NOMINAL FLUX(lm)	3435.24	CIE CLASS	SEMI-D.	η UP,DN(C180-360)	7.9,44.2
LAMPS INSIDE	1	η up(%)	14.9	CIBSE SHR NOM	1.25
TEST VOLTAGE(V)	--	η down(%)	85.1	CIBSE SHR MAX	1.35



C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:XIAOMI  
 Test Date:2023-06-25

γ Range: 0 - 180DEG  
 γ Interval: 1.0DEG  
 Test System:EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
 Humidity:65.0%  
 Test Distance:9.000m [K=1.0000]  
 Remarks:

## ZONAL FLUX DIAGRAM

## ZONAL FLUX DIAGRAM:

$\gamma$	C0	C45	C90	C135	C180	C225	C270	C315	$\gamma$	$\Phi$ zone	$\Phi$ total	%lum,lamp
10	1024	1022	1025	1038	1069	1065	1049	1029	0- 10	100.5	100.5	2.93,2.93
20	922.5	917.1	922.3	956.1	994.6	996.6	970.6	942.6	10- 20	282.1	382.7	11.1,11.1
30	794.9	783.4	787.9	827.9	865.1	876.7	845.8	818.7	20- 30	410.5	793.1	23.1,23.1
40	658.4	645.0	647.0	685.0	717.4	733.2	707.2	684.8	30- 40	472.9	1266	36.9,36.9
50	520.4	515.0	508.8	545.3	573.0	589.5	572.4	558.0	40- 50	476.1	1742	50.7,50.7
60	385.7	392.1	376.0	412.4	433.6	456.0	439.3	432.6	50- 60	432.1	2174	63.3,63.3
70	262.8	277.3	251.7	290.3	293.8	328.4	309.4	314.7	60- 70	350.7	2525	73.5,73.5
80	155.8	175.6	146.6	182.0	173.1	214.9	194.5	209.1	70- 80	249.5	2774	80.8,80.8
90	36.80	56.31	45.92	63.57	63.14	94.46	86.01	88.29	80- 90	148.0	2922	85.1,85.1
100	74.03	99.12	75.92	104.4	75.70	117.0	95.47	115.4	90-100	93.15	3016	87.8,87.8
110	78.33	103.6	80.68	111.4	81.32	119.4	101.5	107.5	100-110	103.2	3119	90.8,90.8
120	76.79	90.72	80.15	86.51	84.30	97.66	94.04	85.72	110-120	95.55	3214	93.6,93.6
130	64.64	83.71	74.87	94.81	59.81	102.2	90.90	94.24	120-130	77.10	3291	95.8,95.8
140	47.21	70.56	53.66	81.09	63.47	89.69	71.89	82.10	130-140	61.13	3353	97.6,97.6
150	40.05	61.71	45.61	67.82	53.34	75.56	58.92	70.61	140-150	41.63	3394	98.8,98.8
160	40.51	46.47	42.08	52.49	48.79	60.10	47.37	52.47	150-160	25.89	3420	99.6,99.6
170	28.78	30.38	29.06	40.00	38.03	45.39	33.38	35.76	160-170	12.31	3432	99.9,99.9
180	20.55	20.09	19.97	20.63	20.59	20.10	19.90	20.70	170-180	2.880	3435	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

Conical surface Flux(90deg): 1506.8 lm

%lum = 43.9%

%lamp = 43.9%

Conical surface Flux(120deg): 2174.2 lm

%lum = 63.3%


%lamp = 63.3%

C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:XIAOMI  
 Test Date:2023-06-25

$\gamma$  Range: 0 - 180DEG  
 $\gamma$  Interval: 1.0DEG  
 Test System:EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
 Humidity:65.0%  
 Test Distance:9.000m [K=1.0000]  
 Remarks:

## LUMINANCE LIMITATION CURVES

Test:U:220.43V I:0.2712A P:51.621W PF:0.8635 Freq:50.00Hz Lamp Flux:3435.24x1 lm		
NAME: SB-J01A50WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1000*1000mm	




C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:XIAOMI  
 Test Date:2023-06-25

γ Range: 0 - 180DEG  
 γ Interval: 1.0DEG  
 Test System:EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
 Humidity:65.0%  
 Test Distance:9.000m [K=1.0000]  
 Remarks:

## CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:220.43V I:0.2712A P:51.621W PF:0.8635 Freq:50.00Hz Lamp Flux:3435.24x1 lm		
NAME: SB-J01A50WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1000*1000mm	

$\rho_{cc}$	80%			70%			50%			30%			10%			0	
$\rho_w$	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
$\rho_{fc}$	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Coefficients of Utilization(CU)										
0.0	1.15	1.15	1.15	1.11	1.11	1.11	1.03	1.03	1.03	.95	.95	.95	.88	.88	.88	.85	
1.0	.99	.94	.90	.95	.91	.87	.88	.85	.82	.82	.79	.77	.76	.74	.72	.69	
2.0	.86	.79	.73	.83	.76	.71	.77	.71	.67	.71	.67	.63	.66	.63	.60	.57	
3.0	.75	.67	.60	.73	.65	.59	.67	.61	.56	.63	.58	.53	.58	.54	.50	.48	
4.0	.67	.58	.51	.64	.56	.50	.60	.53	.48	.56	.50	.45	.52	.47	.43	.41	
5.0	.60	.51	.44	.58	.49	.43	.54	.47	.41	.50	.44	.39	.47	.42	.38	.35	
6.0	.54	.45	.38	.52	.44	.38	.49	.41	.36	.45	.39	.35	.43	.37	.33	.31	
7.0	.49	.40	.34	.47	.39	.33	.44	.37	.32	.42	.35	.31	.39	.34	.30	.27	
8.0	.44	.36	.30	.43	.35	.30	.40	.34	.29	.38	.32	.28	.36	.31	.27	.24	
9.0	.41	.33	.27	.40	.32	.27	.37	.31	.26	.35	.29	.25	.33	.28	.24	.22	
10.0	.38	.30	.25	.36	.29	.24	.34	.28	.23	.33	.27	.23	.31	.26	.22	.20	



C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:XIAOMI  
 Test Date:2023-06-25

$\gamma$  Range: 0 - 180DEG  
 $\gamma$  Interval: 1.0DEG  
 Test System:EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
 Humidity:65.0%  
 Test Distance:9.000m [K=1.0000]  
 Remarks:

## WEC AND CCEC

Test:U:220.43V I:0.2712A P:51.621W PF:0.8635 Freq:50.00Hz Lamp Flux:3435.24x1 lm		
NAME: SB-J01A50WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1000*1000mm	

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Wall Exitance Coefficients(WEC)															
0.0																
1.0	.334	.190	.060	.322	.184	.058	.301	.172	.055	.281	.162	.052	.262	.152	.049	
2.0	.301	.165	.051	.290	.160	.049	.270	.150	.047	.252	.142	.044	.236	.133	.042	
3.0	.273	.145	.043	.263	.141	.042	.246	.133	.040	.229	.126	.039	.214	.118	.037	
4.0	.249	.129	.038	.240	.126	.037	.224	.119	.036	.210	.113	.034	.196	.106	.032	
5.0	.229	.116	.034	.221	.113	.033	.206	.107	.032	.193	.102	.030	.180	.096	.029	
6.0	.211	.106	.030	.204	.103	.030	.191	.098	.028	.178	.093	.027	.167	.088	.026	
7.0	.196	.097	.027	.189	.094	.027	.177	.090	.026	.166	.085	.025	.155	.081	.024	
8.0	.182	.089	.025	.177	.087	.025	.166	.083	.024	.155	.079	.023	.145	.075	.022	
9.0	.171	.083	.023	.165	.081	.023	.155	.077	.022	.146	.073	.021	.137	.069	.020	
10.0	.160	.077	.021	.155	.075	.021	.146	.072	.020	.137	.068	.019	.129	.065	.019	

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Ceiling Cavity Exitance Coefficients(CCEC)															
0.0	.304	.304	.304	.260	.260	.260	.177	.177	.177	.102	.102	.102	.033	.033	.033	
1.0	.297	.271	.247	.254	.232	.213	.174	.160	.147	.100	.092	.086	.032	.030	.028	
2.0	.289	.247	.212	.247	.213	.184	.170	.147	.128	.098	.086	.075	.031	.028	.024	
3.0	.281	.230	.190	.241	.199	.165	.165	.138	.116	.096	.081	.068	.031	.026	.022	
4.0	.273	.218	.175	.235	.188	.152	.161	.131	.107	.093	.077	.063	.030	.025	.021	
5.0	.266	.208	.164	.228	.180	.143	.157	.125	.101	.091	.074	.060	.029	.024	.020	
6.0	.259	.199	.157	.222	.173	.137	.153	.121	.097	.089	.071	.057	.029	.023	.019	
7.0	.252	.193	.151	.217	.167	.132	.150	.117	.093	.087	.069	.056	.028	.023	.018	
8.0	.245	.187	.147	.211	.162	.128	.146	.114	.091	.085	.067	.054	.028	.022	.018	
9.0	.239	.182	.144	.206	.158	.125	.143	.111	.089	.083	.066	.053	.027	.022	.018	
10.0	.234	.178	.141	.202	.155	.123	.140	.109	.087	.082	.064	.052	.026	.021	.017	

C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:XIAOMI  
 Test Date:2023-06-25

γ Range: 0 - 180DEG  
 γ Interval: 1.0DEG  
 Test System:EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
 Humidity:65.0%  
 Test Distance:9.000m [K=1.0000]  
 Remarks:

UGR(Unified Glare Rating) Table

Test:U:220.43V I:0.2712A P:51.621W PF:0.8635 Freq:50.00Hz Lamp Flux:3435.24x1 lm											
NAME: SB-J01A50WSZ					TYPE:			WEIGHT:			
SPEC.:4000K					DIM.:			SERIAL No.:			
MFR.: SNOWBALL					SUR.:1000*1000mm						
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	Viewed crosswise					Viewed endwise					
x = 2H y = 2H	10.8	12.1	11.3	12.6	13.1	10.7	12.0	11.2	12.5	13.0	
	3H	12.5	13.7	13.0	14.2	14.7	12.4	13.6	12.9	14.1	14.6
	4H	13.3	14.5	13.8	15.0	15.5	13.1	14.3	13.7	14.8	15.4
	6H	14.1	15.2	14.6	15.7	16.3	13.9	15.0	14.4	15.5	16.1
	8H	14.5	15.5	15.0	16.0	16.6	14.2	15.3	14.8	15.8	16.4
	12H	14.8	15.9	15.4	16.4	17.0	14.6	15.6	15.2	16.2	16.8
4H	2H	11.4	12.6	11.9	13.1	13.6	11.3	12.5	11.9	13.0	13.6
	3H	13.3	14.4	13.9	14.9	15.5	13.2	14.2	13.8	14.8	15.4
	4H	14.3	15.2	14.9	15.8	16.5	14.2	15.1	14.8	15.7	16.3
	6H	15.3	16.1	15.9	16.7	17.4	15.1	15.9	15.7	16.5	17.2
	8H	15.8	16.5	16.4	17.1	17.8	15.6	16.3	16.2	16.9	17.6
	12H	16.2	17.0	16.9	17.6	18.3	16.1	16.8	16.7	17.4	18.1
8H	4H	14.7	15.5	15.3	16.1	16.8	14.6	15.4	15.2	16.0	16.7
	6H	15.9	16.6	16.6	17.2	18.0	15.8	16.4	16.4	17.1	17.8
	8H	16.6	17.2	17.3	17.8	18.6	16.4	17.0	17.1	17.7	18.4
	12H	17.3	17.8	18.0	18.4	19.2	17.1	17.6	17.8	18.3	19.1
12H	4H	14.8	15.5	15.4	16.1	16.8	14.7	15.4	15.3	16.0	16.7
	6H	16.1	16.7	16.8	17.3	18.1	16.0	16.5	16.6	17.2	17.9
	8H	16.8	17.3	17.5	18.0	18.8	16.7	17.2	17.4	17.9	18.7
Variations with the observer position at spacings:											
S = 1.0H	+ 0.1 / - 0.2					+ 0.1 / - 0.2					
1.5H	+ 0.2 / - 0.3					+ 0.2 / - 0.3					
2.0H	+ 0.1 / - 0.3					+ 0.2 / - 0.3					

CIE Pub.117, 3435 lm Total Lamp Luminous Flux Corrected ( $8\log(F/F_0) = 4.3$ )  
Area: 1 m<sup>2</sup>

C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:XIAOMI  
Test Date:2023-06-25

$\gamma$  Range: 0 - 180DEG  
 $\gamma$  Interval: 1.0DEG  
Test System:EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
Humidity:65.0%  
Test Distance:9.000m [K=1.0000]  
Remarks:

## UTILIZATION FACTORS TABLE

Test:U:220.43V I:0.2712A P:51.621W PF:0.8635 Freq:50.00Hz Lamp Flux:3435.24x1 lm		
NAME: SB-J01A50WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1000*1000mm	


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	53	41	34	52	41	34	50	40	33	27
0.80	62	50	43	61	49	42	58	48	41	34
1.00	70	58	51	68	57	50	65	57	49	41
1.25	77	66	58	75	64	57	70	62	55	46
1.50	82	71	63	79	69	62	75	66	60	50
2.00	89	79	72	86	77	70	80	73	68	57
2.50	93	84	77	90	82	75	84	77	72	60
3.00	96	88	82	93	86	80	87	81	76	64
4.00	101	94	88	97	91	86	90	85	81	68
5.00	103	97	93	99	94	90	92	88	85	71
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:XIAOMI  
 Test Date:2023-06-25

γ Range: 0 - 180DEG  
 γ Interval: 1.0DEG  
 Test System:EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
 Humidity:65.0%  
 Test Distance:9.000m [K=1.0000]  
 Remarks:

## ISOCANDELA DIAGRAM

Test:U:220.43V I:0.2712A P:51.621W PF:0.8635 Freq:50.00Hz Lamp Flux:3435.24x1 lm		
NAME: SB-J01A50WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1000*1000mm	




C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:XIAOMI  
Test Date:2023-06-25

$\gamma$  Range: 0 - 180DEG  
 $\gamma$  Interval: 1.0DEG  
Test System:EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
Humidity:65.0%  
Test Distance:9.000m [K=1.0000]  
Remarks:



## AAI Figure

Test:U:220.43V I:0.2712A P:51.621W PF:0.8635 Freq:50.00Hz Lamp Flux:3435.24x1 lm		
NAME: SB-J01A50WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1000*1000mm	




Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature: 25.3DEG  
 Operators: XIAOMI  
 Test Date: 2023-06-25

γ Range: 0 - 180DEG  
 γ Interval: 1.0DEG  
 Test System: EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
 Humidity: 65.0%  
 Test Distance: 9.000m [K=1.0000]  
 Remarks:

### ISOLUX DIAGRAM


Test:U:220.43V I:0.2712A P:51.621W PF:0.8635 Freq:50.00Hz Lamp Flux:3435.24x1 lm		
NAME: SB-J01A50WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1000*1000mm	



C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:XIAOMI  
 Test Date:2023-06-25

γ Range: 0 - 180DEG  
 γ Interval: 1.0DEG  
 Test System:EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
 Humidity:65.0%  
 Test Distance:9.000m [K=1.0000]  
 Remarks:

### Planar Illuminance Curve



C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature: 25.3DEG  
Operators: XIAOMI  
Test Date: 2023-06-25

$\gamma$  Range: 0 - 180DEG  
 $\gamma$  Interval: 1.0DEG  
Test System: EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
Humidity: 65.0%  
Test Distance: 9.000m [K=1.0000]  
Remarks:

## LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:220.43V I:0.2712A P:51.621W PF:0.8635 Freq:50.00Hz Lamp Flux:3435.24x1 lm																	
NAME: SB-J01A50WSZ									TYPE:						WEIGHT:		
SPEC.:4000K									DIM.:						SERIAL No.:		
MFR.: SNOWBALL									SUR.:1000*1000mm								

Table--1

UNIT: cd

C(DEG) γ (DEG)	0	22.5	45	67.5	90	112.5	135	157.5	180	202.5	225	247.5	270	292.5	315	337.5			
0	1076	1073	1073	1070	1067	1062	1063	1063	1076	1073	1073	1070	1067	1062	1063	1063			
5	1058	1054	1054	1054	1054	1052	1056	1063	1079	1077	1075	1069	1063	1055	1051	1048			
10	1024	1021	1022	1024	1025	1027	1038	1048	1069	1066	1065	1057	1049	1038	1029	1018			
15	978	974	976	978	980	988	1005	1017	1040	1038	1038	1029	1017	1005	992	975			
20	923	920	917	920	922	936	956	971	995	995	997	985	971	957	943	925			
25	860	856	854	854	857	874	896	913	934	938	942	929	912	898	885	867			
30	795	790	783	785	788	807	828	845	865	873	877	865	846	832	819	804			
35	727	722	714	716	717	738	757	773	792	802	806	796	776	765	752	738			
40	658	654	645	649	647	668	685	700	717	729	733	725	707	696	685	672			
45	589	588	579	581	578	598	615	628	644	656	661	655	639	629	618	604			
50	520	525	515	518	509	533	545	561	573	583	590	585	572	564	558	537			
55	452	460	453	454	441	466	478	494	503	511	524	517	507	500	495	470			
60	386	396	392	391	376	401	412	425	434	442	456	450	439	438	433	405			
65	324	335	334	331	312	338	350	359	362	374	391	385	373	376	372	344			
70	263	276	277	273	252	277	290	296	294	309	328	323	309	317	315	286			
75	207	222	225	217	195	219	234	236	231	248	269	262	250	259	260	230			
80	156	172	176	168	147	169	182	182	173	191	215	208	195	208	209	178			
85	109	125	135	127	105	127	139	131	121	141	166	159	144	161	164	133			
90	36.8	65.8	56.3	63.7	45.9	62.9	63.6	66.8	63.1	75.2	94.5	94.4	86.0	90.0	88.3	59.4			
95	71.1	78.9	83.6	81.8	73.5	84.9	92.4	83.3	72.9	91.2	107	105	98.3	109	106	86.9			
100	74.0	88.3	99.1	90.2	75.9	93.5	104	91.6	75.7	95.8	117	106	95.5	114	115	93.0			
105	76.7	92.9	103	90.5	78.6	97.0	109	97.1	78.9	101	120	115	96.0	109	114	87.0			
110	78.3	92.9	104	95.5	80.7	92.2	111	97.9	81.3	100	119	113	102	111	108	84.4			
115	78.8	95.4	76.7	95.5	81.8	101	112	101	83.1	101	118	120	100.0	112	88.8	81.6			
120	76.8	92.2	90.7	91.3	80.2	98.1	86.5	102	84.3	102	97.7	113	94.0	104	85.7	85.7			
125	41.3	59.2	89.8	86.1	78.2	95.8	99.7	90.1	78.5	87.6	102	109	90.6	91.2	88.9	58.4			
130	64.6	75.7	83.7	84.6	74.9	81.5	94.8	75.5	59.8	79.6	102	99.5	90.9	95.1	94.2	79.4			
135	50.7	68.8	76.1	79.4	56.9	77.5	86.7	86.6	74.7	91.1	96.3	95.8	75.4	90.2	86.5	73.5			
140	47.2	61.9	70.6	69.2	53.7	72.3	81.1	77.0	63.5	81.6	89.7	89.0	71.9	82.2	82.1	68.1			
145	43.9	56.2	65.3	58.0	49.8	66.3	74.1	67.1	59.1	72.9	82.3	80.7	65.4	73.1	76.0	62.8			
150	40.1	55.5	61.7	49.1	45.6	62.7	67.8	60.0	53.3	65.4	75.6	74.9	58.9	64.4	70.6	61.3			
155	47.0	52.2	55.1	46.0	48.8	62.1	60.2	51.8	47.9	58.6	68.2	71.8	54.2	57.0	62.7	57.2			
160	40.5	45.7	46.5	40.4	42.1	54.1	52.5	47.8	48.8	54.1	60.1	62.9	47.4	49.1	52.5	50.7			
165	34.5	38.4	37.1	37.9	35.4	44.8	45.8	43.6	42.8	48.6	51.7	52.0	40.7	43.6	43.1	43.8			
170	28.8	29.9	30.4	29.8	29.1	35.3	40.0	37.7	38.0	42.5	45.4	41.1	33.4	35.0	35.8	35.0			
175	23.8	22.6	22.8	23.0	23.3	26.0	28.5	28.7	31.4	32.3	33.3	31.9	28.3	28.8	27.9	26.4			
180	20.6	19.7	20.1	20.1	20.0	20.2	20.6	20.6	20.6	19.7	20.1	20.0	19.9	20.3	20.7	20.6			

C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:XIAOMI  
Test Date:2023-06-25

γ Range: 0 - 180DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
Humidity:65.0%  
Test Distance:9.000m [K=1.0000]  
Remarks: