


LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:220.20V I:0.3741A P:80.321W PF:0.9749 Freq:50.00Hz Lamp Flux:6997.38x1 lm		
NAME: SB-U01A80WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1800mm	

DATA OF LAMP		PHOTOMETRIC DATA Eff: 87.12 lm/W			
MODEL		I _{max} (cd)	1039	S/MH(C0/180)	1.24
NOMINAL POWER(W)		LOR(%)	100.0	S/MH(C90/270)	1.24
RATED VOLTAGE(V)	--	TOTAL FLUX(lm)	6997.4	η UP,DN(C0-180)	24.3,25.4
NOMINAL FLUX(lm)	6997.38	CIE CLASS	DIFFUSE	η UP,DN(C180-360)	23.2,27.1
LAMPS INSIDE	1	η up(%)	47.5	CIBSE SHR NOM	1.25
TEST VOLTAGE(V)	--	η down(%)	52.5	CIBSE SHR MAX	1.35



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-06-02

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum,lamp
10	1017	1001	983.6	985.7	1018	1026	1034	1033	0- 10	97.61	97.61	1.39,1.39
20	930.1	912.7	893.4	902.5	953.6	956.4	974.5	974.8	10- 20	276.6	374.2	5.35,5.35
30	826.4	811.8	794.9	804.7	858.6	851.2	859.6	869.8	20- 30	408.2	782.4	11.2,11.2
40	737.0	725.1	706.2	716.8	773.0	762.9	762.7	769.3	30- 40	494.2	1277	18.2,18.2
50	646.3	635.9	618.5	627.4	688.0	677.1	671.2	670.1	40- 50	540.3	1817	26,26
60	549.0	543.5	530.0	535.3	602.3	589.0	579.6	573.2	50- 60	545.3	2362	33.8,33.8
70	453.7	454.2	442.4	446.1	507.9	492.3	482.2	473.7	60- 70	510.7	2873	41.1,41.1
80	366.9	372.6	361.7	365.0	417.1	401.9	390.2	383.3	70- 80	448.6	3322	47.5,47.5
90	282.8	217.7	222.7	215.9	320.1	262.5	240.4	192.4	80- 90	349.2	3671	52.5,52.5
100	362.2	361.2	376.6	353.5	326.9	344.4	360.5	336.2	90-100	327.2	3998	57.1,57.1
110	471.7	410.8	472.0	415.1	435.5	413.8	453.1	373.1	100-110	418.3	4416	63.1,63.1
120	470.9	528.6	551.2	524.8	478.9	522.2	535.1	503.8	110-120	469.7	4886	69.8,69.8
130	529.6	584.6	602.2	581.8	548.4	553.8	560.5	535.2	120-130	476.8	5363	76.6,76.6
140	636.8	681.9	704.6	665.8	606.3	607.6	623.1	583.7	130-140	455.5	5818	83.1,83.1
150	777.7	797.4	826.6	804.2	754.1	767.7	767.6	739.6	140-150	450.5	6269	89.6,89.6
160	877.8	884.9	920.6	895.5	853.1	858.3	854.7	825.4	150-160	379.8	6649	95,95
170	964.4	959.1	962.9	958.8	952.4	939.0	928.0	924.3	160-170	257.4	6906	98.7,98.7
180	983.5	971.5	967.8	963.2	984.2	972.1	968.1	963.6	170-180	91.43	6997	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

Conical surface Flux(90deg): 1543.7 lm

%lum = 22.1%

%lamp = 22.1%

Conical surface Flux(120deg): 2362.3 lm

%lum = 33.8%


%lamp = 33.8%

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-06-02

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:220.20V I:0.3741A P:80.321W PF:0.9749 Freq:50.00Hz Lamp Flux:6997.38x1 lm		
NAME: SB-U01A80WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1800mm	




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:XIAOMI
Test Date:2023-06-02

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:9.000m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:220.20V I:0.3741A P:80.321W PF:0.9749 Freq:50.00Hz Lamp Flux:6997.38x1 lm		
NAME: SB-U01A80WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1800mm	

ρ_{cc}	80%			70%			50%			30%			10%			0
ρ_w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρ_{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Coefficients of Utilization(CU)															
0.0	1.08	1.08	1.08	.00	.00	.00	.85	.85	.85	.71	.71	.71	.58	.58	.58	.52
1.0	.91	.86	.82	.84	.80	.76	.71	.68	.65	.59	.57	.55	.48	.46	.45	.40
2.0	.78	.71	.65	.72	.66	.61	.61	.56	.52	.51	.47	.44	.41	.38	.36	.31
3.0	.68	.60	.53	.63	.55	.50	.53	.47	.43	.44	.40	.36	.36	.33	.30	.26
4.0	.60	.51	.44	.55	.48	.42	.47	.41	.36	.39	.34	.30	.32	.28	.25	.21
5.0	.53	.44	.38	.49	.41	.35	.42	.35	.31	.35	.30	.26	.28	.25	.22	.18
6.0	.47	.39	.32	.44	.36	.30	.37	.31	.27	.31	.26	.23	.25	.22	.19	.16
7.0	.43	.34	.28	.40	.32	.27	.34	.28	.23	.28	.23	.20	.23	.19	.17	.14
8.0	.39	.30	.25	.36	.29	.23	.31	.25	.20	.26	.21	.18	.21	.18	.15	.12
9.0	.35	.27	.22	.33	.26	.21	.28	.22	.18	.24	.19	.16	.20	.16	.13	.11
10.0	.32	.25	.20	.30	.23	.19	.26	.20	.16	.22	.17	.14	.18	.15	.12	.10



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-06-02

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

WEC AND CCEC

Test:U:220.20V I:0.3741A P:80.321W PF:0.9749 Freq:50.00Hz Lamp Flux:6997.38x1 lm		
NAME: SB-U01A80WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1800mm	

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)									
0.0																
1.0	.343	.195	.062	.321	.183	.058	.281	.161	.051	.244	.141	.045	.210	.121	.039	
2.0	.300	.165	.051	.281	.155	.048	.244	.136	.042	.210	.118	.037	.179	.101	.032	
3.0	.269	.143	.043	.251	.135	.041	.218	.118	.036	.187	.102	.031	.158	.087	.027	
4.0	.244	.127	.037	.228	.119	.035	.197	.104	.031	.168	.090	.027	.142	.077	.023	
5.0	.223	.114	.033	.208	.107	.031	.180	.094	.028	.153	.081	.024	.129	.069	.021	
6.0	.205	.103	.029	.192	.097	.028	.165	.085	.025	.141	.073	.022	.118	.062	.018	
7.0	.190	.094	.027	.177	.088	.025	.153	.077	.022	.130	.067	.019	.109	.057	.017	
8.0	.177	.086	.024	.165	.081	.023	.142	.071	.020	.121	.061	.018	.101	.052	.015	
9.0	.165	.080	.022	.154	.075	.021	.133	.066	.019	.113	.057	.016	.095	.048	.014	
10.0	.155	.074	.021	.145	.070	.019	.125	.061	.017	.106	.053	.015	.089	.045	.013	

pcc	80%			70%			50%			30%			10%			0	
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
pfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)										
0.0	.553	.553	.553	.472	.472	.472	.322	.322	.322	.185	.185	.185	.059	.059	.059		
1.0	.548	.521	.497	.469	.447	.428	.321	.308	.296	.185	.178	.172	.059	.057	.056		
2.0	.541	.500	.465	.463	.430	.402	.318	.297	.280	.183	.173	.164	.059	.056	.054		
3.0	.534	.484	.444	.458	.417	.385	.314	.290	.270	.182	.169	.159	.058	.055	.052		
4.0	.527	.472	.430	.452	.408	.374	.311	.284	.263	.180	.167	.156	.058	.054	.051		
5.0	.520	.463	.421	.446	.400	.366	.308	.280	.259	.178	.164	.153	.057	.054	.051		
6.0	.513	.455	.414	.441	.394	.361	.304	.276	.255	.177	.162	.152	.057	.053	.050		
7.0	.507	.449	.409	.436	.389	.356	.301	.273	.253	.175	.161	.150	.057	.053	.050		
8.0	.501	.444	.405	.431	.385	.353	.298	.270	.251	.173	.160	.149	.056	.052	.049		
9.0	.495	.440	.402	.426	.382	.351	.295	.268	.249	.172	.158	.149	.056	.052	.049		
10.0	.490	.436	.400	.422	.378	.349	.293	.266	.248	.171	.157	.148	.055	.052	.049		

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-06-02

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

UGR(Unified Glare Rating) Table

Test:U:220.20V I:0.3741A P:80.321W PF:0.9749 Freq:50.00Hz Lamp Flux:6997.38x1 lm											
NAME: SB-U01A80WSZ					TYPE:			WEIGHT:			
SPEC.:4000K					DIM.:			SERIAL No.:			
MFR.: SNOWBALL					SUR.:1800mm						
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H y = 2H	6.5	7.6	7.4	8.4	9.5	6.4	7.4	7.2	8.3	9.3	
	3H	8.9	9.8	9.7	10.7	11.8	8.7	9.6	9.6	10.5	11.6
	4H	10.1	11.0	11.0	11.9	13.0	10.0	10.9	10.9	11.8	12.9
	6H	11.5	12.3	12.4	13.2	14.4	11.4	12.2	12.3	13.1	14.3
	8H	12.3	13.1	13.2	14.0	15.1	12.2	13.0	13.1	13.9	15.0
	12H	13.1	13.8	14.0	14.7	15.9	13.1	13.8	14.0	14.7	15.9
4H	2H	7.2	8.1	8.1	9.0	10.1	7.1	8.0	8.0	8.9	10.0
	3H	9.8	10.5	10.7	11.4	12.6	9.6	10.4	10.6	11.3	12.5
	4H	11.2	11.9	12.1	12.8	14.0	11.1	11.8	12.0	12.7	13.9
	6H	12.8	13.4	13.7	14.3	15.5	12.7	13.3	13.6	14.2	15.5
	8H	13.6	14.2	14.6	15.2	16.4	13.6	14.1	14.5	15.1	16.3
	12H	14.5	15.0	15.5	16.0	17.3	14.6	15.1	15.5	16.0	17.3
8H	4H	11.7	12.3	12.7	13.2	14.5	11.6	12.2	12.6	13.1	14.4
	6H	13.6	14.0	14.5	15.0	16.3	13.5	14.0	14.5	14.9	16.2
	8H	14.6	15.0	15.6	16.0	17.3	14.6	15.0	15.6	16.0	17.3
	12H	15.7	16.1	16.7	17.1	18.4	15.8	16.1	16.8	17.1	18.5
12H	4H	11.8	12.3	12.8	13.3	14.6	11.7	12.2	12.7	13.2	14.5
	6H	13.8	14.2	14.8	15.2	16.5	13.7	14.1	14.7	15.1	16.4
	8H	15.0	15.3	16.0	16.3	17.6	14.9	15.3	15.9	16.3	17.6
Variations with the observer position at spacings:											
S = 1.0H	+ 0.1 / - 0.1					+ 0.1 / - 0.1					
1.5H	+ 0.2 / - 0.3					+ 0.2 / - 0.3					
2.0H	+ 0.3 / - 0.4					+ 0.3 / - 0.4					

CIE Pub.117, 6997 lm Total Lamp Luminous Flux Corrected ($8\log(F/F_0) = 6.8$)
Area: 2.543 m²

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:XIAOMI
Test Date:2023-06-02

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:9.000m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:220.20V I:0.3741A P:80.321W PF:0.9749 Freq:50.00Hz Lamp Flux:6997.38x1 lm		
NAME: SB-U01A80WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1800mm	


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	41	30	23	39	28	22	35	26	21	13
0.80	50	38	30	47	36	29	42	33	27	17
1.00	58	45	37	54	43	35	48	40	32	21
1.25	65	52	44	60	49	42	53	44	38	24
1.50	70	58	49	65	54	47	56	48	42	27
2.00	77	66	58	72	62	55	62	54	49	31
2.50	82	72	64	76	67	60	65	58	53	33
3.00	86	76	69	79	71	65	68	62	57	36
4.00	90	83	76	84	77	71	71	66	62	39
5.00	93	87	81	86	81	76	74	69	65	41
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-06-02

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

ISOCANDELA DIAGRAM

Test:U:220.20V I:0.3741A P:80.321W PF:0.9749 Freq:50.00Hz Lamp Flux:6997.38x1 lm		
NAME: SB-U01A80WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1800mm	




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:XIAOMI
Test Date:2023-06-02

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:9.000m [K=1.0000]
Remarks:

AAI Figure

Test:U:220.20V I:0.3741A P:80.321W PF:0.9749 Freq:50.00Hz Lamp Flux:6997.38x1 lm		
NAME: SB-U01A80WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1800mm	




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-06-02

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

ISOLUX DIAGRAM


Test:U:220.20V I:0.3741A P:80.321W PF:0.9749 Freq:50.00Hz Lamp Flux:6997.38x1 lm		
NAME: SB-U01A80WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1800mm	



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-06-02

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: XIAOMI
Test Date: 2023-06-02

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity: 65.0%
Test Distance: 9.000m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:220.20V I:0.3741A P:80.321W PF:0.9749 Freq:50.00Hz Lamp Flux:6997.38x1 lm		
NAME: SB-U01A80WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1800mm	

Table--1

UNIT: cd

C(DEG) γ (DEG)	0	22.5	45	67.5	90	112.5	135	157.5	180	202.5	225	247.5	270	292.5	315	337.5			
0	1038	1038	1037	1035	1032	1032	1032	1032	1038	1038	1037	1035	1032	1032	1032	1032			
5	1031	1028	1024	1019	1013	1012	1013	1019	1033	1035	1036	1037	1037	1037	1036	1033			
10	1017	1010	1001	993	984	982	986	996	1018	1021	1026	1031	1034	1034	1033	1028			
15	981	974	964	954	943	942	949	964	993	994	1000	1007	1015	1018	1015	1005			
20	930	922	913	907	893	893	903	922	954	953	956	962	974	980	975	961			
25	875	869	859	854	842	842	852	874	906	904	902	904	917	927	922	904			
30	826	824	812	803	795	795	805	826	859	857	851	851	860	872	870	850			
35	782	779	769	757	750	749	760	781	815	812	806	804	809	820	819	800			
40	737	736	725	714	706	705	717	738	773	769	763	760	763	770	769	752			
45	693	691	681	670	662	662	672	696	731	726	720	716	717	721	720	705			
50	646	645	636	629	619	621	627	653	688	682	677	672	671	672	670	658			
55	599	602	590	587	575	576	582	612	645	638	634	626	627	623	623	610			
60	549	552	544	542	530	531	535	565	602	591	589	578	580	573	573	560			
65	501	505	499	497	486	486	490	518	555	544	541	530	531	524	523	511			
70	454	458	454	454	442	443	446	472	508	496	492	482	482	475	474	463			
75	407	415	412	412	401	401	404	429	462	451	446	436	435	428	427	419			
80	367	372	373	372	362	362	365	388	417	408	402	391	390	384	383	375			
85	264	312	315	322	314	320	323	348	375	364	360	349	347	341	341	328			
90	283	257	218	219	223	209	216	240	320	276	262	239	240	225	192	234			
95	318	310	316	311	331	309	303	305	281	308	293	307	319	303	290	283			
100	362	361	361	360	377	357	354	344	327	339	344	352	360	342	336	351			
105	420	407	399	397	426	398	397	395	377	391	389	396	409	382	369	402			
110	472	447	411	448	472	454	415	443	436	446	414	445	453	432	373	428			
115	426	447	493	494	519	500	492	451	483	445	471	484	490	475	463	410			
120	471	484	529	533	551	530	525	498	479	489	522	526	535	514	504	482			
125	500	516	552	560	569	548	547	523	519	522	527	524	534	528	513	498			
130	530	551	585	589	602	585	582	556	548	553	554	551	561	552	535	526			
135	552	585	621	621	634	614	611	583	575	579	578	573	581	569	558	543			
140	637	653	682	691	705	692	666	619	606	609	608	618	623	611	584	577			
145	732	742	758	765	779	775	747	708	700	701	707	712	713	692	694	694			
150	778	786	797	813	827	826	804	765	754	758	768	772	768	745	740	748			
155	825	831	833	865	875	875	845	814	798	803	815	818	811	790	779	792			
160	878	878	885	903	921	910	896	870	853	855	858	865	855	839	825	837			
165	928	924	930	940	946	944	936	917	911	905	904	900	892	882	878	889			
170	964	955	959	962	963	962	959	947	952	939	939	933	928	924	924	930			
175	981	972	971	970	967	967	963	959	973	961	959	956	954	951	952	954			
180	983	973	971	970	968	967	963	962	984	973	972	970	968	966	964	962			

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:XIAOMI
Test Date:2023-06-02

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:9.000m [K=1.0000]
Remarks: