


LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:220.15V I:0.2825A P:60.010W PF:0.9648 Freq:50.00Hz Lamp Flux:3976.27x1 lm		
NAME: SB-J01B60WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1200*600mm	

DATA OF LAMP		PHOTOMETRIC DATA Eff: 66.26 lm/W			
MODEL		I _{max} (cd)	1220	S/MH(C0/180)	1.18
NOMINAL POWER(W)		LOR(%)	100.0	S/MH(C90/270)	1.16
RATED VOLTAGE(V)	--	TOTAL FLUX(lm)	3976.3	η UP,DN(C0-180)	7.3,42.7
NOMINAL FLUX(lm)	3976.27	CIE CLASS	SEMI-D.	η UP,DN(C180-360)	7.2,42.8
LAMPS INSIDE	1	η up(%)	14.5	CIBSE SHR NOM	1.25
TEST VOLTAGE(V)	--	η down(%)	85.5	CIBSE SHR MAX	1.35



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:XIAOMI
Test Date:2023-06-24

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:9.000m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum,lamp
10	1188	1185	1179	1177	1189	1187	1185	1184	0- 10	114.4	114.4	2.88,2.88
20	1091	1089	1071	1085	1099	1098	1080	1087	10- 20	321.9	436.4	11,11
30	944.4	944.9	931.6	946.3	959.1	961.9	934.3	951.2	20- 30	470.3	906.7	22.8,22.8
40	779.6	794.3	784.4	798.1	806.1	806.7	777.2	792.3	30- 40	545.4	1452	36.5,36.5
50	612.3	638.8	636.7	648.8	641.0	655.9	623.2	635.9	40- 50	553.1	2005	50.4,50.4
60	447.1	492.6	488.1	502.5	479.3	514.5	474.5	490.2	50- 60	504.4	2510	63.1,63.1
70	297.1	354.7	342.7	368.7	327.6	373.8	331.8	350.4	60- 70	413.5	2923	73.5,73.5
80	168.6	232.4	216.0	248.7	196.6	249.3	209.8	227.8	70- 80	298.5	3222	81,81
90	42.63	84.89	77.89	101.1	75.03	128.8	108.0	112.3	80- 90	179.0	3400	85.5,85.5
100	65.16	123.4	110.5	132.1	79.89	135.0	111.9	120.0	90-100	107.6	3508	88.2,88.2
110	70.18	125.7	114.2	132.3	80.49	127.0	118.7	114.3	100-110	119.1	3627	91.2,91.2
120	71.02	121.0	112.6	121.5	69.25	113.8	110.3	112.5	110-120	107.1	3734	93.9,93.9
130	54.19	113.0	106.9	106.6	58.31	103.1	100.0	110.2	120-130	89.74	3824	96.2,96.2
140	47.44	95.70	92.53	80.46	46.70	73.28	89.17	92.81	130-140	68.21	3892	97.9,97.9
150	41.45	75.82	63.68	62.43	38.81	55.50	55.32	74.34	140-150	44.01	3936	99,99
160	38.59	55.56	47.53	49.93	36.81	48.91	40.60	54.61	150-160	25.82	3962	99.6,99.6
170	28.04	35.93	32.28	33.60	26.91	33.38	31.87	35.45	160-170	11.68	3974	99.9,99.9
180	15.34	14.96	15.21	14.44	15.35	14.96	15.21	14.45	170-180	2.492	3976	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

Conical surface Flux(90deg): 1731.5 lm

%lum = 43.5%

%lamp = 43.5%

Conical surface Flux(120deg): 2509.5 lm

%lum = 63.1%


%lamp = 63.1%

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-06-24

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:220.15V I:0.2825A P:60.010W PF:0.9648 Freq:50.00Hz Lamp Flux:3976.27x1 lm		
NAME: SB-J01B60WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1200*600mm	




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:XIAOMI
Test Date:2023-06-24

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:9.000m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:220.15V I:0.2825A P:60.010W PF:0.9648 Freq:50.00Hz Lamp Flux:3976.27x1 lm		
NAME: SB-J01B60WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1200*600mm	

ρ_{cc}	80%			70%			50%			30%			10%			0	
ρ_w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
ρ_{fc}	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Coefficients of Utilization(CU)										
0.0	1.16	1.16	1.16	1.11	1.11	1.11	1.03	1.03	1.03	.96	.96	.96	.89	.89	.89	.86	
1.0	.99	.94	.90	.95	.91	.87	.88	.85	.82	.82	.79	.77	.76	.74	.72	.69	
2.0	.86	.79	.73	.83	.76	.71	.77	.71	.67	.71	.67	.63	.66	.63	.60	.57	
3.0	.75	.67	.60	.72	.65	.59	.67	.61	.56	.63	.57	.53	.58	.54	.50	.47	
4.0	.66	.58	.51	.64	.56	.50	.60	.53	.47	.56	.50	.45	.52	.47	.43	.40	
5.0	.59	.50	.44	.57	.49	.43	.54	.46	.41	.50	.44	.39	.47	.42	.37	.35	
6.0	.53	.44	.38	.52	.43	.37	.48	.41	.36	.45	.39	.34	.43	.37	.33	.31	
7.0	.48	.40	.34	.47	.39	.33	.44	.37	.32	.41	.35	.31	.39	.33	.29	.27	
8.0	.44	.36	.30	.43	.35	.29	.40	.33	.28	.38	.32	.27	.36	.30	.26	.24	
9.0	.40	.32	.27	.39	.32	.26	.37	.30	.26	.35	.29	.25	.33	.28	.24	.22	
10.0	.37	.30	.24	.36	.29	.24	.34	.28	.23	.32	.27	.22	.31	.25	.22	.20	



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-06-24

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

WEC AND CCEC

Test:U:220.15V I:0.2825A P:60.010W PF:0.9648 Freq:50.00Hz Lamp Flux:3976.27x1 lm		
NAME: SB-J01B60WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1200*600mm	

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Wall Exitance Coefficients(WEC)															
0.0																
1.0	.338	.192	.061	.326	.186	.059	.305	.175	.056	.285	.164	.053	.267	.155	.050	
2.0	.303	.166	.051	.293	.161	.050	.274	.152	.047	.256	.143	.045	.239	.135	.043	
3.0	.275	.146	.044	.265	.142	.043	.248	.134	.041	.232	.127	.039	.217	.120	.037	
4.0	.251	.130	.038	.242	.127	.037	.226	.120	.036	.212	.114	.034	.198	.108	.033	
5.0	.230	.117	.034	.222	.114	.033	.208	.108	.032	.195	.103	.031	.182	.097	.029	
6.0	.212	.106	.030	.205	.104	.030	.192	.098	.029	.180	.094	.027	.169	.089	.026	
7.0	.197	.097	.028	.190	.095	.027	.179	.090	.026	.167	.086	.025	.157	.082	.024	
8.0	.183	.090	.025	.178	.087	.025	.167	.083	.024	.156	.079	.023	.147	.075	.022	
9.0	.171	.083	.023	.166	.081	.023	.156	.077	.022	.147	.074	.021	.138	.070	.020	
10.0	.161	.077	.021	.156	.075	.021	.147	.072	.020	.138	.069	.020	.130	.065	.019	

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Ceiling Cavity Exitance Coefficients(CCEC)															
0.0	.301	.301	.301	.257	.257	.257	.175	.175	.175	.101	.101	.101	.032	.032	.032	
1.0	.293	.267	.243	.251	.229	.209	.172	.158	.145	.099	.091	.084	.032	.029	.027	
2.0	.286	.244	.209	.245	.210	.180	.168	.145	.126	.097	.084	.074	.031	.027	.024	
3.0	.278	.227	.186	.238	.196	.161	.164	.136	.113	.094	.079	.067	.030	.026	.022	
4.0	.270	.214	.171	.232	.185	.149	.159	.129	.105	.092	.076	.062	.030	.025	.020	
5.0	.263	.204	.161	.226	.177	.140	.155	.123	.099	.090	.072	.059	.029	.024	.019	
6.0	.256	.196	.153	.220	.170	.133	.152	.119	.094	.088	.070	.056	.028	.023	.019	
7.0	.249	.189	.148	.214	.164	.129	.148	.115	.091	.086	.068	.054	.028	.022	.018	
8.0	.242	.184	.143	.209	.159	.125	.144	.112	.089	.084	.066	.053	.027	.022	.017	
9.0	.236	.179	.140	.204	.155	.122	.141	.109	.087	.082	.064	.052	.027	.021	.017	
10.0	.231	.175	.137	.199	.152	.120	.138	.107	.085	.080	.063	.051	.026	.021	.017	

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-06-24

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

UGR(Unified Glare Rating) Table

Test:U:220.15V I:0.2825A P:60.010W PF:0.9648 Freq:50.00Hz Lamp Flux:3976.27x1 lm											
NAME: SB-J01B60WSZ					TYPE:			WEIGHT:			
SPEC.:4000K					DIM.:			SERIAL No.:			
MFR.: SNOWBALL					SUR.:1200*600mm						
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H y = 2H	12.7	14.1	13.2	14.5	15.0	13.0	14.3	13.4	14.8	15.2	
	3H	14.4	15.6	14.9	16.1	16.6	14.8	16.0	15.3	16.5	17.0
	4H	15.1	16.3	15.6	16.8	17.3	15.7	16.8	16.2	17.3	17.9
	6H	15.8	16.9	16.4	17.4	18.0	16.5	17.6	17.1	18.1	18.7
	8H	16.2	17.2	16.7	17.7	18.3	17.0	18.0	17.5	18.6	19.1
	12H	16.5	17.5	17.0	18.0	18.6	17.5	18.5	18.0	19.0	19.6
4H	2H	13.4	14.6	13.9	15.1	15.6	13.6	14.8	14.1	15.3	15.8
	3H	15.3	16.3	15.9	16.9	17.5	15.6	16.7	16.2	17.2	17.8
	4H	16.2	17.2	16.8	17.7	18.4	16.7	17.6	17.3	18.2	18.8
	6H	17.1	18.0	17.7	18.6	19.2	17.8	18.6	18.4	19.2	19.8
	8H	17.6	18.3	18.2	18.9	19.6	18.3	19.1	18.9	19.7	20.4
	12H	18.0	18.7	18.6	19.3	20.0	18.9	19.6	19.5	20.2	20.9
8H	4H	16.7	17.5	17.3	18.1	18.8	17.1	17.9	17.7	18.5	19.2
	6H	17.9	18.6	18.6	19.2	19.9	18.4	19.1	19.1	19.7	20.4
	8H	18.5	19.1	19.2	19.7	20.5	19.2	19.7	19.8	20.4	21.1
	12H	19.1	19.6	19.8	20.3	21.1	19.9	20.4	20.6	21.1	21.9
12H	4H	16.8	17.5	17.4	18.1	18.9	17.2	17.9	17.8	18.5	19.2
	6H	18.1	18.7	18.8	19.3	20.1	18.6	19.2	19.3	19.8	20.6
	8H	18.8	19.3	19.5	20.0	20.8	19.4	19.9	20.1	20.6	21.4
Variations with the observer position at spacings:											
S = 1.0H	+ 0.1 / - 0.2					+ 0.1 / - 0.2					
1.5H	+ 0.2 / - 0.3					+ 0.2 / - 0.3					
2.0H	+ 0.2 / - 0.4					+ 0.2 / - 0.3					

CIE Pub.117, 3976 lm Total Lamp Luminous Flux Corrected ($8\log(F/F_0) = 4.8$)
Area: 0.72 m²

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:XIAOMI
Test Date:2023-06-24

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:9.000m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:220.15V I:0.2825A P:60.010W PF:0.9648 Freq:50.00Hz Lamp Flux:3976.27x1 lm		
NAME: SB-J01B60WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1200*600mm	


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	52	41	34	51	40	34	50	39	33	27
0.80	62	50	42	60	49	42	58	48	41	34
1.00	70	58	50	68	57	50	65	57	49	40
1.25	77	65	58	74	64	57	70	62	55	46
1.50	82	71	63	79	69	62	75	66	60	50
2.00	89	79	72	86	77	70	80	73	67	57
2.50	93	84	77	90	82	75	84	77	72	60
3.00	96	88	82	93	86	80	87	81	76	64
4.00	100	94	88	97	91	86	90	85	81	68
5.00	103	97	92	99	94	90	92	88	85	71
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-06-24

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

ISOCANDELA DIAGRAM

Test:U:220.15V I:0.2825A P:60.010W PF:0.9648 Freq:50.00Hz Lamp Flux:3976.27x1 lm		
NAME: SB-J01B60WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1200*600mm	




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:XIAOMI
Test Date:2023-06-24

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:9.000m [K=1.0000]
Remarks:

AAI Figure

Test:U:220.15V I:0.2825A P:60.010W PF:0.9648 Freq:50.00Hz Lamp Flux:3976.27x1 lm		
NAME: SB-J01B60WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1200*600mm	




Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: XIAOMI
 Test Date: 2023-06-24

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity: 65.0%
 Test Distance: 9.000m [K=1.0000]
 Remarks:

ISOLUX DIAGRAM


Test:U:220.15V I:0.2825A P:60.010W PF:0.9648 Freq:50.00Hz Lamp Flux:3976.27x1 lm		
NAME: SB-J01B60WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1200*600mm	



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-06-24

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: XIAOMI
Test Date: 2023-06-24

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity: 65.0%
Test Distance: 9.000m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:220.15V I:0.2825A P:60.010W PF:0.9648 Freq:50.00Hz Lamp Flux:3976.27x1 lm																	
NAME: SB-J01B60WSZ									TYPE:						WEIGHT:		
SPEC.:4000K									DIM.:						SERIAL No.:		
MFR.: SNOWBALL									SUR.:1200*600mm								

Table--1

UNIT: cd

C(DEC) γ (DEC)	0	22.5	45	67.5	90	112.5	135	157.5	180	202.5	225	247.5	270	292.5	315	337.5			
0	1220	1218	1217	1215	1213	1212	1211	1212	1220	1218	1217	1215	1213	1212	1211	1212			
5	1212	1209	1207	1206	1204	1201	1199	1200	1210	1210	1210	1209	1208	1207	1207	1206			
10	1188	1186	1185	1182	1179	1176	1177	1179	1189	1189	1187	1184	1185	1183	1184	1183			
15	1146	1146	1145	1139	1135	1135	1140	1144	1150	1152	1152	1142	1140	1141	1143	1141			
20	1091	1093	1089	1080	1071	1079	1085	1095	1099	1103	1098	1085	1080	1082	1087	1090			
25	1024	1028	1020	1015	1003	1011	1020	1033	1033	1041	1034	1017	1010	1010	1023	1027			
30	944	952	945	942	932	937	946	961	959	969	962	943	934	937	951	953			
35	863	872	870	866	858	863	873	885	884	893	885	867	857	864	872	875			
40	780	792	794	790	784	792	798	808	806	814	807	791	777	788	792	793			
45	697	713	713	715	711	722	725	730	725	735	730	711	700	710	713	708			
50	612	632	639	641	637	650	649	655	641	659	656	636	623	634	636	627			
55	528	555	565	570	561	577	575	578	559	581	583	562	551	558	562	548			
60	447	480	493	499	488	508	503	505	479	505	515	489	475	484	490	473			
65	371	408	422	426	414	437	434	432	401	432	444	418	401	412	419	401			
70	297	338	355	358	343	367	369	360	328	360	374	350	332	344	350	332			
75	232	271	291	291	277	302	308	291	258	293	309	286	268	280	287	267			
80	169	209	232	230	216	240	249	225	197	228	249	229	210	222	228	206			
85	112	152	177	174	160	183	193	164	137	168	195	177	159	169	175	151			
90	42.6	67.4	84.9	83.8	77.9	92.8	101	77.9	75.0	78.6	129	107	108	101	112	60.3			
95	63.4	91.6	113	110	102	116	125	100	83.3	106	121	107	104	106	101	92.7			
100	65.2	96.7	123	122	111	125	132	103	79.9	111	135	124	112	119	120	98.5			
105	67.7	98.6	125	123	112	125	131	107	81.0	110	136	130	115	122	123	95.3			
110	70.2	104	126	126	114	127	132	111	80.5	109	127	132	119	125	114	99.7			
115	71.5	105	104	124	114	124	106	110	79.1	110	105	124	115	114	95.5	98.4			
120	71.0	82.7	121	119	113	118	121	89.0	69.2	86.1	114	118	110	114	112	80.8			
125	46.9	94.4	119	119	111	118	118	97.5	50.8	94.1	114	108	104	110	113	91.1			
130	54.2	90.3	113	117	107	115	107	86.5	58.3	82.0	103	110	100	111	110	88.3			
135	51.3	83.8	105	109	100	106	91.7	70.1	50.2	66.6	85.0	100	94.6	104	104	80.1			
140	47.4	76.6	95.7	101	92.5	89.9	80.5	61.1	46.7	58.4	73.3	81.5	89.2	99.3	92.8	73.9			
145	44.0	69.0	85.6	92.3	75.4	78.6	69.9	52.7	42.1	52.1	63.6	69.3	80.4	90.2	83.8	66.7			
150	41.5	64.5	75.8	81.9	63.7	69.1	62.4	49.5	38.8	50.1	55.5	60.5	55.3	79.8	74.3	63.3			
155	44.1	56.0	65.2	68.6	55.6	59.8	56.5	48.5	41.8	49.5	53.4	52.7	47.3	66.3	64.5	56.3			
160	38.6	47.8	55.6	54.4	47.5	53.0	49.9	43.7	36.8	44.6	48.9	51.2	40.6	52.1	54.6	48.7			
165	33.3	39.8	45.9	44.4	38.5	45.0	42.6	35.5	31.8	36.7	42.2	45.3	33.7	42.5	45.6	41.0			
170	28.0	31.2	35.9	33.8	32.3	35.2	33.6	28.1	26.9	30.2	33.4	34.9	31.9	31.6	35.5	33.3			
175	23.0	25.2	24.3	22.2	20.8	21.1	21.6	22.2	22.1	22.6	23.0	22.5	22.3	22.5	25.7	25.5			
180	15.3	15.2	15.0	15.1	15.2	15.0	14.4	15.1	15.3	15.1	15.0	15.1	15.2	15.0	14.4	15.1			

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:XIAOMI
Test Date:2023-06-24

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:9.000m [K=1.0000]
Remarks: