


LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:220.34V I:0.2043A P:41.526W PF:0.9227 Freq:50.00Hz Lamp Flux:2885.93x1 lm		
NAME: SB-J01A40WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:800*800mm	

DATA OF LAMP		PHOTOMETRIC DATA Eff: 69.50 lm/W			
MODEL		I _{max} (cd)	903.7	S/MH(C0/180)	1.15
NOMINAL POWER(W)		LOR(%)	100.0	S/MH(C90/270)	1.16
RATED VOLTAGE(V)	--	TOTAL FLUX(lm)	2885.9	η UP,DN(C0-180)	7.4,42.4
NOMINAL FLUX(lm)	2885.93	CIE CLASS	SEMI-D.	η UP,DN(C180-360)	6.9,43.4
LAMPS INSIDE	1	η up(%)	14.3	CIBSE SHR NOM	1.25
TEST VOLTAGE(V)	--	η down(%)	85.7	CIBSE SHR MAX	1.35



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:XIAOMI
Test Date:2023-06-25

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:9.000m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum,lamp
10	878.8	877.5	873.8	874.3	882.1	878.9	872.2	873.8	0- 10	84.85	84.85	2.94,2.94
20	799.3	802.5	793.8	800.8	802.1	805.8	801.2	798.4	10- 20	237.6	322.4	11.2,11.2
30	687.1	686.9	682.2	691.1	690.5	696.0	699.3	695.1	20- 30	344.5	666.9	23.1,23.1
40	570.5	570.2	560.5	571.5	577.2	580.7	583.8	578.8	30- 40	396.3	1063	36.8,36.8
50	454.5	459.3	437.8	457.1	462.3	473.3	467.0	471.7	40- 50	400.4	1464	50.7,50.7
60	343.6	351.5	323.0	350.6	348.7	368.2	354.5	370.6	50- 60	364.7	1828	63.4,63.4
70	239.2	254.7	219.9	253.1	242.9	268.5	245.2	269.6	60- 70	298.7	2127	73.7,73.7
80	149.8	167.8	128.3	165.6	151.4	177.4	148.9	180.3	70- 80	216.3	2343	81.2,81.2
90	66.02	70.62	43.01	68.77	53.69	67.22	53.39	97.53	80- 90	131.1	2474	85.7,85.7
100	75.37	88.54	63.46	95.16	78.25	89.28	54.41	86.80	90-100	78.07	2553	88.4,88.4
110	80.00	91.98	64.25	97.67	81.03	88.75	52.79	86.22	100-110	85.50	2638	91.4,91.4
120	79.93	86.56	61.69	92.75	81.37	81.38	47.09	73.76	110-120	79.17	2717	94.2,94.2
130	68.21	75.56	55.02	80.93	69.43	70.09	44.97	71.85	120-130	63.47	2781	96.4,96.4
140	45.57	64.92	40.76	65.05	51.83	59.42	34.51	60.23	130-140	45.82	2826	97.9,97.9
150	37.57	51.85	32.56	49.16	41.49	44.16	30.99	50.29	140-150	31.19	2858	99.99
160	36.74	41.16	26.58	37.02	30.81	34.66	23.58	40.38	150-160	17.91	2876	99.6,99.6
170	24.72	26.04	19.20	24.61	23.13	23.27	18.67	25.59	160-170	8.516	2884	99.9,99.9
180	11.31	10.77	10.90	11.20	11.34	10.79	10.89	11.20	170-180	1.850	2886	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

Conical surface Flux(90deg): 1265.6 lm

%lum = 43.9%

%lamp = 43.9%

Conical surface Flux(120deg): 1828.3 lm

%lum = 63.4%


%lamp = 63.4%

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-06-25

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:220.34V I:0.2043A P:41.526W PF:0.9227 Freq:50.00Hz Lamp Flux:2885.93x1 lm		
NAME: SB-J01A40WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:800*800mm	




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:XIAOMI
Test Date:2023-06-25

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:9.000m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:220.34V I:0.2043A P:41.526W PF:0.9227 Freq:50.00Hz Lamp Flux:2885.93x1 lm		
NAME: SB-J01A40WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:800*800mm	

ρ_{cc}	80%			70%			50%			30%			10%			0	
ρ_w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
ρ_{fc}	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Coefficients of Utilization(CU)										
0.0	1.16	1.16	1.16	1.11	1.11	1.11	1.03	1.03	1.03	.96	.96	.96	.89	.89	.89	.86	
1.0	.99	.94	.90	.95	.91	.87	.88	.85	.82	.82	.79	.77	.76	.74	.72	.69	
2.0	.86	.79	.73	.83	.76	.71	.77	.71	.67	.71	.67	.63	.66	.63	.60	.57	
3.0	.75	.67	.60	.73	.65	.59	.68	.61	.56	.63	.58	.53	.59	.54	.50	.48	
4.0	.67	.58	.51	.64	.56	.50	.60	.53	.48	.56	.50	.45	.52	.47	.43	.41	
5.0	.59	.50	.44	.57	.49	.43	.54	.47	.41	.50	.44	.39	.47	.42	.38	.35	
6.0	.54	.45	.38	.52	.44	.37	.49	.41	.36	.46	.39	.35	.43	.37	.33	.31	
7.0	.49	.40	.34	.47	.39	.33	.44	.37	.32	.42	.35	.31	.39	.34	.30	.27	
8.0	.44	.36	.30	.43	.35	.30	.40	.34	.29	.38	.32	.28	.36	.31	.27	.24	
9.0	.41	.33	.27	.39	.32	.27	.37	.30	.26	.35	.29	.25	.33	.28	.24	.22	
10.0	.37	.30	.24	.36	.29	.24	.35	.28	.23	.33	.27	.23	.31	.26	.22	.20	



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:XIAOMI
Test Date:2023-06-25

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:9.000m [K=1.0000]
Remarks:

WEC AND CCEC

Test:U:220.34V I:0.2043A P:41.526W PF:0.9227 Freq:50.00Hz Lamp Flux:2885.93x1 lm		
NAME: SB-J01A40WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:800*800mm	

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Wall Exitance Coefficients(WEC)															
0.0																
1.0	.338	.192	.061	.326	.186	.059	.305	.175	.056	.285	.164	.053	.267	.155	.050	
2.0	.303	.166	.051	.293	.161	.050	.273	.152	.047	.256	.143	.045	.239	.135	.043	
3.0	.274	.146	.044	.265	.142	.043	.248	.134	.041	.232	.127	.039	.217	.120	.037	
4.0	.250	.130	.038	.242	.127	.037	.226	.120	.036	.212	.114	.034	.198	.108	.033	
5.0	.230	.117	.034	.222	.114	.033	.208	.108	.032	.195	.103	.031	.182	.097	.029	
6.0	.212	.106	.030	.205	.104	.030	.192	.098	.029	.180	.094	.027	.169	.089	.026	
7.0	.196	.097	.028	.190	.095	.027	.178	.090	.026	.167	.086	.025	.157	.082	.024	
8.0	.183	.089	.025	.177	.087	.025	.167	.083	.024	.156	.079	.023	.147	.075	.022	
9.0	.171	.083	.023	.166	.081	.023	.156	.077	.022	.147	.074	.021	.138	.070	.020	
10.0	.161	.077	.021	.156	.075	.021	.147	.072	.020	.138	.069	.020	.130	.065	.019	

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Ceiling Cavity Exitance Coefficients(CCEC)															
0.0	.299	.299	.299	.256	.256	.256	.174	.174	.174	.100	.100	.100	.032	.032	.032	
1.0	.292	.265	.242	.250	.228	.208	.171	.157	.144	.098	.091	.084	.031	.029	.027	
2.0	.284	.242	.207	.243	.208	.179	.167	.144	.125	.096	.084	.073	.031	.027	.024	
3.0	.276	.225	.185	.237	.194	.160	.163	.135	.112	.094	.079	.066	.030	.026	.022	
4.0	.268	.212	.170	.230	.183	.147	.158	.128	.104	.092	.075	.061	.029	.024	.020	
5.0	.261	.202	.159	.224	.175	.138	.154	.122	.098	.089	.072	.058	.029	.023	.019	
6.0	.254	.194	.151	.218	.168	.132	.150	.118	.093	.087	.069	.055	.028	.023	.018	
7.0	.247	.187	.146	.212	.163	.127	.147	.114	.090	.085	.067	.054	.028	.022	.018	
8.0	.240	.182	.142	.207	.158	.123	.143	.111	.088	.083	.065	.052	.027	.021	.017	
9.0	.234	.177	.138	.202	.154	.121	.140	.108	.086	.081	.064	.051	.026	.021	.017	
10.0	.229	.173	.136	.197	.150	.118	.137	.106	.084	.080	.062	.050	.026	.021	.017	

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-06-25

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

UGR(Unified Glare Rating) Table

Test:U:220.34V I:0.2043A P:41.526W PF:0.9227 Freq:50.00Hz Lamp Flux:2885.93x1 lm											
NAME: SB-J01A40WSZ					TYPE:			WEIGHT:			
SPEC.:4000K					DIM.:			SERIAL No.:			
MFR.: SNOWBALL					SUR.:800*800mm						
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H y = 2H	12.2	13.5	12.6	14.0	14.4	12.0	13.3	12.4	13.7	14.2	
	3H	13.9	15.2	14.4	15.7	16.2	13.6	14.9	14.1	15.3	15.9
	4H	14.8	16.0	15.3	16.5	17.0	14.4	15.6	14.9	16.1	16.6
	6H	15.7	16.8	16.2	17.3	17.8	15.2	16.3	15.7	16.8	17.3
	8H	16.1	17.2	16.6	17.7	18.3	15.5	16.6	16.1	17.1	17.7
	12H	16.5	17.6	17.1	18.1	18.7	15.9	16.9	16.4	17.4	18.0
4H	2H	12.8	14.0	13.3	14.5	15.0	12.6	13.8	13.1	14.3	14.8
	3H	14.8	15.8	15.4	16.4	17.0	14.6	15.6	15.1	16.1	16.7
	4H	15.9	16.8	16.4	17.4	18.0	15.5	16.5	16.1	17.0	17.6
	6H	16.9	17.7	17.5	18.3	19.0	16.5	17.3	17.1	17.9	18.5
	8H	17.4	18.2	18.1	18.8	19.5	16.9	17.7	17.5	18.3	19.0
	12H	18.0	18.7	18.6	19.3	20.0	17.4	18.1	18.0	18.7	19.4
8H	4H	16.3	17.1	16.9	17.7	18.3	16.0	16.8	16.6	17.4	18.1
	6H	17.6	18.3	18.2	18.9	19.6	17.2	17.9	17.9	18.5	19.2
	8H	18.3	18.9	19.0	19.6	20.3	17.8	18.4	18.5	19.1	19.8
	12H	19.1	19.6	19.8	20.3	21.0	18.5	19.0	19.2	19.7	20.5
12H	4H	16.3	17.1	17.0	17.7	18.4	16.1	16.8	16.7	17.4	18.1
	6H	17.8	18.4	18.4	19.0	19.7	17.4	18.0	18.1	18.6	19.4
	8H	18.6	19.1	19.3	19.8	20.5	18.2	18.7	18.8	19.3	20.1
Variations with the observer position at spacings:											
S = 1.0H	+ 0.1 / - 0.2					+ 0.1 / - 0.2					
1.5H	+ 0.2 / - 0.3					+ 0.2 / - 0.3					
2.0H	+ 0.2 / - 0.4					+ 0.2 / - 0.4					

CIE Pub.117, 2886 lm Total Lamp Luminous Flux Corrected ($8\log(F/F_0) = 3.7$)
Area: 0.64 m²

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:XIAOMI
Test Date:2023-06-25

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:9.000m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:220.34V I:0.2043A P:41.526W PF:0.9227 Freq:50.00Hz Lamp Flux:2885.93x1 lm		
NAME: SB-J01A40WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:800*800mm	


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	53	41	34	52	41	34	50	40	33	27
0.80	62	50	43	61	49	42	58	48	41	34
1.00	70	58	50	68	57	50	65	58	49	41
1.25	77	65	58	75	64	57	71	62	55	46
1.50	82	71	63	79	69	62	75	66	60	51
2.00	89	79	72	86	77	70	81	73	68	57
2.50	93	84	77	90	82	75	84	77	72	60
3.00	96	88	82	93	86	80	87	81	76	64
4.00	101	94	88	97	91	86	90	86	81	68
5.00	103	97	92	99	94	90	93	88	85	71
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-06-25

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

ISOCANDELA DIAGRAM

Test:U:220.34V I:0.2043A P:41.526W PF:0.9227 Freq:50.00Hz Lamp Flux:2885.93x1 lm		
NAME: SB-J01A40WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:800*800mm	




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:XIAOMI
Test Date:2023-06-25

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:9.000m [K=1.0000]
Remarks:

AAI Figure

Test:U:220.34V I:0.2043A P:41.526W PF:0.9227 Freq:50.00Hz Lamp Flux:2885.93x1 lm		
NAME: SB-J01A40WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:800*800mm	




Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: XIAOMI
 Test Date: 2023-06-25

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity: 65.0%
 Test Distance: 9.000m [K=1.0000]
 Remarks:

ISOLUX DIAGRAM


Test:U:220.34V I:0.2043A P:41.526W PF:0.9227 Freq:50.00Hz Lamp Flux:2885.93x1 lm		
NAME: SB-J01A40WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:800*800mm	



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: XIAOMI
 Test Date: 2023-06-25

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity: 65.0%
 Test Distance: 9.000m [K=1.0000]
 Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: XIAOMI
Test Date: 2023-06-25

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity: 65.0%
Test Distance: 9.000m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:220.34V I:0.2043A P:41.526W PF:0.9227 Freq:50.00Hz Lamp Flux:2885.93x1 lm																	
NAME: SB-J01A40WSZ									TYPE:						WEIGHT:		
SPEC.:4000K									DIM.:						SERIAL No.:		
MFR.: SNOWBALL									SUR.:800*800mm								

Table--1

UNIT: cd

C(DEG) γ (DEG)	0	22.5	45	67.5	90	112.5	135	157.5	180	202.5	225	247.5	270	292.5	315	337.5			
0	903	902	902	901	901	900	897	898	903	902	902	901	901	900	897	898			
5	898	898	897	896	894	894	891	893	899	898	896	894	895	894	893	894			
10	879	878	878	877	874	877	874	875	882	881	879	874	872	873	874	875			
15	844	845	847	845	841	845	843	844	851	849	846	843	842	841	841	841			
20	799	801	802	802	794	802	801	798	802	803	806	804	801	800	798	797			
25	745	750	749	747	741	748	748	744	748	748	754	757	754	752	749	744			
30	687	691	687	690	682	690	691	686	691	692	696	703	699	697	695	684			
35	632	634	628	631	621	630	632	629	633	635	637	646	641	638	636	629			
40	570	575	570	572	560	573	571	574	577	577	581	588	584	580	579	572			
45	513	520	513	513	500	515	514	519	521	520	527	531	526	523	525	516			
50	455	466	459	455	438	458	457	463	462	464	473	473	467	467	472	466			
55	400	411	405	401	379	400	402	409	404	409	420	419	411	414	421	413			
60	344	358	351	344	323	346	351	356	349	356	368	364	354	362	371	360			
65	290	306	299	293	270	295	301	303	295	304	317	311	298	310	320	306			
70	239	255	255	243	220	245	253	254	243	256	268	259	245	260	270	256			
75	193	207	210	196	172	197	208	207	195	210	222	211	195	208	224	211			
80	150	166	168	152	128	153	166	162	151	167	177	164	149	167	180	169			
85	109	127	129	115	90.5	115	127	122	111	128	139	122	106	126	142	131			
90	66.0	86.6	70.6	59.4	43.0	58.2	68.8	64.0	53.7	63.1	67.2	56.1	53.4	71.2	97.5	83.0			
95	73.0	79.8	75.7	67.4	56.2	73.3	88.0	86.9	77.0	86.4	83.1	65.5	47.6	60.3	74.9	78.5			
100	75.4	83.6	88.5	81.5	63.5	84.1	95.2	89.3	78.3	87.9	89.3	72.1	54.4	73.9	86.8	81.3			
105	77.9	87.4	90.2	81.0	64.7	84.2	95.4	91.1	79.2	88.2	89.4	71.8	53.8	75.0	86.7	80.1			
110	80.0	89.9	92.0	71.4	64.2	80.6	97.7	93.1	81.0	89.8	88.8	65.1	52.8	66.7	86.2	84.5			
115	80.7	91.2	90.5	82.3	64.6	82.1	94.2	94.2	81.9	89.9	84.3	69.8	51.2	71.6	78.2	87.0			
120	79.9	91.0	86.6	77.0	61.7	78.2	92.8	93.2	81.4	89.0	81.4	62.9	47.1	61.1	73.8	84.2			
125	77.8	88.6	58.2	73.2	58.6	75.3	70.3	90.3	79.3	86.6	60.2	63.5	46.3	62.8	51.5	79.5			
130	68.2	51.7	75.6	69.3	55.0	72.9	80.9	66.3	69.4	62.2	70.1	61.6	45.0	60.4	71.9	50.3			
135	36.1	50.5	72.0	65.9	51.0	63.1	74.2	58.6	47.4	58.5	68.0	53.4	42.5	60.1	67.4	61.1			
140	45.6	59.9	64.9	60.7	40.8	55.9	65.1	67.4	51.8	63.8	59.4	47.9	34.5	55.3	60.2	58.7			
145	41.9	52.6	58.2	53.1	36.7	49.2	55.9	55.6	46.0	53.5	51.5	42.8	32.5	50.2	56.5	51.8			
150	37.6	46.6	51.9	43.9	32.6	42.8	49.2	45.6	41.5	44.9	44.2	39.0	31.0	43.8	50.3	46.7			
155	33.5	43.4	47.8	37.8	28.6	37.9	43.0	38.6	36.2	37.8	40.4	35.3	27.5	37.6	46.5	42.2			
160	36.7	42.0	41.2	32.8	26.6	34.9	37.0	33.3	30.8	32.8	34.7	32.6	23.6	32.7	40.4	41.8			
165	31.5	34.3	33.4	27.4	23.1	29.6	30.9	29.0	29.5	29.0	28.8	28.2	22.5	27.1	32.9	35.0			
170	24.7	26.6	26.0	23.6	19.2	24.5	24.6	23.6	23.1	23.0	23.3	22.3	18.7	23.1	25.6	26.5			
175	18.5	18.8	18.9	17.2	14.5	16.1	17.7	18.1	18.1	18.2	17.2	14.9	14.6	17.1	18.7	19.4			
180	11.3	11.1	10.8	10.8	10.9	11.0	11.2	11.5	11.3	11.1	10.8	10.9	10.9	11.1	11.2	11.5			

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:XIAOMI
Test Date:2023-06-25

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:9.000m [K=1.0000]
Remarks: