


LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:220.08V I:0.0998A P:20.578W PF:0.9366 Freq:50.00Hz Lamp Flux:1482.06x1 lm		
NAME: SB-U01A20WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:400mm	

DATA OF LAMP		PHOTOMETRIC DATA Eff: 72.02 lm/W			
MODEL		I _{max} (cd)	209.2	S/MH(C0/180)	1.34
NOMINAL POWER(W)		LOR(%)	100.0	S/MH(C90/270)	1.33
RATED VOLTAGE(V)	--	TOTAL FLUX(lm)	1482.1	η UP,DN(C0-180)	21.0,29.7
NOMINAL FLUX(lm)	1482.06	CIE CLASS	DIFFUSE	η UP,DN(C180-360)	20.1,29.2
LAMPS INSIDE	1	η up(%)	41.1	CIBSE SHR NOM	1.50
TEST VOLTAGE(V)	--	η down(%)	58.9	CIBSE SHR MAX	1.55



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-05-31

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum, lamp
10	209.0	208.8	207.3	205.2	205.4	205.5	206.5	208.0	0- 10	19.72	19.72	1.33,1.33
20	201.2	201.6	198.7	195.7	195.9	195.5	196.3	199.3	10- 20	57.51	77.23	5.21,5.21
30	185.6	186.9	185.3	181.0	182.2	181.8	181.8	185.0	20- 30	88.15	165.4	11.2,11.2
40	171.3	172.9	171.6	167.6	169.7	168.8	168.5	171.3	30- 40	110.9	276.3	18.6,18.6
50	158.2	159.0	157.4	154.3	156.7	155.2	154.3	157.3	40- 50	126.4	402.7	27.2,27.2
60	143.9	144.0	140.5	139.8	142.4	139.9	136.4	141.8	50- 60	133.5	536.2	36.2,36.2
70	127.8	125.7	117.0	122.0	126.2	120.3	111.9	122.1	60- 70	130.4	666.6	45,45
80	104.7	99.78	95.90	96.37	98.45	94.13	92.57	96.59	70- 80	116.0	782.6	52.8,52.8
90	61.08	62.98	59.42	57.87	61.18	57.89	57.03	57.94	80- 90	89.63	872.2	58.9,58.9
100	87.65	67.76	72.09	70.19	95.55	68.51	68.55	63.81	90-100	71.33	943.6	63.7,63.7
110	109.5	84.17	82.49	85.76	113.2	78.58	74.42	75.16	100-110	85.63	1029	69.4,69.4
120	121.6	98.53	90.55	101.7	124.9	90.22	84.35	86.75	110-120	93.61	1123	75.8,75.8
130	133.8	113.8	104.1	116.7	136.1	113.0	100.1	101.1	120-130	93.27	1216	82.1,82.1
140	143.3	107.8	121.0	106.2	137.3	111.4	111.0	104.6	130-140	90.30	1306	88.1,88.1
150	121.0	120.1	128.3	118.7	118.8	124.2	117.2	110.9	140-150	74.06	1380	93.1,93.1
160	120.0	132.9	132.4	122.9	121.4	112.7	115.3	111.0	150-160	55.38	1436	96.9,96.9
170	122.7	133.7	131.7	116.2	123.3	115.4	121.8	88.35	160-170	33.78	1470	99.2,99.2
180	149.8	143.0	137.9	140.3	149.8	143.3	137.9	140.3	170-180	12.47	1482	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

Conical surface Flux(90deg): 338.07 lm

%lum = 22.8%

%lamp = 22.8%

Conical surface Flux(120deg): 536.22 lm

%lum = 36.2%


%lamp = 36.2%

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-05-31

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:220.08V I:0.0998A P:20.578W PF:0.9366 Freq:50.00Hz Lamp Flux:1482.06x1 lm		
NAME: SB-U01A20WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:400mm	




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:XIAOMI
Test Date:2023-05-31

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:9.000m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:220.08V I:0.0998A P:20.578W PF:0.9366 Freq:50.00Hz Lamp Flux:1482.06x1 lm		
NAME: SB-U01A20WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:400mm	

ρ_{cc}	80%			70%			50%			30%			10%			0
ρ_w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρ_{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Coefficients of Utilization(CU)															
0.0	1.09	1.09	1.09	1.02	1.02	1.02	.88	.88	.88	.76	.76	.76	.64	.64	.64	.59
1.0	.91	.86	.82	.85	.80	.76	.73	.70	.66	.62	.60	.57	.52	.50	.48	.44
2.0	.78	.71	.64	.73	.66	.60	.62	.57	.53	.53	.49	.45	.44	.41	.39	.34
3.0	.68	.59	.52	.63	.55	.49	.54	.48	.43	.46	.41	.37	.38	.35	.32	.28
4.0	.59	.50	.43	.55	.47	.41	.47	.41	.36	.40	.35	.31	.34	.30	.26	.23
5.0	.52	.43	.37	.49	.41	.35	.42	.35	.30	.36	.31	.26	.30	.26	.22	.19
6.0	.47	.38	.31	.44	.36	.30	.38	.31	.26	.32	.27	.23	.27	.23	.19	.17
7.0	.42	.33	.27	.39	.31	.26	.34	.28	.23	.29	.24	.20	.25	.20	.17	.14
8.0	.38	.30	.24	.36	.28	.23	.31	.25	.20	.27	.21	.18	.22	.18	.15	.13
9.0	.35	.27	.21	.33	.25	.20	.28	.22	.18	.24	.19	.16	.21	.17	.14	.11
10.0	.32	.24	.19	.30	.23	.18	.26	.20	.16	.23	.18	.14	.19	.15	.12	.10



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-05-31

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

WEC AND CCEC

Test:U:220.08V I:0.0998A P:20.578W PF:0.9366 Freq:50.00Hz Lamp Flux:1482.06x1 lm		
NAME: SB-U01A20WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:400mm	

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Wall Exitance Coefficients(WEC)												
0.0																
1.0	.363	.207	.065	.344	.196	.062	.307	.176	.056	.273	.158	.051	.242	.140	.045	
2.0	.316	.173	.053	.298	.164	.051	.265	.147	.046	.234	.131	.041	.205	.116	.037	
3.0	.281	.150	.045	.265	.142	.043	.235	.127	.039	.206	.113	.035	.180	.100	.031	
4.0	.254	.132	.039	.239	.125	.037	.211	.112	.033	.185	.099	.030	.161	.087	.027	
5.0	.231	.118	.034	.218	.112	.033	.192	.100	.029	.168	.089	.026	.146	.078	.023	
6.0	.212	.106	.030	.200	.101	.029	.176	.090	.026	.154	.080	.023	.133	.070	.021	
7.0	.196	.097	.027	.184	.092	.026	.162	.082	.024	.142	.073	.021	.123	.064	.019	
8.0	.182	.089	.025	.171	.084	.024	.151	.075	.022	.132	.067	.019	.114	.058	.017	
9.0	.170	.082	.023	.160	.078	.022	.141	.070	.020	.123	.062	.018	.106	.054	.016	
10.0	.159	.076	.021	.150	.072	.020	.132	.065	.018	.115	.057	.016	.100	.050	.014	

pcc	80%			70%			50%			30%			10%			0	
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
pfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)										
0.0	.504	.504	.504	.431	.431	.431	.294	.294	.294	.169	.169	.169	.054	.054	.054		
1.0	.500	.472	.446	.428	.405	.384	.293	.279	.266	.168	.161	.154	.054	.052	.050		
2.0	.494	.450	.413	.423	.387	.357	.290	.268	.249	.167	.156	.146	.054	.050	.048		
3.0	.487	.434	.393	.417	.375	.340	.286	.260	.239	.165	.152	.141	.053	.049	.046		
4.0	.479	.422	.379	.411	.365	.329	.283	.254	.232	.164	.149	.137	.053	.049	.045		
5.0	.472	.413	.370	.406	.357	.321	.279	.250	.227	.162	.147	.135	.052	.048	.044		
6.0	.465	.406	.363	.400	.351	.316	.276	.246	.224	.160	.145	.133	.052	.047	.044		
7.0	.459	.399	.358	.394	.346	.312	.273	.243	.221	.158	.143	.132	.051	.047	.043		
8.0	.452	.394	.354	.389	.342	.309	.269	.240	.219	.157	.142	.130	.051	.046	.043		
9.0	.446	.390	.351	.385	.338	.306	.266	.238	.217	.155	.140	.130	.050	.046	.043		
10.0	.441	.386	.349	.380	.335	.304	.264	.236	.216	.154	.139	.129	.050	.046	.043		

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-05-31

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

UGR(Unified Glare Rating) Table

Test:U:220.08V I:0.0998A P:20.578W PF:0.9366 Freq:50.00Hz Lamp Flux:1482.06x1 lm											
NAME: SB-U01A20WSZ					TYPE:			WEIGHT:			
SPEC.:4000K					DIM.:			SERIAL No.:			
MFR.: SNOWBALL					SUR.:400mm						
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H y = 2H	13.0	14.1	13.8	14.9	15.9	13.0	14.1	13.7	14.9	15.8	
	3H	15.7	16.7	16.5	17.5	18.5	15.4	16.4	16.2	17.2	18.2
	4H	17.1	18.0	17.9	18.9	19.9	16.7	17.6	17.5	18.5	19.5
	6H	18.6	19.5	19.4	20.3	21.4	18.1	19.0	18.9	19.8	20.9
	8H	19.3	20.2	20.2	21.0	22.1	18.9	19.8	19.7	20.6	21.7
	12H	20.1	20.9	21.0	21.8	22.9	19.8	20.7	20.7	21.5	22.6
4H	2H	13.8	14.8	14.7	15.6	16.7	13.8	14.7	14.6	15.6	16.6
	3H	16.6	17.4	17.5	18.3	19.4	16.4	17.2	17.3	18.1	19.2
	4H	18.2	18.9	19.1	19.8	20.9	17.8	18.6	18.7	19.5	20.6
	6H	19.9	20.5	20.8	21.4	22.6	19.4	20.1	20.3	21.0	22.1
	8H	20.7	21.3	21.6	22.2	23.4	20.3	20.9	21.2	21.8	23.0
	12H	21.6	22.2	22.5	23.1	24.3	21.3	21.9	22.3	22.8	24.0
8H	4H	18.7	19.3	19.6	20.2	21.4	18.4	19.0	19.3	20.0	21.1
	6H	20.6	21.2	21.6	22.1	23.3	20.3	20.8	21.2	21.7	22.9
	8H	21.6	22.1	22.6	23.0	24.2	21.3	21.8	22.3	22.7	23.9
	12H	22.8	23.2	23.7	24.1	25.4	22.6	23.0	23.5	23.9	25.2
12H	4H	18.8	19.4	19.7	20.3	21.5	18.5	19.1	19.5	20.0	21.2
	6H	20.8	21.3	21.8	22.3	23.5	20.5	21.0	21.4	21.9	23.1
	8H	21.9	22.3	22.9	23.3	24.5	21.7	22.1	22.6	23.0	24.3
Variations with the observer position at spacings:											
S = 1.0H	+ 0.1 / - 0.1					+ 0.1 / - 0.1					
1.5H	+ 0.2 / - 0.2					+ 0.2 / - 0.3					
2.0H	+ 0.2 / - 0.4					+ 0.3 / - 0.4					

CIE Pub.117, 1482 lm Total Lamp Luminous Flux Corrected ($8\log(F/F_0) = 1.4$)
Area: 0.125 m²

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:XIAOMI
Test Date:2023-05-31

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:9.000m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:220.08V I:0.0998A P:20.578W PF:0.9366 Freq:50.00Hz Lamp Flux:1482.06x1 lm		
NAME: SB-U01A20WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:400mm	


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	42	30	23	40	29	22	36	27	21	13
0.80	51	38	30	48	36	29	43	33	27	18
1.00	58	45	37	55	43	35	49	41	33	22
1.25	65	52	44	61	50	42	54	45	38	26
1.50	70	58	49	66	55	47	58	49	43	29
2.00	78	67	58	73	63	55	64	56	50	33
2.50	82	72	64	77	68	61	67	60	54	36
3.00	86	77	69	81	72	66	70	64	58	39
4.00	91	83	77	85	78	72	74	69	64	42
5.00	94	87	81	88	82	77	76	72	68	45
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-05-31

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

ISOCANDELA DIAGRAM

Test:U:220.08V I:0.0998A P:20.578W PF:0.9366 Freq:50.00Hz Lamp Flux:1482.06x1 lm		
NAME: SB-U01A20WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:400mm	




C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: XIAOMI
 Test Date: 2023-05-31

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity: 65.0%
 Test Distance: 9.000m [K=1.0000]
 Remarks:

AAI Figure

Test:U:220.08V I:0.0998A P:20.578W PF:0.9366 Freq:50.00Hz Lamp Flux:1482.06x1 lm		
NAME: SB-U01A20WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:400mm	

Flux out:782.6 lm




Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: XIAOMI
 Test Date: 2023-05-31

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity: 65.0%
 Test Distance: 9.000m [K=1.0000]
 Remarks:

ISOLUX DIAGRAM


Test:U:220.08V I:0.0998A P:20.578W PF:0.9366 Freq:50.00Hz Lamp Flux:1482.06x1 lm		
NAME: SB-U01A20WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:400mm	



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: XIAOMI
 Test Date: 2023-05-31

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity: 65.0%
 Test Distance: 9.000m [K=1.0000]
 Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: XIAOMI
Test Date: 2023-05-31

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity: 65.0%
Test Distance: 9.000m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:220.08V I:0.0998A P:20.578W PF:0.9366 Freq:50.00Hz Lamp Flux:1482.06x1 lm		
NAME: SB-U01A20WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:400mm	

Table--1

UNIT: cd

C(DEG) γ (DEG)	0	22.5	45	67.5	90	112.5	135	157.5	180	202.5	225	247.5	270	292.5	315	337.5			
0	205	205	205	205	205	205	205	204	205	205	205	205	205	205	205	204			
5	207	207	207	206	206	205	205	204	206	206	206	207	207	208	207	207			
10	209	209	209	209	207	206	205	205	205	205	206	206	207	207	208	208			
15	207	208	207	206	205	203	202	201	202	201	202	201	202	203	205	206			
20	201	202	202	201	199	197	196	195	196	195	196	195	196	197	199	200			
25	194	194	194	194	192	190	188	188	189	189	189	188	189	190	193	193			
30	186	187	187	187	185	183	181	181	182	182	182	181	182	183	185	185			
35	178	179	180	181	178	177	174	174	176	175	175	175	175	177	178	178			
40	171	172	173	173	172	170	168	167	170	169	169	168	168	170	171	171			
45	165	165	166	167	165	163	161	161	163	162	162	161	161	163	164	164			
50	158	159	159	159	157	156	154	154	157	156	155	154	154	156	157	157			
55	151	152	152	152	149	149	148	148	150	148	148	146	146	148	150	150			
60	144	144	144	143	141	140	140	140	142	141	140	137	136	139	142	142			
65	136	136	135	133	129	131	132	133	135	132	131	126	124	127	133	134			
70	128	127	126	121	117	119	122	124	126	123	120	114	112	115	122	125			
75	118	116	113	109	105	107	110	113	116	112	108	103	101	104	110	114			
80	105	104	99.8	97.1	95.9	95.5	96.4	98.5	98.5	95.7	94.1	92.0	92.6	92.8	96.6	101			
85	85.8	87.2	87.3	87.6	86.7	86.3	85.5	85.3	84.6	83.4	83.3	82.3	83.0	83.3	84.6	85.1			
90	61.1	64.2	63.0	63.5	59.4	58.4	57.9	58.8	61.2	59.9	57.9	57.5	57.0	56.7	57.9	59.1			
95	79.3	66.9	60.8	61.2	65.2	61.5	61.6	69.1	80.5	68.5	61.6	61.8	63.5	60.5	58.9	66.2			
100	87.7	77.7	67.8	66.5	72.1	67.1	70.2	83.4	95.5	82.0	68.5	64.6	68.5	64.2	63.8	76.6			
105	103	88.1	74.8	76.2	79.0	77.2	76.1	91.1	107	90.3	73.1	69.9	72.1	66.7	66.8	86.8			
110	110	97.9	84.2	80.5	82.5	81.6	85.8	101	113	98.8	78.6	75.4	74.4	68.3	75.2	96.6			
115	116	105	90.9	88.2	86.6	89.9	93.1	109	120	105	85.2	83.8	75.1	77.5	85.6	103			
120	122	111	98.5	95.1	90.6	94.8	102	114	125	109	90.2	90.2	84.3	78.8	86.8	110			
125	127	117	107	86.1	96.7	87.9	111	119	131	117	102	84.5	92.3	77.7	95.8	116			
130	134	123	114	85.5	104	88.8	117	125	136	124	113	87.8	100	79.9	101	117			
135	139	128	120	105	113	107	119	129	141	130	122	98.9	108	103	111	125			
140	143	132	108	117	121	114	106	128	137	122	111	109	111	114	105	132			
145	147	124	103	121	126	114	98.5	116	125	118	106	119	119	115	105	125			
150	121	114	120	127	128	120	119	114	119	120	124	123	117	110	111	114			
155	114	117	128	133	135	127	133	119	117	116	118	117	115	106	114	110			
160	120	125	133	136	132	129	123	111	121	113	113	118	115	109	111	103			
165	121	130	139	135	134	129	118	109	122	111	109	117	114	109	105	109			
170	123	131	134	133	132	129	116	104	123	114	115	116	122	112	88.4	105			
175	147	144	140	138	132	128	131	130	146	144	138	136	136	139	137	132			
180	150	148	143	139	138	139	140	130	150	148	143	139	138	139	140	132			

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:XIAOMI
Test Date:2023-05-31

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:9.000m [K=1.0000]
Remarks: