


LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:220.12V I:0.2346A P:48.616W PF:0.9414 Freq:50.00Hz Lamp Flux:3606.23x1 lm		
NAME: SB-U01A50WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1000mm	

DATA OF LAMP		PHOTOMETRIC DATA Eff: 74.18 lm/W			
MODEL		I _{max} (cd)	399.0	S/MH(C0/180)	1.57
NOMINAL POWER(W)		LOR(%)	100.0	S/MH(C90/270)	1.53
RATED VOLTAGE(V)	--	TOTAL FLUX(lm)	3606.2	η UP,DN(C0-180)	22.8,27.1
NOMINAL FLUX(lm)	3606.23	CIE CLASS	DIFFUSE	η UP,DN(C180-360)	22.4,27.7
LAMPS INSIDE	1	η up(%)	45.2	CIBSE SHR NOM	1.75
TEST VOLTAGE(V)	--	η down(%)	54.8	CIBSE SHR MAX	1.75



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-05-31

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum,lamp
10	389.3	383.7	382.1	382.7	387.5	392.6	391.3	390.0	0- 10	36.62	36.62	1.02,1.02
20	390.8	383.0	381.0	387.8	398.8	398.3	393.9	390.5	10- 20	110.6	147.2	4.08,4.08
30	385.0	375.4	372.9	381.1	395.7	390.7	385.7	382.0	20- 30	179.2	326.4	9.05,9.05
40	372.8	363.3	360.0	368.7	385.3	377.8	372.8	368.9	30- 40	237.1	563.5	15.6,15.6
50	352.3	344.7	341.7	350.7	368.4	359.9	354.0	349.4	40- 50	280.3	843.8	23.4,23.4
60	322.6	317.3	316.9	325.7	343.6	334.5	325.9	319.7	50- 60	304.6	1148	31.8,31.8
70	287.1	283.4	285.2	294.0	311.7	301.1	290.8	282.4	60- 70	306.8	1455	40.4,40.4
80	250.5	244.1	248.4	257.2	275.4	264.1	248.7	240.1	70- 80	288.5	1744	48.4,48.4
90	190.3	159.8	132.7	186.6	200.1	188.9	133.5	154.3	80- 90	232.9	1977	54.8,54.8
100	259.8	240.6	239.5	218.0	241.8	220.3	233.2	225.1	90-100	216.0	2193	60.8,60.8
110	291.9	263.5	268.1	249.2	270.9	250.8	258.7	252.5	100-110	259.5	2452	68,68
120	310.0	256.8	287.0	235.4	303.1	245.3	275.7	234.2	110-120	262.5	2715	75.3,75.3
130	260.2	288.8	303.1	281.6	268.5	282.5	293.4	273.4	120-130	240.8	2955	82,82
140	244.8	288.9	297.1	266.9	265.1	262.7	293.0	278.4	130-140	216.7	3172	88,88
150	256.3	296.2	289.6	264.6	277.8	272.2	287.9	286.2	140-150	173.7	3346	92.8,92.8
160	327.1	329.5	301.3	308.4	338.6	317.6	314.4	325.8	150-160	135.7	3482	96.5,96.5
170	339.6	322.3	323.9	331.3	355.9	338.1	332.1	324.7	160-170	92.84	3574	99.1,99.1
180	345.2	333.0	336.6	336.4	345.4	333.6	336.7	335.0	170-180	31.86	3606	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

Conical surface Flux(90deg): 699.36 lm

%lum = 19.4%

%lamp = 19.4%

Conical surface Flux(120deg): 1148.4 lm

%lum = 31.8%


%lamp = 31.8%

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-05-31

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:220.12V I:0.2346A P:48.616W PF:0.9414 Freq:50.00Hz Lamp Flux:3606.23x1 lm		
NAME: SB-U01A50WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1000mm	




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:XIAOMI
Test Date:2023-05-31

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:9.000m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:220.12V I:0.2346A P:48.616W PF:0.9414 Freq:50.00Hz Lamp Flux:3606.23x1 lm		
NAME: SB-U01A50WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1000mm	

ρ_{cc}	80%			70%			50%			30%			10%			0
ρ_w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρ_{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Coefficients of Utilization(CU)															
0.0	1.08	1.08	1.08	1.01	1.01	1.01	.86	.86	.86	.73	.73	.73	.61	.61	.61	.55
1.0	.90	.85	.80	.83	.79	.75	.71	.67	.64	.59	.56	.54	.48	.47	.45	.40
2.0	.77	.69	.63	.71	.64	.59	.60	.55	.50	.50	.46	.43	.41	.38	.35	.30
3.0	.66	.58	.51	.61	.54	.47	.52	.46	.41	.43	.38	.35	.35	.31	.28	.24
4.0	.58	.49	.42	.54	.45	.39	.45	.39	.34	.38	.33	.29	.31	.27	.24	.20
5.0	.51	.42	.35	.47	.39	.33	.40	.34	.29	.33	.28	.24	.27	.23	.20	.17
6.0	.46	.37	.30	.42	.34	.28	.36	.29	.25	.30	.25	.21	.24	.20	.17	.14
7.0	.41	.32	.26	.38	.30	.24	.32	.26	.21	.27	.22	.18	.22	.18	.15	.12
8.0	.37	.29	.23	.34	.27	.21	.29	.23	.19	.25	.20	.16	.20	.16	.13	.11
9.0	.34	.26	.20	.31	.24	.19	.27	.21	.17	.23	.18	.14	.19	.15	.12	.10
10.0	.31	.23	.18	.29	.22	.17	.25	.19	.15	.21	.16	.13	.17	.13	.11	.09



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-05-31

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

WEC AND CCEC

Test:U:220.12V I:0.2346A P:48.616W PF:0.9414 Freq:50.00Hz Lamp Flux:3606.23x1 lm		
NAME: SB-U01A50WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1000mm	

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)									
0.0																
1.0	.370	.210	.067	.349	.199	.063	.310	.178	.057	.274	.158	.051	.241	.140	.045	
2.0	.320	.175	.054	.301	.166	.051	.265	.147	.046	.232	.130	.041	.201	.114	.036	
3.0	.284	.151	.045	.266	.143	.043	.234	.127	.038	.204	.112	.034	.176	.097	.030	
4.0	.255	.133	.039	.240	.125	.037	.210	.111	.033	.182	.098	.029	.156	.085	.026	
5.0	.232	.118	.034	.218	.112	.033	.190	.099	.029	.165	.087	.026	.141	.075	.023	
6.0	.213	.107	.031	.200	.101	.029	.174	.089	.026	.150	.078	.023	.128	.068	.020	
7.0	.196	.097	.028	.184	.092	.026	.161	.081	.023	.139	.071	.021	.118	.061	.018	
8.0	.182	.089	.025	.171	.084	.024	.149	.074	.021	.128	.065	.019	.109	.056	.016	
9.0	.170	.082	.023	.159	.078	.022	.139	.069	.019	.120	.060	.017	.102	.052	.015	
10.0	.159	.076	.021	.149	.072	.020	.130	.064	.018	.112	.056	.016	.095	.048	.014	

pcc	80%			70%			50%			30%			10%			0	
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
pfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)										
0.0	.535	.535	.535	.457	.457	.457	.312	.312	.312	.179	.179	.179	.057	.057	.057		
1.0	.532	.503	.477	.455	.432	.410	.311	.297	.284	.179	.172	.165	.057	.055	.053		
2.0	.525	.481	.444	.450	.414	.384	.308	.287	.268	.178	.167	.157	.057	.054	.051		
3.0	.518	.466	.424	.445	.402	.367	.305	.279	.258	.176	.163	.152	.057	.053	.050		
4.0	.511	.454	.410	.439	.392	.356	.302	.273	.251	.175	.160	.148	.056	.052	.049		
5.0	.504	.445	.401	.433	.385	.349	.298	.269	.246	.173	.158	.146	.056	.052	.048		
6.0	.497	.437	.394	.427	.379	.344	.295	.265	.243	.171	.156	.144	.055	.051	.048		
7.0	.491	.431	.390	.422	.374	.340	.292	.262	.241	.169	.154	.143	.055	.051	.047		
8.0	.484	.426	.386	.417	.370	.337	.288	.259	.239	.168	.153	.142	.054	.050	.047		
9.0	.478	.422	.383	.412	.366	.334	.286	.257	.237	.166	.152	.141	.054	.050	.047		
10.0	.473	.418	.381	.408	.363	.332	.283	.255	.236	.165	.151	.141	.053	.050	.047		

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-05-31

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

UGR(Unified Glare Rating) Table

Test:U:220.12V I:0.2346A P:48.616W PF:0.9414 Freq:50.00Hz Lamp Flux:3606.23x1 lm											
NAME: SB-U01A50WSZ					TYPE:			WEIGHT:			
SPEC.:4000K					DIM.:			SERIAL No.:			
MFR.: SNOWBALL					SUR.:1000mm						
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	Viewed crosswise					Viewed endwise					
x = 2H y = 2H	9.0	10.1	9.8	11.0	12.0	8.9	10.0	9.7	10.9	11.9	
	3H	11.7	12.7	12.5	13.5	14.6	11.6	12.6	12.5	13.5	14.6
	4H	13.2	14.1	14.0	15.0	16.1	13.1	14.0	14.0	14.9	16.0
	6H	14.8	15.7	15.7	16.6	17.7	14.7	15.6	15.6	16.5	17.6
	8H	15.7	16.5	16.5	17.4	18.5	15.6	16.5	16.5	17.4	18.5
	12H	16.4	17.2	17.2	18.1	19.2	16.6	17.4	17.5	18.3	19.5
4H	2H	9.8	10.8	10.7	11.6	12.7	9.8	10.7	10.6	11.6	12.7
	3H	12.7	13.5	13.6	14.4	15.5	12.6	13.4	13.5	14.3	15.5
	4H	14.3	15.0	15.2	15.9	17.1	14.2	15.0	15.2	15.9	17.1
	6H	16.1	16.7	17.0	17.7	18.9	16.0	16.7	17.0	17.6	18.8
	8H	17.1	17.7	18.0	18.6	19.8	17.0	17.6	18.0	18.6	19.8
	12H	17.8	18.4	18.8	19.3	20.6	18.1	18.7	19.1	19.6	20.9
8H	4H	14.9	15.5	15.8	16.4	17.6	14.8	15.4	15.8	16.4	17.6
	6H	16.9	17.4	17.9	18.4	19.6	16.9	17.4	17.9	18.4	19.6
	8H	18.1	18.5	19.0	19.5	20.8	18.1	18.5	19.0	19.5	20.8
	12H	19.0	19.4	20.0	20.4	21.7	19.3	19.7	20.3	20.7	22.0
12H	4H	15.0	15.5	15.9	16.5	17.7	15.0	15.5	15.9	16.5	17.7
	6H	17.2	17.6	18.1	18.6	19.9	17.1	17.6	18.1	18.6	19.8
	8H	18.4	18.8	19.4	19.8	21.1	18.4	18.8	19.4	19.8	21.1
Variations with the observer position at spacings:											
S = 1.0H	+ 0.1 / - 0.1					+ 0.1 / - 0.1					
1.5H	+ 0.2 / - 0.2					+ 0.2 / - 0.3					
2.0H	+ 0.2 / - 0.3					+ 0.3 / - 0.4					

CIE Pub.117, 3606 lm Total Lamp Luminous Flux Corrected ($8\log(F/F_0) = 4.5$)
Area: 0.785 m²

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:XIAOMI
Test Date:2023-05-31

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:9.000m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:220.12V I:0.2346A P:48.616W PF:0.9414 Freq:50.00Hz Lamp Flux:3606.23x1 lm		
NAME: SB-U01A50WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1000mm	


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	40	27	21	38	26	20	34	24	19	11
0.80	49	35	27	46	34	26	41	31	24	15
1.00	56	43	34	53	41	33	46	38	30	19
1.25	63	50	41	59	47	39	52	42	35	22
1.50	68	56	47	64	52	44	55	46	40	25
2.00	76	64	55	71	60	53	61	53	47	29
2.50	81	70	62	75	66	58	65	57	51	32
3.00	85	75	67	79	70	63	67	61	55	35
4.00	90	81	74	83	76	70	71	66	61	38
5.00	93	85	79	86	80	74	74	69	65	41
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-05-31

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

ISOCANDELA DIAGRAM

Test:U:220.12V I:0.2346A P:48.616W PF:0.9414 Freq:50.00Hz Lamp Flux:3606.23x1 lm		
NAME: SB-U01A50WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1000mm	




C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-05-31

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

AAI Figure

Test:U:220.12V I:0.2346A P:48.616W PF:0.9414 Freq:50.00Hz Lamp Flux:3606.23x1 lm		
NAME: SB-U01A50WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1000mm	




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-05-31

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

ISOLUX DIAGRAM


Test:U:220.12V I:0.2346A P:48.616W PF:0.9414 Freq:50.00Hz Lamp Flux:3606.23x1 lm		
NAME: SB-U01A50WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1000mm	



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-05-31

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: XIAOMI
Test Date: 2023-05-31

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity: 65.0%
Test Distance: 9.000m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:220.12V I:0.2346A P:48.616W PF:0.9414 Freq:50.00Hz Lamp Flux:3606.23x1 lm		
NAME: SB-U01A50WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1000mm	

Table--1

UNIT: cd

C(DEG) γ (DEG)	0	22.5	45	67.5	90	112.5	135	157.5	180	202.5	225	247.5	270	292.5	315	337.5			
0	379	379	379	379	378	378	378	378	379	379	379	379	378	378	378	378			
5	384	382	380	379	379	378	379	378	381	382	383	385	384	384	385	384			
10	389	387	384	383	382	381	383	385	388	389	393	393	391	390	390	390			
15	391	389	385	383	383	384	387	391	395	396	397	398	395	392	392	391			
20	391	388	383	381	381	383	388	393	399	398	398	398	394	391	390	390			
25	389	385	380	378	378	381	385	392	398	397	395	394	390	387	387	387			
30	385	380	375	373	373	376	381	389	396	393	391	389	386	382	382	382			
35	380	375	370	368	367	371	376	384	391	388	385	383	380	376	376	376			
40	373	368	363	361	360	364	369	377	385	382	378	376	373	369	369	369			
45	363	359	355	353	351	355	361	370	377	374	370	367	364	360	360	360			
50	352	349	345	343	342	346	351	360	368	364	360	357	354	350	349	349			
55	338	336	332	331	330	335	339	349	357	353	348	345	341	337	336	335			
60	323	321	317	317	317	322	326	335	344	339	335	330	326	321	320	319			
65	305	304	301	301	302	307	311	320	329	324	319	313	309	304	302	301			
70	287	285	283	284	285	290	294	304	312	308	301	296	291	285	282	282			
75	269	266	265	266	267	272	276	286	294	290	283	277	270	264	262	262			
80	251	248	244	247	248	253	257	266	275	270	264	254	249	242	240	242			
85	179	181	186	209	219	229	236	247	257	251	242	229	217	193	182	174			
90	190	178	160	137	133	179	187	194	200	196	189	154	133	147	154	173			
95	245	233	218	205	204	173	167	170	182	179	174	182	198	200	205	219			
100	260	250	241	230	239	225	218	227	242	234	220	214	233	219	225	239			
105	276	264	254	239	254	235	237	240	256	244	236	227	248	230	241	256			
110	292	279	263	252	268	238	249	253	271	260	251	234	259	242	253	265			
115	306	294	243	258	279	252	257	269	287	276	264	250	271	244	224	266			
120	310	271	257	260	287	254	235	286	303	290	245	250	276	250	234	242			
125	257	257	278	272	294	271	253	259	302	261	251	270	284	256	266	237			
130	260	279	289	288	303	288	282	261	269	258	283	286	293	280	273	264			
135	249	279	287	298	306	288	279	276	270	273	280	278	297	291	276	268			
140	245	276	289	302	297	276	267	267	265	265	263	276	293	295	278	264			
145	249	280	294	299	293	271	263	266	268	267	270	273	290	293	282	267			
150	256	284	296	297	290	268	265	269	278	271	272	271	288	288	286	272			
155	295	317	321	304	288	269	270	271	288	276	276	276	293	301	311	304			
160	327	343	329	307	301	304	308	316	339	320	318	318	314	311	326	330			
165	338	347	326	314	318	319	322	331	352	332	330	331	327	321	326	335			
170	340	337	322	322	324	326	331	340	356	340	338	334	332	327	325	329			
175	340	333	325	326	329	331	335	341	353	339	337	337	335	330	330	330			
180	345	334	333	336	337	335	336	338	345	334	334	336	337	335	335	338			

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:XIAOMI
Test Date:2023-05-31

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:9.000m [K=1.0000]
Remarks: