


LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:220.22V I:0.2011A P:40.717W PF:0.9194 Freq:50.00Hz Lamp Flux:2662.16x1 lm		
NAME: SB-D01A40WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:800mm	

DATA OF LAMP		PHOTOMETRIC DATA Eff: 65.38 lm/W			
MODEL		I _{max} (cd)	368.9	S/MH(C0/180)	1.90
NOMINAL POWER(W)		LOR(%)	100.0	S/MH(C90/270)	1.84
RATED VOLTAGE(V)	--	TOTAL FLUX(lm)	2662.2	η UP,DN(C0-180)	14.4,36.0
NOMINAL FLUX(lm)	2662.16	CIE CLASS	SEMI-D.	η UP,DN(C180-360)	14.0,35.6
LAMPS INSIDE	1	η up(%)	28.4	CIBSE SHR NOM	2.00
TEST VOLTAGE(V)	--	η down(%)	71.6	CIBSE SHR MAX	2.00



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:XIAOMI
Test Date:2023-05-30

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:9.000m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum,lamp
10	304.2	301.2	297.8	299.3	303.9	301.2	296.7	297.1	0- 10	27.63	27.63	1.04,1.04
20	335.2	330.6	323.7	326.8	333.5	327.8	321.5	323.9	10- 20	89.49	117.1	4.4,4.4
30	358.3	352.3	341.6	346.5	355.4	347.6	338.0	344.1	20- 30	156.9	274.0	10.3,10.3
40	368.7	362.0	348.0	354.1	365.0	355.4	343.7	352.5	30- 40	221.8	495.8	18.6,18.6
50	363.0	356.3	340.5	347.5	359.5	348.7	335.7	346.3	40- 50	274.0	769.8	28.9,28.9
60	341.8	335.4	319.1	326.3	338.5	328.0	314.5	325.9	50- 60	304.9	1075	40.4,40.4
70	309.0	302.9	287.0	294.3	306.3	296.5	283.4	294.7	60- 70	310.7	1385	52,52
80	267.5	262.2	248.2	254.7	266.0	257.8	245.2	256.1	70- 80	293.2	1679	63.1,63.1
90	132.5	128.2	112.8	110.3	114.5	112.6	113.9	125.9	80- 90	227.2	1906	71.6,71.6
100	196.7	179.3	180.7	169.0	198.1	169.8	165.5	163.0	90-100	165.3	2071	77.8,77.8
110	180.4	169.3	160.0	160.0	175.0	156.4	154.4	156.9	100-110	180.3	2251	84.6,84.6
120	162.2	145.9	133.2	137.5	155.2	142.8	130.3	133.6	110-120	147.7	2399	90.1,90.1
130	141.4	102.6	110.9	84.12	130.8	86.61	108.5	95.15	120-130	112.4	2511	94.3,94.3
140	81.73	90.29	89.02	88.40	73.21	90.29	83.20	86.74	130-140	74.40	2586	97.1,97.1
150	60.04	64.84	57.15	49.33	53.33	45.57	58.48	63.47	140-150	44.25	2630	98.8,98.8
160	41.57	42.24	34.84	28.71	37.38	27.82	34.57	39.54	150-160	21.46	2652	99.6,99.6
170	27.19	23.70	18.79	21.81	27.83	21.86	18.72	23.52	160-170	8.983	2661	99.9,99.9
180	12.67	12.29	11.90	12.46	12.65	12.27	11.89	12.45	170-180	1.647	2662	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

Conical surface Flux(90deg): 627.43 lm

%lum = 23.6%

%lamp = 23.6%

Conical surface Flux(120deg): 1074.7 lm

%lum = 40.4%


%lamp = 40.4%

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-05-30

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:220.22V I:0.2011A P:40.717W PF:0.9194 Freq:50.00Hz Lamp Flux:2662.16x1 lm		
NAME: SB-D01A40WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:800mm	




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:XIAOMI
Test Date:2023-05-30

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:9.000m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:220.22V I:0.2011A P:40.717W PF:0.9194 Freq:50.00Hz Lamp Flux:2662.16x1 lm		
NAME: SB-D01A40WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:800mm	

ρ_{cc}	80%			70%			50%			30%			10%			0	
ρ_w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
ρ_{fc}	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Coefficients of Utilization(CU)										
0.0	1.12	1.12	1.12	1.06	1.06	1.06	.95	.95	.95	.85	.85	.85	.76	.76	.76	.72	
1.0	.92	.86	.81	.87	.82	.77	.77	.73	.69	.68	.65	.62	.60	.58	.55	.51	
2.0	.77	.69	.62	.73	.66	.59	.65	.59	.54	.57	.52	.48	.50	.46	.43	.39	
3.0	.66	.57	.50	.63	.54	.47	.55	.49	.43	.49	.43	.38	.43	.38	.34	.31	
4.0	.58	.48	.41	.55	.46	.39	.48	.41	.35	.43	.36	.32	.37	.32	.28	.25	
5.0	.51	.41	.34	.48	.39	.32	.43	.35	.29	.38	.31	.26	.33	.28	.24	.21	
6.0	.45	.36	.29	.43	.34	.28	.38	.31	.25	.34	.27	.23	.29	.24	.20	.17	
7.0	.41	.31	.25	.38	.30	.24	.34	.27	.22	.30	.24	.20	.27	.21	.17	.15	
8.0	.37	.28	.22	.35	.26	.21	.31	.24	.19	.28	.21	.17	.24	.19	.15	.13	
9.0	.33	.25	.19	.32	.24	.18	.28	.21	.17	.25	.19	.15	.22	.17	.14	.11	
10.0	.30	.22	.17	.29	.21	.16	.26	.19	.15	.23	.17	.13	.21	.16	.12	.10	



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-05-30

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

WEC AND CCEC

Test:U:220.22V I:0.2011A P:40.717W PF:0.9194 Freq:50.00Hz Lamp Flux:2662.16x1 lm		
NAME: SB-D01A40WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:800mm	

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)									
0.0																
1.0	.411	.234	.074	.395	.225	.072	.365	.210	.067	.338	.195	.063	.313	.181	.058	
2.0	.351	.192	.059	.336	.185	.057	.309	.172	.053	.284	.159	.050	.261	.148	.047	
3.0	.309	.164	.049	.296	.158	.048	.271	.147	.045	.248	.136	.042	.227	.126	.039	
4.0	.276	.143	.042	.264	.138	.041	.241	.128	.038	.220	.118	.036	.201	.109	.033	
5.0	.249	.127	.037	.238	.122	.036	.218	.113	.033	.199	.105	.031	.181	.097	.029	
6.0	.227	.114	.033	.217	.110	.032	.199	.102	.030	.181	.094	.028	.164	.087	.026	
7.0	.209	.103	.029	.200	.100	.028	.182	.092	.027	.166	.085	.025	.151	.078	.023	
8.0	.193	.094	.027	.185	.091	.026	.169	.084	.024	.154	.078	.022	.139	.072	.021	
9.0	.180	.087	.024	.172	.084	.023	.157	.078	.022	.143	.072	.021	.130	.066	.019	
10.0	.168	.080	.022	.160	.077	.022	.147	.072	.020	.134	.066	.019	.121	.061	.018	

pcc	80%			70%			50%			30%			10%			0	
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
pfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)										
0.0	.407	.407	.407	.348	.348	.348	.237	.237	.237	.136	.136	.136	.044	.044	.044		
1.0	.406	.374	.345	.347	.321	.297	.237	.221	.205	.137	.128	.119	.044	.041	.039		
2.0	.400	.351	.311	.342	.302	.268	.235	.209	.187	.135	.122	.110	.043	.039	.036		
3.0	.393	.335	.290	.337	.289	.251	.231	.201	.176	.134	.117	.104	.043	.038	.034		
4.0	.385	.323	.276	.331	.279	.240	.227	.195	.169	.132	.114	.100	.042	.037	.033		
5.0	.378	.314	.267	.324	.272	.232	.223	.190	.164	.129	.111	.097	.042	.036	.032		
6.0	.370	.306	.260	.318	.265	.227	.220	.186	.160	.127	.109	.095	.041	.036	.032		
7.0	.363	.300	.256	.312	.260	.223	.216	.182	.158	.125	.107	.094	.041	.035	.031		
8.0	.356	.295	.252	.307	.255	.220	.212	.179	.156	.123	.106	.093	.040	.035	.031		
9.0	.350	.290	.249	.302	.252	.217	.209	.177	.154	.122	.104	.092	.039	.034	.031		
10.0	.344	.286	.247	.297	.248	.216	.206	.175	.153	.120	.103	.091	.039	.034	.030		

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-05-30

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

UGR(Unified Glare Rating) Table

Test:U:220.22V I:0.2011A P:40.717W PF:0.9194 Freq:50.00Hz Lamp Flux:2662.16x1 lm											
NAME: SB-D01A40WSZ					TYPE:			WEIGHT:			
SPEC.:4000K					DIM.:			SERIAL No.:			
MFR.: SNOWBALL					SUR.:800mm						
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	Viewed crosswise					Viewed endwise					
x = 2H y = 2H	12.3	13.6	12.9	14.2	15.0	12.0	13.3	12.6	13.9	14.7	
	3H	15.0	16.2	15.7	16.9	17.7	14.7	15.9	15.3	16.6	17.4
	4H	16.6	17.7	17.2	18.4	19.2	16.2	17.3	16.8	18.0	18.8
	6H	18.2	19.3	18.9	20.0	20.9	17.8	18.9	18.5	19.6	20.4
	8H	19.1	20.1	19.8	20.9	21.7	18.7	19.7	19.4	20.4	21.3
	12H	20.1	21.1	20.8	21.9	22.7	19.7	20.7	20.4	21.4	22.3
4H	2H	13.1	14.3	13.8	15.0	15.8	12.9	14.1	13.6	14.8	15.6
	3H	16.1	17.1	16.8	17.8	18.7	15.8	16.8	16.5	17.5	18.4
	4H	17.7	18.7	18.5	19.4	20.3	17.4	18.3	18.2	19.1	20.0
	6H	19.6	20.4	20.3	21.2	22.1	19.2	20.0	20.0	20.8	21.7
	8H	20.6	21.3	21.3	22.1	23.1	20.2	21.0	21.0	21.7	22.7
	12H	21.7	22.4	22.5	23.2	24.2	21.3	22.0	22.1	22.8	23.8
8H	4H	18.3	19.1	19.1	19.9	20.9	18.1	18.9	18.9	19.7	20.6
	6H	20.4	21.1	21.2	21.9	22.9	20.1	20.8	21.0	21.6	22.6
	8H	21.6	22.2	22.4	23.0	24.1	21.3	21.9	22.1	22.7	23.7
	12H	23.0	23.5	23.8	24.3	25.4	22.6	23.1	23.5	24.0	25.0
12H	4H	18.5	19.2	19.3	20.0	21.0	18.3	19.0	19.0	19.8	20.7
	6H	20.7	21.3	21.5	22.1	23.1	20.4	21.0	21.3	21.9	22.9
	8H	22.0	22.5	22.8	23.4	24.4	21.7	22.2	22.5	23.1	24.1
Variations with the observer position at spacings:											
S = 1.0H	+ 0.1 / - 0.1					+ 0.1 / - 0.1					
1.5H	+ 0.2 / - 0.3					+ 0.2 / - 0.3					
2.0H	+ 0.3 / - 0.4					+ 0.3 / - 0.4					

CIE Pub.117, 2662 lm Total Lamp Luminous Flux Corrected ($8\log(F/F_0) = 3.4$)
Area: 0.5 m²

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:XIAOMI
Test Date:2023-05-30

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:9.000m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:220.22V I:0.2011A P:40.717W PF:0.9194 Freq:50.00Hz Lamp Flux:2662.16x1 lm		
NAME: SB-D01A40WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:800mm	


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	42	29	21	40	28	21	38	27	20	13
0.80	51	37	28	49	36	28	45	34	27	18
1.00	58	44	35	56	43	35	51	43	33	23
1.25	65	52	42	62	50	41	57	46	39	28
1.50	71	57	48	67	55	47	61	51	44	31
2.00	78	66	57	74	63	55	67	58	51	37
2.50	83	72	63	79	69	61	71	63	56	41
3.00	87	77	69	83	74	66	74	67	61	45
4.00	92	84	76	88	80	73	79	72	67	49
5.00	96	88	82	91	84	78	81	76	71	52
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-05-30

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

ISOCANDELA DIAGRAM

Test:U:220.22V I:0.2011A P:40.717W PF:0.9194 Freq:50.00Hz Lamp Flux:2662.16x1 lm		
NAME: SB-D01A40WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:800mm	




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: XIAOMI
Test Date: 2023-05-30

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity: 65.0%
Test Distance: 9.000m [K=1.0000]
Remarks:

AAI Figure

Test:U:220.22V I:0.2011A P:40.717W PF:0.9194 Freq:50.00Hz Lamp Flux:2662.16x1 lm		
NAME: SB-D01A40WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:800mm	




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-05-30

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

ISOLUX DIAGRAM


Test:U:220.22V I:0.2011A P:40.717W PF:0.9194 Freq:50.00Hz Lamp Flux:2662.16x1 lm		
NAME: SB-D01A40WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:800mm	



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: XIAOMI
 Test Date: 2023-05-30

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity: 65.0%
 Test Distance: 9.000m [K=1.0000]
 Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: XIAOMI
Test Date: 2023-05-30

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity: 65.0%
Test Distance: 9.000m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:220.22V I:0.2011A P:40.717W PF:0.9194 Freq:50.00Hz Lamp Flux:2662.16x1 lm		
NAME: SB-D01A40WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:800mm	

Table--1

UNIT: cd

C(DEG) γ (DEG)	0	22.5	45	67.5	90	112.5	135	157.5	180	202.5	225	247.5	270	292.5	315	337.5			
0	278	277	276	276	275	274	274	273	278	277	276	276	275	274	274	273			
5	287	286	285	283	283	282	283	283	287	288	286	285	282	282	282	282			
10	304	302	301	298	298	298	299	299	304	304	301	299	297	297	297	299			
15	321	319	317	313	312	312	314	315	320	319	315	312	310	310	311	314			
20	335	333	331	326	324	324	327	328	333	332	328	324	321	322	324	328			
25	348	346	343	337	334	334	338	340	346	344	339	335	331	332	335	340			
30	358	356	352	346	342	342	347	349	355	353	348	342	338	339	344	349			
35	365	364	359	352	347	347	352	356	362	359	353	347	343	344	350	356			
40	369	367	362	354	348	349	354	358	365	362	355	348	344	345	352	360			
45	368	367	361	353	346	347	353	357	364	361	354	346	342	344	351	359			
50	363	362	356	348	340	342	348	353	359	356	349	341	336	338	346	354			
55	354	354	348	340	331	332	339	344	351	347	340	332	327	328	338	345			
60	342	341	335	328	319	320	326	332	339	335	328	320	315	316	326	333			
65	327	326	320	313	304	305	311	318	324	320	313	305	300	302	311	319			
70	309	308	303	296	287	288	294	301	306	303	296	288	283	285	295	302			
75	289	288	283	277	268	270	275	282	287	283	278	270	265	267	276	283			
80	268	267	262	256	248	249	255	261	266	262	258	249	245	247	256	262			
85	238	239	233	228	219	220	223	231	236	230	227	217	215	217	228	233			
90	132	133	128	124	113	110	110	111	115	113	113	111	114	119	126	131			
95	189	178	164	146	141	138	153	174	187	184	158	139	138	143	157	178			
100	197	188	179	177	181	171	169	182	198	185	170	164	166	161	163	174			
105	190	183	176	170	171	163	168	177	189	176	160	150	160	152	168	174			
110	180	175	169	159	160	154	160	168	175	164	156	150	154	147	157	167			
115	171	165	158	131	148	122	149	154	165	155	151	121	146	116	144	160			
120	162	155	146	126	133	121	137	145	155	148	143	121	130	112	134	150			
125	152	145	124	116	121	113	112	137	148	140	118	113	117	103	106	132			
130	141	133	103	107	111	104	84.1	120	131	124	86.6	103	109	102	95.2	123			
135	110	92.6	103	94.4	99.9	97.0	94.5	75.8	102	76.4	91.9	95.9	96.4	91.0	99.6	87.0			
140	81.7	85.6	90.3	86.3	89.0	85.8	88.4	80.7	73.2	80.7	90.3	85.8	83.2	83.2	86.7	82.7			
145	70.4	76.8	76.1	75.6	71.7	65.1	64.0	62.5	63.5	62.0	65.1	60.4	72.7	73.7	75.0	74.9			
150	60.0	65.5	64.8	62.6	57.1	50.0	49.3	49.1	53.3	49.2	45.6	51.0	58.5	60.2	63.5	63.4			
155	51.5	54.2	53.6	49.3	45.5	38.6	36.9	40.2	46.1	40.5	36.4	39.3	45.6	47.9	51.2	53.1			
160	41.6	43.1	42.2	38.6	34.8	29.0	28.7	32.2	37.4	32.4	27.8	28.9	34.6	37.8	39.5	42.3			
165	39.1	40.6	37.1	29.8	26.5	24.8	27.0	33.5	39.1	34.8	28.9	25.7	26.1	29.8	34.4	40.0			
170	27.2	27.2	23.7	20.4	18.8	18.9	21.8	24.9	27.8	24.8	21.9	19.4	18.7	20.2	23.5	26.8			
175	14.9	14.6	13.5	13.0	12.7	13.0	13.9	15.5	16.4	15.1	14.3	13.0	12.4	13.2	14.4	14.9			
180	12.7	12.5	12.3	12.2	11.9	12.0	12.5	12.9	12.6	12.5	12.3	12.2	11.9	12.0	12.4	12.9			

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:XIAOMI
Test Date:2023-05-30

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:9.000m [K=1.0000]
Remarks: