


LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:219.96V I:0.7382A P:159.12W PF:0.9799 Freq:50.00Hz Lamp Flux:9433.1x1 lm		
NAME: SB-J01P160WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1800*900mm	

DATA OF LAMP		PHOTOMETRIC DATA Eff: 59.28 lm/W			
MODEL		I _{max} (cd)	1531	S/MH(C0/180)	1.38
NOMINAL POWER(W)		LOR(%)	100.0	S/MH(C90/270)	1.36
RATED VOLTAGE(V)	--	TOTAL FLUX(lm)	9433.1	η UP,DN(C0-180)	20.5,27.5
NOMINAL FLUX(lm)	9433.1	CIE CLASS	DIFFUSE	η UP,DN(C180-360)	22.9,29.2
LAMPS INSIDE	1	η up(%)	43.4	CIBSE SHR NOM	1.50
TEST VOLTAGE(V)	--	η down(%)	56.6	CIBSE SHR MAX	1.55



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOXIN
 Test Date:2023-06-25

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum,lamp
10	1492	1474	1431	1440	1450	1448	1462	1434	0- 10	138.1	138.1	1.46,1.46
20	1530	1461	1355	1434	1427	1434	1432	1429	10- 20	409.9	548.0	5.81,5.81
30	1415	1337	1250	1315	1355	1384	1330	1394	20- 30	645.6	1194	12.7,12.7
40	1196	1177	1139	1155	1194	1259	1199	1279	30- 40	802.0	1996	21.2,21.2
50	961.2	1004	984.0	988.0	967.7	1088	1054	1103	40- 50	860.8	2856	30.3,30.3
60	728.4	823.0	797.2	812.0	742.2	898.6	879.9	914.5	50- 60	827.4	3684	39.1,39.1
70	498.9	636.0	605.5	631.4	520.9	702.0	689.1	714.8	60- 70	719.2	4403	46.7,46.7
80	295.2	458.7	434.6	458.9	320.9	517.1	506.6	521.5	70- 80	563.2	4966	52.6,52.6
90	106.0	217.1	221.2	193.4	124.2	290.0	304.6	300.1	80- 90	376.1	5342	56.6,56.6
100	252.0	409.4	425.5	419.5	249.2	469.2	480.2	475.9	90-100	344.1	5686	60.3,60.3
110	356.2	482.6	556.9	493.2	337.1	555.6	633.0	566.1	100-110	481.4	6168	65.4,65.4
120	467.8	654.5	691.1	595.8	462.7	679.2	764.7	715.6	110-120	566.2	6734	71.4,71.4
130	582.5	751.6	814.2	587.3	573.6	767.2	911.2	847.0	120-130	614.9	7349	77.9,77.9
140	824.6	843.6	689.4	738.9	769.5	914.4	942.0	980.1	130-140	607.1	7956	84.3,84.3
150	973.8	997.9	855.5	986.9	974.1	1112	1039	1091	140-150	581.7	8538	90.5,90.5
160	1030	1033	1059	1066	1117	1108	1110	1165	150-160	485.0	9023	95.6,95.6
170	1060	1011	1114	1098	1101	1047	1126	1092	160-170	307.9	9331	98.9,98.9
180	1043	1013	1090	1052	1046	1016	1092	1063	170-180	102.5	9433	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

Conical surface Flux(90deg): 2424.7 lm

%lum = 25.7%

%lamp = 25.7%

Conical surface Flux(120deg): 3683.8 lm

%lum = 39.1%


%lamp = 39.1%

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOXIN
 Test Date:2023-06-25

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:219.96V I:0.7382A P:159.12W PF:0.9799 Freq:50.00Hz Lamp Flux:9433.1x1 lm		
NAME: SB-J01P160WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1800*900mm	




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:XIAOXIN
Test Date:2023-06-25

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:9.000m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:219.96V I:0.7382A P:159.12W PF:0.9799 Freq:50.00Hz Lamp Flux:9433.1x1 lm		
NAME: SB-J01P160WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1800*900mm	

ρ_{cc}	80%			70%			50%			30%			10%			0
ρ_w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρ_{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Coefficients of Utilization(CU)															
0.0	1.09	1.09	1.09	1.01	1.01	1.01	.87	.87	.87	.74	.74	.74	.62	.62	.62	.57
1.0	.92	.88	.84	.86	.82	.78	.74	.71	.68	.63	.60	.58	.52	.51	.49	.44
2.0	.80	.73	.67	.74	.68	.63	.64	.59	.55	.54	.50	.47	.45	.42	.40	.36
3.0	.69	.61	.55	.65	.57	.52	.56	.50	.45	.47	.43	.39	.39	.36	.33	.29
4.0	.61	.53	.46	.57	.49	.43	.49	.43	.38	.42	.37	.33	.35	.31	.28	.25
5.0	.54	.46	.39	.51	.43	.37	.44	.37	.33	.37	.32	.28	.31	.27	.24	.21
6.0	.49	.40	.34	.45	.37	.32	.39	.33	.28	.33	.28	.25	.28	.24	.21	.18
7.0	.44	.35	.29	.41	.33	.28	.35	.29	.25	.30	.25	.22	.26	.22	.19	.16
8.0	.40	.31	.26	.37	.30	.24	.32	.26	.22	.28	.23	.19	.23	.19	.17	.14
9.0	.36	.28	.23	.34	.27	.22	.29	.24	.19	.25	.21	.17	.22	.18	.15	.13
10.0	.33	.26	.20	.31	.24	.19	.27	.21	.17	.23	.19	.15	.20	.16	.13	.11



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOXIN
 Test Date:2023-06-25

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

WEC AND CCEC

Test:U:219.96V I:0.7382A P:159.12W PF:0.9799 Freq:50.00Hz Lamp Flux:9433.1x1 lm		
NAME: SB-J01P160WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1800*900mm	

pcc	80%			70%			50%			30%			10%			0	
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
pfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)										
0.0																	
1.0	.330	.188	.059	.310	.177	.056	.272	.156	.050	.237	.137	.044	.205	.119	.038		
2.0	.294	.161	.049	.276	.152	.047	.241	.134	.042	.209	.117	.037	.180	.102	.032		
3.0	.266	.141	.042	.249	.133	.040	.218	.118	.036	.188	.103	.032	.161	.089	.028		
4.0	.242	.126	.037	.227	.119	.035	.198	.105	.031	.171	.092	.028	.146	.079	.024		
5.0	.222	.113	.033	.208	.107	.031	.182	.095	.028	.157	.083	.025	.134	.071	.021		
6.0	.205	.103	.029	.192	.097	.028	.168	.086	.025	.145	.075	.022	.123	.065	.019		
7.0	.190	.094	.027	.178	.089	.025	.155	.079	.023	.134	.069	.020	.114	.059	.017		
8.0	.177	.087	.024	.166	.082	.023	.145	.072	.021	.125	.063	.018	.107	.055	.016		
9.0	.166	.080	.022	.155	.076	.021	.136	.067	.019	.117	.059	.017	.100	.051	.015		
10.0	.155	.074	.021	.146	.070	.020	.128	.062	.018	.110	.055	.016	.094	.047	.014		

pcc	80%			70%			50%			30%			10%			0	
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
pfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)										
0.0	.521	.521	.521	.445	.445	.445	.304	.304	.304	.175	.175	.175	.056	.056	.056		
1.0	.515	.489	.466	.441	.420	.401	.301	.289	.277	.173	.167	.161	.056	.054	.052		
2.0	.508	.467	.433	.435	.402	.374	.298	.278	.261	.172	.162	.153	.055	.052	.050		
3.0	.501	.451	.412	.429	.389	.357	.295	.271	.251	.170	.158	.148	.055	.051	.048		
4.0	.494	.439	.398	.424	.380	.346	.291	.265	.243	.169	.155	.144	.054	.050	.047		
5.0	.487	.430	.388	.418	.372	.338	.288	.260	.238	.167	.153	.141	.054	.050	.047		
6.0	.480	.423	.381	.413	.366	.332	.285	.256	.235	.165	.151	.140	.053	.049	.046		
7.0	.474	.416	.376	.408	.361	.328	.282	.253	.232	.164	.149	.138	.053	.049	.046		
8.0	.468	.411	.372	.403	.357	.325	.279	.250	.230	.162	.148	.137	.052	.048	.045		
9.0	.462	.407	.369	.398	.353	.322	.276	.248	.229	.161	.147	.136	.052	.048	.045		
10.0	.457	.403	.367	.394	.350	.320	.273	.246	.227	.159	.145	.136	.052	.048	.045		

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOXIN
 Test Date:2023-06-25

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

UGR(Unified Glare Rating) Table

Test:U:219.96V I:0.7382A P:159.12W PF:0.9799 Freq:50.00Hz Lamp Flux:9433.1x1 lm										
NAME: SB-J01P160WSZ					TYPE:			WEIGHT:		
SPEC.:4000K					DIM.:			SERIAL No.:		
MFR.: SNOWBALL					SUR.:1800*900mm					
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
x = 2H y = 2H	9.8	10.9	10.6	11.7	12.7	9.8	10.9	10.6	11.7	12.7
3H	11.5	12.5	12.3	13.3	14.3	11.8	12.8	12.7	13.6	14.7
4H	12.3	13.2	13.2	14.1	15.1	12.9	13.8	13.7	14.6	15.7
6H	13.1	13.9	13.9	14.8	15.9	14.0	14.8	14.9	15.7	16.8
8H	13.4	14.2	14.3	15.1	16.2	14.6	15.4	15.5	16.3	17.4
12H	13.8	14.6	14.7	15.4	16.6	15.3	16.1	16.2	17.0	18.1
4H 2H	10.5	11.4	11.3	12.2	13.3	10.5	11.4	11.3	12.2	13.3
3H	12.5	13.2	13.3	14.1	15.2	12.7	13.5	13.6	14.4	15.5
4H	13.5	14.2	14.4	15.1	16.2	13.9	14.6	14.8	15.5	16.6
6H	14.4	15.0	15.3	16.0	17.1	15.2	15.8	16.1	16.7	17.9
8H	14.9	15.5	15.8	16.4	17.6	15.9	16.5	16.8	17.4	18.6
12H	15.3	15.9	16.3	16.8	18.0	16.7	17.3	17.7	18.2	19.4
8H 4H	14.0	14.6	14.9	15.5	16.7	14.4	14.9	15.3	15.9	17.0
6H	15.3	15.8	16.2	16.7	17.9	15.9	16.4	16.9	17.3	18.6
8H	15.9	16.4	16.9	17.3	18.5	16.8	17.2	17.8	18.2	19.4
12H	16.6	17.0	17.6	17.9	19.2	17.8	18.2	18.8	19.2	20.4
12H 4H	14.1	14.6	15.0	15.6	16.8	14.4	14.9	15.4	15.9	17.1
6H	15.5	15.9	16.5	16.9	18.1	16.1	16.5	17.1	17.5	18.7
8H	16.3	16.7	17.3	17.6	18.9	17.1	17.5	18.1	18.4	19.7
Variations with the observer position at spacings:										
S = 1.0H	+ 0.1 / - 0.2					+ 0.1 / - 0.1				
1.5H	+ 0.2 / - 0.3					+ 0.2 / - 0.3				
2.0H	+ 0.2 / - 0.4					+ 0.2 / - 0.4				

CIE Pub.117, 9433 lm Total Lamp Luminous Flux Corrected ($8\log(F/F_0) = 7.8$)
Area: 1.62 m²

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:XIAOXIN
Test Date:2023-06-25

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:9.000m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:219.96V I:0.7382A P:159.12W PF:0.9799 Freq:50.00Hz Lamp Flux:9433.1x1 lm		
NAME: SB-J01P160WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1800*900mm	


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	43	31	25	41	30	24	37	28	23	15
0.80	52	40	32	49	38	31	44	35	29	20
1.00	60	48	40	57	45	38	50	43	35	24
1.25	67	55	47	63	52	45	55	47	41	28
1.50	72	60	52	68	57	50	59	51	45	31
2.00	79	69	61	74	65	58	65	58	52	35
2.50	84	74	67	78	70	63	68	62	57	38
3.00	88	79	72	82	74	68	71	65	60	40
4.00	92	85	79	86	80	74	74	70	65	43
5.00	95	89	83	89	83	78	76	72	69	45
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOXIN
 Test Date:2023-06-25

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

ISOCANDELA DIAGRAM

Test:U:219.96V I:0.7382A P:159.12W PF:0.9799 Freq:50.00Hz Lamp Flux:9433.1x1 lm		
NAME: SB-J01P160WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1800*900mm	




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:XIAOXIN
Test Date:2023-06-25

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:9.000m [K=1.0000]
Remarks:

AAI Figure

Test:U:219.96V I:0.7382A P:159.12W PF:0.9799 Freq:50.00Hz Lamp Flux:9433.1x1 lm		
NAME: SB-J01P160WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1800*900mm	

Flux out:3762 lm




Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: XIAOXIN
 Test Date: 2023-06-25

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity: 65.0%
 Test Distance: 9.000m [K=1.0000]
 Remarks:

ISOLUX DIAGRAM


Test:U:219.96V I:0.7382A P:159.12W PF:0.9799 Freq:50.00Hz Lamp Flux:9433.1x1 lm		
NAME: SB-J01P160WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1800*900mm	



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: XIAOXIN
 Test Date: 2023-06-25

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity: 65.0%
 Test Distance: 9.000m [K=1.0000]
 Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: XIAOXIN
Test Date: 2023-06-25

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity: 65.0%
Test Distance: 9.000m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:219.96V I:0.7382A P:159.12W PF:0.9799 Freq:50.00Hz Lamp Flux:9433.1x1 lm		
NAME: SB-J01P160WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1800*900mm	

Table--1

UNIT: cd

C(DEG) γ (DEG)	0	22.5	45	67.5	90	112.5	135	157.5	180	202.5	225	247.5	270	292.5	315	337.5			
0	1450	1449	1451	1447	1448	1442	1427	1416	1450	1449	1451	1447	1448	1442	1427	1416			
5	1466	1465	1466	1452	1449	1445	1437	1433	1443	1440	1443	1446	1451	1443	1421	1406			
10	1492	1487	1474	1441	1431	1434	1440	1458	1450	1437	1448	1456	1462	1455	1434	1408			
15	1516	1511	1472	1417	1397	1410	1439	1477	1445	1440	1448	1443	1455	1453	1435	1419			
20	1530	1516	1461	1386	1355	1376	1434	1480	1427	1441	1434	1412	1432	1429	1429	1430			
25	1498	1469	1409	1350	1304	1339	1389	1437	1398	1420	1410	1368	1389	1386	1412	1419			
30	1415	1406	1337	1294	1250	1282	1315	1364	1355	1392	1384	1319	1330	1343	1394	1396			
35	1310	1322	1258	1219	1196	1203	1235	1283	1298	1324	1336	1270	1267	1296	1359	1336			
40	1196	1234	1177	1138	1139	1121	1155	1197	1194	1236	1259	1220	1199	1247	1279	1246			
45	1080	1129	1092	1055	1071	1038	1073	1101	1082	1141	1175	1148	1129	1186	1193	1150			
50	961	1023	1004	969	984	955	988	1001	968	1035	1088	1066	1054	1099	1103	1044			
55	844	915	915	880	892	868	902	901	853	929	996	977	971	1005	1010	936			
60	728	806	823	790	797	780	812	799	742	823	899	882	880	907	915	830			
65	611	697	729	699	700	689	721	698	631	720	799	786	785	806	815	722			
70	499	593	636	610	605	603	631	598	521	616	702	690	689	706	715	619			
75	393	495	546	525	516	519	544	502	419	513	606	597	595	610	617	516			
80	295	402	459	448	435	443	459	412	321	417	517	511	507	518	521	418			
85	206	307	368	368	360	364	368	319	229	328	428	426	427	434	433	328			
90	106	175	217	236	221	221	193	216	124	201	290	302	305	311	300	195			
95	188	269	333	330	348	343	363	294	182	299	403	396	396	395	388	305			
100	252	326	409	408	425	406	420	344	249	343	469	471	480	474	476	355			
105	309	417	466	463	488	457	462	431	310	412	511	537	558	546	548	431			
110	356	448	483	537	557	531	493	456	337	456	556	599	633	628	566	466			
115	405	520	586	588	626	583	584	527	393	546	624	663	696	674	643	541			
120	468	587	654	650	691	648	596	579	463	616	679	706	765	708	716	645			
125	520	635	704	722	751	678	576	622	514	672	729	768	847	795	788	704			
130	582	689	752	791	814	600	587	661	574	694	767	794	911	880	847	765			
135	649	745	796	847	780	648	612	743	630	755	809	853	944	944	911	829			
140	825	836	844	890	689	684	739	854	770	888	914	909	942	1003	980	936			
145	920	913	907	882	694	736	880	948	872	1001	1032	974	967	1029	1047	1017			
150	974	995	998	890	855	883	987	999	974	1067	1112	1069	1039	1098	1091	1078			
155	1007	1055	1028	882	884	1004	1043	1026	1077	1121	1130	1111	1056	1076	1154	1133			
160	1030	1087	1033	853	1059	1056	1066	1057	1117	1142	1108	1123	1110	1073	1165	1176			
165	1057	1083	1031	968	1091	1088	1091	1068	1110	1122	1074	1127	1125	1100	1132	1167			
170	1060	1047	1011	1051	1114	1106	1098	1053	1101	1079	1047	1134	1126	1127	1092	1121			
175	1044	1012	1002	1091	1103	1104	1066	1020	1074	1024	1029	1128	1114	1125	1061	1073			
180	1043	1007	1013	1113	1090	1102	1052	1032	1046	1005	1016	1110	1092	1100	1063	1033			

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:XIAOXIN
Test Date:2023-06-25

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:9.000m [K=1.0000]
Remarks: