


LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:220.20V I:0.3739A P:80.243W PF:0.9745 Freq:50.00Hz Lamp Flux:4985.19x1 lm		
NAME: SB-J01P80WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:800*400mm	

DATA OF LAMP		PHOTOMETRIC DATA Eff: 62.13 lm/W			
MODEL		I _{max} (cd)	915.6	S/MH(C0/180)	1.19
NOMINAL POWER(W)		LOR(%)	100.0	S/MH(C90/270)	1.21
RATED VOLTAGE(V)	--	TOTAL FLUX(lm)	4985.2	η UP,DN(C0-180)	22.3,28.1
NOMINAL FLUX(lm)	4985.19	CIE CLASS	DIFFUSE	η UP,DN(C180-360)	21.3,28.3
LAMPS INSIDE	1	η up(%)	43.6	CIBSE SHR NOM	1.25
TEST VOLTAGE(V)	--	η down(%)	56.4	CIBSE SHR MAX	1.35



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-06-24

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum,lamp
10	888.1	907.3	910.9	894.3	877.2	877.4	887.1	880.1	0- 10	85.61	85.61	1.72,1.72
20	825.7	853.6	834.2	835.1	809.6	820.0	823.8	829.0	10- 20	243.8	329.4	6.61,6.61
30	726.6	749.4	722.4	731.7	718.7	725.6	728.0	737.2	20- 30	360.4	689.8	13.8,13.8
40	618.3	637.7	617.3	626.5	618.8	630.1	632.9	636.6	30- 40	426.0	1116	22.4,22.4
50	501.4	530.3	519.3	524.9	503.2	533.9	541.1	539.8	40- 50	447.0	1563	31.3,31.3
60	380.8	428.6	412.0	423.8	388.2	438.5	429.9	443.9	50- 60	425.0	1988	39.9,39.9
70	272.0	328.3	311.5	327.1	277.0	338.5	322.0	339.7	60- 70	366.3	2354	47.2,47.2
80	175.0	233.9	208.2	233.4	175.5	242.7	224.6	242.6	70- 80	284.6	2639	52.9,52.9
90	66.02	103.3	98.57	126.3	70.43	112.6	104.4	125.2	80- 90	174.6	2813	56.4,56.4
100	159.2	199.5	197.7	203.3	168.0	184.7	149.2	175.3	90-100	148.0	2961	59.4,59.4
110	250.7	275.2	262.3	280.9	251.7	272.5	245.5	272.9	100-110	230.3	3192	64,64
120	352.3	311.0	349.6	322.8	349.9	318.1	345.5	309.9	110-120	297.2	3489	70,70
130	371.7	429.5	446.2	438.7	366.8	404.5	433.2	412.0	120-130	329.2	3818	76.6,76.6
140	450.0	508.8	535.2	465.1	456.9	415.3	501.6	487.4	130-140	343.9	4162	83.5,83.5
150	519.2	579.6	614.9	481.8	528.4	440.6	508.9	545.0	140-150	313.6	4476	89.8,89.8
160	656.8	655.5	606.0	548.1	666.7	514.1	553.9	638.3	150-160	256.1	4732	94.9,94.9
170	754.1	740.7	634.7	681.5	755.4	686.6	603.2	728.9	160-170	184.2	4916	98.6,98.6
180	785.0	745.4	752.6	719.7	786.0	746.7	753.8	719.5	170-180	69.33	4985	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

Conical surface Flux(90deg): 1339.4 lm

%lum = 26.9%

%lamp = 26.9%

Conical surface Flux(120deg): 1987.8 lm

%lum = 39.9%


%lamp = 39.9%

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-06-24

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:220.20V I:0.3739A P:80.243W PF:0.9745 Freq:50.00Hz Lamp Flux:4985.19x1 lm		
NAME: SB-J01P80WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:800*400mm	




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:XIAOMI
Test Date:2023-06-24

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:9.000m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:220.20V I:0.3739A P:80.243W PF:0.9745 Freq:50.00Hz Lamp Flux:4985.19x1 lm		
NAME: SB-J01P80WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:800*400mm	

ρ_{cc}	80%			70%			50%			30%			10%			0
ρ_w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρ_{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Coefficients of Utilization(CU)															
0.0	1.09	1.09	1.09	1.01	1.01	1.01	.87	.87	.87	.74	.74	.74	.62	.62	.62	.56
1.0	.93	.88	.84	.86	.82	.79	.74	.71	.68	.63	.61	.59	.53	.51	.50	.45
2.0	.80	.73	.68	.75	.69	.64	.64	.60	.56	.54	.51	.48	.45	.43	.41	.36
3.0	.70	.62	.56	.65	.58	.52	.56	.51	.46	.48	.43	.40	.40	.37	.34	.30
4.0	.62	.53	.47	.58	.50	.44	.50	.44	.39	.42	.38	.34	.35	.32	.29	.25
5.0	.55	.46	.40	.51	.44	.38	.44	.38	.33	.38	.33	.29	.32	.28	.25	.22
6.0	.49	.41	.35	.46	.38	.33	.40	.34	.29	.34	.29	.25	.29	.25	.22	.19
7.0	.44	.36	.30	.42	.34	.29	.36	.30	.26	.31	.26	.22	.26	.22	.19	.17
8.0	.40	.32	.27	.38	.30	.25	.33	.27	.23	.28	.23	.20	.24	.20	.17	.15
9.0	.37	.29	.24	.34	.27	.23	.30	.24	.20	.26	.21	.18	.22	.18	.16	.13
10.0	.34	.26	.21	.32	.25	.20	.28	.22	.18	.24	.19	.16	.21	.17	.14	.12



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-06-24

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

WEC AND CCEC

Test:U:220.20V I:0.3739A P:80.243W PF:0.9745 Freq:50.00Hz Lamp Flux:4985.19x1 lm		
NAME: SB-J01P80WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:800*400mm	

pcc	80%			70%			50%			30%			10%			0	
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
pfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)										
0.0																	
1.0	.322	.183	.058	.301	.172	.055	.264	.151	.048	.229	.132	.042	.196	.114	.037		
2.0	.289	.158	.049	.270	.149	.046	.236	.131	.041	.204	.114	.036	.174	.099	.031		
3.0	.262	.139	.042	.245	.131	.039	.213	.116	.035	.184	.101	.031	.157	.087	.027		
4.0	.239	.124	.036	.223	.117	.035	.194	.103	.031	.168	.090	.027	.143	.078	.024		
5.0	.219	.112	.032	.205	.105	.031	.179	.093	.027	.154	.081	.024	.131	.070	.021		
6.0	.203	.102	.029	.190	.096	.028	.165	.085	.025	.142	.074	.022	.121	.064	.019		
7.0	.188	.093	.026	.176	.088	.025	.153	.078	.022	.132	.068	.020	.112	.058	.017		
8.0	.175	.086	.024	.164	.081	.023	.143	.071	.020	.123	.062	.018	.105	.054	.016		
9.0	.164	.079	.022	.154	.075	.021	.134	.066	.019	.116	.058	.017	.098	.050	.014		
10.0	.154	.074	.020	.144	.070	.019	.126	.062	.017	.109	.054	.015	.092	.046	.013		

pcc	80%			70%			50%			30%			10%			0	
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
pfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)										
0.0	.522	.522	.522	.446	.446	.446	.305	.305	.305	.175	.175	.175	.056	.056	.056		
1.0	.516	.491	.468	.441	.421	.403	.302	.290	.279	.174	.168	.162	.056	.054	.052		
2.0	.509	.469	.435	.436	.404	.376	.299	.279	.262	.172	.162	.154	.055	.053	.050		
3.0	.502	.453	.414	.430	.391	.359	.295	.271	.252	.171	.159	.148	.055	.051	.049		
4.0	.494	.441	.400	.424	.381	.348	.292	.266	.245	.169	.156	.145	.054	.051	.048		
5.0	.488	.432	.390	.419	.373	.339	.288	.261	.240	.167	.153	.142	.054	.050	.047		
6.0	.481	.424	.383	.413	.367	.334	.285	.257	.236	.165	.151	.140	.053	.049	.046		
7.0	.475	.418	.378	.408	.362	.329	.282	.254	.233	.164	.150	.139	.053	.049	.046		
8.0	.469	.413	.374	.403	.358	.326	.279	.251	.231	.162	.148	.138	.053	.049	.046		
9.0	.463	.408	.371	.399	.354	.324	.276	.249	.230	.161	.147	.137	.052	.048	.045		
10.0	.458	.404	.369	.395	.351	.322	.274	.247	.228	.160	.146	.136	.052	.048	.045		

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-06-24

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

UGR(Unified Glare Rating) Table

Test:U:220.20V I:0.3739A P:80.243W PF:0.9745 Freq:50.00Hz Lamp Flux:4985.19x1 lm											
NAME: SB-J01P80WSZ					TYPE:			WEIGHT:			
SPEC.:4000K					DIM.:			SERIAL No.:			
MFR.: SNOWBALL					SUR.:800*400mm						
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H y = 2H	13.2	14.2	14.0	15.0	16.0	13.3	14.4	14.1	15.2	16.2	
	3H	15.0	15.9	15.8	16.7	17.8	15.3	16.2	16.1	17.1	18.1
	4H	15.8	16.7	16.7	17.6	18.6	16.3	17.2	17.1	18.0	19.1
	6H	16.7	17.5	17.6	18.4	19.5	17.3	18.2	18.2	19.0	20.1
	8H	17.1	17.9	18.0	18.8	19.9	17.7	18.5	18.6	19.4	20.5
	12H	17.6	18.4	18.5	19.2	20.4	18.2	18.9	19.0	19.8	20.9
4H	2H	13.9	14.7	14.7	15.6	16.6	14.0	14.8	14.8	15.7	16.7
	3H	15.9	16.7	16.8	17.5	18.6	16.2	16.9	17.0	17.8	18.9
	4H	17.0	17.6	17.9	18.5	19.7	17.3	18.0	18.2	18.9	20.1
	6H	18.0	18.6	18.9	19.5	20.7	18.6	19.2	19.5	20.1	21.2
	8H	18.5	19.1	19.5	20.0	21.2	19.0	19.6	20.0	20.5	21.7
	12H	19.1	19.6	20.0	20.6	21.8	19.6	20.1	20.5	21.0	22.2
8H	4H	17.5	18.0	18.4	18.9	20.1	17.8	18.3	18.7	19.2	20.4
	6H	18.8	19.3	19.8	20.2	21.4	19.3	19.7	20.2	20.7	21.9
	8H	19.5	19.9	20.5	20.9	22.1	19.9	20.3	20.9	21.3	22.5
	12H	20.3	20.6	21.3	21.6	22.9	20.6	20.9	21.6	21.9	23.2
12H	4H	17.5	18.0	18.5	19.0	20.2	17.8	18.3	18.8	19.3	20.5
	6H	19.0	19.4	20.0	20.4	21.6	19.4	19.8	20.4	20.8	22.0
	8H	19.8	20.2	20.8	21.2	22.4	20.2	20.5	21.1	21.5	22.7
Variations with the observer position at spacings:											
S = 1.0H	+ 0.1 / - 0.2					+ 0.1 / - 0.1					
1.5H	+ 0.2 / - 0.3					+ 0.2 / - 0.3					
2.0H	+ 0.2 / - 0.4					+ 0.1 / - 0.4					

CIE Pub.117, 4985 lm Total Lamp Luminous Flux Corrected ($8\log(F/F_0) = 5.6$)
Area: 0.32 m2

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:XIAOMI
Test Date:2023-06-24

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:9.000m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:220.20V I:0.3739A P:80.243W PF:0.9745 Freq:50.00Hz Lamp Flux:4985.19x1 lm		
NAME: SB-J01P80WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:800*400mm	


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	44	32	26	42	31	25	38	29	24	16
0.80	53	41	34	50	39	32	45	36	30	21
1.00	61	49	41	57	46	39	51	44	36	25
1.25	68	56	48	64	53	46	56	48	42	29
1.50	73	61	53	68	58	51	60	52	46	32
2.00	80	70	62	75	66	59	65	58	53	36
2.50	84	75	68	79	71	64	68	62	57	38
3.00	88	80	73	82	75	69	71	66	61	41
4.00	93	85	80	86	80	75	75	70	66	44
5.00	95	89	84	89	84	79	77	73	69	46
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-06-24

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

ISOCANDELA DIAGRAM

Test:U:220.20V I:0.3739A P:80.243W PF:0.9745 Freq:50.00Hz Lamp Flux:4985.19x1 lm		
NAME: SB-J01P80WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:800*400mm	




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:XIAOMI
Test Date:2023-06-24

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:9.000m [K=1.0000]
Remarks:

AAI Figure

Test:U:220.20V I:0.3739A P:80.243W PF:0.9745 Freq:50.00Hz Lamp Flux:4985.19x1 lm		
NAME: SB-J01P80WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:800*400mm	




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-06-24

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

ISOLUX DIAGRAM


Test:U:220.20V I:0.3739A P:80.243W PF:0.9745 Freq:50.00Hz Lamp Flux:4985.19x1 lm		
NAME: SB-J01P80WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:800*400mm	



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-06-24

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: XIAOMI
Test Date: 2023-06-24

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity: 65.0%
Test Distance: 9.000m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:220.20V I:0.3739A P:80.243W PF:0.9745 Freq:50.00Hz Lamp Flux:4985.19x1 lm		
NAME: SB-J01P80WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:800*400mm	

Table--1

UNIT: cd

C(DEC) γ (DEC)	0	22.5	45	67.5	90	112.5	135	157.5	180	202.5	225	247.5	270	292.5	315	337.5			
0	907	907	907	905	903	902	900	897	907	907	907	905	903	902	900	897			
5	899	907	910	914	915	913	906	897	900	895	895	896	894	891	888	886			
10	888	901	907	909	911	907	894	881	877	871	877	886	887	882	880	875			
15	863	883	891	882	881	879	874	857	848	845	854	858	863	859	863	853			
20	826	850	854	840	834	832	835	822	810	808	820	819	824	827	829	820			
25	782	810	804	788	780	781	784	784	765	766	775	776	775	782	786	782			
30	727	760	749	733	722	725	732	740	719	721	726	729	728	733	737	732			
35	672	703	695	677	668	669	678	691	669	675	677	679	679	682	687	682			
40	618	647	638	628	617	620	627	639	619	624	630	631	633	632	637	628			
45	563	595	582	580	569	573	576	586	561	572	583	584	588	587	590	575			
50	501	537	530	532	519	524	525	528	503	520	534	538	541	540	540	522			
55	439	480	479	482	467	474	475	471	445	470	486	490	488	491	492	469			
60	381	424	429	429	412	426	424	416	388	418	438	437	430	438	444	418			
65	326	370	378	377	362	377	375	365	331	366	388	385	374	383	391	365			
70	272	316	328	328	312	327	327	313	277	317	338	334	322	331	340	315			
75	222	266	281	281	264	278	279	259	224	269	290	283	271	282	291	267			
80	175	217	234	234	208	230	233	211	175	218	243	234	225	235	243	218			
85	133	163	169	161	142	159	168	157	131	163	177	164	150	164	185	166			
90	66.0	87.9	103	104	98.6	115	126	99.9	70.4	78.4	113	102	104	115	125	98.1			
95	120	134	153	154	142	155	167	147	131	139	128	114	106	120	124	124			
100	159	182	200	200	198	201	203	191	168	189	185	166	149	170	175	177			
105	204	222	230	222	230	226	244	231	207	229	221	199	199	199	218	218			
110	251	267	275	209	262	212	281	272	252	261	272	205	245	219	273	257			
115	299	308	319	283	305	287	329	313	299	298	319	290	295	288	321	296			
120	352	349	311	336	350	340	323	355	350	339	318	344	345	338	310	328			
125	393	335	382	386	395	390	390	341	374	322	360	381	392	380	367	328			
130	372	364	430	439	446	440	439	378	367	348	405	429	433	422	412	361			
135	413	421	467	484	498	489	470	425	429	412	420	463	470	459	452	414			
140	450	457	509	518	535	519	465	430	457	412	415	467	502	501	487	450			
145	486	501	544	564	581	512	476	441	489	426	417	470	540	550	519	484			
150	519	547	580	615	615	514	482	473	528	465	441	482	509	577	545	534			
155	551	588	622	644	570	534	504	487	562	492	449	503	524	615	593	567			
160	657	664	655	658	606	564	548	578	667	598	514	526	554	625	638	656			
165	711	709	697	668	629	622	613	666	714	684	598	585	584	625	682	707			
170	754	743	741	661	635	707	682	704	755	727	687	699	603	638	729	740			
175	777	767	741	684	735	733	703	732	779	758	729	741	739	664	727	763			
180	785	769	745	726	753	720	720	753	786	768	747	725	754	719	720	752			

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:XIAOMI
Test Date:2023-06-24

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:9.000m [K=1.0000]
Remarks: