


LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:220.24V I:0.4431A P:95.905W PF:0.9828 Freq:50.00Hz Lamp Flux:6297.77x1 lm		
NAME: SB-J01P100WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1000*500mm	

DATA OF LAMP		PHOTOMETRIC DATA Eff: 65.67 lm/W			
MODEL		I _{max} (cd)	1166	S/MH(C0/180)	1.18
NOMINAL POWER(W)		LOR(%)	100.0	S/MH(C90/270)	1.14
RATED VOLTAGE(V)	--	TOTAL FLUX(lm)	6297.8	η UP,DN(C0-180)	23.5,28.4
NOMINAL FLUX(lm)	6297.77	CIE CLASS	DIFFUSE	η UP,DN(C180-360)	21.1,27.0
LAMPS INSIDE	1	η up(%)	44.7	CIBSE SHR NOM	1.25
TEST VOLTAGE(V)	--	η down(%)	55.3	CIBSE SHR MAX	1.35



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-06-24

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum,lamp
10	1117	1159	1157	1144	1114	1090	1083	1091	0- 10	107.8	107.8	1.71,1.71
20	1036	1093	1073	1073	1028	1000	981.4	1005	10- 20	305.7	413.6	6.57,6.57
30	911.1	969.4	933.7	944.4	898.6	874.4	858.4	885.7	20- 30	449.8	863.4	13.7,13.7
40	767.6	825.5	795.7	800.6	751.9	747.7	747.3	761.8	30- 40	528.7	1392	22.1,22.1
50	619.1	687.2	663.2	662.3	603.4	632.6	635.3	648.6	40- 50	549.8	1942	30.8,30.8
60	474.7	558.0	528.1	531.2	453.7	520.0	513.4	540.5	50- 60	522.4	2464	39.1,39.1
70	343.3	432.3	398.2	404.8	317.1	399.5	386.0	421.9	60- 70	451.4	2916	46.3,46.3
80	221.0	311.7	285.5	287.4	194.4	281.1	276.1	302.8	70- 80	351.1	3267	51.9,51.9
90	98.24	120.9	135.7	152.1	78.46	125.4	134.8	166.7	80- 90	217.9	3485	55.3,55.3
100	191.9	275.4	285.5	283.2	204.8	233.3	230.3	224.5	90-100	196.0	3681	58.4,58.4
110	305.7	384.3	380.1	388.6	318.4	347.4	316.9	324.0	100-110	307.7	3988	63.3,63.3
120	431.7	480.1	497.7	484.7	393.4	420.3	435.7	410.5	110-120	386.5	4375	69.5,69.5
130	480.7	598.7	621.6	568.2	483.4	501.1	532.3	515.8	120-130	434.7	4809	76.4,76.4
140	576.7	691.6	715.7	562.9	561.8	515.5	620.7	596.2	130-140	438.0	5248	83.3,83.3
150	660.0	771.0	651.3	608.8	642.3	564.2	616.4	691.1	140-150	395.1	5643	89.6,89.6
160	834.7	840.0	719.0	781.5	832.0	703.9	704.3	782.3	150-160	331.8	5974	94.9,94.9
170	934.1	918.9	923.5	914.3	927.2	850.1	903.0	882.1	160-170	236.3	6211	98.6,98.6
180	963.8	900.5	894.2	928.8	965.4	901.6	901.2	929.5	170-180	87.08	6298	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

Conical surface Flux(90deg): 1667.5 lm

%lum = 26.5%

%lamp = 26.5%

Conical surface Flux(120deg): 2464.2 lm

%lum = 39.1%


%lamp = 39.1%

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-06-24

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:220.24V I:0.4431A P:95.905W PF:0.9828 Freq:50.00Hz Lamp Flux:6297.77x1 lm		
NAME: SB-J01P100WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1000*500mm	




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:XIAOMI
Test Date:2023-06-24

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:9.000m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:220.24V I:0.4431A P:95.905W PF:0.9828 Freq:50.00Hz Lamp Flux:6297.77x1 lm		
NAME: SB-J01P100WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1000*500mm	

ρ_{cc}	80%			70%			50%			30%			10%			0
ρ_w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρ_{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Coefficients of Utilization(CU)															
0.0	1.08	1.08	1.08	1.01	1.01	1.01	.86	.86	.86	.73	.73	.73	.61	.61	.61	.55
1.0	.93	.88	.84	.86	.82	.79	.74	.71	.68	.62	.60	.58	.52	.50	.49	.44
2.0	.80	.73	.68	.74	.68	.63	.64	.59	.55	.54	.50	.47	.45	.42	.40	.36
3.0	.70	.62	.56	.65	.58	.52	.56	.50	.46	.47	.43	.40	.39	.36	.34	.30
4.0	.62	.53	.47	.57	.50	.44	.49	.43	.39	.42	.37	.34	.35	.31	.29	.25
5.0	.55	.46	.40	.51	.43	.38	.44	.38	.33	.37	.33	.29	.31	.28	.25	.22
6.0	.49	.41	.35	.46	.38	.33	.40	.33	.29	.34	.29	.25	.28	.25	.22	.19
7.0	.44	.36	.30	.41	.34	.29	.36	.30	.25	.31	.26	.22	.26	.22	.19	.17
8.0	.40	.32	.27	.38	.30	.25	.33	.27	.23	.28	.23	.20	.24	.20	.17	.15
9.0	.37	.29	.24	.34	.27	.23	.30	.24	.20	.26	.21	.18	.22	.18	.15	.13
10.0	.34	.26	.21	.32	.25	.20	.28	.22	.18	.24	.19	.16	.20	.17	.14	.12



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-06-24

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

WEC AND CCEC

Test:U:220.24V I:0.4431A P:95.905W PF:0.9828 Freq:50.00Hz Lamp Flux:6297.77x1 lm		
NAME: SB-J01P100WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1000*500mm	

pcc	80%			70%			50%			30%			10%			0	
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
pfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)										
0.0																	
1.0	.320	.182	.058	.300	.171	.054	.261	.150	.048	.226	.130	.042	.193	.112	.036		
2.0	.287	.157	.048	.269	.148	.046	.233	.130	.040	.201	.113	.035	.171	.097	.031		
3.0	.260	.139	.042	.243	.130	.039	.211	.115	.035	.182	.100	.031	.154	.085	.026		
4.0	.238	.124	.036	.222	.116	.034	.193	.102	.031	.165	.089	.027	.140	.076	.023		
5.0	.218	.111	.032	.204	.105	.031	.177	.092	.027	.152	.080	.024	.128	.069	.021		
6.0	.202	.101	.029	.189	.095	.027	.164	.084	.024	.140	.073	.021	.119	.062	.019		
7.0	.187	.093	.026	.175	.087	.025	.152	.077	.022	.130	.067	.019	.110	.057	.017		
8.0	.175	.085	.024	.163	.080	.023	.142	.071	.020	.122	.062	.018	.103	.053	.015		
9.0	.163	.079	.022	.153	.075	.021	.133	.066	.019	.114	.057	.016	.096	.049	.014		
10.0	.153	.074	.020	.144	.069	.019	.125	.061	.017	.107	.053	.015	.091	.046	.013		

pcc	80%			70%			50%			30%			10%			0	
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
pfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)										
0.0	.531	.531	.531	.454	.454	.454	.310	.310	.310	.178	.178	.178	.057	.057	.057		
1.0	.524	.499	.477	.449	.428	.410	.307	.295	.284	.177	.171	.165	.057	.055	.053		
2.0	.517	.477	.444	.443	.411	.384	.304	.284	.268	.175	.165	.157	.056	.053	.051		
3.0	.510	.462	.423	.437	.398	.367	.300	.277	.257	.173	.162	.152	.056	.052	.050		
4.0	.503	.450	.409	.432	.388	.355	.297	.271	.250	.172	.159	.148	.055	.052	.049		
5.0	.496	.440	.399	.426	.381	.347	.293	.266	.245	.170	.156	.145	.055	.051	.048		
6.0	.489	.433	.392	.421	.375	.341	.290	.262	.241	.168	.154	.144	.054	.050	.047		
7.0	.483	.426	.387	.416	.370	.337	.287	.259	.239	.167	.153	.142	.054	.050	.047		
8.0	.477	.421	.383	.411	.365	.334	.284	.256	.237	.165	.151	.141	.053	.050	.047		
9.0	.471	.417	.380	.406	.362	.331	.281	.254	.235	.164	.150	.140	.053	.049	.046		
10.0	.466	.413	.377	.402	.358	.329	.279	.252	.234	.163	.149	.140	.053	.049	.046		

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-06-24

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

UGR(Unified Glare Rating) Table

Test:U:220.24V I:0.4431A P:95.905W PF:0.9828 Freq:50.00Hz Lamp Flux:6297.77x1 lm											
NAME: SB-J01P100WSZ					TYPE:			WEIGHT:			
SPEC.:4000K					DIM.:			SERIAL No.:			
MFR.: SNOWBALL					SUR.:1000*500mm						
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H y = 2H	12.5	13.5	13.3	14.3	15.3	12.7	13.8	13.5	14.6	15.6	
	3H	14.2	15.2	15.1	16.0	17.1	14.7	15.6	15.5	16.5	17.5
	4H	15.1	16.0	16.0	16.8	17.9	15.7	16.6	16.6	17.5	18.5
	6H	16.0	16.8	16.8	17.7	18.8	16.8	17.6	17.7	18.5	19.6
	8H	16.4	17.2	17.3	18.1	19.2	17.3	18.0	18.1	18.9	20.0
	12H	16.9	17.6	17.7	18.5	19.6	17.7	18.4	18.5	19.3	20.4
4H	2H	13.2	14.0	14.0	14.9	16.0	13.4	14.2	14.2	15.1	16.2
	3H	15.2	16.0	16.1	16.9	18.0	15.6	16.3	16.5	17.2	18.3
	4H	16.3	16.9	17.2	17.9	19.0	16.8	17.5	17.7	18.4	19.5
	6H	17.3	17.9	18.2	18.8	20.0	18.1	18.6	19.0	19.6	20.8
	8H	17.8	18.4	18.8	19.3	20.5	18.6	19.2	19.5	20.1	21.3
	12H	18.4	18.9	19.3	19.8	21.1	19.1	19.6	20.0	20.5	21.8
8H	4H	16.8	17.4	17.7	18.3	19.5	17.2	17.8	18.2	18.7	19.9
	6H	18.2	18.6	19.1	19.6	20.8	18.8	19.2	19.7	20.2	21.4
	8H	18.9	19.3	19.8	20.2	21.5	19.5	19.9	20.5	20.9	22.1
	12H	19.6	20.0	20.6	21.0	22.2	20.2	20.5	21.2	21.5	22.8
12H	4H	16.9	17.4	17.9	18.4	19.6	17.3	17.8	18.2	18.7	19.9
	6H	18.4	18.8	19.4	19.8	21.0	19.0	19.4	19.9	20.3	21.6
	8H	19.2	19.6	20.2	20.5	21.8	19.8	20.1	20.8	21.1	22.4
Variations with the observer position at spacings:											
S = 1.0H	+ 0.1 / - 0.2					+ 0.1 / - 0.1					
1.5H	+ 0.2 / - 0.3					+ 0.2 / - 0.2					
2.0H	+ 0.2 / - 0.4					+ 0.2 / - 0.4					

CIE Pub.117, 6298 lm Total Lamp Luminous Flux Corrected ($8\log(F/F_0) = 6.4$)
Area: 0.5 m²

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:XIAOMI
Test Date:2023-06-24

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:9.000m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:220.24V I:0.4431A P:95.905W PF:0.9828 Freq:50.00Hz Lamp Flux:6297.77x1 lm		
NAME: SB-J01P100WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1000*500mm	


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	44	32	26	42	31	25	38	29	23	16
0.80	53	41	33	50	39	32	45	36	30	20
1.00	60	48	41	57	46	39	51	43	36	25
1.25	67	56	48	63	53	46	56	47	42	28
1.50	72	61	53	68	58	51	59	52	46	31
2.00	80	69	62	74	65	59	65	58	53	35
2.50	84	75	68	78	70	64	68	62	57	38
3.00	88	79	73	82	74	68	71	65	61	40
4.00	92	85	79	86	80	75	74	69	66	43
5.00	95	89	84	88	83	79	76	72	69	45
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-06-24

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

ISOCANDELA DIAGRAM

Test:U:220.24V I:0.4431A P:95.905W PF:0.9828 Freq:50.00Hz Lamp Flux:6297.77x1 lm		
NAME: SB-J01P100WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1000*500mm	




C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-06-24

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

AAI Figure

Test:U:220.24V I:0.4431A P:95.905W PF:0.9828 Freq:50.00Hz Lamp Flux:6297.77x1 lm		
NAME: SB-J01P100WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1000*500mm	




Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: XIAOMI
 Test Date: 2023-06-24

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity: 65.0%
 Test Distance: 9.000m [K=1.0000]
 Remarks:

ISOLUX DIAGRAM


Test:U:220.24V I:0.4431A P:95.905W PF:0.9828 Freq:50.00Hz Lamp Flux:6297.77x1 lm		
NAME: SB-J01P100WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1000*500mm	



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: XIAOMI
 Test Date: 2023-06-24

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity: 65.0%
 Test Distance: 9.000m [K=1.0000]
 Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: XIAOMI
Test Date: 2023-06-24

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity: 65.0%
Test Distance: 9.000m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:220.24V I:0.4431A P:95.905W PF:0.9828 Freq:50.00Hz Lamp Flux:6297.77x1 lm		
NAME: SB-J01P100WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1000*500mm	

Table--1

UNIT: cd

C(°) γ (°)	0	22.5	45	67.5	90	112.5	135	157.5	180	202.5	225	247.5	270	292.5	315	337.5			
0	1141	1140	1139	1136	1134	1132	1130	1128	1141	1140	1139	1136	1134	1132	1130	1128			
5	1138	1157	1165	1165	1163	1159	1152	1140	1134	1120	1115	1111	1110	1110	1113	1114			
10	1117	1149	1159	1162	1157	1152	1144	1130	1114	1094	1090	1085	1083	1086	1091	1093			
15	1084	1123	1135	1135	1125	1124	1118	1103	1079	1057	1052	1042	1038	1045	1054	1059			
20	1036	1082	1093	1085	1073	1073	1073	1057	1028	1006	1000	987	981	990	1005	1013			
25	977	1028	1035	1024	1007	1010	1013	1000	966	946	939	926	920	930	947	957			
30	911	965	969	955	934	940	944	934	899	879	874	867	858	871	886	894			
35	840	896	898	884	861	870	873	862	827	811	809	810	803	814	823	828			
40	768	822	825	813	796	801	801	789	752	742	748	753	747	757	762	762			
45	694	750	756	746	730	735	730	716	676	674	688	697	692	702	704	695			
50	619	676	687	684	663	671	662	643	603	607	633	641	635	648	649	631			
55	547	611	622	622	595	610	597	575	528	542	578	581	578	591	598	571			
60	475	539	558	558	528	543	531	503	454	478	520	521	513	530	541	509			
65	410	472	494	494	463	477	467	438	386	419	460	461	450	469	482	449			
70	343	405	432	431	398	415	405	373	317	359	399	399	386	407	422	393			
75	280	340	371	371	340	355	345	310	254	299	339	338	326	345	362	333			
80	221	278	312	312	285	295	287	250	194	238	281	284	276	292	303	273			
85	166	214	227	212	180	194	197	182	143	172	222	200	190	216	247	209			
90	98.2	125	121	125	136	145	152	122	78.5	83.6	125	128	135	156	167	132			
95	143	171	217	201	190	203	235	192	153	170	168	171	145	162	165	150			
100	192	238	275	281	285	280	283	255	205	231	233	232	230	232	224	214			
105	247	291	314	323	328	321	328	310	260	284	300	266	275	278	270	267			
110	306	354	384	359	380	359	389	369	318	335	347	316	317	299	324	317			
115	366	412	410	415	435	417	401	422	380	372	354	375	380	367	360	353			
120	432	427	480	488	498	490	485	409	393	359	420	437	436	431	411	363			
125	422	474	546	553	562	553	544	473	434	420	480	483	473	473	472	406			
130	481	542	599	615	622	612	568	525	483	463	501	536	532	529	516	466			
135	532	576	648	662	665	632	555	523	519	471	494	559	577	572	559	503			
140	577	621	692	714	716	616	563	543	562	495	516	555	621	624	596	562			
145	620	675	734	772	762	601	589	579	602	543	542	570	612	666	637	618			
150	660	724	771	803	651	625	609	624	642	588	564	605	616	707	691	666			
155	766	810	803	801	693	666	682	760	767	682	635	633	659	735	733	756			
160	835	870	840	795	719	744	781	848	832	778	704	709	704	743	782	820			
165	892	919	888	783	744	864	889	890	883	830	806	820	745	768	845	877			
170	934	951	919	811	924	943	914	927	927	879	850	880	903	825	882	919			
175	952	953	909	865	948	925	928	943	955	910	873	922	907	886	897	939			
180	964	938	901	904	894	949	929	941	965	937	902	903	901	949	930	940			

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:XIAOMI
Test Date:2023-06-24

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:9.000m [K=1.0000]
Remarks: