



Page: 1 of 4

# Vail 5 Tier F Black / H Black with Gold

### PRODUCT DESCRIPTION

Each Vail light pod is roughly 3.5" dia. and weighs just over 1 lb, It is machined from a block of solid aluminum. It has an indirect and direct lighting component. Available with 1 to 16 light pods. Custom configurations, over 6,500 color finishes and suspension cable lengths are available. 3000K/3500K/4000K selectable by switch or RGB, Tunable White / Dimmable. Ships assembled.

#### **FEATURES**

- 5-years limited warranty.
- · Direct and Indirect illumination.
- Ships Assembled.
- Fixture delivered lumens per watt ratio 22 LPW.
- Customize color temperatures and adjust lumen output, RGB, Tunable White available.
- Driver concealed within the canopy or in the remote box.
- White and White with Gold color finish as standard, custom color is available.

#### **SPECIFICATIONS**

- 90+ CRI.
- Input: 100-277V, 50/60Hz
- UL listed, suitable for dry Location
- Built in color temperature selectable. Select from 3000K/3500K/4000K.
- 1-10V dimming standard, ELV,TRIAC dimming available.
- Suspended on 10' adjustable height cables, custom cable lengths available
- Solid aluminum housing, each individual Vail size 3.35" x 3.48", 1.15 lbs.

#### PARTS PACKED WITH STANDARD FIXTURE

- Plastic Anchors, Screws, Wire Connectors
- CCT Selector Switch







SB-P05F Black with Ring





**MODEL INFORMATION:** 



Page: 2 of 4

Example: SB-P05F40WSB

Products Series	Vail housing Finishes	Wattage	Options	RGB/CCT Select Only	Canopy Finishes	Aircraft Cable
*SB-P05	*F=Black(standard)	*40W=40W	*S=1-10V dimming, CRI 90 3000K/3500K/4000K Color Selectable (Standard), 4000K factory color default set.	T=3000K-4000K Tunable White	*B=Black Jack	*Blank=10' foot 120" (Standard)
	H=Black with Gold (standard)		L=ELV / Triac dimming with 3000K/3500K/4000K Color Selectable	R=RGB	S=Platinum Silver	5'=5 foot 60" 15'=15 foot 180"
			D=DMX Z=ZigBee		W=Gloss White	20'=20 foot 240" 25'=25 foot 300"
	Full Color Name or RAL number for Custom Colors, select from Color Collections		DMX for RGB and Tunable White, control by Wall Switch or DMX control system.  ZigBee for RGB and CCT tunable / dimmable using remote, DMX, App and Google Alexa.	Do not select this column if selected "S"	Full Color Name or RAL number for Custom Colors, select from Color Collections	

## **LUMEN OUTPUT**

Model Number	Number of lights	Wattage	Kevin	Lumen
SB-P05F/H	5	40W	3000K/3500K/4000K selectable	905 lm

## STANDARD COLOR FINISHES



F: Black



H: Black with Gold

In addition to our standard colors, we offer more than 6,500 <u>finishes and colors</u> for your luminaire. We can match your paint sample or any RAL finish. Add texture and originality to create a perfect match





Page: 3 of 4

## **EMERGENCY BATTRY OPTIONS**

## **SEE SPEC**

PICTURE	MODEL NUMBER	DESCRIPTION
	SB-EBP/5W/B	Factory installed Remote Emergency Battery Pack 5W 90 minutes
	SB-EBP/10.7W/B	Factory installed Remote Emergency Battery Pack 10.7W 90 minutes
	SB-EBP/17W/B	Factory installed Remote Emergency Battery Pack 17W 90 minutes


## **RGB/TUNABLE WHITE SMART CONTROL**

**SEE SPEC AND VIDEO** 

# **Get Smart**

Using Amazon Echo, Echo Dot, or any Alexa-enabled device allows you to turn your luminaire on and off, dim the light and change light color to Red, Green, Blue or White independently by using voice command or Smart phone app, DMX, Handheld remote or wall control.

**DIMENSION & WEIGHT:** Canopy Size for ZigBee & DMX: 15.75" x 2.76"







Page: 4 of 4

# **PHOTOMETRIC:** For 1 Light only

