


LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:220.18V I:0.1025A P:21.210W PF:0.9397 Freq:50.00Hz Lamp Flux:1333.58x1 lm		
NAME: SB-D01A20WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:400mm	

DATA OF LAMP		PHOTOMETRIC DATA Eff: 62.88 lm/W			
MODEL		I _{max} (cd)	193.0	S/MH(C0/180)	1.62
NOMINAL POWER(W)		LOR(%)	100.0	S/MH(C90/270)	1.61
RATED VOLTAGE(V)	--	TOTAL FLUX(lm)	1333.6	η UP,DN(C0-180)	12.4,37.3
NOMINAL FLUX(lm)	1333.58	CIE CLASS	SEMI-D.	η UP,DN(C180-360)	12.6,37.7
LAMPS INSIDE	1	η up(%)	25.0	CIBSE SHR NOM	1.75
TEST VOLTAGE(V)	--	η down(%)	75.0	CIBSE SHR MAX	1.75



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-05-31

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum,lamp
10	188.4	188.6	187.4	186.8	189.1	189.0	188.4	186.7	0- 10	17.69	17.69	1.33,1.33
20	189.9	191.2	190.1	189.8	192.2	191.3	190.8	188.5	10- 20	53.72	71.41	5.35,5.35
30	189.5	192.1	191.6	191.1	193.0	191.4	190.7	188.5	20- 30	88.29	159.7	12.12
40	187.3	189.7	189.5	188.2	190.1	188.9	188.4	186.3	30- 40	119.3	279.0	20.9,20.9
50	180.3	182.5	182.1	180.7	182.6	181.7	181.9	180.0	40- 50	143.5	422.5	31.7,31.7
60	168.6	170.3	170.5	168.6	170.6	169.8	170.5	168.9	50- 60	157.7	580.2	43.5,43.5
70	152.9	153.8	154.0	152.3	154.6	154.2	155.4	153.9	60- 70	160.7	740.9	55.6,55.6
80	130.1	128.7	128.3	127.2	131.4	133.1	135.2	133.7	70- 80	151.8	892.6	66.9,66.9
90	65.51	64.09	63.15	62.21	63.84	69.29	73.44	71.88	80- 90	107.2	999.8	75.75
100	89.97	65.28	61.07	63.59	89.54	65.76	63.65	67.05	90-100	71.70	1072	80.3,80.3
110	88.49	63.21	60.27	62.23	89.05	65.90	56.49	67.16	100-110	73.95	1145	85.9,85.9
120	76.80	56.12	52.01	55.19	77.67	52.39	56.45	59.96	110-120	64.77	1210	90.8,90.8
130	65.16	48.83	42.46	48.58	65.91	45.53	46.08	47.84	120-130	50.07	1260	94.5,94.5
140	53.89	41.06	33.03	40.87	53.51	40.88	36.57	37.22	130-140	35.52	1296	97.2,97.2
150	39.68	27.49	24.10	23.27	31.52	28.21	27.19	26.39	140-150	22.29	1318	98.8,98.8
160	18.29	20.61	15.53	18.74	17.54	19.45	16.70	18.51	150-160	10.93	1329	99.7,99.7
170	9.757	9.133	6.457	7.119	9.509	10.04	9.823	7.387	160-170	3.881	1333	100,100
180	4.394	4.449	4.443	4.269	4.388	4.439	4.434	4.264	170-180	0.6602	1334	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

Conical surface Flux(90deg): 348.33 lm

%lum = 26.1%

%lamp = 26.1%

Conical surface Flux(120deg): 580.17 lm

%lum = 43.5%


%lamp = 43.5%

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-05-31

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:220.18V I:0.1025A P:21.210W PF:0.9397 Freq:50.00Hz Lamp Flux:1333.58x1 lm		
NAME: SB-D01A20WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:400mm	




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:XIAOMI
Test Date:2023-05-31

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:9.000m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:220.18V I:0.1025A P:21.210W PF:0.9397 Freq:50.00Hz Lamp Flux:1333.58x1 lm		
NAME: SB-D01A20WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:400mm	

ρ_{cc}	80%			70%			50%			30%			10%			0
ρ_w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρ_{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Coefficients of Utilization(CU)															
0.0	1.13	1.13	1.13	1.08	1.08	1.08	.97	.97	.97	.88	.88	.88	.79	.79	.79	.75
1.0	.93	.87	.82	.88	.83	.78	.79	.75	.71	.71	.68	.65	.63	.61	.58	.54
2.0	.78	.70	.63	.74	.67	.61	.67	.61	.55	.59	.55	.50	.53	.49	.46	.42
3.0	.67	.58	.51	.64	.55	.48	.57	.50	.44	.51	.45	.40	.45	.41	.37	.33
4.0	.59	.49	.41	.56	.47	.40	.50	.42	.37	.45	.38	.33	.40	.34	.30	.27
5.0	.52	.42	.35	.49	.40	.33	.44	.37	.31	.39	.33	.28	.35	.30	.26	.23
6.0	.46	.36	.30	.44	.35	.28	.39	.32	.26	.35	.29	.24	.31	.26	.22	.19
7.0	.41	.32	.26	.39	.31	.25	.35	.28	.23	.32	.26	.21	.28	.23	.19	.17
8.0	.37	.29	.22	.36	.27	.22	.32	.25	.20	.29	.23	.18	.26	.21	.17	.14
9.0	.34	.26	.20	.32	.25	.19	.29	.23	.18	.27	.21	.16	.24	.19	.15	.13
10.0	.31	.23	.18	.30	.22	.17	.27	.20	.16	.25	.19	.15	.22	.17	.13	.11



WEC AND CCEC

Test:U:220.18V I:0.1025A P:21.210W PF:0.9397 Freq:50.00Hz Lamp Flux:1333.58x1 lm		
NAME: SB-D01A20WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:400mm	

pcc	80%			70%			50%			30%			10%			0	
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
pfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)										
0.0																	
1.0	.407	.231	.073	.392	.223	.071	.364	.209	.067	.338	.195	.063	.315	.182	.059		
2.0	.349	.191	.059	.336	.185	.057	.310	.173	.054	.287	.161	.050	.265	.150	.047		
3.0	.308	.164	.049	.296	.158	.048	.273	.148	.045	.251	.138	.042	.231	.128	.040		
4.0	.275	.143	.042	.264	.138	.041	.243	.129	.039	.224	.120	.036	.206	.112	.034		
5.0	.249	.127	.037	.239	.123	.036	.220	.114	.034	.202	.107	.032	.185	.099	.030		
6.0	.227	.114	.033	.218	.110	.032	.201	.103	.030	.184	.096	.028	.169	.089	.026		
7.0	.209	.103	.029	.200	.100	.028	.184	.093	.027	.169	.087	.025	.155	.081	.024		
8.0	.193	.094	.027	.185	.091	.026	.171	.085	.024	.157	.079	.023	.144	.074	.021		
9.0	.180	.087	.024	.172	.084	.024	.159	.078	.022	.146	.073	.021	.134	.068	.020		
10.0	.168	.080	.022	.161	.078	.022	.148	.073	.020	.136	.068	.019	.125	.063	.018		

pcc	80%			70%			50%			30%			10%			0	
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
pfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)										
0.0	.381	.381	.381	.326	.326	.326	.222	.222	.222	.128	.128	.128	.041	.041	.041		
1.0	.379	.348	.319	.325	.298	.275	.222	.205	.190	.128	.119	.110	.041	.038	.036		
2.0	.373	.325	.285	.320	.280	.246	.219	.194	.172	.126	.113	.101	.041	.036	.033		
3.0	.366	.309	.264	.314	.267	.228	.216	.185	.160	.125	.108	.094	.040	.035	.031		
4.0	.359	.297	.250	.308	.257	.217	.212	.179	.153	.122	.105	.090	.039	.034	.030		
5.0	.351	.287	.241	.302	.249	.209	.208	.174	.148	.120	.102	.088	.039	.033	.029		
6.0	.344	.280	.234	.295	.242	.204	.204	.170	.144	.118	.100	.086	.038	.033	.028		
7.0	.336	.273	.229	.289	.237	.200	.200	.166	.141	.116	.098	.084	.038	.032	.028		
8.0	.330	.268	.225	.284	.232	.196	.196	.163	.139	.114	.096	.083	.037	.032	.027		
9.0	.323	.263	.222	.278	.228	.194	.193	.161	.138	.112	.095	.082	.036	.031	.027		
10.0	.317	.259	.220	.274	.225	.192	.190	.158	.137	.111	.094	.081	.036	.031	.027		

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-05-31

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

UGR(Unified Glare Rating) Table

Test:U:220.18V I:0.1025A P:21.210W PF:0.9397 Freq:50.00Hz Lamp Flux:1333.58x1 lm											
NAME: SB-D01A20WSZ					TYPE:			WEIGHT:			
SPEC.:4000K					DIM.:			SERIAL No.:			
MFR.: SNOWBALL					SUR.:400mm						
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H y = 2H	14.7	16.0	15.3	16.7	17.4	14.8	16.1	15.4	16.7	17.4	
	3H	17.5	18.7	18.1	19.3	20.1	17.5	18.8	18.2	19.4	
	4H	19.0	20.2	19.6	20.8	21.6	19.0	20.2	19.7	20.9	
	6H	20.6	21.7	21.3	22.4	23.2	20.6	21.7	21.3	22.4	
	8H	21.4	22.5	22.1	23.2	24.0	21.4	22.4	22.0	23.1	
	12H	22.2	23.2	22.9	23.9	24.7	22.0	23.0	22.7	23.7	
4H	2H	15.6	16.8	16.3	17.4	18.2	15.7	16.8	16.3	17.5	
	3H	18.5	19.6	19.2	20.3	21.1	18.6	19.6	19.3	20.3	
	4H	20.2	21.1	20.9	21.9	22.7	20.3	21.2	21.0	21.9	
	6H	22.0	22.8	22.7	23.6	24.4	22.0	22.9	22.7	23.6	
	8H	22.9	23.7	23.6	24.4	25.3	22.8	23.6	23.6	24.4	
	12H	23.7	24.5	24.5	25.2	26.1	23.6	24.3	24.3	25.1	
8H	4H	20.8	21.6	21.6	22.4	23.3	20.9	21.7	21.6	22.4	
	6H	22.9	23.5	23.6	24.3	25.2	22.9	23.6	23.7	24.3	
	8H	23.9	24.5	24.7	25.3	26.3	23.9	24.5	24.7	25.3	
	12H	24.9	25.5	25.7	26.3	27.3	24.8	25.3	25.6	26.1	
12H	4H	21.0	21.7	21.7	22.5	23.4	21.0	21.7	21.8	22.5	
	6H	23.1	23.7	23.9	24.5	25.5	23.1	23.7	23.9	24.5	
	8H	24.3	24.8	25.1	25.6	26.6	24.2	24.7	25.0	25.5	
Variations with the observer position at spacings:											
S = 1.0H	+ 0.1 / - 0.1					+ 0.1 / - 0.1					
1.5H	+ 0.2 / - 0.2					+ 0.2 / - 0.2					
2.0H	+ 0.2 / - 0.3					+ 0.2 / - 0.3					

CIE Pub.117, 1334 lm Total Lamp Luminous Flux Corrected ($8\log(F/F_0) = 1.0$)
Area: 0.125 m²

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:XIAOMI
Test Date:2023-05-31

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:9.000m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:220.18V I:0.1025A P:21.210W PF:0.9397 Freq:50.00Hz Lamp Flux:1333.58x1 lm		
NAME: SB-D01A20WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:400mm	


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	43	30	23	42	30	23	40	29	22	15
0.80	52	39	30	50	38	30	47	36	29	20
1.00	60	46	37	58	45	37	53	45	35	25
1.25	67	53	44	64	52	43	59	49	41	30
1.50	72	59	50	69	57	49	63	53	46	34
2.00	80	68	59	76	65	57	69	61	54	40
2.50	85	74	65	81	71	63	73	65	59	44
3.00	89	79	71	84	75	68	76	69	63	48
4.00	94	85	78	89	82	75	81	75	69	53
5.00	97	90	83	92	86	80	83	78	74	56
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-05-31

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

ISOCANDELA DIAGRAM

Test:U:220.18V I:0.1025A P:21.210W PF:0.9397 Freq:50.00Hz Lamp Flux:1333.58x1 lm		
NAME: SB-D01A20WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:400mm	




C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-05-31

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

AAI Figure

Test:U:220.18V I:0.1025A P:21.210W PF:0.9397 Freq:50.00Hz Lamp Flux:1333.58x1 lm		
NAME: SB-D01A20WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:400mm	

Flux out:966.3 lm




Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: XIAOMI
 Test Date: 2023-05-31

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity: 65.0%
 Test Distance: 9.000m [K=1.0000]
 Remarks:

ISOLUX DIAGRAM


Test:U:220.18V I:0.1025A P:21.210W PF:0.9397 Freq:50.00Hz Lamp Flux:1333.58x1 lm		
NAME: SB-D01A20WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:400mm	



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: XIAOMI
 Test Date: 2023-05-31

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity: 65.0%
 Test Distance: 9.000m [K=1.0000]
 Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: XIAOMI
Test Date: 2023-05-31

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity: 65.0%
Test Distance: 9.000m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:220.18V I:0.1025A P:21.210W PF:0.9397 Freq:50.00Hz Lamp Flux:1333.58x1 lm		
NAME: SB-D01A20WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:400mm	

Table--1

UNIT: cd

C(DEC) γ (DEC)	0	22.5	45	67.5	90	112.5	135	157.5	180	202.5	225	247.5	270	292.5	315	337.5			
0	180	179	179	179	179	178	178	178	180	179	179	179	179	178	178	178			
5	185	185	185	185	184	184	184	183	185	185	184	184	183	183	182	182			
10	188	189	189	188	187	187	187	187	189	189	189	189	188	188	187	186			
15	189	190	190	190	189	188	189	189	191	191	191	191	190	189	188	187			
20	190	191	191	191	190	190	190	190	192	192	191	191	191	190	189	187			
25	190	191	192	192	191	191	191	191	193	192	191	192	191	190	189	187			
30	190	191	192	192	192	191	191	191	193	192	191	191	191	190	189	187			
35	189	190	192	192	191	191	190	190	192	191	191	191	190	189	188	187			
40	187	189	190	190	189	189	188	188	190	189	189	189	188	188	186	185			
45	184	186	187	187	186	186	185	185	187	186	186	186	186	185	184	182			
50	180	182	183	183	182	181	181	180	183	182	182	182	182	181	180	179			
55	175	176	177	178	177	176	175	175	177	176	176	176	177	176	175	173			
60	169	169	170	171	170	170	169	168	171	170	170	170	171	170	169	167			
65	161	162	163	164	163	162	161	161	163	162	162	163	163	163	162	160			
70	153	153	154	155	154	153	152	153	155	154	154	154	155	155	154	152			
75	143	143	144	144	144	143	142	142	145	144	145	145	147	146	145	143			
80	130	130	129	130	128	128	127	129	131	131	133	134	135	134	134	131			
85	96.3	94.3	90.2	90.1	87.0	88.2	87.9	91.9	97.2	99.0	104	106	110	108	107	100			
90	65.5	64.7	64.1	63.9	63.1	62.6	62.2	62.4	63.8	64.9	69.3	70.6	73.4	72.1	71.9	66.8			
95	69.9	66.6	62.4	61.3	60.7	60.1	60.8	65.0	67.6	65.3	63.3	64.0	64.9	65.0	64.9	66.3			
100	90.0	77.5	65.3	61.5	61.1	60.5	63.6	77.0	89.5	76.2	65.8	64.2	63.7	64.5	67.1	75.5			
105	93.6	77.9	63.2	60.8	61.3	59.7	61.4	76.8	94.0	78.4	65.0	63.5	61.7	59.6	66.3	76.8			
110	88.5	76.5	63.2	59.1	60.3	58.3	62.2	75.5	89.1	76.3	65.9	60.9	56.5	58.2	67.2	75.0			
115	82.7	72.3	59.3	58.0	59.7	57.8	59.0	72.0	83.4	72.3	61.9	60.2	58.1	59.9	63.5	71.5			
120	76.8	67.3	56.1	53.1	52.0	53.3	55.2	67.2	77.7	64.0	52.4	54.8	56.4	52.2	60.0	67.2			
125	70.9	64.2	52.9	48.7	47.4	48.8	52.6	63.8	71.6	60.1	49.4	49.7	51.1	46.0	54.6	63.6			
130	65.2	61.0	48.8	39.1	42.5	38.7	48.6	60.3	65.9	58.3	45.5	40.6	46.1	39.2	47.8	60.3			
135	59.8	55.4	44.6	33.3	37.7	32.8	44.4	53.4	60.4	55.5	43.4	34.8	40.4	36.0	41.8	51.3			
140	53.9	49.8	41.1	33.2	33.0	33.1	40.9	46.9	53.5	50.4	40.9	32.5	36.6	35.7	37.2	49.9			
145	47.7	43.6	31.7	31.0	28.5	31.0	29.2	39.1	43.2	36.6	31.1	31.8	32.1	32.0	30.2	43.8			
150	39.7	31.7	27.5	27.7	24.1	26.5	23.3	27.1	31.5	29.6	28.2	29.2	27.2	25.7	26.4	32.5			
155	24.0	23.0	27.4	23.8	20.6	20.7	24.7	21.5	22.8	24.0	27.7	22.9	21.4	21.1	24.9	24.4			
160	18.3	19.9	20.6	18.6	15.5	16.4	18.7	17.1	17.5	18.4	19.5	18.4	16.7	17.0	18.5	19.1			
165	14.3	14.4	15.1	11.8	10.6	10.9	12.0	11.2	14.0	13.4	14.0	14.5	13.0	13.0	13.8	13.1			
170	9.76	9.79	9.13	7.47	6.46	6.91	7.12	7.09	9.51	8.95	10.0	10.0	9.82	9.18	7.39	8.92			
175	7.12	5.89	4.93	4.16	3.76	3.44	3.73	4.69	6.76	7.49	7.77	7.87	7.94	8.14	7.63	7.06			
180	4.39	4.41	4.45	4.52	4.44	4.21	4.27	4.02	4.39	4.41	4.44	4.51	4.43	4.21	4.26	3.94			

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:XIAOMI
Test Date:2023-05-31

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:9.000m [K=1.0000]
Remarks: