


LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:220.25V I:0.3302A P:70.155W PF:0.9647 Freq:50.00Hz Lamp Flux:5354.62x1 lm		
NAME: SB-D01A70WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1500mm	

DATA OF LAMP		PHOTOMETRIC DATA Eff: 76.33 lm/W			
MODEL		I _{max} (cd)	1029	S/MH(C0/180)	1.31
NOMINAL POWER(W)		LOR(%)	100.0	S/MH(C90/270)	1.30
RATED VOLTAGE(V)	--	TOTAL FLUX(lm)	5354.6	η UP,DN(C0-180)	12.7,37.1
NOMINAL FLUX(lm)	5354.62	CIE CLASS	SEMI-D.	η UP,DN(C180-360)	12.2,37.9
LAMPS INSIDE	1	η up(%)	25.0	CIBSE SHR NOM	1.50
TEST VOLTAGE(V)	--	η down(%)	75.0	CIBSE SHR MAX	1.55



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-06-02

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum,lamp
10	987.5	981.7	970.7	976.7	1009	1000	994.4	997.4	0- 10	96.02	96.02	1.79,1.79
20	924.8	919.9	911.0	916.8	948.4	942.3	929.3	929.2	10- 20	270.4	366.4	6.84,6.84
30	868.9	879.1	874.2	865.0	895.5	890.0	881.1	873.0	20- 30	417.0	783.4	14.6,14.6
40	803.4	823.9	822.8	796.7	832.2	823.0	821.1	810.7	30- 40	532.2	1316	24.6,24.6
50	719.8	742.7	744.3	706.8	749.7	735.4	742.1	729.1	40- 50	600.2	1916	35.8,35.8
60	622.2	645.0	646.7	604.5	650.7	635.9	646.7	636.4	50- 60	613.5	2529	47.2,47.2
70	519.3	539.3	541.0	501.4	548.5	533.7	549.9	538.8	60- 70	579.8	3109	58.1,58.1
80	420.6	436.8	439.2	403.4	445.5	436.1	453.1	442.6	70- 80	510.7	3620	67.6,67.6
90	181.2	265.4	314.4	311.2	223.1	179.1	287.2	321.5	80- 90	398.4	4018	75,75
100	251.1	284.2	322.9	283.3	278.0	269.0	291.1	262.2	90-100	301.0	4319	80.7,80.7
110	251.3	271.4	303.9	263.1	264.7	254.8	290.5	243.3	100-110	286.1	4605	86,86
120	216.5	242.2	269.4	229.9	245.3	227.2	271.5	222.4	110-120	250.5	4856	90.7,90.7
130	170.1	205.4	217.6	183.3	197.0	187.7	214.3	198.8	120-130	196.8	5052	94.4,94.4
140	140.9	166.6	169.0	138.0	156.8	151.6	155.6	155.8	130-140	134.3	5187	96.9,96.9
150	131.7	140.1	124.3	107.3	131.9	135.2	144.1	140.5	140-150	86.35	5273	98.5,98.5
160	98.36	95.83	81.05	72.19	100.7	104.0	121.5	111.0	150-160	54.27	5327	99.5,99.5
170	58.90	54.03	41.27	36.97	57.80	64.26	75.47	74.11	160-170	22.44	5350	99.9,99.9
180	42.62	43.53	44.86	43.41	42.43	43.34	44.70	43.30	170-180	4.748	5355	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

Conical surface Flux(90deg): 1610.6 lm

%lum = 30.1%

%lamp = 30.1%

Conical surface Flux(120deg): 2529.3 lm

%lum = 47.2%


%lamp = 47.2%

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-06-02

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:220.25V I:0.3302A P:70.155W PF:0.9647 Freq:50.00Hz Lamp Flux:5354.62x1 lm		
NAME: SB-D01A70WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1500mm	




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:XIAOMI
Test Date:2023-06-02

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:9.000m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:220.25V I:0.3302A P:70.155W PF:0.9647 Freq:50.00Hz Lamp Flux:5354.62x1 lm		
NAME: SB-D01A70WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1500mm	

ρ_{cc}	80%			70%			50%			30%			10%			0
ρ_w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρ_{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Coefficients of Utilization(CU)															
0.0	1.13	1.13	1.13	1.08	1.08	1.08	.97	.97	.97	.88	.88	.88	.79	.79	.79	.75
1.0	.94	.89	.84	.89	.84	.80	.80	.76	.73	.72	.69	.66	.64	.62	.60	.56
2.0	.80	.72	.66	.76	.69	.63	.68	.63	.58	.61	.57	.53	.55	.51	.48	.44
3.0	.69	.60	.53	.66	.58	.51	.59	.52	.47	.53	.48	.43	.47	.43	.39	.36
4.0	.61	.51	.44	.58	.49	.42	.52	.45	.39	.47	.41	.36	.42	.37	.33	.30
5.0	.54	.44	.37	.51	.42	.36	.46	.39	.33	.42	.35	.31	.37	.32	.28	.25
6.0	.48	.39	.32	.46	.37	.31	.41	.34	.29	.37	.31	.27	.34	.28	.24	.22
7.0	.43	.34	.28	.41	.33	.27	.37	.30	.25	.34	.28	.23	.31	.25	.21	.19
8.0	.39	.31	.25	.38	.29	.24	.34	.27	.22	.31	.25	.21	.28	.23	.19	.17
9.0	.36	.28	.22	.34	.26	.21	.31	.25	.20	.28	.23	.18	.26	.21	.17	.15
10.0	.33	.25	.20	.32	.24	.19	.29	.22	.18	.26	.21	.17	.24	.19	.15	.13



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-06-02

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

WEC AND CCEC

Test:U:220.25V I:0.3302A P:70.155W PF:0.9647 Freq:50.00Hz Lamp Flux:5354.62x1 lm		
NAME: SB-D01A70WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1500mm	

pcc	80%			70%			50%			30%			10%			0														
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0														
pfc	20%			20%			20%			20%			20%			0														
RCR	RCR:Room Cavity Ratio															Wall Exitance Coefficients(WEC)														
0.0																														
1.0	.386	.220	.070	.372	.212	.067	.344	.197	.063	.318	.184	.059	.295	.171	.055															
2.0	.333	.183	.056	.320	.176	.054	.295	.164	.051	.272	.152	.048	.250	.142	.045															
3.0	.296	.157	.047	.284	.152	.046	.261	.141	.043	.239	.131	.040	.220	.122	.038															
4.0	.266	.138	.041	.255	.133	.039	.234	.124	.037	.215	.115	.035	.197	.107	.033															
5.0	.241	.123	.036	.231	.119	.035	.212	.111	.033	.195	.103	.031	.178	.095	.029															
6.0	.221	.111	.032	.212	.107	.031	.194	.100	.029	.178	.093	.027	.163	.086	.025															
7.0	.204	.101	.029	.195	.097	.028	.179	.091	.026	.164	.084	.025	.150	.078	.023															
8.0	.189	.092	.026	.181	.089	.025	.166	.083	.024	.152	.077	.022	.139	.072	.021															
9.0	.176	.085	.024	.169	.082	.023	.155	.077	.022	.142	.071	.020	.130	.066	.019															
10.0	.164	.079	.022	.158	.076	.021	.145	.071	.020	.133	.066	.019	.122	.061	.018															

pcc	80%			70%			50%			30%			10%			0	
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
pfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)										
0.0	.381	.381	.381	.325	.325	.325	.222	.222	.222	.128	.128	.128	.041	.041	.041		
1.0	.377	.347	.320	.323	.298	.275	.221	.205	.190	.127	.119	.111	.041	.038	.036		
2.0	.371	.325	.286	.318	.280	.247	.218	.193	.172	.126	.113	.101	.040	.036	.033		
3.0	.363	.309	.265	.312	.266	.230	.214	.185	.161	.124	.108	.095	.040	.035	.031		
4.0	.356	.296	.251	.305	.256	.218	.210	.178	.153	.121	.105	.091	.039	.034	.030		
5.0	.348	.287	.241	.299	.248	.210	.206	.173	.148	.119	.102	.088	.038	.033	.029		
6.0	.341	.279	.234	.293	.241	.204	.202	.169	.144	.117	.099	.086	.038	.033	.028		
7.0	.334	.272	.229	.287	.236	.200	.198	.166	.142	.115	.098	.084	.037	.032	.028		
8.0	.327	.267	.225	.282	.231	.197	.195	.163	.139	.113	.096	.083	.037	.031	.027		
9.0	.321	.262	.222	.277	.228	.194	.192	.160	.138	.112	.094	.082	.036	.031	.027		
10.0	.315	.258	.220	.272	.224	.192	.189	.158	.136	.110	.093	.081	.036	.031	.027		

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-06-02

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

UGR(Unified Glare Rating) Table

Test:U:220.25V I:0.3302A P:70.155W PF:0.9647 Freq:50.00Hz Lamp Flux:5354.62x1 lm											
NAME: SB-D01A70WSZ					TYPE:			WEIGHT:			
SPEC.:4000K					DIM.:			SERIAL No.:			
MFR.: SNOWBALL					SUR.:1500mm						
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H y = 2H	10.0	11.3	10.6	11.9	12.6	10.2	11.5	10.8	12.1	12.8	
	3H	12.4	13.6	13.0	14.2	15.0	12.6	13.8	13.2	14.4	15.2
	4H	13.7	14.8	14.3	15.5	16.2	13.9	15.1	14.6	15.7	16.5
	6H	15.1	16.2	15.8	16.9	17.6	15.4	16.4	16.0	17.1	17.9
	8H	15.9	16.9	16.6	17.6	18.4	16.2	17.2	16.8	17.9	18.7
	12H	16.8	17.8	17.5	18.5	19.3	17.1	18.1	17.7	18.7	19.6
4H	2H	10.8	12.0	11.5	12.6	13.4	11.0	12.1	11.6	12.7	13.5
	3H	13.4	14.4	14.1	15.1	15.9	13.6	14.6	14.3	15.3	16.1
	4H	14.9	15.8	15.6	16.5	17.3	15.1	16.0	15.8	16.7	17.5
	6H	16.5	17.3	17.2	18.0	18.9	16.7	17.5	17.4	18.2	19.1
	8H	17.4	18.1	18.1	18.9	19.8	17.6	18.4	18.3	19.1	20.0
	12H	18.4	19.1	19.1	19.8	20.8	18.6	19.3	19.4	20.1	21.0
8H	4H	15.5	16.2	16.2	17.0	17.9	15.6	16.4	16.4	17.1	18.0
	6H	17.4	18.0	18.1	18.8	19.7	17.5	18.2	18.3	18.9	19.9
	8H	18.4	19.0	19.2	19.8	20.7	18.6	19.2	19.4	20.0	20.9
	12H	19.7	20.2	20.5	21.0	21.9	19.9	20.4	20.7	21.2	22.1
12H	4H	15.6	16.3	16.4	17.1	18.0	15.7	16.4	16.5	17.2	18.1
	6H	17.6	18.2	18.4	19.0	19.9	17.8	18.3	18.6	19.1	20.1
	8H	18.8	19.3	19.6	20.1	21.1	19.0	19.5	19.8	20.3	21.2
Variations with the observer position at spacings:											
S = 1.0H	+ 0.1 / - 0.1					+ 0.1 / - 0.1					
1.5H	+ 0.2 / - 0.3					+ 0.2 / - 0.3					
2.0H	+ 0.3 / - 0.4					+ 0.3 / - 0.4					

CIE Pub.117, 5355 lm Total Lamp Luminous Flux Corrected ($8\log(F/F_0) = 5.8$)
Area: 1.766 m²

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:XIAOMI
Test Date:2023-06-02

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:9.000m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:220.25V I:0.3302A P:70.155W PF:0.9647 Freq:50.00Hz Lamp Flux:5354.62x1 lm		
NAME: SB-D01A70WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1500mm	


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	45	33	26	44	32	25	42	31	25	18
0.80	54	41	33	52	40	33	49	38	31	23
1.00	62	49	40	60	47	40	55	47	38	29
1.25	69	56	47	66	54	46	61	51	44	33
1.50	74	62	53	71	60	51	65	56	49	37
2.00	81	70	62	78	68	60	71	63	56	43
2.50	86	76	67	82	73	65	75	67	61	47
3.00	90	80	73	86	77	70	78	71	65	50
4.00	95	87	80	90	83	77	82	76	71	55
5.00	98	91	85	93	87	81	84	79	75	57
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-06-02

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

ISOCANDELA DIAGRAM

Test:U:220.25V I:0.3302A P:70.155W PF:0.9647 Freq:50.00Hz Lamp Flux:5354.62x1 lm		
NAME: SB-D01A70WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1500mm	




C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-06-02

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

AAI Figure

Test:U:220.25V I:0.3302A P:70.155W PF:0.9647 Freq:50.00Hz Lamp Flux:5354.62x1 lm		
NAME: SB-D01A70WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1500mm	




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-06-02

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

ISOLUX DIAGRAM


Test:U:220.25V I:0.3302A P:70.155W PF:0.9647 Freq:50.00Hz Lamp Flux:5354.62x1 lm		
NAME: SB-D01A70WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1500mm	



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-06-02

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: XIAOMI
Test Date: 2023-06-02

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity: 65.0%
Test Distance: 9.000m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:220.25V I:0.3302A P:70.155W PF:0.9647 Freq:50.00Hz Lamp Flux:5354.62x1 lm		
NAME: SB-D01A70WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1500mm	

Table--1

UNIT: cd

C(DEC) γ (DEC)	0	22.5	45	67.5	90	112.5	135	157.5	180	202.5	225	247.5	270	292.5	315	337.5			
0	1027	1028	1026	1024	1022	1021	1021	1021	1027	1028	1026	1024	1022	1021	1021	1021			
5	1011	1012	1009	1005	1002	1002	1005	1010	1024	1024	1022	1021	1021	1024	1023	1013			
10	988	988	982	975	971	971	977	987	1009	1006	1000	997	994	997	997	990			
15	956	955	947	939	936	939	944	955	980	976	970	965	960	961	963	958			
20	925	925	920	914	911	913	917	925	948	947	942	936	929	928	929	926			
25	897	900	899	896	893	892	892	898	921	921	916	910	905	902	900	896			
30	869	875	879	879	874	870	865	870	895	894	890	884	881	878	873	867			
35	838	847	854	857	852	843	833	838	867	865	860	853	853	850	844	836			
40	803	814	824	828	823	810	797	801	832	830	823	818	821	819	811	800			
45	763	776	786	792	787	771	754	759	794	789	782	779	784	783	772	760			
50	720	732	743	751	744	727	707	712	750	743	735	735	742	742	729	717			
55	672	685	696	703	697	679	657	662	702	693	686	687	695	697	683	670			
60	622	636	645	653	647	631	605	614	651	640	636	636	647	649	636	621			
65	571	586	592	604	594	581	553	561	601	587	585	585	600	600	588	570			
70	519	534	539	550	541	529	501	509	549	536	534	534	550	550	539	521			
75	468	483	487	497	489	478	451	460	497	484	484	485	501	502	490	471			
80	421	433	437	446	439	429	403	411	446	436	436	438	453	455	443	426			
85	371	382	386	392	379	354	327	351	397	383	388	391	408	409	396	377			
90	181	201	265	247	314	325	311	256	223	236	179	220	287	332	321	261			
95	297	302	284	315	334	315	287	279	326	306	300	283	299	258	240	280			
100	251	253	284	306	323	305	283	257	278	278	269	264	291	281	262	245			
105	256	269	280	291	315	295	273	268	259	257	253	255	286	261	255	246			
110	251	267	271	281	304	281	263	264	265	248	255	256	291	254	243	240			
115	246	258	219	271	288	270	222	254	259	255	222	251	288	257	215	241			
120	217	221	242	260	269	255	230	218	245	229	227	237	272	250	222	205			
125	185	205	231	245	250	236	216	207	207	213	221	230	255	235	221	187			
130	170	191	205	219	218	200	183	181	197	194	188	185	214	217	199	182			
135	154	172	186	194	191	172	159	164	172	171	168	160	175	180	169	156			
140	141	155	167	172	169	150	138	146	157	156	152	141	156	159	156	139			
145	124	137	143	145	143	123	116	128	139	140	135	123	135	132	134	122			
150	132	140	140	130	124	112	107	118	132	133	135	143	144	130	140	129			
155	119	124	119	112	104	93.5	91.1	101	119	119	122	130	139	130	129	123			
160	98.4	101	95.8	90.2	81.1	72.6	72.2	80.9	101	100	104	112	121	118	111	106			
165	77.5	77.7	74.1	68.0	59.0	51.2	51.9	60.3	78.4	78.8	83.5	90.7	98.1	98.1	93.3	85.2			
170	58.9	57.2	54.0	48.5	41.3	35.2	37.0	43.5	57.8	59.6	64.3	69.8	75.5	77.4	74.1	67.5			
175	46.3	44.3	42.3	40.0	38.6	37.5	37.9	38.5	43.2	45.2	48.8	52.1	55.9	57.6	55.4	50.6			
180	42.6	42.5	43.5	44.1	44.9	44.7	43.4	42.2	42.4	42.7	43.3	44.3	44.7	44.8	43.3	42.2			

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:XIAOMI
Test Date:2023-06-02

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:9.000m [K=1.0000]
Remarks: