


## LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:220.29V I:0.1131A P:14.399W PF:0.5777 Freq:50.00Hz Lamp Flux:1014.28x1 lm		
NAME: SB-J01E14WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:800*12mm	

DATA OF LAMP		PHOTOMETRIC DATA Eff: 70.44 lm/W			
MODEL		I <sub>max</sub> (cd)	355.1	S/MH(C0/180)	1.24
NOMINAL POWER(W)		LOR(%)	100.0	S/MH(C90/270)	1.17
RATED VOLTAGE(V)	--	TOTAL FLUX(lm)	1014.3	η UP,DN(C0-180)	5.0,40.2
NOMINAL FLUX(lm)	1014.28	CIE CLASS	SEMI-D.	η UP,DN(C180-360)	5.6,49.2
LAMPS INSIDE	1	η up(%)	10.6	CIBSE SHR NOM	1.25
TEST VOLTAGE(V)	--	η down(%)	89.4	CIBSE SHR MAX	1.30



C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:XIAOMI  
 Test Date:2023-06-25

γ Range: 0 - 180DEG  
 γ Interval: 1.0DEG  
 Test System:EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
 Humidity:65.0%  
 Test Distance:9.000m [K=1.0000]  
 Remarks:

## ZONAL FLUX DIAGRAM

## ZONAL FLUX DIAGRAM:

$\gamma$	C0	C45	C90	C135	C180	C225	C270	C315	$\gamma$	$\Phi$ zone	$\Phi$ total	%lum,lamp
10	335.0	333.3	331.0	339.7	347.7	333.0	326.5	323.6	0- 10	32.61	32.61	3.21,3.21
20	300.0	289.0	277.9	300.4	325.8	308.0	305.7	294.2	10- 20	89.46	122.1	12,12
30	253.3	235.3	224.5	250.0	291.1	276.3	272.1	254.8	20- 30	128.1	250.2	24.7,24.7
40	203.7	185.8	181.7	203.4	244.9	238.7	231.4	213.9	30- 40	146.6	396.7	39.1,39.1
50	151.7	141.7	140.0	159.7	192.5	198.3	191.9	173.6	40- 50	146.9	543.6	53.6,53.6
60	103.7	100.9	99.66	118.8	140.6	158.0	155.3	136.8	50- 60	132.1	675.7	66.6,66.6
70	61.27	66.44	65.12	81.50	93.71	119.9	119.8	101.4	60- 70	107.2	782.9	77.2,77.2
80	25.06	38.59	39.79	48.89	50.02	84.67	86.31	68.66	70- 80	76.31	859.2	84.7,84.7
90	2.796	30.15	36.31	34.06	14.22	50.85	53.82	39.25	80- 90	47.49	906.7	89.4,89.4
100	3.323	22.56	31.77	24.99	7.159	23.34	29.16	21.23	90-100	28.46	935.2	92.2,92.2
110	4.238	19.83	26.92	17.15	4.460	14.44	21.07	16.11	100-110	18.96	954.1	94.1,94.1
120	5.120	19.18	26.00	21.33	4.607	22.07	26.51	21.84	110-120	17.00	971.1	95.7,95.7
130	5.597	14.05	23.54	16.10	4.775	17.89	26.35	18.17	120-130	15.06	986.2	97.2,97.2
140	5.460	12.30	19.64	12.95	4.538	15.00	24.61	16.49	130-140	11.83	998.0	98.4,98.4
150	5.345	10.76	14.86	11.32	4.369	13.87	19.04	16.31	140-150	8.367	1006	99.2,99.2
160	5.213	8.276	11.43	6.412	4.640	8.332	15.73	13.04	150-160	4.996	1011	99.7,99.7
170	6.214	5.026	7.245	3.549	5.940	7.275	11.28	10.59	160-170	2.278	1014	99.9,99.9
180	6.889	6.923	4.769	6.403	6.874	6.902	4.767	6.355	170-180	0.6196	1014	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

Conical surface Flux(90deg): 471.2 lm

%lum = 46.5%

%lamp = 46.5%

Conical surface Flux(120deg): 675.75 lm

%lum = 66.6%


%lamp = 66.6%

C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:XIAOMI  
 Test Date:2023-06-25

$\gamma$  Range: 0 - 180DEG  
 $\gamma$  Interval: 1.0DEG  
 Test System:EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
 Humidity:65.0%  
 Test Distance:9.000m [K=1.0000]  
 Remarks:

## LUMINANCE LIMITATION CURVES

Test:U:220.29V I:0.1131A P:14.399W PF:0.5777 Freq:50.00Hz Lamp Flux:1014.28x1 lm		
NAME: SB-J01E14WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:800*12mm	



LUMINANCE cd/(m2)		
G(DEG)	C0/180	C90/270
85	11691	43677
80	15032	23870
75	17034	20548
70	18660	19832
65	20140	20079
60	21604	20763
55	23087	21678
50	24591	22681
45	26157	23708


C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:XIAOMI  
Test Date:2023-06-25

$\gamma$  Range: 0 - 180DEG  
 $\gamma$  Interval: 1.0DEG  
Test System:EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
Humidity:65.0%  
Test Distance:9.000m [K=1.0000]  
Remarks:

## CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:220.29V I:0.1131A P:14.399W PF:0.5777 Freq:50.00Hz Lamp Flux:1014.28x1 lm		
NAME: SB-J01E14WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:800*12mm	

$\rho_{cc}$	80%			70%			50%			30%			10%			0	
$\rho_w$	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
$\rho_{fc}$	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Coefficients of Utilization(CU)										
0.0	1.17	1.17	1.17	1.13	1.13	1.13	1.05	1.05	1.05	.98	.98	.98	.92	.92	.92	.89	
1.0	.00	.95	.91	.97	.92	.88	.90	.87	.84	.85	.82	.79	.79	.77	.75	.72	
2.0	.87	.80	.74	.84	.77	.72	.79	.73	.69	.74	.69	.65	.69	.66	.62	.60	
3.0	.76	.68	.61	.74	.66	.60	.69	.63	.57	.65	.60	.55	.61	.57	.53	.50	
4.0	.67	.59	.52	.65	.57	.51	.62	.54	.49	.58	.52	.47	.55	.50	.45	.43	
5.0	.60	.51	.45	.59	.50	.44	.55	.48	.42	.52	.46	.41	.49	.44	.40	.37	
6.0	.54	.45	.39	.53	.44	.38	.50	.43	.37	.47	.41	.36	.45	.39	.35	.33	
7.0	.49	.41	.34	.48	.40	.34	.45	.38	.33	.43	.37	.32	.41	.35	.31	.29	
8.0	.45	.37	.31	.44	.36	.30	.42	.35	.30	.40	.33	.29	.38	.32	.28	.26	
9.0	.41	.33	.28	.40	.33	.27	.38	.32	.27	.37	.30	.26	.35	.29	.25	.23	
10.0	.38	.30	.25	.37	.30	.25	.36	.29	.24	.34	.28	.24	.32	.27	.23	.21	



C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:XIAOMI  
 Test Date:2023-06-25

$\gamma$  Range: 0 - 180DEG  
 $\gamma$  Interval: 1.0DEG  
 Test System:EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
 Humidity:65.0%  
 Test Distance:9.000m [K=1.0000]  
 Remarks:

## WEC AND CCEC

Test:U:220.29V I:0.1131A P:14.399W PF:0.5777 Freq:50.00Hz Lamp Flux:1014.28x1 lm		
NAME: SB-J01E14WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:800*12mm	

pcc	80%			70%			50%			30%			10%			0	
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
pfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)										
0.0																	
1.0	.338	.192	.061	.328	.187	.059	.308	.177	.056	.290	.168	.054	.274	.159	.051		
2.0	.303	.166	.051	.294	.162	.050	.277	.154	.048	.261	.146	.046	.246	.139	.044		
3.0	.275	.146	.044	.266	.143	.043	.251	.136	.041	.236	.129	.040	.223	.123	.038		
4.0	.250	.130	.038	.243	.127	.038	.229	.121	.036	.216	.116	.035	.204	.111	.034		
5.0	.230	.117	.034	.223	.115	.033	.210	.110	.032	.199	.105	.031	.188	.100	.030		
6.0	.212	.106	.030	.206	.104	.030	.195	.100	.029	.184	.096	.028	.174	.092	.027		
7.0	.197	.097	.028	.191	.095	.027	.181	.091	.026	.171	.088	.026	.162	.084	.025		
8.0	.183	.090	.025	.178	.088	.025	.169	.084	.024	.160	.081	.023	.151	.078	.023		
9.0	.172	.083	.023	.167	.081	.023	.158	.078	.022	.150	.075	.022	.142	.072	.021		
10.0	.161	.077	.021	.157	.076	.021	.149	.073	.021	.141	.070	.020	.134	.067	.019		

pcc	80%			70%			50%			30%			10%			0	
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
pfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)										
0.0	.271	.271	.271	.232	.232	.232	.158	.158	.158	.091	.091	.091	.029	.029	.029		
1.0	.264	.237	.214	.226	.204	.184	.154	.140	.127	.089	.081	.074	.028	.026	.024		
2.0	.256	.214	.179	.219	.184	.154	.150	.127	.108	.087	.074	.063	.028	.024	.021		
3.0	.248	.197	.156	.212	.170	.135	.146	.118	.095	.084	.069	.056	.027	.022	.018		
4.0	.240	.184	.141	.206	.159	.122	.142	.111	.086	.082	.065	.051	.026	.021	.017		
5.0	.232	.174	.130	.200	.150	.113	.137	.105	.080	.080	.062	.048	.026	.020	.016		
6.0	.225	.165	.123	.193	.143	.107	.133	.100	.076	.077	.059	.045	.025	.019	.015		
7.0	.218	.159	.117	.188	.138	.102	.130	.096	.072	.075	.057	.043	.024	.019	.014		
8.0	.212	.153	.113	.182	.133	.098	.126	.093	.070	.073	.055	.042	.024	.018	.014		
9.0	.206	.148	.109	.177	.129	.095	.123	.090	.068	.072	.053	.040	.023	.018	.013		
10.0	.200	.144	.107	.172	.125	.093	.120	.088	.066	.070	.052	.039	.023	.017	.013		

C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:XIAOMI  
 Test Date:2023-06-25

γ Range: 0 - 180DEG  
 γ Interval: 1.0DEG  
 Test System:EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
 Humidity:65.0%  
 Test Distance:9.000m [K=1.0000]  
 Remarks:

UGR(Unified Glare Rating) Table

Test:U:220.29V I:0.1131A P:14.399W PF:0.5777 Freq:50.00Hz Lamp Flux:1014.28x1 lm											
NAME: SB-J01E14WSZ					TYPE:			WEIGHT:			
SPEC.:4000K					DIM.:			SERIAL No.:			
MFR.: SNOWBALL					SUR.:800*12mm						
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H y = 2H	2H	22.4	23.8	22.8	24.2	24.6	21.9	23.3	22.3	23.7	24.1
	3H	23.7	25.0	24.2	25.4	25.9	23.4	24.7	23.9	25.1	25.6
	4H	24.3	25.5	24.7	25.9	26.4	24.2	25.4	24.6	25.8	26.3
	6H	24.6	25.8	25.1	26.2	26.7	24.9	26.1	25.4	26.5	27.0
	8H	24.7	25.8	25.2	26.3	26.8	25.3	26.4	25.8	26.9	27.4
	12H	24.8	25.8	25.3	26.3	26.9	25.9	27.0	26.4	27.5	28.0
4H	2H	22.9	24.1	23.3	24.5	25.0	22.5	23.7	23.0	24.1	24.6
	3H	24.4	25.5	24.9	26.0	26.5	24.2	25.3	24.7	25.8	26.3
	4H	25.1	26.1	25.7	26.6	27.2	25.1	26.1	25.6	26.6	27.1
	6H	25.7	26.5	26.2	27.1	27.7	26.0	26.9	26.6	27.4	28.0
	8H	25.9	26.7	26.4	27.2	27.8	26.5	27.4	27.1	27.9	28.5
	12H	26.0	26.7	26.5	27.3	27.9	27.3	28.0	27.9	28.6	29.2
8H	4H	25.4	26.3	26.0	26.8	27.4	25.4	26.2	26.0	26.8	27.4
	6H	26.2	26.9	26.8	27.5	28.1	26.6	27.3	27.2	27.8	28.5
	8H	26.5	27.1	27.1	27.7	28.4	27.3	27.9	27.9	28.5	29.2
	12H	26.8	27.3	27.4	27.9	28.6	28.3	28.8	28.9	29.4	30.1
12H	4H	25.5	26.2	26.1	26.8	27.4	25.5	26.2	26.0	26.8	27.4
	6H	26.4	27.0	27.0	27.6	28.2	26.7	27.3	27.3	27.9	28.6
	8H	26.8	27.3	27.4	27.9	28.6	27.5	28.0	28.1	28.6	29.3
Variations with the observer position at spacings:											
S = 1.0H		+ 0.2 / - 0.2					+ 0.2 / - 0.2				
1.5H		+ 0.2 / - 0.3					+ 0.2 / - 0.3				
2.0H		+ 0.2 / - 0.3					+ 0.1 / - 0.3				

CIE Pub.117, 1014 lm Total Lamp Luminous Flux Corrected ( $8\log(F/F_0) = 0.0$ )  
Area: 0.0096 m<sup>2</sup>

C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:XIAOMI  
Test Date:2023-06-25

$\gamma$  Range: 0 - 180DEG  
 $\gamma$  Interval: 1.0DEG  
Test System:EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
Humidity:65.0%  
Test Distance:9.000m [K=1.0000]  
Remarks:

## UTILIZATION FACTORS TABLE

Test:U:220.29V I:0.1131A P:14.399W PF:0.5777 Freq:50.00Hz Lamp Flux:1014.28x1 lm		
NAME: SB-J01E14WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:800*12mm	


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	54	42	36	53	42	35	52	41	35	29
0.80	64	52	44	62	51	44	60	50	43	36
1.00	71	60	52	70	59	52	67	60	51	43
1.25	78	67	59	76	66	59	73	64	57	49
1.50	83	72	65	81	71	64	77	68	62	53
2.00	90	80	73	87	79	72	83	75	70	60
2.50	94	85	78	91	83	77	86	79	74	63
3.00	97	90	83	94	87	82	89	83	78	67
4.00	102	95	89	98	92	87	92	88	83	71
5.00	104	99	94	101	96	91	95	90	87	74
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:XIAOMI  
 Test Date:2023-06-25

γ Range: 0 - 180DEG  
 γ Interval: 1.0DEG  
 Test System:EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
 Humidity:65.0%  
 Test Distance:9.000m [K=1.0000]  
 Remarks:

## ISOCANDELA DIAGRAM

Test:U:220.29V I:0.1131A P:14.399W PF:0.5777 Freq:50.00Hz Lamp Flux:1014.28x1 lm		
NAME: SB-J01E14WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:800*12mm	



C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:XIAOMI  
Test Date:2023-06-25


$\gamma$  Range: 0 - 180DEG  
 $\gamma$  Interval: 1.0DEG  
Test System:EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
Humidity:65.0%  
Test Distance:9.000m [K=1.0000]  
Remarks:



## AAI Figure

Test:U:220.29V I:0.1131A P:14.399W PF:0.5777 Freq:50.00Hz Lamp Flux:1014.28x1 lm		
NAME: SB-J01E14WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:800*12mm	

Flux out:515.0 lm




Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature: 25.3DEG  
 Operators: XIAOMI  
 Test Date: 2023-06-25

γ Range: 0 - 180DEG  
 γ Interval: 1.0DEG  
 Test System: EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
 Humidity: 65.0%  
 Test Distance: 9.000m [K=1.0000]  
 Remarks:

### ISOLUX DIAGRAM


Test:U:220.29V I:0.1131A P:14.399W PF:0.5777 Freq:50.00Hz Lamp Flux:1014.28x1 lm		
NAME: SB-J01E14WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:800*12mm	



C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:XIAOMI  
 Test Date:2023-06-25

$\gamma$  Range: 0 - 180DEG  
 $\gamma$  Interval: 1.0DEG  
 Test System:EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
 Humidity:65.0%  
 Test Distance:9.000m [K=1.0000]  
 Remarks:

### Planar Illuminance Curve



C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature: 25.3DEG  
Operators: XIAOMI  
Test Date: 2023-06-25

$\gamma$  Range: 0 - 180DEG  
 $\gamma$  Interval: 1.0DEG  
Test System: EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
Humidity: 65.0%  
Test Distance: 9.000m [K=1.0000]  
Remarks:

## LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:220.29V I:0.1131A P:14.399W PF:0.5777 Freq:50.00Hz Lamp Flux:1014.28x1 lm																	
NAME: SB-J01E14WSZ									TYPE:						WEIGHT:		
SPEC.:4000K									DIM.:						SERIAL No.:		
MFR.: SNOWBALL									SUR.:800*12mm								

Table--1

UNIT: cd

C(DEG) γ (DEG)	0	22.5	45	67.5	90	112.5	135	157.5	180	202.5	225	247.5	270	292.5	315	337.5			
0	352	352	351	350	350	349	349	349	352	352	351	350	350	349	349	349			
5	345	346	346	345	347	350	351	351	353	350	348	344	340	337	338	340			
10	335	337	333	331	331	337	340	344	348	340	333	330	326	322	324	328			
15	318	321	314	307	306	313	323	334	339	328	320	318	317	311	309	311			
20	300	300	289	279	278	285	300	318	326	311	308	306	306	299	294	288			
25	278	278	262	251	250	258	275	299	309	293	293	291	290	283	274	268			
30	253	252	235	224	225	232	250	278	291	275	276	273	272	263	255	244			
35	229	227	210	201	202	209	226	257	270	257	257	253	252	241	234	223			
40	204	202	186	179	182	189	203	232	245	236	239	233	231	221	214	201			
45	178	177	163	158	161	168	181	207	219	214	219	213	211	201	193	180			
50	152	153	142	138	140	148	160	182	193	192	198	195	192	183	174	158			
55	127	129	120	118	119	128	139	158	166	169	178	176	174	166	154	137			
60	104	108	101	99.7	99.7	109	119	135	141	147	158	159	155	149	137	118			
65	81.7	86.8	83.4	82.3	81.5	90.2	99.7	112	118	127	139	141	137	131	119	101			
70	61.3	67.3	66.4	65.9	65.1	72.8	81.5	90.8	93.7	108	120	122	120	114	101	82.4			
75	42.3	48.5	51.5	50.7	51.1	56.6	64.4	70.8	72.1	88.2	102	104	103	96.6	84.5	64.9			
80	25.1	32.8	38.6	39.4	39.8	43.1	48.9	51.0	50.0	69.8	84.7	87.0	86.3	80.0	68.7	49.4			
85	9.78	20.3	32.3	35.8	36.5	36.6	36.4	34.1	31.2	52.7	68.0	70.5	70.0	64.4	52.7	35.0			
90	2.80	16.9	30.2	35.1	36.3	35.8	34.1	24.9	14.2	36.3	50.8	55.1	53.8	50.0	39.3	21.8			
95	3.01	12.7	25.9	32.3	34.6	33.9	29.9	19.4	8.96	20.6	33.2	39.3	39.5	36.1	24.7	13.7			
100	3.32	9.35	22.6	29.3	31.8	30.5	25.0	16.0	7.16	14.6	23.3	28.9	29.2	26.3	21.2	10.9			
105	3.74	11.3	17.8	26.0	28.6	27.6	22.8	11.9	5.22	10.9	22.5	24.9	26.4	24.6	15.6	12.8			
110	4.24	10.2	19.8	15.1	26.9	17.2	17.1	14.4	4.46	13.3	14.4	14.6	21.1	14.0	16.1	14.3			
115	4.68	10.3	20.0	21.2	26.5	21.8	22.1	13.9	4.51	13.5	21.0	18.7	26.1	21.1	21.4	14.5			
120	5.12	10.4	19.2	20.7	26.0	21.3	21.3	13.0	4.61	12.9	22.1	21.0	26.5	21.6	21.8	14.3			
125	5.49	10.1	15.5	19.9	25.0	20.5	19.5	11.6	4.71	11.9	20.8	21.0	26.6	21.7	19.3	13.3			
130	5.60	9.70	14.0	20.2	23.5	20.2	16.1	11.0	4.77	12.2	17.9	22.2	26.3	22.8	18.2	11.3			
135	5.50	8.57	13.1	19.6	21.7	19.8	14.8	9.45	4.63	10.9	16.5	23.1	25.7	23.5	17.5	10.1			
140	5.46	7.62	12.3	17.9	19.6	18.8	12.9	8.17	4.54	10.4	15.0	23.0	24.6	23.3	16.5	10.4			
145	5.41	6.77	11.7	15.9	17.3	16.4	12.1	6.78	4.35	8.92	16.2	17.7	23.0	21.7	16.6	10.8			
150	5.34	6.54	10.8	13.8	14.9	13.9	11.3	5.78	4.37	7.65	13.9	18.8	19.0	19.7	16.3	10.9			
155	5.33	6.61	9.68	12.4	12.7	12.3	8.67	5.16	4.52	6.83	10.7	16.6	18.2	16.6	15.1	10.1			
160	5.21	5.17	8.28	10.5	11.4	10.5	6.41	3.78	4.64	6.31	8.33	13.0	15.7	15.0	13.0	10.3			
165	5.68	4.15	7.53	8.34	8.82	6.90	5.56	3.46	5.19	6.97	7.14	8.88	12.8	12.8	11.5	9.60			
170	6.21	4.91	5.03	6.65	7.25	4.76	3.55	4.49	5.94	7.50	7.27	6.77	11.3	11.1	10.6	8.61			
175	6.66	5.78	5.24	4.86	3.46	3.71	4.82	5.72	6.59	7.58	7.81	6.03	5.89	9.35	8.81	7.90			
180	6.89	6.84	6.92	6.42	4.77	6.51	6.40	6.90	6.87	6.84	6.90	6.44	4.77	6.51	6.36	6.93			

C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:XIAOMI  
Test Date:2023-06-25

γ Range: 0 - 180DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
Humidity:65.0%  
Test Distance:9.000m [K=1.0000]  
Remarks: