


## LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:220.20V I:0.3920A P:84.216W PF:0.9757 Freq:50.00Hz Lamp Flux:6622.1lx1 lm		
NAME: SB-D01A80WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1800mm	

DATA OF LAMP		PHOTOMETRIC DATA Eff: 78.63 lm/W			
MODEL		I <sub>max</sub> (cd)	1281	S/MH(C0/180)	1.31
NOMINAL POWER(W)		LOR(%)	100.0	S/MH(C90/270)	1.28
RATED VOLTAGE(V)	--	TOTAL FLUX(lm)	6622.1	η UP,DN(C0-180)	12.4,36.6
NOMINAL FLUX(lm)	6622.11	CIE CLASS	SEMI-D.	η UP,DN(C180-360)	12.5,38.5
LAMPS INSIDE	1	η up(%)	24.9	CIBSE SHR NOM	1.50
TEST VOLTAGE(V)	--	η down(%)	75.1	CIBSE SHR MAX	1.55



C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:XIAOMI  
 Test Date:2023-06-02

γ Range: 0 - 180DEG  
 γ Interval: 1.0DEG  
 Test System:EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
 Humidity:65.0%  
 Test Distance:9.000m [K=1.0000]  
 Remarks:

## ZONAL FLUX DIAGRAM

## ZONAL FLUX DIAGRAM:

$\gamma$	C0	C45	C90	C135	C180	C225	C270	C315	$\gamma$	$\Phi$ zone	$\Phi$ total	%lum,lamp
10	1249	1240	1213	1197	1231	1227	1232	1244	0- 10	119.0	119.0	1.8,1.8
20	1185	1147	1124	1121	1154	1151	1157	1175	10- 20	335.7	454.8	6.87,6.87
30	1135	1066	1038	1060	1107	1077	1081	1130	20- 30	516.4	971.1	14.7,14.7
40	1065	976.1	949.3	988.2	1053	989.2	997.9	1066	30- 40	658.2	1629	24.6,24.6
50	956.3	862.8	842.9	892.2	970.2	882.1	894.2	966.0	40- 50	742.5	2372	35.8,35.8
60	821.0	733.3	721.7	774.2	859.1	761.1	774.1	838.1	50- 60	758.7	3131	47.3,47.3
70	682.0	601.9	597.3	651.0	733.0	637.3	648.2	703.4	60- 70	714.0	3845	58.1,58.1
80	551.1	480.2	481.2	533.9	612.4	520.8	529.2	576.4	70- 80	629.2	4474	67.6,67.6
90	444.6	342.1	299.8	295.5	491.9	378.7	360.1	330.2	80- 90	496.5	4970	75.1,75.1
100	398.4	343.9	355.1	336.0	323.5	298.4	362.6	393.9	90-100	372.4	5343	80.7,80.7
110	378.0	288.2	328.1	306.5	331.5	290.9	341.1	339.7	100-110	359.7	5702	86.1,86.1
120	311.3	275.9	292.4	296.0	277.9	281.5	304.5	328.7	110-120	308.6	6011	90.8,90.8
130	256.8	228.4	219.2	209.8	215.1	208.4	234.8	267.4	120-130	233.7	6245	94.3,94.3
140	208.7	189.2	171.1	166.7	175.6	157.5	180.9	211.1	130-140	159.8	6404	96.7,96.7
150	159.5	140.3	159.0	198.6	220.2	172.5	164.6	171.0	140-150	114.5	6519	98.4,98.4
160	91.74	87.42	112.0	147.9	172.5	133.3	113.6	107.4	150-160	68.97	6588	99.5,99.5
170	47.23	53.82	69.75	94.44	112.8	89.79	69.17	58.47	160-170	27.91	6616	99.9,99.9
180	68.08	61.81	59.58	62.96	67.38	61.50	59.38	62.97	170-180	6.432	6622	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

Conical surface Flux(90deg): 1994.3 lm

%lum = 30.1%

%lamp = 30.1%

Conical surface Flux(120deg): 3130.5 lm

%lum = 47.3%


%lamp = 47.3%

C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:XIAOMI  
 Test Date:2023-06-02

$\gamma$  Range: 0 - 180DEG  
 $\gamma$  Interval: 1.0DEG  
 Test System:EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
 Humidity:65.0%  
 Test Distance:9.000m [K=1.0000]  
 Remarks:

## LUMINANCE LIMITATION CURVES

Test:U:220.20V I:0.3920A P:84.216W PF:0.9757 Freq:50.00Hz Lamp Flux:6622.11x1 lm		
NAME: SB-D01A80WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1800mm	



LUMINANCE cd/(m2)		
G(DEG)	C0/180	C90/270
85	1820	1891
80	1248	1090
75	933	817
70	784	687
65	699	613
60	646	568
55	611	537
50	585	516
45	565	500


C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:XIAOMI  
Test Date:2023-06-02

γ Range: 0 - 180DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
Humidity:65.0%  
Test Distance:9.000m [K=1.0000]  
Remarks:

## CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:220.20V I:0.3920A P:84.216W PF:0.9757 Freq:50.00Hz Lamp Flux:6622.11x1 lm		
NAME: SB-D01A80WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1800mm	

$\rho_{cc}$	80%			70%			50%			30%			10%			0
$\rho_w$	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
$\rho_{fc}$	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio                      Coefficients of Utilization(CU)															
0.0	1.13	1.13	1.13	1.08	1.08	1.08	.97	.97	.97	.88	.88	.88	.79	.79	.79	.75
1.0	.94	.88	.84	.89	.84	.80	.80	.76	.73	.72	.69	.66	.64	.62	.60	.56
2.0	.80	.72	.66	.76	.69	.63	.68	.63	.58	.61	.57	.53	.55	.51	.48	.44
3.0	.69	.60	.53	.66	.58	.51	.59	.52	.47	.53	.48	.43	.47	.43	.39	.36
4.0	.61	.51	.44	.58	.49	.42	.52	.45	.39	.47	.41	.36	.42	.37	.33	.30
5.0	.54	.44	.37	.51	.42	.36	.46	.39	.33	.42	.35	.31	.37	.32	.28	.25
6.0	.48	.39	.32	.46	.37	.31	.41	.34	.29	.37	.31	.27	.34	.28	.24	.22
7.0	.43	.34	.28	.41	.33	.27	.37	.30	.25	.34	.28	.23	.31	.25	.21	.19
8.0	.39	.31	.25	.38	.29	.24	.34	.27	.22	.31	.25	.21	.28	.23	.19	.17
9.0	.36	.28	.22	.34	.27	.21	.31	.25	.20	.28	.23	.18	.26	.21	.17	.15
10.0	.33	.25	.20	.32	.24	.19	.29	.22	.18	.26	.21	.17	.24	.19	.15	.13



C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:XIAOMI  
 Test Date:2023-06-02

$\gamma$  Range: 0 - 180DEG  
 $\gamma$  Interval: 1.0DEG  
 Test System:EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
 Humidity:65.0%  
 Test Distance:9.000m [K=1.0000]  
 Remarks:

## WEC AND CCEC

Test:U:220.20V I:0.3920A P:84.216W PF:0.9757 Freq:50.00Hz Lamp Flux:6622.11x1 lm		
NAME: SB-D01A80WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1800mm	

pcc	80%			70%			50%			30%			10%			0	
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
pfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients(WEC)										
0.0																	
1.0	.387	.220	.070	.372	.212	.067	.344	.197	.063	.319	.184	.059	.295	.171	.055		
2.0	.334	.183	.056	.320	.176	.054	.295	.164	.051	.272	.152	.048	.250	.142	.045		
3.0	.296	.157	.047	.283	.152	.046	.261	.141	.043	.239	.131	.040	.220	.122	.038		
4.0	.266	.138	.041	.255	.133	.039	.234	.124	.037	.215	.115	.035	.197	.107	.033		
5.0	.241	.123	.036	.231	.119	.035	.212	.111	.033	.195	.103	.031	.178	.095	.029		
6.0	.221	.111	.032	.212	.107	.031	.194	.100	.029	.178	.093	.027	.163	.086	.025		
7.0	.204	.101	.029	.195	.097	.028	.179	.091	.026	.164	.084	.025	.150	.078	.023		
8.0	.189	.092	.026	.181	.089	.025	.166	.083	.024	.152	.077	.022	.139	.072	.021		
9.0	.176	.085	.024	.169	.082	.023	.155	.077	.022	.142	.071	.020	.130	.066	.019		
10.0	.164	.079	.022	.158	.076	.021	.145	.071	.020	.133	.066	.019	.122	.061	.018		

pcc	80%			70%			50%			30%			10%			0	
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
pfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)										
0.0	.381	.381	.381	.325	.325	.325	.222	.222	.222	.128	.128	.128	.041	.041	.041		
1.0	.377	.347	.320	.323	.298	.275	.221	.205	.190	.127	.119	.111	.041	.038	.036		
2.0	.371	.325	.286	.318	.279	.247	.218	.193	.172	.125	.112	.101	.040	.036	.033		
3.0	.363	.308	.265	.312	.266	.229	.214	.185	.161	.124	.108	.095	.040	.035	.031		
4.0	.356	.296	.251	.305	.256	.218	.210	.178	.153	.121	.104	.091	.039	.034	.030		
5.0	.348	.287	.241	.299	.248	.210	.206	.173	.148	.119	.102	.088	.038	.033	.029		
6.0	.341	.279	.234	.293	.241	.204	.202	.169	.144	.117	.099	.086	.038	.032	.028		
7.0	.334	.272	.229	.287	.236	.200	.198	.165	.141	.115	.097	.084	.037	.032	.028		
8.0	.327	.267	.225	.282	.231	.196	.195	.162	.139	.113	.096	.083	.037	.031	.027		
9.0	.321	.262	.222	.276	.227	.194	.192	.160	.138	.112	.094	.082	.036	.031	.027		
10.0	.315	.258	.220	.272	.224	.192	.188	.158	.136	.110	.093	.081	.036	.031	.027		

C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:XIAOMI  
 Test Date:2023-06-02

γ Range: 0 - 180DEG  
 γ Interval: 1.0DEG  
 Test System:EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
 Humidity:65.0%  
 Test Distance:9.000m [K=1.0000]  
 Remarks:

UGR(Unified Glare Rating) Table

Test:U:220.20V I:0.3920A P:84.216W PF:0.9757 Freq:50.00Hz Lamp Flux:6622.11x1 lm											
NAME: SB-D01A80WSZ						TYPE:		WEIGHT:			
SPEC.:4000K						DIM.:		SERIAL No.:			
MFR.: SNOWBALL						SUR.:1800mm					
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions	Viewed crosswise					Viewed endwise					
x = 2H y = 2H	9.5	10.9	10.1	11.5	12.1	9.0	10.3	9.6	10.9	11.6	
	3H	12.0	13.2	12.6	13.8	14.5	11.3	12.5	11.9	13.1	13.9
	4H	13.3	14.4	13.9	15.1	15.9	12.6	13.7	13.2	14.4	15.1
	6H	14.8	15.8	15.4	16.5	17.3	14.0	15.1	14.7	15.7	16.5
	8H	15.6	16.6	16.3	17.3	18.1	14.8	15.8	15.5	16.5	17.3
	12H	16.4	17.4	17.1	18.0	18.9	15.7	16.7	16.4	17.4	18.2
4H	2H	10.2	11.3	10.8	12.0	12.7	9.8	10.9	10.4	11.5	12.3
	3H	12.8	13.8	13.5	14.5	15.3	12.3	13.3	13.0	14.0	14.8
	4H	14.3	15.2	15.0	15.9	16.8	13.7	14.6	14.4	15.3	16.2
	6H	16.0	16.8	16.7	17.5	18.4	15.3	16.1	16.0	16.9	17.7
	8H	16.9	17.7	17.6	18.4	19.3	16.2	17.0	16.9	17.7	18.6
	12H	17.8	18.5	18.6	19.3	20.2	17.2	17.9	18.0	18.7	19.6
8H	4H	14.8	15.5	15.5	16.3	17.2	14.3	15.1	15.0	15.8	16.7
	6H	16.7	17.4	17.5	18.1	19.1	16.1	16.8	16.9	17.6	18.5
	8H	17.8	18.4	18.6	19.2	20.1	17.2	17.8	18.0	18.6	19.5
	12H	19.0	19.5	19.8	20.3	21.2	18.5	19.0	19.3	19.8	20.7
12H	4H	14.9	15.6	15.6	16.3	17.2	14.4	15.1	15.2	15.9	16.8
	6H	16.9	17.5	17.7	18.3	19.2	16.4	17.0	17.2	17.8	18.7
	8H	18.1	18.6	18.9	19.4	20.4	17.6	18.1	18.4	18.9	19.8
Variations with the observer position at spacings:											
S = 1.0H	+ 0.1 / - 0.1					+ 0.1 / - 0.1					
1.5H	+ 0.2 / - 0.3					+ 0.2 / - 0.3					
2.0H	+ 0.2 / - 0.3					+ 0.2 / - 0.4					

CIE Pub.117, 6622 lm Total Lamp Luminous Flux Corrected ( $8\log(F/F_0) = 6.6$ )  
Area: 2.543 m<sup>2</sup>

C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:XIAOMI  
Test Date:2023-06-02

$\gamma$  Range: 0 - 180DEG  
 $\gamma$  Interval: 1.0DEG  
Test System:EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
Humidity:65.0%  
Test Distance:9.000m [K=1.0000]  
Remarks:

## UTILIZATION FACTORS TABLE

Test:U:220.20V I:0.3920A P:84.216W PF:0.9757 Freq:50.00Hz Lamp Flux:6622.1lx1 lm		
NAME: SB-D01A80WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1800mm	


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	45	33	26	44	32	25	42	31	25	18
0.80	54	41	33	52	40	33	49	38	31	23
1.00	62	49	40	60	47	40	55	47	38	29
1.25	69	56	47	66	54	46	61	51	44	33
1.50	74	62	53	71	60	51	65	56	49	37
2.00	81	70	62	78	68	60	71	63	56	43
2.50	86	76	67	82	73	65	75	67	61	47
3.00	90	80	73	86	77	70	78	71	65	50
4.00	95	87	80	90	83	77	82	76	71	54
5.00	98	91	85	93	87	81	84	79	75	57
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:XIAOMI  
 Test Date:2023-06-02

γ Range: 0 - 180DEG  
 γ Interval: 1.0DEG  
 Test System:EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
 Humidity:65.0%  
 Test Distance:9.000m [K=1.0000]  
 Remarks:

## ISOCANDELA DIAGRAM

Test:U:220.20V I:0.3920A P:84.216W PF:0.9757 Freq:50.00Hz Lamp Flux:6622.1lx1 lm		
NAME: SB-D01A80WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1800mm	




C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:XIAOMI  
Test Date:2023-06-02

$\gamma$  Range: 0 - 180DEG  
 $\gamma$  Interval: 1.0DEG  
Test System:EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
Humidity:65.0%  
Test Distance:9.000m [K=1.0000]  
Remarks:



## AAI Figure

Test:U:220.20V I:0.3920A P:84.216W PF:0.9757 Freq:50.00Hz Lamp Flux:6622.11x1 lm		
NAME: SB-D01A80WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1800mm	




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:XIAOMI  
 Test Date:2023-06-02

γ Range: 0 - 180DEG  
 γ Interval: 1.0DEG  
 Test System:EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
 Humidity:65.0%  
 Test Distance:9.000m [K=1.0000]  
 Remarks:

## ISOLUX DIAGRAM


Test:U:220.20V I:0.3920A P:84.216W PF:0.9757 Freq:50.00Hz Lamp Flux:6622.1lx1 lm		
NAME: SB-D01A80WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1800mm	



C Range: 0 - 360DEG  
 C Interval: 22.5DEG  
 Test Speed: HIGH  
 Temperature: 25.3DEG  
 Operators: XIAOMI  
 Test Date: 2023-06-02

$\gamma$  Range: 0 - 180DEG  
 $\gamma$  Interval: 1.0DEG  
 Test System: EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
 Humidity: 65.0%  
 Test Distance: 9.000m [K=1.0000]  
 Remarks:

### Planar Illuminance Curve



C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature: 25.3DEG  
Operators: XIAOMI  
Test Date: 2023-06-02

$\gamma$  Range: 0 - 180DEG  
 $\gamma$  Interval: 1.0DEG  
Test System: EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
Humidity: 65.0%  
Test Distance: 9.000m [K=1.0000]  
Remarks:

## LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:220.20V I:0.3920A P:84.216W PF:0.9757 Freq:50.00Hz Lamp Flux:6622.11x1 lm		
NAME: SB-D01A80WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1800mm	

Table--1

UNIT: cd

C(DEC) γ (DEC)	0	22.5	45	67.5	90	112.5	135	157.5	180	202.5	225	247.5	270	292.5	315	337.5			
0	1279	1277	1275	1272	1267	1264	1261	1257	1279	1277	1275	1272	1267	1264	1261	1257			
5	1274	1272	1264	1253	1242	1236	1234	1240	1274	1269	1264	1260	1257	1255	1258	1257			
10	1249	1248	1240	1228	1213	1203	1197	1197	1231	1226	1227	1227	1232	1239	1244	1239			
15	1214	1208	1193	1181	1170	1162	1157	1156	1189	1185	1188	1192	1199	1205	1207	1204			
20	1185	1171	1147	1130	1124	1121	1121	1122	1154	1150	1151	1151	1157	1168	1175	1176			
25	1161	1140	1106	1085	1080	1084	1091	1098	1128	1121	1114	1110	1118	1137	1151	1156			
30	1135	1108	1066	1042	1038	1047	1060	1075	1107	1092	1077	1067	1081	1108	1130	1136			
35	1105	1070	1024	999	996	1008	1027	1049	1083	1060	1035	1022	1042	1075	1102	1110			
40	1065	1025	976	951	949	965	988	1018	1053	1023	989	974	998	1035	1066	1074			
45	1015	972	922	899	899	917	944	978	1015	979	938	922	948	988	1020	1028			
50	956	912	863	842	843	863	892	930	970	928	882	865	894	934	966	972			
55	891	846	800	782	784	804	835	876	918	873	823	807	836	875	904	909			
60	821	778	733	718	722	743	774	816	859	812	761	745	774	811	838	842			
65	751	709	667	655	659	681	713	755	797	751	698	683	711	745	771	774			
70	682	643	602	596	597	622	651	692	733	689	637	622	648	680	703	706			
75	614	583	540	535	538	564	591	634	670	627	579	562	590	615	638	639			
80	551	519	480	477	481	507	534	578	612	568	521	504	529	553	576	573			
85	403	427	398	407	419	449	477	518	551	506	465	448	471	493	513	503			
90	445	403	342	309	300	214	295	420	492	431	379	346	360	324	330	420			
95	405	377	351	353	368	340	305	359	219	282	262	304	355	380	409	416			
100	398	378	344	342	355	345	336	308	323	313	298	324	363	370	394	404			
105	389	362	327	326	343	322	337	341	316	310	294	306	348	353	373	391			
110	378	347	288	313	328	322	306	342	332	324	291	305	341	344	340	376			
115	320	298	298	297	314	316	288	328	346	318	279	288	321	330	347	326			
120	311	289	276	278	292	299	296	249	278	223	281	277	305	311	329	327			
125	283	263	250	255	247	234	238	250	256	255	251	239	269	284	297	299			
130	257	240	228	232	219	201	210	222	215	217	208	205	235	256	267	272			
135	228	216	204	199	185	172	192	208	201	200	187	184	210	226	242	240			
140	209	198	189	184	171	163	167	186	176	170	158	157	181	196	211	210			
145	194	185	169	168	176	188	199	209	201	187	167	166	177	185	200	199			
150	159	153	140	145	159	180	199	214	220	199	173	161	165	165	171	171			
155	125	122	112	121	135	155	174	192	199	179	155	140	139	138	139	136			
160	91.7	91.2	87.4	98.0	112	129	148	165	173	154	133	119	114	110	107	101			
165	61.6	64.2	67.0	76.4	89.2	104	121	135	143	128	111	97.4	89.7	85.4	79.8	70.1			
170	47.2	48.5	53.8	61.2	69.7	81.2	94.4	106	113	101	89.8	78.2	69.2	65.1	58.5	49.2			
175	56.2	54.3	54.6	56.8	61.1	67.1	73.6	79.9	85.0	77.1	70.7	65.1	60.0	57.2	55.0	54.5			
180	68.1	63.7	61.8	59.9	59.6	60.9	63.0	65.3	67.4	63.7	61.5	59.9	59.4	61.2	63.0	65.7			

C Range: 0 - 360DEG  
C Interval: 22.5DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:XIAOMI  
Test Date:2023-06-02

γ Range: 0 - 180DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-3000H\_V1 SYSTEM V2.00.411  
Humidity:65.0%  
Test Distance:9.000m [K=1.0000]  
Remarks: