


LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:220.16V I:0.1680A P:31.143W PF:0.8420 Freq:50.00Hz Lamp Flux:2073.73x1 lm		
NAME: SB-D01A30WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:600mm	

DATA OF LAMP		PHOTOMETRIC DATA Eff: 66.59 lm/W			
MODEL		I _{max} (cd)	277.2	S/MH(C0/180)	1.71
NOMINAL POWER(W)		LOR(%)	100.0	S/MH(C90/270)	1.68
RATED VOLTAGE(V)	--	TOTAL FLUX(lm)	2073.7	η UP,DN(C0-180)	14.6,36.0
NOMINAL FLUX(lm)	2073.73	CIE CLASS	SEMI-D.	η UP,DN(C180-360)	13.7,35.7
LAMPS INSIDE	1	η up(%)	28.3	CIBSE SHR NOM	1.75
TEST VOLTAGE(V)	--	η down(%)	71.7	CIBSE SHR MAX	1.75



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:XIAOMI
Test Date:2023-05-30

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:9.000m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum, lamp
10	258.1	257.9	258.1	257.7	257.6	254.3	253.0	254.2	0- 10	23.96	23.96	1.16,1.16
20	268.0	267.3	267.9	268.7	268.0	263.2	261.7	264.1	10- 20	74.26	98.22	4.74,4.74
30	274.8	273.6	274.0	275.4	274.3	268.9	267.8	271.2	20- 30	124.8	223.0	10.8,10.8
40	275.7	274.9	275.3	276.9	275.8	270.3	269.5	272.9	30- 40	171.9	394.9	19,19
50	268.9	268.3	268.8	270.5	270.0	264.8	263.7	266.8	40- 50	210.1	605.0	29.2,29.2
60	253.7	253.3	253.9	255.6	256.0	251.4	249.7	252.4	50- 60	234.0	839.0	40.5,40.5
70	231.7	231.1	232.0	233.9	235.2	230.1	228.8	230.9	60- 70	240.9	1080	52.1,52.1
80	202.8	201.5	202.8	205.7	206.9	202.8	201.4	202.7	70- 80	230.7	1311	63.2,63.2
90	103.8	103.9	99.60	96.90	100.1	94.73	94.32	100.0	80- 90	175.7	1486	71.7,71.7
100	152.1	132.4	132.2	128.0	151.6	123.5	117.8	127.2	90-100	123.7	1610	77.6,77.6
110	139.1	127.6	134.3	126.7	139.1	115.8	115.3	119.3	100-110	140.8	1751	84.4,84.4
120	124.0	110.8	105.5	110.3	123.4	102.8	95.20	103.7	110-120	116.1	1867	90,90
130	106.7	90.86	87.42	91.15	106.5	87.92	82.02	81.75	120-130	88.10	1955	94.3,94.3
140	85.00	62.44	69.69	56.86	73.23	49.84	64.34	58.74	130-140	60.53	2016	97.2,97.2
150	39.55	48.85	50.93	46.52	38.08	43.63	41.07	44.64	140-150	34.38	2050	98.9,98.9
160	29.19	30.23	28.09	24.22	29.64	21.47	25.66	27.74	150-160	16.65	2067	99.7,99.7
170	17.39	16.38	13.07	14.22	21.33	15.42	11.21	16.05	160-170	5.979	2073	99.9,99.9
180	7.687	7.075	6.942	7.313	7.666	7.052	6.966	7.348	170-180	1.120	2074	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

Conical surface Flux(90deg): 495.96 lm

%lum = 23.9%

%lamp = 23.9%

Conical surface Flux(120deg): 839.04 lm

%lum = 40.5%


%lamp = 40.5%

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-05-30

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:220.16V I:0.1680A P:31.143W PF:0.8420 Freq:50.00Hz Lamp Flux:2073.73x1 lm		
NAME: SB-D01A30WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:600mm	




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:XIAOMI
Test Date:2023-05-30

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:9.000m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:220.16V I:0.1680A P:31.143W PF:0.8420 Freq:50.00Hz Lamp Flux:2073.73x1 lm		
NAME: SB-D01A30WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:600mm	

ρ_{cc}	80%			70%			50%			30%			10%			0
ρ_w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρ_{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Coefficients of Utilization(CU)															
0.0	1.12	1.12	1.12	1.06	1.06	1.06	.95	.95	.95	.85	.85	.85	.76	.76	.76	.72
1.0	.92	.86	.81	.87	.82	.77	.77	.73	.69	.68	.65	.62	.60	.58	.55	.51
2.0	.78	.69	.62	.73	.66	.59	.65	.59	.54	.57	.52	.48	.50	.46	.43	.39
3.0	.67	.57	.50	.63	.54	.47	.56	.49	.43	.49	.43	.39	.43	.38	.34	.31
4.0	.58	.48	.41	.55	.46	.39	.48	.41	.35	.43	.37	.32	.37	.32	.28	.25
5.0	.51	.41	.34	.48	.39	.33	.43	.35	.30	.38	.32	.27	.33	.28	.24	.21
6.0	.45	.36	.29	.43	.34	.28	.38	.31	.25	.34	.28	.23	.30	.24	.20	.18
7.0	.41	.32	.25	.39	.30	.24	.34	.27	.22	.31	.24	.20	.27	.22	.18	.15
8.0	.37	.28	.22	.35	.27	.21	.31	.24	.19	.28	.22	.17	.25	.19	.16	.13
9.0	.34	.25	.19	.32	.24	.18	.29	.22	.17	.25	.20	.15	.23	.18	.14	.12
10.0	.31	.23	.17	.29	.22	.16	.26	.20	.15	.23	.18	.14	.21	.16	.12	.10



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-05-30

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

WEC AND CCEC

Test:U:220.16V I:0.1680A P:31.143W PF:0.8420 Freq:50.00Hz Lamp Flux:2073.73x1 lm		
NAME: SB-D01A30WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:600mm	

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Wall Exitance Coefficients(WEC)															
0.0																
1.0	.410	.233	.074	.394	.225	.071	.364	.209	.067	.337	.194	.062	.312	.181	.058	
2.0	.350	.192	.059	.336	.185	.057	.309	.172	.053	.284	.159	.050	.260	.147	.046	
3.0	.308	.164	.049	.295	.158	.048	.270	.146	.045	.247	.136	.042	.226	.125	.039	
4.0	.275	.143	.042	.263	.138	.041	.241	.128	.038	.220	.118	.036	.200	.109	.033	
5.0	.249	.127	.037	.238	.122	.036	.217	.113	.033	.198	.105	.031	.180	.096	.029	
6.0	.227	.114	.033	.217	.110	.032	.198	.101	.030	.180	.094	.028	.164	.086	.026	
7.0	.208	.103	.029	.199	.099	.028	.182	.092	.026	.166	.085	.025	.150	.078	.023	
8.0	.193	.094	.026	.184	.091	.026	.168	.084	.024	.153	.078	.022	.139	.071	.021	
9.0	.179	.087	.024	.171	.083	.023	.157	.077	.022	.143	.071	.020	.129	.066	.019	
10.0	.167	.080	.022	.160	.077	.022	.146	.072	.020	.133	.066	.019	.121	.061	.017	

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Ceiling Cavity Exitance Coefficients(CCEC)															
0.0	.406	.406	.406	.347	.347	.347	.237	.237	.237	.136	.136	.136	.044	.044	.044	
1.0	.405	.373	.344	.346	.320	.296	.237	.220	.205	.136	.127	.119	.044	.041	.039	
2.0	.399	.351	.310	.342	.302	.268	.234	.209	.187	.135	.121	.110	.043	.039	.036	
3.0	.392	.335	.289	.336	.289	.251	.231	.201	.176	.133	.117	.104	.043	.038	.034	
4.0	.384	.323	.276	.330	.279	.239	.227	.194	.169	.131	.114	.100	.042	.037	.033	
5.0	.377	.313	.266	.324	.271	.232	.223	.189	.164	.129	.111	.097	.042	.036	.032	
6.0	.369	.306	.260	.317	.265	.226	.219	.185	.160	.127	.109	.095	.041	.036	.031	
7.0	.362	.299	.255	.312	.259	.222	.215	.182	.158	.125	.107	.094	.040	.035	.031	
8.0	.355	.294	.251	.306	.255	.219	.212	.179	.156	.123	.106	.093	.040	.035	.031	
9.0	.349	.289	.249	.301	.251	.217	.208	.176	.154	.121	.104	.092	.039	.034	.030	
10.0	.343	.285	.246	.296	.248	.215	.205	.174	.153	.120	.103	.091	.039	.034	.030	

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-05-30

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

UGR(Unified Glare Rating) Table

Test:U:220.16V I:0.1680A P:31.143W PF:0.8420 Freq:50.00Hz Lamp Flux:2073.73x1 lm											
NAME: SB-D01A30WSZ					TYPE:			WEIGHT:			
SPEC.:4000K					DIM.:			SERIAL No.:			
MFR.: SNOWBALL					SUR.:600mm						
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H y = 2H	13.1	14.4	13.7	15.1	15.8	13.1	14.4	13.7	15.1	15.8	
	3H	15.9	17.1	16.6	17.8	18.6	15.9	17.1	16.6	17.8	18.6
	4H	17.4	18.6	18.1	19.3	20.1	17.5	18.6	18.1	19.3	20.1
	6H	19.1	20.2	19.8	20.9	21.8	19.1	20.2	19.8	20.9	21.8
	8H	20.0	21.1	20.7	21.8	22.7	20.0	21.1	20.7	21.8	22.7
	12H	20.9	21.9	21.7	22.7	23.6	21.0	22.0	21.7	22.7	23.6
4H	2H	14.0	15.1	14.7	15.8	16.7	14.0	15.1	14.7	15.8	16.7
	3H	17.0	18.0	17.7	18.7	19.6	17.0	18.0	17.7	18.7	19.6
	4H	18.7	19.6	19.4	20.3	21.2	18.7	19.6	19.4	20.3	21.2
	6H	20.5	21.3	21.3	22.1	23.0	20.5	21.3	21.3	22.1	23.0
	8H	21.5	22.3	22.3	23.1	24.0	21.5	22.3	22.3	23.1	24.0
	12H	22.5	23.2	23.3	24.0	25.0	22.6	23.3	23.4	24.1	25.1
8H	4H	19.3	20.1	20.1	20.8	21.8	19.3	20.1	20.1	20.8	21.8
	6H	21.4	22.1	22.2	22.9	23.9	21.4	22.1	22.2	22.9	23.9
	8H	22.6	23.2	23.4	24.0	25.0	22.6	23.2	23.4	24.0	25.0
	12H	23.8	24.3	24.6	25.2	26.2	23.9	24.4	24.7	25.2	26.2
12H	4H	19.4	20.2	20.2	21.0	21.9	19.4	20.2	20.2	21.0	21.9
	6H	21.7	22.3	22.5	23.1	24.1	21.7	22.3	22.5	23.1	24.1
	8H	23.0	23.5	23.8	24.3	25.3	23.0	23.5	23.8	24.3	25.3
Variations with the observer position at spacings:											
S = 1.0H	+ 0.1 / - 0.1					+ 0.1 / - 0.1					
1.5H	+ 0.2 / - 0.3					+ 0.2 / - 0.3					
2.0H	+ 0.3 / - 0.4					+ 0.3 / - 0.4					

CIE Pub.117, 2074 lm Total Lamp Luminous Flux Corrected ($8\log(F/F_0) = 2.5$)
Area: 0.28 m²

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:XIAOMI
Test Date:2023-05-30

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:9.000m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:220.16V I:0.1680A P:31.143W PF:0.8420 Freq:50.00Hz Lamp Flux:2073.73x1 lm		
NAME: SB-D01A30WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:600mm	


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	42	29	22	41	29	21	38	27	21	14
0.80	51	37	29	49	36	28	45	34	27	18
1.00	58	45	36	56	43	35	52	43	33	23
1.25	65	52	43	63	50	41	57	47	39	28
1.50	71	58	48	67	55	47	61	51	44	32
2.00	79	66	57	75	64	55	67	59	52	37
2.50	83	72	64	79	69	61	71	63	57	41
3.00	87	77	69	83	74	66	74	67	61	45
4.00	93	84	77	88	80	73	79	72	67	49
5.00	96	88	82	91	84	78	81	76	71	53
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-05-30

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

ISOCANDELA DIAGRAM

Test:U:220.16V I:0.1680A P:31.143W PF:0.8420 Freq:50.00Hz Lamp Flux:2073.73x1 lm		
NAME: SB-D01A30WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:600mm	




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:XIAOMI
Test Date:2023-05-30

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:9.000m [K=1.0000]
Remarks:

AAI Figure

Test:U:220.16V I:0.1680A P:31.143W PF:0.8420 Freq:50.00Hz Lamp Flux:2073.73x1 lm		
NAME: SB-D01A30WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:600mm	




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-05-30

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

ISOLUX DIAGRAM


Test:U:220.16V I:0.1680A P:31.143W PF:0.8420 Freq:50.00Hz Lamp Flux:2073.73x1 lm		
NAME: SB-D01A30WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:600mm	



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: XIAOMI
 Test Date: 2023-05-30

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity: 65.0%
 Test Distance: 9.000m [K=1.0000]
 Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: XIAOMI
Test Date: 2023-05-30

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity: 65.0%
Test Distance: 9.000m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:220.16V I:0.1680A P:31.143W PF:0.8420 Freq:50.00Hz Lamp Flux:2073.73x1 lm		
NAME: SB-D01A30WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:600mm	

Table--1

UNIT: cd

C(DEC) γ (DEC)	0	22.5	45	67.5	90	112.5	135	157.5	180	202.5	225	247.5	270	292.5	315	337.5			
0	243	243	243	242	242	241	241	241	243	243	243	242	242	241	241	241			
5	251	250	250	250	250	249	248	247	249	248	247	247	246	247	247	248			
10	258	258	258	258	258	258	258	257	258	256	254	254	253	254	254	255			
15	263	263	263	263	264	264	264	263	264	261	259	258	258	259	260	261			
20	268	267	267	267	268	268	269	268	268	265	263	262	262	263	264	265			
25	272	271	271	271	271	272	273	271	272	269	266	265	265	266	268	269			
30	275	274	274	274	274	275	275	274	274	271	269	268	268	269	271	272			
35	276	276	275	275	276	277	277	276	276	273	270	269	269	269	271	273	274		
40	276	275	275	275	275	276	277	276	276	273	270	269	269	271	273	273			
45	273	273	273	273	273	274	275	274	274	271	269	267	268	269	271	271			
50	269	269	268	269	269	270	270	270	270	267	265	263	264	265	267	267			
55	262	263	262	262	262	264	264	263	264	261	259	257	258	259	261	261			
60	254	254	253	254	254	255	256	255	256	253	251	249	250	250	252	252			
65	243	244	243	244	244	245	246	245	246	244	241	239	240	241	242	242			
70	232	232	231	232	232	234	234	234	235	232	230	228	229	229	231	231			
75	218	218	218	218	219	221	221	221	222	219	218	216	216	216	218	217			
80	203	203	201	203	203	205	206	206	207	204	203	201	201	201	203	202			
85	162	168	166	172	171	177	178	180	182	177	177	172	174	170	171	164			
90	104	105	104	102	99.6	98.7	96.9	99.3	100	93.9	94.7	92.1	94.3	97.0	100	102			
95	139	132	122	112	108	104	112	116	116	115	105	99.8	99.7	107	115	128			
100	152	142	132	128	132	123	128	139	152	138	123	117	118	119	127	137			
105	147	138	133	136	145	136	132	136	148	134	126	126	132	130	130	134			
110	139	133	128	133	134	133	127	131	139	128	116	113	115	119	119	127			
115	131	125	119	119	118	120	120	124	131	117	110	103	107	101	112	121			
120	124	118	111	92.1	105	90.1	110	116	123	111	103	85.2	95.2	81.8	104	116			
125	116	110	103	85.3	96.2	83.8	102	109	115	105	99.0	80.6	89.3	80.5	96.9	107			
130	107	101	90.9	81.3	87.4	80.8	91.2	100	106	98.1	87.9	72.6	82.0	74.3	81.8	90.4			
135	97.1	91.2	70.8	75.3	78.5	76.1	64.3	88.9	97.3	88.9	65.0	66.6	72.3	68.5	67.8	86.2			
140	85.0	69.1	62.4	66.4	69.7	70.4	56.9	58.5	73.2	56.5	49.8	63.1	64.3	60.2	58.7	65.6			
145	55.4	49.3	56.2	56.7	60.9	62.8	61.5	44.9	54.1	44.3	55.9	56.6	54.7	50.9	53.1	48.6			
150	39.6	43.9	48.9	49.2	50.9	45.7	46.5	41.2	38.1	41.2	43.6	42.1	41.1	44.7	44.6	43.9			
155	35.7	39.1	39.7	40.2	37.9	33.8	33.8	34.1	34.2	31.0	30.1	30.2	34.5	36.9	35.3	38.8			
160	29.2	30.7	30.2	29.5	28.1	25.3	24.2	26.3	29.6	25.9	21.5	21.9	25.7	28.9	27.7	31.7			
165	21.3	22.3	22.1	21.7	19.8	18.0	16.8	18.5	22.1	18.7	15.5	15.1	17.6	20.2	20.6	22.0			
170	17.4	18.3	16.4	14.5	13.1	14.4	14.2	16.6	21.3	18.5	15.4	12.4	11.2	14.2	16.1	17.7			
175	9.07	9.03	8.57	8.10	8.65	9.38	10.4	12.1	12.8	11.5	10.0	8.72	7.79	8.09	9.05	8.93			
180	7.69	7.55	7.08	7.05	6.94	6.83	7.31	7.70	7.67	7.57	7.05	7.05	6.97	6.84	7.35	7.71			

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:XIAOMI
Test Date:2023-05-30

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:9.000m [K=1.0000]
Remarks: