


LUMINAIRE PHOTOMETRIC TEST REPORT

Test:U:220.27V I:0.2822A P:60.035W PF:0.9660 Freq:50.00Hz Lamp Flux:4714.66x1 lm		
NAME: SB-D01A60WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1200mm	

DATA OF LAMP		PHOTOMETRIC DATA Eff: 78.53 lm/W			
MODEL		I _{max} (cd)	885.3	S/MH(C0/180)	1.32
NOMINAL POWER(W)		LOR(%)	100.0	S/MH(C90/270)	1.32
RATED VOLTAGE(V)	--	TOTAL FLUX(lm)	4714.7	η UP,DN(C0-180)	12.2,35.1
NOMINAL FLUX(lm)	4714.66	CIE CLASS	SEMI-D.	η UP,DN(C180-360)	13.0,39.7
LAMPS INSIDE	1	η up(%)	25.3	CIBSE SHR NOM	1.50
TEST VOLTAGE(V)	--	η down(%)	74.7	CIBSE SHR MAX	1.55



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-05-31

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum,lamp
10	856.0	846.1	809.4	799.2	860.0	849.8	847.5	875.6	0- 10	81.72	81.72	1.73,1.73
20	816.9	800.2	759.1	753.3	803.9	794.8	797.7	834.7	10- 20	231.1	312.8	6.63,6.63
30	786.8	758.9	716.4	708.9	771.8	758.6	756.8	787.9	20- 30	358.0	670.8	14.2,14.2
40	736.4	704.1	659.7	649.9	736.5	715.6	709.5	751.0	30- 40	459.7	1131	24,24
50	662.9	630.6	586.0	575.8	680.8	655.0	646.5	700.3	40- 50	523.1	1654	35.1,35.1
60	577.0	545.9	501.2	493.1	606.7	578.9	572.0	630.5	50- 60	540.9	2195	46.5,46.5
70	484.9	457.0	414.7	409.1	527.9	497.5	489.9	552.2	60- 70	516.7	2711	57.5,57.5
80	394.4	370.5	329.2	312.9	438.7	410.5	403.8	463.4	70- 80	459.4	3171	67.3,67.3
90	308.6	246.1	253.4	262.9	327.7	235.0	306.1	373.6	80- 90	353.3	3524	74.7,74.7
100	244.2	244.4	244.5	226.2	303.2	236.5	257.9	280.3	90-100	273.3	3797	80.5,80.5
110	246.7	239.2	237.7	221.6	205.6	219.2	234.8	256.3	100-110	250.7	4048	85.9,85.9
120	234.7	208.0	212.8	166.5	225.9	181.4	235.8	233.9	110-120	222.7	4271	90.6,90.6
130	170.1	185.0	180.8	164.4	191.0	193.3	206.0	200.2	120-130	179.8	4450	94.4,94.4
140	133.5	144.5	123.4	98.76	132.1	132.3	150.0	176.5	130-140	124.1	4574	97,97
150	97.50	105.9	90.28	65.66	107.4	88.93	108.0	131.8	140-150	73.69	4648	98.6,98.6
160	76.66	78.32	68.49	58.67	110.2	86.71	92.52	104.4	150-160	42.85	4691	99.5,99.5
170	39.35	41.39	39.99	32.95	70.92	60.58	61.30	66.59	160-170	19.68	4711	99.9,99.9
180	36.36	31.75	35.09	33.40	36.18	31.93	33.77	33.32	170-180	4.068	4715	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

Conical surface Flux(90deg): 1387 lm

%lum = 29.4%

%lamp = 29.4%

Conical surface Flux(120deg): 2194.5 lm

%lum = 46.5%


%lamp = 46.5%

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-05-31

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:220.27V I:0.2822A P:60.035W PF:0.9660 Freq:50.00Hz Lamp Flux:4714.66x1 lm		
NAME: SB-D01A60WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1200mm	




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:XIAOMI
Test Date:2023-05-31

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:9.000m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:220.27V I:0.2822A P:60.035W PF:0.9660 Freq:50.00Hz Lamp Flux:4714.66x1 lm		
NAME: SB-D01A60WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1200mm	

ρ_{cc}	80%			70%			50%			30%			10%			0
ρ_w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
ρ_{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Coefficients of Utilization(CU)															
0.0	1.13	1.13	1.13	1.07	1.07	1.07	.97	.97	.97	.88	.88	.88	.79	.79	.79	.75
1.0	.94	.88	.83	.89	.84	.80	.80	.76	.73	.72	.69	.66	.64	.62	.60	.56
2.0	.80	.72	.65	.76	.69	.63	.68	.62	.57	.61	.56	.52	.54	.51	.47	.44
3.0	.69	.60	.53	.65	.57	.51	.59	.52	.47	.53	.47	.43	.47	.43	.39	.35
4.0	.60	.51	.44	.57	.49	.42	.52	.44	.39	.46	.40	.36	.41	.36	.32	.29
5.0	.53	.44	.37	.51	.42	.36	.46	.39	.33	.41	.35	.30	.37	.32	.28	.25
6.0	.48	.38	.32	.45	.37	.31	.41	.34	.28	.37	.31	.26	.33	.28	.24	.21
7.0	.43	.34	.28	.41	.33	.27	.37	.30	.25	.34	.27	.23	.30	.25	.21	.19
8.0	.39	.30	.24	.37	.29	.23	.34	.27	.22	.31	.25	.20	.28	.22	.19	.16
9.0	.36	.27	.22	.34	.26	.21	.31	.24	.19	.28	.22	.18	.25	.20	.17	.15
10.0	.33	.25	.19	.31	.24	.19	.29	.22	.17	.26	.20	.16	.24	.19	.15	.13



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-05-31

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

WEC AND CCEC

Test:U:220.27V I:0.2822A P:60.035W PF:0.9660 Freq:50.00Hz Lamp Flux:4714.66x1 lm		
NAME: SB-D01A60WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1200mm	

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Wall Exitance Coefficients(WEC)															
0.0																
1.0	.389	.221	.070	.374	.213	.068	.346	.198	.063	.320	.185	.059	.296	.172	.055	
2.0	.335	.184	.056	.322	.177	.055	.296	.165	.051	.273	.153	.048	.251	.142	.045	
3.0	.297	.158	.047	.285	.153	.046	.262	.142	.043	.240	.132	.040	.221	.122	.038	
4.0	.267	.139	.041	.256	.134	.040	.235	.124	.037	.215	.116	.035	.197	.107	.033	
5.0	.242	.123	.036	.232	.119	.035	.213	.111	.033	.195	.103	.031	.178	.095	.029	
6.0	.222	.111	.032	.212	.107	.031	.195	.100	.029	.178	.093	.027	.163	.086	.026	
7.0	.204	.101	.029	.196	.098	.028	.180	.091	.026	.165	.084	.025	.150	.078	.023	
8.0	.189	.092	.026	.181	.089	.025	.167	.083	.024	.153	.077	.022	.140	.072	.021	
9.0	.176	.085	.024	.169	.082	.023	.155	.077	.022	.142	.071	.020	.130	.066	.019	
10.0	.165	.079	.022	.158	.076	.021	.145	.071	.020	.133	.066	.019	.122	.061	.018	

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio Ceiling Cavity Exitance Coefficients(CCEC)															
0.0	.383	.383	.383	.327	.327	.327	.223	.223	.223	.128	.128	.128	.041	.041	.041	
1.0	.380	.349	.322	.325	.300	.277	.222	.206	.192	.128	.119	.112	.041	.038	.036	
2.0	.373	.327	.288	.320	.282	.249	.219	.195	.174	.126	.113	.102	.041	.037	.033	
3.0	.366	.311	.267	.314	.268	.231	.215	.186	.162	.124	.109	.096	.040	.035	.031	
4.0	.358	.299	.253	.308	.258	.220	.212	.180	.155	.122	.105	.092	.039	.034	.030	
5.0	.351	.289	.243	.301	.250	.212	.208	.175	.149	.120	.103	.089	.039	.033	.029	
6.0	.343	.281	.237	.295	.244	.206	.204	.170	.146	.118	.100	.087	.038	.033	.029	
7.0	.336	.275	.231	.289	.238	.202	.200	.167	.143	.116	.098	.085	.038	.032	.028	
8.0	.330	.269	.228	.284	.234	.199	.196	.164	.141	.114	.097	.084	.037	.032	.028	
9.0	.324	.265	.225	.279	.230	.196	.193	.161	.139	.113	.095	.083	.036	.031	.027	
10.0	.318	.260	.222	.274	.226	.194	.190	.159	.138	.111	.094	.082	.036	.031	.027	

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-05-31

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

UGR(Unified Glare Rating) Table

Test:U:220.27V I:0.2822A P:60.035W PF:0.9660 Freq:50.00Hz Lamp Flux:4714.66x1 lm											
NAME: SB-D01A60WSZ					TYPE:			WEIGHT:			
SPEC.:4000K					DIM.:			SERIAL No.:			
MFR.: SNOWBALL					SUR.:1200mm						
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H y = 2H	11.2	12.5	11.8	13.2	13.9	10.7	12.0	11.3	12.6	13.3	
	3H	13.7	14.9	14.3	15.5	16.3	13.0	14.2	13.6	14.8	15.6
	4H	15.0	16.2	15.7	16.8	17.6	14.2	15.4	14.9	16.0	16.8
	6H	16.5	17.6	17.1	18.2	19.0	15.6	16.7	16.3	17.3	18.1
	8H	17.3	18.3	18.0	19.0	19.8	16.3	17.4	17.0	18.1	18.9
	12H	18.0	19.0	18.7	19.7	20.5	16.9	17.9	17.6	18.6	19.4
4H	2H	11.9	13.1	12.6	13.7	14.5	11.5	12.7	12.2	13.3	14.1
	3H	14.6	15.6	15.3	16.3	17.1	14.1	15.0	14.7	15.7	16.6
	4H	16.1	17.0	16.8	17.7	18.6	15.5	16.4	16.2	17.1	17.9
	6H	17.8	18.6	18.5	19.3	20.2	17.0	17.8	17.7	18.6	19.4
	8H	18.7	19.5	19.4	20.2	21.1	17.8	18.6	18.6	19.4	20.3
	12H	19.5	20.2	20.2	21.0	21.9	18.5	19.2	19.3	20.0	20.9
8H	4H	16.6	17.4	17.4	18.1	19.0	16.1	16.9	16.9	17.6	18.5
	6H	18.6	19.2	19.3	20.0	20.9	17.9	18.6	18.7	19.4	20.3
	8H	19.7	20.3	20.5	21.1	22.0	19.0	19.5	19.7	20.3	21.3
	12H	20.7	21.2	21.5	22.0	22.9	19.9	20.4	20.7	21.2	22.2
12H	4H	16.7	17.4	17.5	18.2	19.1	16.3	17.0	17.0	17.7	18.6
	6H	18.8	19.4	19.6	20.1	21.1	18.2	18.8	19.0	19.6	20.5
	8H	20.0	20.5	20.8	21.3	22.3	19.4	19.9	20.2	20.7	21.6
Variations with the observer position at spacings:											
S = 1.0H	+ 0.1 / - 0.1					+ 0.1 / - 0.1					
1.5H	+ 0.2 / - 0.3					+ 0.2 / - 0.3					
2.0H	+ 0.2 / - 0.4					+ 0.2 / - 0.4					

CIE Pub.117, 4715 lm Total Lamp Luminous Flux Corrected ($8\log(F/F_0) = 5.4$)
Area: 1.13 m²

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:XIAOMI
Test Date:2023-05-31

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:9.000m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:220.27V I:0.2822A P:60.035W PF:0.9660 Freq:50.00Hz Lamp Flux:4714.66x1 lm		
NAME: SB-D01A60WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1200mm	


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS(PERCENT) $k(RI) \times RCR = 5$									
k = 0.60	45	32	25	44	32	25	41	31	24	17
0.80	54	41	33	52	40	32	49	38	31	23
1.00	62	48	40	59	47	39	55	47	37	28
1.25	69	56	47	66	54	46	61	51	44	33
1.50	74	61	52	71	59	51	65	55	48	37
2.00	81	70	61	78	67	59	71	62	56	42
2.50	86	75	67	82	72	65	74	67	61	46
3.00	90	80	72	85	77	70	78	71	65	50
4.00	95	86	80	90	83	76	82	76	71	54
5.00	98	90	84	93	87	81	84	79	75	57
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-05-31

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

ISOCANDELA DIAGRAM

Test:U:220.27V I:0.2822A P:60.035W PF:0.9660 Freq:50.00Hz Lamp Flux:4714.66x1 lm		
NAME: SB-D01A60WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1200mm	




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:XIAOMI
Test Date:2023-05-31

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:9.000m [K=1.0000]
Remarks:

AAI Figure

Test:U:220.27V I:0.2822A P:60.035W PF:0.9660 Freq:50.00Hz Lamp Flux:4714.66x1 lm		
NAME: SB-D01A60WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1200mm	




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:XIAOMI
 Test Date:2023-05-31

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity:65.0%
 Test Distance:9.000m [K=1.0000]
 Remarks:

ISOLUX DIAGRAM


Test:U:220.27V I:0.2822A P:60.035W PF:0.9660 Freq:50.00Hz Lamp Flux:4714.66x1 lm		
NAME: SB-D01A60WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1200mm	



C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 25.3DEG
 Operators: XIAOMI
 Test Date: 2023-05-31

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System: EVERFINE GO-3000H_V1 SYSTEM V2.00.411
 Humidity: 65.0%
 Test Distance: 9.000m [K=1.0000]
 Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: XIAOMI
Test Date: 2023-05-31

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity: 65.0%
Test Distance: 9.000m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:220.27V I:0.2822A P:60.035W PF:0.9660 Freq:50.00Hz Lamp Flux:4714.66x1 lm		
NAME: SB-D01A60WSZ	TYPE:	WEIGHT:
SPEC.:4000K	DIM.:	SERIAL No.:
MFR.: SNOWBALL	SUR.:1200mm	

Table--1

UNIT: cd

C(DEG) γ (DEG)	0	22.5	45	67.5	90	112.5	135	157.5	180	202.5	225	247.5	270	292.5	315	337.5			
0	885	883	878	869	861	859	862	867	885	883	878	869	861	859	862	867			
5	879	875	869	856	839	832	831	838	880	880	874	865	864	872	880	881			
10	856	854	846	830	809	800	799	807	860	858	850	842	847	862	876	881			
15	833	830	821	802	782	774	774	781	830	828	819	814	822	842	862	865			
20	817	811	800	779	759	751	753	762	804	803	795	789	798	817	835	837			
25	803	794	780	758	739	730	732	744	786	786	776	768	777	795	808	816			
30	787	776	759	736	716	706	709	723	772	772	759	749	757	774	788	800			
35	765	754	734	710	690	679	682	698	756	756	739	727	735	754	770	786			
40	736	725	704	680	660	647	650	669	737	736	716	701	710	732	751	767			
45	702	691	669	646	625	612	614	637	712	710	688	671	680	706	728	744			
50	663	652	631	607	586	575	576	600	681	680	655	636	646	676	700	714			
55	621	610	589	568	545	536	535	564	646	644	618	598	610	641	667	680			
60	577	567	546	526	501	493	493	521	607	606	579	557	572	604	630	640			
65	532	523	502	481	458	450	451	477	569	564	540	514	533	563	590	598			
70	485	477	457	437	415	408	409	432	528	521	498	471	490	521	552	554			
75	438	433	413	395	373	367	368	390	485	477	454	428	446	478	509	509			
80	394	388	371	352	329	317	313	347	439	431	410	385	404	435	463	463			
85	268	280	304	289	210	172	190	161	394	386	367	341	361	392	419	416			
90	309	294	246	217	253	260	263	282	328	296	235	227	306	346	374	367			
95	305	293	268	251	251	251	225	215	218	230	235	245	171	209	228	234			
100	244	232	244	238	244	242	226	193	303	273	236	240	258	271	280	306			
105	245	237	236	231	240	219	233	213	215	209	239	220	235	249	259	252			
110	247	251	239	221	238	219	222	228	206	219	219	214	235	228	256	251			
115	242	242	227	210	223	212	203	223	218	214	220	220	239	226	239	246			
120	235	232	208	203	213	203	167	211	226	219	181	212	236	223	234	240			
125	212	202	186	196	196	190	189	147	226	224	187	199	220	215	194	230			
130	170	172	185	178	181	167	164	160	191	150	193	185	206	201	200	198			
135	151	162	162	156	147	128	122	127	151	177	178	161	185	185	196	184			
140	133	141	144	135	123	104	98.8	106	132	134	132	130	150	167	176	174			
145	116	124	125	116	105	85.4	80.3	89.6	120	114	107	107	127	140	151	149			
150	97.5	105	106	99.4	90.3	72.1	65.7	74.4	107	95.9	88.9	88.5	108	120	132	127			
155	94.1	99.8	100.0	90.4	83.0	72.7	72.1	82.5	102	89.5	83.3	90.2	93.9	102	110	108			
160	76.7	79.8	78.3	75.3	68.5	61.0	58.7	71.0	110	96.6	86.7	85.9	92.5	96.1	104	104			
165	56.6	56.8	59.6	58.3	54.1	45.8	43.9	53.3	92.2	83.8	75.2	71.9	78.1	82.6	84.3	86.8			
170	39.4	36.6	41.4	41.8	40.0	33.2	32.9	37.0	70.9	66.3	60.6	57.7	61.3	66.1	66.6	64.1			
175	32.1	30.3	29.3	29.9	31.2	28.5	29.4	31.3	50.1	48.0	43.9	42.3	45.1	49.3	49.1	44.5			
180	36.4	34.3	31.7	31.7	35.1	34.6	33.4	31.4	36.2	34.0	31.9	32.3	33.8	34.6	33.3	31.1			

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:XIAOMI
Test Date:2023-05-31

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-3000H_V1 SYSTEM V2.00.411
Humidity:65.0%
Test Distance:9.000m [K=1.0000]
Remarks: